

Fortinet

Exam Questions NSE7_SDW-7.0

Fortinet NSE 7 - SD-WAN 7.0



NEW QUESTION 1

Refer to the exhibit.

```

config system virtual-wan-link
  set status enable
  set load-balance-mode source-ip-based
  config members
    edit 1
      set interface "port1"
      set gateway 100.64.1.254
      set source 100.64.1.1
      set cost 15
    next
    edit 2
      set interface "port2"
      set gateway 100.64.2.254
      set priority 10
    next
  end
end
  
```

Based on the output shown in the exhibit, which two criteria on the SD-WAN member configuration can be used to select an outgoing interface in an SD-WAN rule? (Choose two.)

- A. Set priority 10.
- B. Set cost 15.
- C. Set load-balance-mode source-ip-ip-based.
- D. Set source 100.64.1.1.

Answer: AB

NEW QUESTION 2

Exhibit A –

#	Name	Type	Normalized Interface	Addressing Mode	IP/Netmask	Access
Physical (10)						
1	port1	Physical	port1	Manual	203.0.113.1/255.255.255.2	PING
2	port2	Physical	port2	Manual	203.0.113.9/255.255.255.2	PING
3	port3	Physical	port3	Manual	0.0.0.0/0.0.0.0	
4	port4	Physical	port4	Manual	172.16.0.9/255.255.255.24	PING
5	port5	Physical	port5	Manual	10.0.2.254/255.255.255.0	PING
6	port6	Physical	port6	Manual	0.0.0.0/0.0.0.0	
7	port7	Physical	port7	Manual	0.0.0.0/0.0.0.0	
8	port8	Physical	port8	Manual	0.0.0.0/0.0.0.0	
9	port9	Physical	port9	Manual	0.0.0.0/0.0.0.0	
10	port10	Physical	port10	Manual	192.168.0.32/255.255.255.	HTTPS, PING, SSH, HT
Aggregate (1)						
11	fortilink	Aggregate		Manual	169.254.1.1/255.255.255.0	PING, Security Fabric C
Tunnel (3)						
12	raf.root	Tunnel		Manual	0.0.0.0/0.0.0.0	
13	l2t.root	Tunnel		Manual	0.0.0.0/0.0.0.0	
14	ssl.root (SSL VPN interf	Tunnel		Manual	0.0.0.0/0.0.0.0	
EMAC VLAN (1)						
15	vl_lan_bs	EMAC VLAN		Manual	10.0.102.1/255.255.255.0	PING
SD-WAN Zone (2)						
16	virtual-wan-link	SD-WAN Zone				
17	SASE	SD-WAN Zone	SASE			

#	ID	Destination	Gateway	Interface	Distance	Priority	Status	Description
Static Route (2)								
1	1	0.0.0.0/0.0.0.0	203.0.113.2	port1	10	0	Enable	
2	2	0.0.0.0/0.0.0.0	203.0.113.10	port2	10	0	Enable	

Exhibit B –

#	Name	From	To	Source	Destination	Schedule	Service
1	Internet_Access	port5	port1	all	all	always	ALL
Implicit (2-2 / Total: 1)							
2	Implicit Deny	any	any	all	all	always	ALL

Exhibit A shows the system interface with the static routes and exhibit B shows the firewall policies on the managed FortiGate. Based on the FortiGate configuration shown in the exhibits, what issue might you encounter when creating an SD-WAN zone for port1 and port2?

- A. port1 is assigned a manual IP address.
- B. port1 is referenced in a firewall policy.
- C. port2 is referenced in a static route.
- D. port1 and port2 are not administratively down.

Answer: B

NEW QUESTION 3

Refer to the exhibit.

```

config vpn ipsec phase1-interface
edit "T_INET_0_0"
set type dynamic
set interface "port1"
set keylife 28800
set peertype any
set net-device disable
set proposal aes128-sha256
set add-route enable
set psksecret ENC
Zv9n4Urfk0W4jj8vWI+KywxBG4ZDT7jWHKd8YaL8j4+pRpY0x/N7mSgc7VL0BW2ZHQXWJ6zvFxnKktiPYNtA8aP
i6ly7gDx2lP/OfKexTQQJzgcGRYzLM8eFTOnK7K6AuX0bFDCpBBhEIdf+03CYBMLwkFZmdU6RsT+qvybb1VX+Ioy
HK5EXakpmz5RiltELgZ9Gg==
next
end

```

Which configuration change is required if the responder FortiGate uses a dynamic routing protocol to exchange routes over IPsec?

- A. type must be set to static.
- B. mode-cfg must be enabled.
- C. exchange-interface-ip must be enabled.
- D. add-route must be disabled.

Answer: D

Explanation:

for using "non ike" routes (for example BGP/static and so on) you must do disable the add-route that inject automatically kernel route based on p2 selectors from the remote site from the SD-WAN_7.2_Study_Guide page 236

NEW QUESTION 4

Refer to the exhibit.

```

FortiGate # diagnose sys session list
session info: proto=1 proto_state=00 duration=25 expire=34 timeout=0 flags=00000000
socktype=0 sockport=0 av_idx=0 use=3
origin-shaper=
reply-shaper=
per_ip_shaper=
class_id=0 ha_id=0 policy_dir=0 tunnel=/ vlan_cos=0/255
state=dirty may_dirty
statistic(bytes/packets/allow_err): org=84/1/1 reply=84/1/1 tuples=2
tx speed(Bps/kbps): 0/0 rx speed(Bps/kbps): 0/0
origin->sink: org pre->post, reply pre->post dev=5->4/4->5 gwy=192.168.73.2/10.0.1.10
hook=post dir=org act=snat 10.0.1.10:2246->8.8.8.8:8(192.168.73.132:62662)
hook=pre dir=reply act=dnat 8.8.8.8:62662->192.168.73.132:0(10.0.1.10:2246)
misc=0 policy_id=1 auth_info=0 chk_client_info=0 vd=0
serial=00000a2c tos=ff/ff app_list=0 app=0 url_cat=0
rpidb_link_id= 80000000 rpidb_svc_id=0 ngfwid=n/a
npu_state=0x040000
total session 1

```

Based on the exhibit, which statement about FortiGate re-evaluating traffic is true?

- A. The type of traffic defined and allowed on firewall policy ID 1 is UDP.
- B. FortiGate has terminated the session after a change on policy ID 1.
- C. Changes have been made on firewall policy ID 1 on FortiGate.
- D. Firewall policy ID 1 has source NAT disabled.

Answer: C

NEW QUESTION 5

What are two reasons for using FortiManager to organize and manage the network for a group of FortiGate devices? (Choose two)

- A. It simplifies the deployment and administration of SD-WAN on managed FortiGate devices.
- B. It improves SD-WAN performance on the managed FortiGate devices.
- C. It sends probe signals as health checks to the beacon servers on behalf of FortiGate.
- D. It acts as a policy compliance entity to review all managed FortiGate devices.
- E. It reduces WAN usage on FortiGate devices by acting as a local FortiGuard server.

Answer: AE

NEW QUESTION 6

Refer to the exhibit.

```

config vpn ipsec phase1-interface
edit "FIRST_VPN"
    set type dynamic
    set interface "port1"
    set peertype any
    set proposal aes128-sha256 aes256-sha38
    set dhgrp 14 15 19
    set xauthtype auto
    set authusrgrp "first-group"
    set psksecret fortinet1
next
edit "SECOND_VPN"
    set type dynamic
    set interface "port1"
    set peertype any
    set proposal aes128-sha256 aes256-sha38
    set dhgrp 14 15 19
    set xauthtype auto
    set authusrgrp "second-group"
    set psksecret fortinet2
next
edit

```

FortiGate has multiple dial-up VPN interfaces incoming on port1 that match only FIRST_VPN. Which two configuration changes must be made to both IPsec VPN interfaces to allow incoming connections to match all possible IPsec dial-up interfaces? (Choose two.)

- A. Specify a unique peer ID for each dial-up VPN interface.
- B. Use different proposals are used between the interfaces.
- C. Configure the IKE mode to be aggressive mode.
- D. Use unique Diffie Hellman groups on each VPN interface.

Answer: AC

NEW QUESTION 7

Refer to the exhibits.
 Exhibit A

```

branch1_fgt (3) # show
config service
edit 3
    set name "Corp"
    set mode sla
    set dst "Corp-net"
    set src "LAN-net"
    config sla
        edit "VPN_PING"
            set id 1
        next
        edit "VPN_HTTP"
            set id 1
        next
    end
    set priority-members 3 4 5
    set gateway enable
next
end

```

Exhibit B

```
branch1_fgt # diagnose sys sdwan service 3

Service(3): Address Mode(IPV4) flags=0x200 use-shortcut-sla
Gen(1), TOS(0x0/0x0), Protocol(0: 1->65535), Mode(sla), sla-compare-order
Members(2):
  1: Seq_num(5 T_MPLS_0), alive, sla(0x3), gid(0), cfg_order(2), cost(0), selected
  2: Seq_num(4 T_INET_1_0), alive, sla(0x1), gid(0), cfg_order(1), cost(0), selected
  3: Seq_num(3 T_INET_0_0), alive, sla(0x0), gid(0), cfg_order(0), cost(0), selected
Src address(1):
  10.0.1.0-10.0.1.255

Dst address(1):
  10.0.0.0-10.255.255.255

branch1_fgt # get router info routing-table all | grep T_
S      10.0.0.0/8 [1/0] via T_INET_0_0 tunnel 100.64.1.1
      [1/0] via T_INET_1_0 tunnel 100.64.1.9
S      10.201.1.254/32 [15/0] via T_INET_0_0 tunnel 100.64.1.1
S      10.202.1.254/32 [15/0] via T_INET_1_0 tunnel 100.64.1.9
S      10.203.1.254/32 [15/0] via T_MPLS_0 tunnel 172.16.1.5

branch1_fgt # diagnose sys sdwan member | grep T_
Member(3): interface: T_INET_0_0, flags=0x4 , gateway: 100.64.1.1, peer: 10.201.1.254,
priority: 0 1024, weight: 0
Member(4): interface: T_INET_1_0, flags=0x4 , gateway: 100.64.1.9, peer: 10.202.1.254,
priority: 0 1024, weight: 0
Member(5): interface: T_MPLS_0, flags=0x4 , gateway: 172.16.1.5, peer: 10.203.1.254,
priority: 0 1024, weight: 0
```

Exhibit A shows the configuration for an SD-WAN rule and exhibit B shows the respective rule status, the routing table, and the member status. The administrator wants to understand the expected behavior for traffic matching the SD-WAN rule. Based on the exhibits, what can the administrator expect for traffic matching the SD-WAN rule?

- A. The traffic will be load balanced across all three overlays.
- B. The traffic will be routed over T_INET_0_0.
- C. The traffic will be routed over T_MPLS_0.
- D. The traffic will be routed over T_INET_1_0.

Answer: C

NEW QUESTION 8

What are two reasons why FortiGate would be unable to complete the zero-touch provisioning process? (Choose two.)

- A. The FortiGate cloud key has not been added to the FortiGate cloud portal.
- B. FortiDeploy has connected with FortiGate and provided the initial configuration to contact FortiManager
- C. The zero-touch provisioning process has completed internally, behind FortiGate.
- D. FortiGate has obtained a configuration from the platform template in FortiGate cloud.
- E. A factory reset performed on FortiGate.

Answer: AC

NEW QUESTION 9

Which two protocols in the IPsec suite are most used for authentication and encryption? (Choose two.)

- A. Encapsulating Security Payload (ESP)
- B. Secure Shell (SSH)
- C. Internet Key Exchange (IKE)
- D. Security Association (SA)

Answer: AC

NEW QUESTION 10

Which diagnostic command can you use to show the member utilization statistics measured by performance SLAs for the last 10 minutes?

- A. diagnose sys sdwan intf-sla-log
- B. diagnose sys sdwan health-check
- C. diagnose sys sdwan log
- D. diagnose sys sdwan sla-log

Answer: D

NEW QUESTION 10

Which two statements describe how IPsec phase 1 main mode is different from aggressive mode when performing IKE negotiation? (Choose two)

- A. A peer ID is included in the first packet from the initiator, along with suggested security policies.
- B. XAuth is enabled as an additional level of authentication, which requires a username and password.

- C. A total of six packets are exchanged between an initiator and a responder instead of three packets.
- D. The use of Diffie Hellman keys is limited by the responder and needs initiator acceptance.

Answer: BC

NEW QUESTION 14

Refer to the exhibit.

```
branch1_fgt # diagnose sys sdwan service 1

Service(3): Address Mode(IPV4) flags=0x200 use-shortcut-sla
Gen(6), TOS(0x0/0x0), Protocol(0: 1->65535), Mode(manual)
Members(2):
  1: Seq_num(3 T_INET_0_0), alive, selected
  2: Seq_num(4 T_INET_1_0), alive, selected
Src address(1):
  10.0.1.0-10.0.1.255

Dst address(1):
  10.0.0.0-10.255.255.255

branch1_fgt # diagnose sys sdwan member | grep T_INET_
Member(3): interface: T_INET_0_0, flags=0x4, gateway: 100.64.1.1, priority: 10 1024,
weight: 0
Member(4): interface: T_INET_1_0, flags=0x4, gateway: 100.64.1.9, priority: 0 1024,
weight: 0

branch1_fgt # get router info routing-table all | grep T_INET_
S      10.0.0.0/8 [1/0] via T_INET_1_0 tunnel 100.64.1.9
```

An administrator is troubleshooting SD-WAN on FortiGate. A device behind branch1_fgt generates traffic to the 10.0.0.0/8 network. The administrator expects the traffic to match SD-WAN rule ID 1 and be routed over T_INET_0_0. However, the traffic is routed over T_INET_1_0. Based on the output shown in the exhibit, which two reasons can cause the observed behavior? (Choose two.)

- A. The traffic matches a regular policy route configured with T_INET_1_0 as the outgoing device.
- B. T_INET_1_0 has a lower route priority value (higher priority) than T_INET_0_0.
- C. T_INET_0_0 does not have a valid route to the destination.
- D. T_INET_1_0 has a higher member configuration priority than T_INET_0_0.

Answer: AC

NEW QUESTION 18

Which are three key routing principles in SD-WAN? (Choose three.)

- A. FortiGate performs route lookups for new sessions only.
- B. Regular policy routes have precedence over SD-WAN rules.
- C. SD-WAN rules have precedence over ISDB routes.
- D. By default, SD-WAN members are skipped if they do not have a valid route to the destination.
- E. By default, SD-WAN rules are skipped if the best route to the destination is not an SD-WAN member.

Answer: BDE

NEW QUESTION 19

In the default SD-WAN minimum configuration, which two statements are correct when traffic matches the default implicit SD-WAN rule? (Choose two)

- A. Traffic has matched none of the FortiGate policy routes.
- B. Matched traffic failed RPF and was caught by the rule.
- C. The FIB lookup resolved interface was the SD-WAN interface.
- D. An absolute SD-WAN rule was defined and matched traffic.

Answer: AC

NEW QUESTION 24

In a hub-and-spoke topology, what are two advantages of enabling ADVPN on the IPsec overlays? (Choose two.)

- A. It provides the benefits of a full-mesh topology in a hub-and-spoke network.
- B. It provides direct connectivity between spokes by creating shortcuts.
- C. It enables spokes to bypass the hub during shortcut negotiation.
- D. It enables spokes to establish shortcuts to third-party gateways.

Answer: AB

NEW QUESTION 26

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

NSE7_SDW-7.0 Practice Exam Features:

- * NSE7_SDW-7.0 Questions and Answers Updated Frequently
- * NSE7_SDW-7.0 Practice Questions Verified by Expert Senior Certified Staff
- * NSE7_SDW-7.0 Most Realistic Questions that Guarantee you a Pass on Your First Try
- * NSE7_SDW-7.0 Practice Test Questions in Multiple Choice Formats and Updates for 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The NSE7_SDW-7.0 Practice Test Here](#)