

Exam Questions AWS-Solution-Architect-Associate

Amazon AWS Certified Solutions Architect - Associate

<https://www.2passeasy.com/dumps/AWS-Solution-Architect-Associate/>



NEW QUESTION 1

You are trying to launch an EC2 instance, however the instance seems to go into a terminated status immediately. What would probably not be a reason that this is happening?

- A. The AMI is missing a required part.
- B. The snapshot is corrupt.
- C. You need to create storage in EBS first.
- D. You've reached your volume limit

Answer: C

Explanation:

Amazon EC2 provides a virtual computing environments, known as an instance.

After you launch an instance, AWS recommends that you check its status to confirm that it goes from the pending status to the running status, the not terminated status.

The following are a few reasons why an Amazon EBS-backed instance might immediately terminate: You've reached your volume limit.

The AMI is missing a required part. The snapshot is corrupt. Reference:

http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/Using_InstanceStraightToTerminated.html

NEW QUESTION 2

Can a user get a notification of each instance start / terminate configured with Auto Scaling?

- A. Yes, if configured with the Launch Config
- B. Yes, always
- C. Yes, if configured with the Auto Scaling group
- D. No

Answer: C

Explanation:

The user can get notifications using SNS if he has configured the notifications while creating the Auto Scaling group.

Reference: <http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/GettingStartedTutorial.html>

NEW QUESTION 3

Amazon EBS provides the ability to create backups of any Amazon EC2 volume into what is known as

- A. snapshots
- B. images
- C. instance backups
- D. mirrors

Answer: A

Explanation:

Amazon allows you to make backups of the data stored in your EBS volumes through snapshots that can later be used to create a new EBS volume.

Reference: <http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/Storage.html>

NEW QUESTION 4

A user is storing a large number of objects on AWS S3. The user wants to implement the search functionality among the objects. How can the user achieve this?

- A. Use the indexing feature of S3.
- B. Tag the objects with the metadata to search on that.
- C. Use the query functionality of S3.
- D. Make your own DB system which stores the S3 metadata for the search functionalit

Answer: D

Explanation:

In Amazon Web Services, AWS S3 does not provide any query facility. To retrieve a specific object the user needs to know the exact bucket / object key. In this case it is recommended to have an own DB system which manages the S3 metadata and key mapping.

Reference: http://media.amazonwebservices.com/AWS_Storage_Options.pdf

NEW QUESTION 5

After setting up a Virtual Private Cloud (VPC) network, a more experienced cloud engineer suggests that to achieve low network latency and high network throughput you should look into setting up a placement group. You know nothing about this, but begin to do some research about it and are especially curious about its limitations. Which of the below statements is wrong in describing the limitations of a placement group?

- A. Although launching multiple instance types into a placement group is possible, this reduces the likelihood that the required capacity will be available for your launch to succeed.
- B. A placement group can span multiple Availability Zones.
- C. You can't move an existing instance into a placement group.
- D. A placement group can span peered VPCs

Answer: B

Explanation:

A placement group is a logical grouping of instances within a single Availability Zone. Using placement groups enables applications to participate in a low-latency, 10 Gbps network. Placement groups are recommended for applications that benefit from low network latency, high network throughput, or both. To provide the lowest latency, and the highest packet-per-second network performance for your placement group, choose an instance type that supports enhanced networking. Placement groups have the following limitations:

The name you specify for a placement group a name must be unique within your AWS account. A placement group can't span multiple Availability Zones. Although launching multiple instance types into a placement group is possible, this reduces the likelihood that the required capacity will be available for your launch to succeed. We recommend using the same instance type for all instances in a placement group.

You can't merge placement groups. Instead, you must terminate the instances in one placement group, and then relaunch those instances into the other placement group.

A placement group can span peered VPCs; however, you will not get full-bisection bandwidth between instances in peered VPCs. For more information about VPC peering connections, see VPC Peering in the Amazon VPC User Guide.

You can't move an existing instance into a placement group. You can create an AM from your existing instance, and then launch a new instance from the AMI into a placement group.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/placement-groups.html>

NEW QUESTION 6

A client needs you to import some existing infrastructure from a dedicated hosting provider to AWS to try and save on the cost of running his current website. He also needs an automated process that manages backups, software patching, automatic failure detection, and recovery. You are aware that his existing set up currently uses an Oracle database. Which of the following AWS databases would be best for accomplishing this task?

- A. Amazon RDS
- B. Amazon Redshift
- C. Amazon SimpleDB
- D. Amazon ElastiCache

Answer: A

Explanation:

Amazon RDS gives you access to the capabilities of a familiar MySQL, Oracle, SQL Server, or PostgreSQL database engine. This means that the code, applications, and tools you already use today with your existing databases can be used with Amazon RDS. Amazon RDS automatically patches the database software and backs up your database, storing the backups for a user-defined retention period and enabling point-in-time recovery.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Welcome.html>

NEW QUESTION 7

True or false? A VPC contains multiple subnets, where each subnet can span multiple Availability Zones.

- A. This is true only if requested during the set-up of VPC.
- B. This is true.
- C. This is false.
- D. This is true only for US region

Answer: C

Explanation:

A VPC can span several Availability Zones. In contrast, a subnet must reside within a single Availability Zone.

Reference: <https://aws.amazon.com/vpc/faqs/>

NEW QUESTION 8

An edge location refers to which Amazon Web Service?

- A. An edge location is referred to the network configured within a Zone or Region
- B. An edge location is an AWS Region
- C. An edge location is the location of the data center used for Amazon CloudFront.
- D. An edge location is a Zone within an AWS Region

Answer: C

Explanation:

Amazon CloudFront is a content distribution network. A content delivery network or content distribution network (CDN) is a large distributed system of servers deployed in multiple data centers across the world. The location of the data center used for CDN is called edge location.

Amazon CloudFront can cache static content at each edge location. This means that your popular static content (e.g., your site's logo, navigational images, cascading style sheets, JavaScript code, etc.) will be available at a nearby edge location for the browsers to download with low latency and improved performance for viewers. Caching popular static content with Amazon CloudFront also helps you offload requests for such files from your origin server — CloudFront serves the cached copy when available and only makes a request to your origin server if the edge location receiving the browser's request does not have a copy of the file.

Reference: <http://aws.amazon.com/cloudfront/>

NEW QUESTION 9

Your supervisor has asked you to build a simple file synchronization service for your department. He doesn't want to spend too much money and he wants to be notified of any changes to files by email. What do you think would be the best Amazon service to use for the email solution?

- A. Amazon SES
- B. Amazon CloudSearch
- C. Amazon SWF
- D. Amazon AppStream

Answer: A

Explanation:

File change notifications can be sent via email to users following the resource with Amazon Simple Email Service (Amazon SES), an easy-to-use, cost-effective

email solution.

Reference: http://media.amazonwebservices.com/architecturecenter/AWS_ac_ra_filesync_08.pdf

NEW QUESTION 10

Does DynamoDB support in-place atomic updates?

- A. Yes
- B. No
- C. It does support in-place non-atomic updates
- D. It is not defined

Answer: A

Explanation:

DynamoDB supports in-place atomic updates.

Reference:

<http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/WorkingWithItems.html#WorkingWithItems.AtomicCounters>

NEW QUESTION 10

Amazon EC2 provides a . It is an HTTP or HTTPS request that uses the HTTP verbs GET or POST.

- A. web database
- B. .net framework
- C. Query API
- D. C library

Answer: C

Explanation:

Amazon EC2 provides a Query API. These requests are HTTP or HTTPS requests that use the HTTP verbs GET or POST and a Query parameter named Action.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/APIReference/making-api-requests.html>

NEW QUESTION 15

In Amazon AWS, which of the following statements is true of key pairs?

- A. Key pairs are used only for Amazon SDKs.
- B. Key pairs are used only for Amazon EC2 and Amazon CloudFront.
- C. Key pairs are used only for Elastic Load Balancing and AWS IAM.
- D. Key pairs are used for all Amazon service

Answer: B

Explanation:

Key pairs consist of a public and private key, where you use the private key to create a digital signature, and then AWS uses the corresponding public key to validate the signature. Key pairs are used only for Amazon EC2 and Amazon CloudFront.

Reference: <http://docs.aws.amazon.com/general/latest/gr/aws-sec-cred-types.html>

NEW QUESTION 18

An organization has three separate AWS accounts, one each for development, testing, and production. The organization wants the testing team to have access to certain AWS resources in the production account. How can the organization achieve this?

- A. It is not possible to access resources of one account with another account.
- B. Create the IAM roles with cross account access.
- C. Create the IAM user in a test account, and allow it access to the production environment with the IAM policy.
- D. Create the IAM users with cross account acces

Answer: B

Explanation:

An organization has multiple AWS accounts to isolate a development environment from a testing or production environment. At times the users from one account need to access resources in the other account, such as promoting an update from the development environment to the production environment. In this case the IAM role with cross account access will provide a solution. Cross account access lets one account share access to their resources with users in the other AWS accounts.

Reference: http://media.amazonwebservices.com/AWS_Security_Best_Practices.pdf

NEW QUESTION 21

You need to import several hundred megabytes of data from a local Oracle database to an Amazon RDS DB instance. What does AWS recommend you use to accomplish this?

- A. Oracle export/import utilities
- B. Oracle SQL Developer
- C. Oracle Data Pump
- D. DBMS_FILE_TRANSFER

Answer: C

Explanation:

How you import data into an Amazon RDS DB instance depends on the amount of data you have and the number and variety of database objects in your database.

For example, you can use Oracle SQL Developer to import a simple, 20 MB database; you want to use Oracle Data Pump to import complex databases or databases that are several hundred megabytes or several terabytes in size.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Oracle.Procedural.Importing.html>

NEW QUESTION 22

A user wants to use an EBS-backed Amazon EC2 instance for a temporary job. Based on the input data, the job is most likely to finish within a week. Which of the following steps should be followed to terminate the instance automatically once the job is finished?

- A. Configure the EC2 instance with a stop instance to terminate it.
- B. Configure the EC2 instance with ELB to terminate the instance when it remains idle.
- C. Configure the CloudWatch alarm on the instance that should perform the termination action once the instance is idle.
- D. Configure the Auto Scaling schedule actMty that terminates the instance after 7 day

Answer: C

Explanation:

Auto Scaling can start and stop the instance at a pre-defined time. Here, the total running time is unknown. Thus, the user has to use the CloudWatch alarm, which monitors the CPU utilization. The user can create an alarm that is triggered when the average CPU utilization percentage has been lower than 10 percent for 24 hours, signaling that it is idle and no longer in use. When the utilization is below the threshold limit, it will terminate the instance as a part of the instance action.

Reference: <http://docs.aws.amazon.com/AmazonCloudWatch/latest/DeveloperGuide/UsingAlarmActions.html>

NEW QUESTION 24

You are setting up a VPC and you need to set up a public subnet within that VPC. Which following requirement must be met for this subnet to be considered a public subnet?

- A. Subnet's traffic is not routed to an internet gateway but has its traffic routed to a virtual private gateway.
- B. Subnet's traffic is routed to an internet gateway.
- C. Subnet's traffic is not routed to an internet gateway.
- D. None of these answers can be considered a public subne

Answer: B

Explanation:

A virtual private cloud (VPC) is a virtual network dedicated to your AWS account. It is logically isolated from other virtual networks in the AWS cloud. You can launch your AWS resources, such as Amazon EC2 instances, into your VPC. You can configure your VPC: you can select its IP address range, create subnets, and configure route tables, network gateways, and security settings.

A subnet is a range of IP addresses in your VPC. You can launch AWS resources into a subnet that you select. Use a public subnet for resources that must be connected to the internet, and a private subnet for resources that won't be connected to the Internet.

If a subnet's traffic is routed to an internet gateway, the subnet is known as a public subnet.

If a subnet doesn't have a route to the internet gateway, the subnet is known as a private subnet.

If a subnet doesn't have a route to the internet gateway, but has its traffic routed to a virtual private gateway, the subnet is known as a VPN-only subnet.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Subnets.html

NEW QUESTION 26

Can you specify the security group that you created for a VPC when you launch an instance in EC2-Classic?

- A. No, you can specify the security group created for EC2-Classic when you launch a VPC instance.
- B. No
- C. Yes
- D. No, you can specify the security group created for EC2-Classic to a non-VPC based instance onl

Answer: B

Explanation:

If you're using EC2-Classic, you must use security groups created specifically for EC2-Classic. When you launch an instance in EC2-Classic, you must specify a security group in the same region as the instance. You can't specify a security group that you created for a VPC when you launch an instance in EC2-Classic.

Reference:

<http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/using-network-security.html#ec2-classic-security-groups>

NEW QUESTION 31

You have been asked to build a database warehouse using Amazon Redshift. You know a little about it, including that it is a SQL data warehouse solution, and uses industry standard ODBC and JDBC connections and PostgreSQL drivers. However you are not sure about what sort of storage it uses for database tables. What sort of storage does Amazon Redshift use for database tables?

- A. InnoDB Tables
- B. NDB data storage
- C. Columnar data storage
- D. NDB CLUSTER Storage

Answer: C

Explanation:

Amazon Redshift achieves efficient storage and optimum query performance through a combination of massively parallel processing, columnar data storage, and very efficient, targeted data compression encoding schemes.

Columnar storage for database tables is an important factor in optimizing analytic query performance because it drastically reduces the overall disk I/O

requirements and reduces the amount of data you need to load from disk.

Reference: http://docs.aws.amazon.com/redshift/latest/dg/c_columnar_storage_disk_mem_mgmt.html

NEW QUESTION 35

You have been given a scope to deploy some AWS infrastructure for a large organisation. The requirements are that you will have a lot of EC2 instances but may need to add more when the average utilization of your Amazon EC2 fleet is high and conversely remove them when CPU utilization is low. Which AWS services would be best to use to accomplish this?

- A. Auto Scaling, Amazon CloudWatch and AWS Elastic Beanstalk
- B. Auto Scaling, Amazon CloudWatch and Elastic Load Balancing.
- C. Amazon CloudFront, Amazon CloudWatch and Elastic Load Balancing.
- D. AWS Elastic Beanstalk, Amazon CloudWatch and Elastic Load Balancing

Answer: B

Explanation:

Auto Scaling enables you to follow the demand curve for your applications closely, reducing the need to manually provision Amazon EC2 capacity in advance. For example, you can set a condition to add new

Amazon EC2 instances in increments to the Auto Scaling group when the average utilization of your Amazon EC2 fleet is high; and similarly, you can set a condition to remove instances in the same increments when CPU utilization is low. If you have predictable load changes, you can set a schedule through Auto Scaling to plan your scaling activities. You can use Amazon CloudWatch to send alarms to trigger scaling activities and Elastic Load Balancing to help distribute traffic to your instances within Auto Scaling groups. Auto Scaling enables you to run your Amazon EC2 fleet at optimal utilization. Reference: <http://aws.amazon.com/autoscaling/>

NEW QUESTION 38

In DynamoDB, could you use IAM to grant access to Amazon DynamoDB resources and API actions?

- A. In DynamoDB there is no need to grant access
- B. Depended to the type of access
- C. No
- D. Yes

Answer: D

Explanation:

Amazon DynamoDB integrates with AWS Identity and Access Management (IAM). You can use AWS IAM to grant access to Amazon DynamoDB resources and API actions. To do this, you first write an AWS IAM policy, which is a document that explicitly lists the permissions you want to grant. You then attach that policy to an AWS IAM user or role.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/UsingIAMWithDDB.html>

NEW QUESTION 40

Much of your company's data does not need to be accessed often, and can take several hours for retrieval time, so it's stored on Amazon Glacier. However someone within your organization has expressed concerns that his data is more sensitive than the other data, and is wondering whether the high level of encryption that he knows is on S3 is also used on the much cheaper Glacier service. Which of the following statements would be most applicable in regards to this concern?

- A. There is no encryption on Amazon Glacier, that's why it is cheaper.
- B. Amazon Glacier automatically encrypts the data using AES-128 a lesser encryption method than Amazon S3 but you can change it to AES-256 if you are willing to pay more.
- C. Amazon Glacier automatically encrypts the data using AES-256, the same as Amazon S3.
- D. Amazon Glacier automatically encrypts the data using AES-128 a lesser encryption method than Amazon S3.

Answer: C

Explanation:

Like Amazon S3, the Amazon Glacier service provides low-cost, secure, and durable storage. But where S3 is designed for rapid retrieval, Glacier is meant to be used as an archival service for data that is not accessed often, and for which retrieval times of several hours are suitable.

Amazon Glacier automatically encrypts the data using AES-256 and stores it durably in an immutable form. Amazon Glacier is designed to provide average annual durability of 99.99999999% for an archive. It stores each archive in multiple facilities and multiple devices. Unlike traditional systems which can require laborious data verification and manual repair, Glacier performs regular, systematic data integrity checks, and is built to be automatically self-healing.

Reference: <http://d0.awsstatic.com/whitepapers/Security/AWS%20Security%20Whitepaper.pdf>

NEW QUESTION 41

Your EBS volumes do not seem to be performing as expected and your team leader has requested you look into improving their performance. Which of the following is not a true statement relating to the performance of your EBS volumes?

- A. Frequent snapshots provide a higher level of data durability and they will not degrade the performance of your application while the snapshot is in progress.
- B. General Purpose (SSD) and Provisioned IOPS (SSD) volumes have a throughput limit of 128 MB/s per volume.
- C. There is a relationship between the maximum performance of your EBS volumes, the amount of I/O you are driving to them, and the amount of time it takes for each transaction to complete.
- D. There is a 5 to 50 percent reduction in IOPS when you first access each block of data on a newly created or restored EBS volume

Answer: A

Explanation:

Several factors can affect the performance of Amazon EBS volumes, such as instance configuration, I/O characteristics, workload demand, and storage configuration.

Frequent snapshots provide a higher level of data durability, but they may slightly degrade the performance of your application while the snapshot is in progress. This trade off becomes critical when you have data that changes rapidly. Whenever possible,

plan for snapshots to occur during off-peak times in order to minimize workload impact.
Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSPerformance.html>

NEW QUESTION 46

You've created your first load balancer and have registered your EC2 instances with the load balancer. Elastic Load Balancing routinely performs health checks on all the registered EC2 instances and automatically distributes all incoming requests to the DNS name of your load balancer across your registered, healthy EC2 instances. By default, the load balancer uses the _ protocol for checking the health of your instances.

- A. HTTPS
- B. HTTP
- C. ICMP
- D. IPv6

Answer: B

Explanation:

In Elastic Load Balancing a health configuration uses information such as protocol, ping port, ping path (URL), response timeout period, and health check interval to determine the health state of the instances registered with the load balancer.

Currently, HTTP on port 80 is the default health check. Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/TerminologyandKeyConcepts.html>

NEW QUESTION 48

In Amazon EC2 Container Service, are other container types supported?

- A. Yes, EC2 Container Service supports any container service you need.
- B. Yes, EC2 Container Service also supports Microsoft container service.
- C. No, Docker is the only container platform supported by EC2 Container Service presently.
- D. Yes, EC2 Container Service supports Microsoft container service and Openstac

Answer: C

Explanation:

In Amazon EC2 Container Service, Docker is the only container platform supported by EC2 Container Service presently.

Reference: <http://aws.amazon.com/ecs/faqs/>

NEW QUESTION 53

is a fast, filexible, fully managed push messaging service.

- A. Amazon SNS
- B. Amazon SES
- C. Amazon SQS
- D. Amazon FPS

Answer: A

Explanation:

Amazon Simple Notification Service (Amazon SNS) is a fast, filexible, fully managed push messaging service. Amazon SNS makes it simple and cost-effective to push to mobile devices such as iPhone, iPad, Android, Kindle Fire, and internet connected smart devices, as well as pushing to other distributed services.

Reference: http://aws.amazon.com/sns/?nc1=h_l2_as

NEW QUESTION 58

You need to set up a complex network infrastructure for your organization that will be reasonably easy to deploy, replicate, control, and track changes on. Which AWS service would be best to use to help you accomplish this?

- A. AWS Import/Export
- B. AWS CloudFormation
- C. Amazon Route 53
- D. Amazon CloudWatch

Answer: B

Explanation:

AWS CloudFormation is a service that helps you model and set up your Amazon Web Services resources so that you can spend less time managing those resources and more time focusing on your applications that run in AWS. You create a template that describes all the AWS resources that you want (like Amazon EC2 instances or Amazon RDS DB instances), and AWS CloudFormation takes care of provisioning and configuring those resources for you. You don't need to indMdually create and configure AWS resources and figure out what's dependent on what. AWS CloudFormation handles all of that.

Reference: <http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/Welcome.html>

NEW QUESTION 63

You have just been given a scope for a new client who has an enormous amount of data(petabytes) that he constantly needs analysed. Currently he is paying a huge amount of money for a data warehousing company to do this for him and is wondering if AWS can provide a cheaper solution. Do you think AWS has a solution for this?

- A. Ye
- B. Amazon SimpleDB
- C. N
- D. Not presently

- E. Ye
- F. Amazon Redshift
- G. Ye
- H. Your choice of relational AMIs on Amazon EC2 and EBS

Answer: C

Explanation:

Amazon Redshift is a fast, fully managed, petabyte-scale data warehouse service that makes it simple and cost-effective to efficiently analyze all your data using your existing business intelligence tools. You can start small for just \$0.25 per hour with no commitments or upfront costs and scale to a petabyte or more for \$1,000 per terabyte per year, less than a tenth of most other data warehousing solutions. Amazon Redshift delivers fast query performance by using columnar storage technology to improve I/O efficiency and parallelizing queries across multiple nodes. Redshift uses standard PostgreSQL JDBC and ODBC drivers, allowing you to use a wide range of familiar SQL clients. Data load speed scales linearly with cluster size, with integrations to Amazon S3, Amazon DynamoDB, Amazon Elastic MapReduce, Amazon Kinesis or any SSH-enabled host.

Reference: https://aws.amazon.com/running_databases/#redshift_anchor

NEW QUESTION 68

A user has launched 10 EC2 instances inside a placement group. Which of the below mentioned statements is true with respect to the placement group?

- A. All instances must be in the same AZ
- B. All instances can be across multiple regions
- C. The placement group cannot have more than 5 instances
- D. All instances must be in the same region

Answer: A

Explanation:

A placement group is a logical grouping of EC2 instances within a single Availability Zone. Using placement groups enables applications to participate in a low-latency, 10 Gbps network. Placement groups are recommended for applications that benefit from low network latency, high network throughput or both.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/placement-groups.html>

NEW QUESTION 71

Which of the following AWS CLI commands is syntactically incorrect?

1. `$ aws ec2 describe-instances`
2. `$ aws ec2 start-instances --instance-ids i-1348636c`
3. `$ aws sns publish --topic-arn arn:aws:sns:us-east-1:546419318123:OperationsError -message "Script Failure"`
4. `$ aws sqs receive-message --queue-url https://queue.amazonaws.com/546419318123/Test`

- A. 3
- B. 4
- C. 2
- D. 1

Answer: A

Explanation:

The following CLI command is missing a hyphen before "-message".

`aws sns publish --topic-arn arn:aws:sns:us-east-1:546419318123:OperationsError -message "Script Failure"`

It has been added below in red

`aws sns publish --topic-arn arn:aws:sns:us-east-1:546419318123:OperationsError ---message "Script Failure"`

Reference: <http://aws.amazon.com/cji/>

NEW QUESTION 75

An organization has developed a mobile application which allows end users to capture a photo on their mobile device, and store it inside an application. The application internally uploads the data to AWS S3. The organization wants each user to be able to directly upload data to S3 using their Google ID. How will the mobile app allow this?

- A. Use the AWS Web identity federation for mobile applications, and use it to generate temporary security credentials for each user.
- B. It is not possible to connect to AWS S3 with a Google ID.
- C. Create an IAM user every time a user registers with their Google ID and use IAM to upload files to S3.
- D. Create a bucket policy with a condition which allows everyone to upload if the login ID has a Google part to it.

Answer: A

Explanation:

For Amazon Web Services, the Web identity federation allows you to create cloud-backed mobile apps that use public identity providers, such as login with Facebook, Google, or Amazon. It will create temporary security credentials for each user, which will be authenticated by the AWS services, such as S3.

Reference: <http://docs.aws.amazon.com/STS/latest/UsingSTS/CreatingWIF.html>

NEW QUESTION 80

You are architecting an auto-scalable batch processing system using video processing pipelines and Amazon Simple Queue Service (Amazon SQS) for a customer. You are unsure of the limitations of SQS and need to find out. What do you think is a correct statement about the limitations of Amazon SQS?

- A. It supports an unlimited number of queues but a limited number of messages per queue for each user but automatically deletes messages that have been in the queue for more than 4 weeks.
- B. It supports an unlimited number of queues and unlimited number of messages per queue for each user but automatically deletes messages that have been in the queue for more than 4 days.
- C. It supports an unlimited number of queues but a limited number of messages per queue for each user but automatically deletes messages that have been in the queue for more than 4 days.

D. It supports an unlimited number of queues and unlimited number of messages per queue for each user but automatically deletes messages that have been in the queue for more than 4 weeks.

Answer: B

Explanation:

Amazon Simple Queue Service (Amazon SQS) is a messaging queue service that handles message or workflows between other components in a system. Amazon SQS supports an unlimited number of queues and unlimited number of messages per queue for each user. Please be aware that Amazon SQS automatically deletes messages that have been in the queue for more than 4 days.

Reference: <http://aws.amazon.com/documentation/sqs/>

NEW QUESTION 85

Your company has been storing a lot of data in Amazon Glacier and has asked for an inventory of what is in there exactly. So you have decided that you need to download a vault inventory. Which of the following statements is incorrect in relation to Vault Operations in Amazon Glacier?

- A. You can use Amazon Simple Notification Service (Amazon SNS) notifications to notify you when the job completes.
- B. A vault inventory refers to the list of archives in a vault.
- C. You can use Amazon Simple Queue Service (Amazon SQS) notifications to notify you when the job completes.
- D. Downloading a vault inventory is an asynchronous operation.

Answer: C

Explanation:

Amazon Glacier supports various vault operations.

A vault inventory refers to the list of archives in a vault. For each archive in the list, the inventory provides archive information such as archive ID, creation date, and size. Amazon Glacier updates the vault inventory approximately once a day, starting on the day the first archive is uploaded to the vault. A vault inventory must exist for you to be able to download it.

Downloading a vault inventory is an asynchronous operation. You must first initiate a job to download the inventory. After receiving the job request, Amazon Glacier prepares your inventory for download. After the job completes, you can download the inventory data.

Given the asynchronous nature of the job, you can use Amazon Simple Notification Service (Amazon SNS) notifications to notify you when the job completes. You can specify an Amazon SNS topic for each individual job request or configure your vault to send a notification when specific vault events occur. Amazon Glacier prepares an inventory for each vault periodically, every 24 hours. If there have been no archive additions or deletions to the vault since the last inventory, the inventory date is not updated. When you initiate a job for a vault inventory, Amazon Glacier returns the last inventory it generated, which is a point-in-time snapshot and not real-time data. You might not find it useful to retrieve vault inventory for each archive upload. However, suppose you maintain a database on the client-side associating metadata about the archives you upload to Amazon Glacier. Then, you might find the vault inventory useful to reconcile information in your database with the actual vault inventory.

Reference: <http://docs.aws.amazon.com/amazonglacier/latest/dev/working-with-vaults.html>

NEW QUESTION 90

A customer enquires about whether all his data is secure on AWS and is especially concerned about Elastic Map Reduce (EMR) so you need to inform him of some of the security features in place for AWS. Which of the below statements would be an incorrect response to your customer's enquiry?

- A. Amazon EMR customers can choose to send data to Amazon S3 using the HTTPS protocol for secure transmission.
- B. Amazon S3 provides authentication mechanisms to ensure that stored data is secured against unauthorized access.
- C. Every packet sent in the AWS network uses Internet Protocol Security (IPsec).
- D. Customers may encrypt the input data before they upload it to Amazon S3.

Answer: C

Explanation:

Amazon S3 provides authentication mechanisms to ensure that stored data is secured against unauthorized access. Unless the customer who is uploading the data specifies otherwise, only that customer can access the data. Amazon EMR customers can also choose to send data to Amazon S3

using the HTTPS protocol for secure transmission. In addition, Amazon EMR always uses HTTPS to send data between Amazon S3 and Amazon EC2. For added security, customers may encrypt the input data before they upload it to Amazon S3 (using any common data compression tool); they then need to add a decryption step to the beginning of their cluster when Amazon EMR fetches the data from Amazon S3. Reference: <https://aws.amazon.com/elasticmapreduce/faqs/>

NEW QUESTION 93

You are in the process of building an online gaming site for a client and one of the requirements is that it must be able to process vast amounts of data easily. Which AWS Service would be very helpful in processing all this data?

- A. Amazon S3
- B. AWS Data Pipeline
- C. AWS Direct Connect
- D. Amazon EMR

Answer: D

Explanation:

Managing and analyzing high data volumes produced by online games platforms can be difficult. The back-end infrastructures of online games can be challenging to maintain and operate. Peak usage periods, multiple players, and high volumes of write operations are some of the most common problems that operations teams face.

Amazon Elastic MapReduce (Amazon EMR) is a service that processes vast amounts of data easily. Input data can be retrieved from web server logs stored on Amazon S3 or from player data stored in Amazon DynamoDB tables to run analytics on player behavior, usage patterns, etc. Those results can be stored again on Amazon S3, or inserted in a relational database for further analysis with classic business intelligence tools.

Reference: http://media.amazonwebservices.com/architecturecenter/AWS_ac_ra_games_10.pdf

NEW QUESTION 97

You need to change some settings on Amazon Relational Database Service but you do not want the database to reboot immediately which you know might happen depending on the setting that you change. Which of the following will cause an immediate DB instance reboot to occur?

- A. You change storage type from standard to PIOPS, and Apply Immediately is set to true.
- B. You change the DB instance class, and Apply Immediately is set to false.
- C. You change a static parameter in a DB parameter group.
- D. You change the backup retention period for a DB instance from 0 to a nonzero value or from a nonzero value to 0, and Apply Immediately is set to false.

Answer: A

Explanation:

A DB instance outage can occur when a DB instance is rebooted, when the DB instance is put into a state that prevents access to it, and when the database is restarted. A reboot can occur when you manually reboot your DB instance or when you change a DB instance setting that requires a reboot before it can take effect.

A DB instance reboot occurs immediately when one of the following occurs:

You change the backup retention period for a DB instance from 0 to a nonzero value or from a nonzero value to 0 and set Apply Immediately to true.

You change the DB instance class, and Apply Immediately is set to true.

You change storage type from standard to PIOPS, and Apply Immediately is set to true.

A DB instance reboot occurs during the maintenance window when one of the following occurs:

You change the backup retention period for a DB instance from 0 to a nonzero value or from a nonzero value to 0, and Apply Immediately is set to false.

You change the DB instance class, and Apply Immediately is set to false. Reference:

http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/CHAP_Troubleshooting.html#CHAP_Troubleshooting.Security

NEW QUESTION 102

What does the following policy for Amazon EC2 do?

```
{
  "Statement": [{
    "Effect": "Allow", "Action": "ec2:Describe*", "Resource": "*"
  }]
}
```

- A. Allow users to use actions that start with "Describe" over all the EC2 resources.
- B. Share an AMI with a partner
- C. Share an AMI within the account
- D. Allow a group to only be able to describe, run, stop, start, and terminate instances

Answer: A

Explanation:

You can use IAM policies to control the actions that your users can perform against your EC2 resources. For instance, a policy with the following statement will allow users to perform actions whose name start with "Describe" against all your EC2 resources.

```
{
  "Statement": [{
    "Effect": "Allow", "Action": "ec2:Describe*", "Resource": "*"
  }]
}
```

Reference: <http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/UsingIAM.html>

NEW QUESTION 103

You are setting up a very complex financial services grid and so far it has 5 Elastic IP (EIP) addresses.

You go to assign another EIP address, but all accounts are limited to 5 Elastic IP addresses per region by default, so you aren't able to. What is the reason for this?

- A. For security reasons.
- B. Hardware restrictions.
- C. Public (IPv4) internet addresses are a scarce resource.
- D. There are only 5 network interfaces per instance

Answer: C

Explanation:

Public (IPv4) internet addresses are a scarce resource. There is only a limited amount of public IP space available, and Amazon EC2 is committed to helping use that space efficiently.

By default, all accounts are limited to 5 Elastic IP addresses per region. If you need more than 5 Elastic IP addresses, AWS asks that you apply for your limit to be raised. They will ask you to think through your use case and help them understand your need for additional addresses.

Reference: http://aws.amazon.com/ec2/faqs/#How_many_instances_can_I_run_in_Amazon_EC2

NEW QUESTION 104

A major customer has asked you to set up his AWS infrastructure so that it will be easy to recover in the case of a disaster of some sort. Which of the following is important when thinking about being able to quickly launch resources in AWS to ensure business continuity in case of a disaster?

- A. Create and maintain AMIs of key servers where fast recovery is required.
- B. Regularly run your servers, test them, and apply any software updates and configuration changes.
- C. All items listed here are important when thinking about disaster recovery.
- D. Ensure that you have all supporting custom software packages available in AWS

Answer: C

Explanation:

In the event of a disaster to your AWS infrastructure you should be able to quickly launch resources in Amazon Web Services (AWS) to ensure business continuity.

The following are some key steps you should have in place for preparation:

1. Set up Amazon EC2 instances to replicate or mirror data.

2. Ensure that you have all supporting custom software packages available in AWS.
3. Create and maintain AMIs of key servers where fast recovery is required.
4. Regularly run these servers, test them, and apply any software updates and configuration changes.
5. Consider automating the provisioning of AWS resources.

Reference: http://d36cz9buwru1tt.cloudfront.net/AWS_Disaster_Recovery.pdf

NEW QUESTION 108

You want to use AWS Import/Export to send data from your S3 bucket to several of your branch offices. What should you do if you want to send 10 storage units to AWS?

- A. Make sure your disks are encrypted prior to shipping.
- B. Make sure you format your disks prior to shipping.
- C. Make sure your disks are 1TB or more.
- D. Make sure you submit a separate job request for each device

Answer: D

Explanation:

When using Amazon Import/Export, a separate job request needs to be submitted for each physical device even if they belong to the same import or export job.
Reference: <http://docs.aws.amazon.com/AWSImportExport/latest/DG/Concepts.html>

NEW QUESTION 111

What would be the best way to retrieve the public IP address of your EC2 instance using the CLI?

- A. Using tags
- B. Using traceroute
- C. Using ipconfig
- D. Using instance metadata

Answer: D

Explanation:

To determine your instance's public IP address from within the instance, you can use instance metadata. Use the following command to access the public IP address: For Linux use, `$ curl http://169.254.169.254/latest/meta-data/public-ipv4`, and for Windows use, `$ wget http://169.254.169.254/latest/meta-data/public-ipv4`.
Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/using-instance-addressing.htm>

NEW QUESTION 114

You need to measure the performance of your EBS volumes as they seem to be under performing. You have come up with a measurement of 1,024 KB I/O but your colleague tells you that EBS volume performance is measured in IOPS. How many IOPS is equal to 1,024 KB I/O?

- A. 16
- B. 256
- C. 8
- D. 4

Answer: D

Explanation:

Several factors can affect the performance of Amazon EBS volumes, such as instance configuration, I/O characteristics, workload demand, and storage configuration.

IOPS are input/output operations per second. Amazon EBS measures each I/O operation per second (that is 256 KB or smaller) as one IOPS. I/O operations that are larger than 256 KB are counted in 256 KB capacity units. For example, a 1,024 KB I/O operation would count as 4 IOPS.

When you provision a 4,000 IOPS volume and attach it to an EBS-optimized instance that can provide the necessary bandwidth, you can transfer up to 4,000 chunks of data per second (provided that the I/O does not exceed the 128 MB/s per volume throughput limit of General Purpose (SSD) and Provisioned IOPS (SSD) volumes).

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSPerformance.html>

NEW QUESTION 118

AWS CloudFormation is a service that helps you model and set up your Amazon Web Services resources so that you can spend less time managing those resources and more time focusing on your applications that run in AWS. You create a template that describes all the AWS resources that you want (like Amazon EC2 instances or Amazon RDS DB instances), and AWS CloudFormation takes care of provisioning and configuring those resources for you. What formatting is required for this template?

- A. JSON-formatted document
- B. CSS-formatted document
- C. XML-formatted document
- D. HTML-formatted document

Answer: A

Explanation:

You can write an AWS CloudFormation template (a JSON-formatted document) in a text editor or pick an existing template. The template describes the resources you want and their settings. For example, suppose you want to create an Amazon EC2. Your template can declare an instance Amazon EC2 and describe its properties, as shown in the following example:

```
{
  "AWSTemplateFormatVersion" : "2010-09-09",
  "Description" : "A simple Amazon EC2 instance", "Resources" : {
```

```
"MyEC2Instance" : {  
  "Type" : "AWS::EC2::Instance", "Properties" : {  
    "ImageId" : "ami-2f726546", "InstanceType" : "t1.micro"  
  }  
}
```

Reference:

<http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/cfn-what-is-how-does-it-work.html>

NEW QUESTION 123

You decide that you need to create a number of Auto Scaling groups to try and save some money as you have noticed that at certain times most of your EC2 instances are not being used. By default, what is the maximum number of Auto Scaling groups that AWS will allow you to create?

- A. 12
- B. Unlimited
- C. 20
- D. 2

Answer: C

Explanation:

Auto Scaling is an AWS service that allows you to increase or decrease the number of EC2 instances within your application's architecture. With Auto Scaling, you create collections of EC2 instances, called Auto Scaling groups. You can create these groups from scratch, or from existing EC2 instances that are already in production.

Reference: http://docs.aws.amazon.com/general/latest/gr/aws_service_limits.html#limits_autoscaling

NEW QUESTION 128

A user needs to run a batch process which runs for 10 minutes. This will only be run once, or at maximum twice, in the next month, so the processes will be temporary only. The process needs 15 X-Large instances. The process downloads the code from S3 on each instance when it is launched, and then generates a temporary log file. Once the instance is terminated, all the data will be lost. Which of the below mentioned pricing models should the user choose in this case?

- A. Spot instance.
- B. Reserved instance.
- C. On-demand instance.
- D. EBS optimized instance

Answer: A

Explanation:

In Amazon Web Services, the spot instance is useful when the user wants to run a process temporarily. The spot instance can terminate the instance if the other user outbids the existing bid. In this case all storage is temporary and the data is not required to be persistent. Thus, the spot instance is a good option to save money.

Reference: <http://aws.amazon.com/ec2/purchasing-options/spot-instances/>

NEW QUESTION 132

You have been storing massive amounts of data on Amazon Glacier for the past 2 years and now start to wonder if there are any limitations on this. What is the correct answer to your QUESTION ?

- A. The total volume of data is limited but the number of archives you can store are unlimited.
- B. The total volume of data is unlimited but the number of archives you can store are limited.
- C. The total volume of data and number of archives you can store are unlimited.
- D. The total volume of data is limited and the number of archives you can store are limited.

Answer: C

Explanation:

An archive is a durably stored block of information. You store your data in Amazon Glacier as archives. You may upload a single file as an archive, but your costs will be lower if you aggregate your data. TAR and ZIP are common formats that customers use to aggregate multiple files into a single file before uploading to Amazon Glacier.

The total volume of data and number of archives you can store are unlimited. Individual Amazon Glacier archives can range in size from 1 byte to 40 terabytes. The largest archive that can be uploaded in a single upload request is 4 gigabytes.

For items larger than 100 megabytes, customers should consider using the Multipart upload capability. Archives stored in Amazon Glacier are immutable, i.e. archives can be uploaded and deleted but cannot be edited or overwritten.

Reference: <https://aws.amazon.com/glacier/faqs/>

NEW QUESTION 134

You are setting up your first Amazon Virtual Private Cloud (Amazon VPC) so you decide to use the VPC wizard in the AWS console to help make it easier for you. Which of the following statements is correct regarding instances that you launch into a default subnet via the VPC wizard?

- A. Instances that you launch into a default subnet receive a public IP address and 10 private IP addresses.
- B. Instances that you launch into a default subnet receive both a public IP address and a private IP address.
- C. Instances that you launch into a default subnet don't receive any IP addresses and you need to define them manually.
- D. Instances that you launch into a default subnet receive a public IP address and 5 private IP addresses.

Answer: B

Explanation:

Instances that you launch into a default subnet receive both a public IP address and a private IP address. Instances in a default subnet also receive both public

and private DNS hostnames. Instances that you launch into a nondefault subnet in a default VPC don't receive a public IP address or a DNS hostname. You can change your subnet's default public IP addressing behavior.

Reference: <http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/default-vpc.html>

NEW QUESTION 138

An existing client comes to you and says that he has heard that launching instances into a VPC (virtual private cloud) is a better strategy than launching instances into a EC2-classic which he knows is what you currently do. You suspect that he is correct and he has asked you to do some research about this and get back to him. Which of the following statements is true in regards to what ability launching your instances into a VPC instead of EC2-Classic gives you?

- A. All of the things listed here.
- B. Change security group membership for your instances while they're running
- C. Assign static private IP addresses to your instances that persist across starts and stops
- D. Define network interfaces, and attach one or more network interfaces to your instances

Answer: A

Explanation:

By launching your instances into a VPC instead of EC2-Classic, you gain the ability to: Assign static private IP addresses to your instances that persist across starts and stops Assign multiple IP addresses to your instances

Define network interfaces, and attach one or more network interfaces to your instances Change security group membership for your instances while they're running

Control the outbound traffic from your instances (egress filtering) in addition to controlling the inbound traffic to them (ingress filtering)

Add an additional layer of access control to your instances in the form of network access control lists (ACL)

Run your instances on single-tenant hardware

Reference: http://media.amazonwebservices.com/AWS_Cloud_Best_Practices.pdf

NEW QUESTION 141

Amazon S3 allows you to set per-file permissions to grant read and/or write access. However you have decided that you want an entire bucket with 100 files already in it to be accessible to the public. You don't want to go through 100 files individually and set permissions. What would be the best way to do this?

- A. Move the bucket to a new region
- B. Add a bucket policy to the bucket.
- C. Move the files to a new bucket.
- D. Use Amazon EBS instead of S3

Answer: B

Explanation:

Amazon S3 supports several mechanisms that give you flexibility to control who can access your data as well as how, when, and where they can access it.

Amazon S3 provides four different access control mechanisms: AWS Identity and Access Management (IAM) policies, Access Control Lists (ACLs), bucket policies, and query string authentication. IAM enables organizations to create and manage multiple users under a single AWS account. With IAM policies, you can grant IAM users fine-grained control to your Amazon S3 bucket or objects. You can use ACLs to selectively add (grant) certain permissions on individual objects.

Amazon S3 bucket policies can be used to add or deny permissions across some or all of the objects within a single bucket.

With Query string authentication, you have the ability to share Amazon S3 objects through URLs that are

valid for a specified period of time.

Reference: <http://aws.amazon.com/s3/details/#security>

NEW QUESTION 145

You need to set up a high level of security for an Amazon Relational Database Service (RDS) you have just built in order to protect the confidential information stored in it. What are all the possible security groups that RDS uses?

- A. DB security groups, VPC security groups, and EC2 security groups.
- B. DB security groups only.
- C. EC2 security groups only.
- D. VPC security groups, and EC2 security group

Answer: A

Explanation:

A security group controls the access to a DB instance. It does so by allowing access to IP address ranges or Amazon EC2 instances that you specify.

Amazon RDS uses DB security groups, VPC security groups, and EC2 security groups. In simple terms, a DB security group controls access to a DB instance that is not in a VPC, a VPC security group controls access to a DB instance inside a VPC, and an Amazon EC2 security group controls access to an EC2 instance and can be used with a DB instance.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Welcome.html>

NEW QUESTION 146

You have set up an Elastic Load Balancer (ELB) with the usual default settings, which route each request independently to the application instance with the smallest load. However, someone has asked you to bind a user's session to a specific application instance so as to ensure that all requests coming from the user during the session will be sent to the same application instance. AWS has a feature to do this. What is it called?

- A. Connection draining
- B. Proxy protocol
- C. Tagging
- D. Sticky session

Answer: D

Explanation:

An Elastic Load Balancer(ELB) by default, routes each request independently to the application instance

with the smallest load. However, you can use the sticky session feature (also known as session affinity), which enables the load balancer to bind a user's session to a specific application instance. This ensures that all requests coming from the user during the session will be sent to the same application instance. The key to managing the sticky session is determining how long your load balancer should consistently route the user's request to the same application instance. If your application has its own session cookie, then you can set Elastic Load Balancing to create the session cookie to follow the duration specified by the application's session cookie. If your application does not have its own session cookie, then you can set Elastic Load Balancing to create a session cookie by specifying your own stickiness duration. You can associate stickiness duration for only HTTP/HTTPS load balancer listeners.

An application instance must always receive and send two cookies: A cookie that defines the stickiness duration and a special Elastic Load Balancing cookie named AWSELB, that has the mapping to the application instance.

Reference: <http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/TerminologyandKeyConcepts.html#session-stickiness>

NEW QUESTION 149

A user has created an application which will be hosted on EC2. The application makes calls to DynamoDB to fetch certain data. The application is using the DynamoDB SDK to connect with from the EC2 instance. Which of the below mentioned statements is true with respect to the best practice for security in this scenario?

- A. The user should create an IAM user with DynamoDB access and use its credentials within the application to connect with DynamoDB
- B. The user should attach an IAM role with DynamoDB access to the EC2 instance
- C. The user should create an IAM role, which has EC2 access so that it will allow deploying the application
- D. The user should create an IAM user with DynamoDB and EC2 access
- E. Attach the user with the application so that it does not use the root account credentials

Answer: B

Explanation:

With AWS IAM a user is creating an application which runs on an EC2 instance and makes requests to AWS, such as DynamoDB or S3 calls. Here it is recommended that the user should not create an IAM user and pass the user's credentials to the application or embed those credentials inside the application. Instead, the user should use roles for EC2 and give that role access to DynamoDB /S3. When the roles are attached to EC2, it will give temporary security credentials to the application hosted on that EC2, to connect with DynamoDB / S3.

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/Using_WorkingWithGroupsAndUsers.html

NEW QUESTION 151

After setting up several database instances in Amazon Relational Database Service (Amazon RDS) you decide that you need to track the performance and health of your databases. How can you do this?

- A. Subscribe to Amazon RDS events to be notified when changes occur with a DB instance, DB snapshot, DB parameter group, or DB security group.
- B. Use the free Amazon CloudWatch service to monitor the performance and health of a DB instance.
- C. All of the items listed will track the performance and health of a database.
- D. View, download, or watch database log files using the Amazon RDS console or Amazon RDS API
- E. You can also query some database log files that are loaded into database tables.

Answer: C

Explanation:

Amazon Relational Database Service (Amazon RDS) is a web service that makes it easier to set up, operate, and scale a relational database in the cloud. It provides cost-efficient, resizable capacity for an industry-standard relational database and manages common database administration tasks.

There are several ways you can track the performance and health of a database or a DB instance. You can:

Use the free Amazon CloudWatch service to monitor the performance and health of a DB instance. Subscribe to Amazon RDS events to be notified when changes occur with a DB instance, DB snapshot, DB parameter group, or DB security group.

View, download, or watch database log files using the Amazon RDS console or Amazon RDS APIs. You can also query some database log files that are loaded into database tables.

Use the AWS CloudTrail service to record AWS calls made by your AWS account. The calls are recorded in log files and stored in an Amazon S3 bucket.

Reference: http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/CHAP_Monitoring.html

NEW QUESTION 155

A user has attached 1 EBS volume to a VPC instance. The user wants to achieve the best fault tolerance of data possible. Which of the below mentioned options can help achieve fault tolerance?

- A. Attach one more volume with RAID 1 configuration.
- B. Attach one more volume with RAID 0 configuration.
- C. Connect multiple volumes and stripe them with RAID 6 configuration.
- D. Use the EBS volume as a root device

Answer: A

Explanation:

The user can join multiple provisioned IOPS volumes together in a RAID 1 configuration to achieve better fault tolerance. RAID 1 does not provide a write performance improvement; it requires more bandwidth than non-RAID configurations since the data is written simultaneously to multiple volumes.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/raid-config.html>

NEW QUESTION 157

Select a true statement about Amazon EC2 Security Groups (EC2-Classic).

- A. After you launch an instance in EC2-Classic, you can't change its security groups.
- B. After you launch an instance in EC2-Classic, you can change its security groups only once.
- C. After you launch an instance in EC2-Classic, you can only add rules to a security group.
- D. After you launch an instance in EC2-Classic, you cannot add or remove rules from a security group

Answer: A

Explanation:

After you launch an instance in EC2-Classic, you can't change its security groups. However, you can add rules to or remove rules from a security group, and those changes are automatically applied to all instances that are associated with the security group.

Reference: <http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/using-network-security.html>

NEW QUESTION 161

Which one of the following answers is not a possible state of Amazon CloudWatch Alarm?

- A. INSUFFICIENT_DATA
- B. ALARM
- C. OK
- D. STATUS_CHECK_FAILED

Answer: D

Explanation:

Amazon CloudWatch Alarms have three possible states: OK: The metric is within the defined threshold ALARM: The metric is outside of the defined threshold INSUFFICIENT_DATA: The alarm has just started, the metric is not available, or not enough data is available for the metric to determine the alarm state

Reference: <http://docs.aws.amazon.com/AmazonCloudWatch/latest/DeveloperGuide/AlarmThatSendsEmail.html>

NEW QUESTION 164

An accountant asks you to design a small VPC network for him and, due to the nature of his business, just needs something where the workload on the network will be low, and dynamic data will be accessed infrequently. Being an accountant, low cost is also a major factor. Which EBS volume type would best suit his requirements?

- A. Magnetic
- B. Any, as they all perform the same and cost the same.
- C. General Purpose (SSD)
- D. Magnetic or Provisioned IOPS (SSD)

Answer: A

Explanation:

You can choose between three EBS volume types to best meet the needs of their workloads: General Purpose (SSD), Provisioned IOPS (SSD), and Magnetic. General Purpose (SSD) is the new, SSD-backed, general purpose EBS volume type that we recommend as the default choice for customers. General Purpose (SSD) volumes are suitable for a broad range of workloads, including small to medium sized databases, development and test environments, and boot volumes. Provisioned IOPS (SSD) volumes offer storage with consistent and low-latency performance, and are designed for I/O intensive applications such as large relational or NoSQL databases. Magnetic volumes provide the lowest cost per gigabyte of all EBS volume types. Magnetic volumes are ideal for workloads where data is accessed infrequently, and applications where the lowest storage cost is important.

Reference: <https://aws.amazon.com/ec2/faqs/>

NEW QUESTION 167

A user has launched one EC2 instance in the US East region and one in the US West region. The user has launched an RDS instance in the US East region. How can the user configure access from both the EC2 instances to RDS?

- A. It is not possible to access RDS of the US East region from the US West region
- B. Configure the US West region's security group to allow a request from the US East region's instance and configure the RDS security group's ingress rule for the US East EC2 group
- C. Configure the security group of the US East region to allow traffic from the US West region's instance and configure the RDS security group's ingress rule for the US East EC2 group
- D. Configure the security group of both instances in the ingress rule of the RDS security group

Answer: C

Explanation:

The user cannot authorize an Amazon EC2 security group if it is in a different AWS Region than the RDS DB instance. The user can authorize an IP range or specify an Amazon EC2 security group in the same region that refers to an IP address in another region. In this case allow IP of US West inside US East's security group and open the RDS security group for US East region.

Reference: http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER_WorkingWithSecurityGroups.html

NEW QUESTION 169

In Amazon EC2, if your EBS volume stays in the detaching state, you can force the detachment by clicking .

- A. Force Detach
- B. Detach Instance
- C. AttachVolume
- D. AttachInstance

Answer: A

Explanation:

If your volume stays in the detaching state, you can force the detachment by clicking Force Detach. Reference: <http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/ebs-detaching-volume.html>

NEW QUESTION 170

A client of yours has a huge amount of data stored on Amazon S3, but is concerned about someone stealing it while it is in transit. You know that all data is encrypted in transit on AWS, but which of the following is wrong when describing server-side encryption on AWS?

- A. Amazon S3 server-side encryption employs strong multi-factor encryption.
- B. Amazon S3 server-side encryption uses one of the strongest block ciphers available, 256-bit Advanced Encryption Standard (AES-256), to encrypt your data.
- C. In server-side encryption, you manage encryption/decryption of your data, the encryption keys, and related tools.
- D. Server-side encryption is about data encryption at rest—that is, Amazon S3 encrypts your data as it writes it to disks.

Answer: C

Explanation:

Amazon S3 encrypts your object before saving it on disks in its data centers and decrypts it when you download the objects. You have two options depending on how you choose to manage the encryption keys: Server-side encryption and client-side encryption.

Server-side encryption is about data encryption at rest—that is, Amazon S3 encrypts your data as it writes it to disks in its data centers and decrypts it for you when you access it. As long as you authenticate your request and you have access permissions, there is no difference in the way you access encrypted or unencrypted objects. Amazon S3 manages encryption and decryption for you. For example, if you share your objects using a pre-signed URL, that URL works the same way for both encrypted and unencrypted objects.

In client-side encryption, you manage encryption/decryption of your data, the encryption keys, and related tools. Server-side encryption is an alternative to client-side encryption in which Amazon S3 manages the encryption of your data, freeing you from the tasks of managing encryption and encryption keys.

Amazon S3 server-side encryption employs strong multi-factor encryption. Amazon S3 encrypts each object with a unique key. As an additional safeguard, it encrypts the key itself with a master key that it regularly rotates. Amazon S3 server-side encryption uses one of the strongest block ciphers available, 256-bit Advanced Encryption Standard (AES-256), to encrypt your data.

Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/UsingServerSideEncryption.html>

NEW QUESTION 174

A user is running a batch process which runs for 1 hour every day. Which of the below mentioned options is the right instance type and costing model in this case if the user performs the same task for the whole year?

- A. EBS backed instance with on-demand instance pricing.
- B. EBS backed instance with heavy utilized reserved instance pricing.
- C. EBS backed instance with low utilized reserved instance pricing.
- D. Instance store backed instance with spot instance pricing

Answer: A

Explanation:

For Amazon Web Services, the reserved instance helps the user save money if the user is going to run the same instance for a longer period. Generally if the user uses the instances around 30-40% annually it is recommended to use RI. Here as the instance runs only for 1 hour daily it is not recommended to have RI as it will be costlier. The user should use on-demand with EBS in this case.

Reference: <http://aws.amazon.com/ec2/purchasing-options/reserved-instances/>

NEW QUESTION 177

Which IAM role do you use to grant AWS Lambda permission to access a DynamoDB Stream?

- A. Dynamic role
- B. Invocation role
- C. Execution role
- D. Event Source role

Answer: C

Explanation:

You grant AWS Lambda permission to access a DynamoDB Stream using an IAM role known as the "execution role".

Reference: <http://docs.aws.amazon.com/lambda/latest/dg/intro-permission-model.html>

NEW QUESTION 180

Name the disk storage supported by Amazon Elastic Compute Cloud (EC2).

- A. None of these
- B. Amazon AppStream store
- C. Amazon SNS store
- D. Amazon Instance Store

Answer: D

Explanation:

Amazon EC2 supports the following storage options: Amazon Elastic Block Store (Amazon EBS) Amazon EC2 Instance Store Amazon Simple Storage Service (Amazon S3)

Reference: <http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/Storage.html>

NEW QUESTION 183

You are signed in as root user on your account but there is an Amazon S3 bucket under your account that you cannot access. What is a possible reason for this?

- A. An IAM user assigned a bucket policy to an Amazon S3 bucket and didn't specify the root user as a principal
- B. The S3 bucket is full.
- C. The S3 bucket has reached the maximum number of objects allowed.
- D. You are in the wrong availability zone

Answer: A

Explanation:

With IAM, you can centrally manage users, security credentials such as access keys, and permissions that control which AWS resources users can access. In some cases, you might have an IAM user with full access to IAM and Amazon S3. If the IAM user assigns a bucket policy to an Amazon S3 bucket and doesn't specify the root user as a principal, the root user is denied access to that bucket. However, as the root user, you can still access the bucket by modifying the bucket policy to allow root user access.

Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/iam-troubleshooting.html#testing2>

NEW QUESTION 188

You have a number of image files to encode. In an Amazon SQS worker queue, you create an Amazon SQS message for each file specifying the command (jpeg-encode) and the location of the file in Amazon S3. Which of the following statements best describes the functionality of Amazon SQS?

- A. Amazon SQS is a distributed queuing system that is optimized for horizontal scalability, not for single-threaded sending or receiving speeds.
- B. Amazon SQS is for single-threaded sending or receiving speeds.
- C. Amazon SQS is a non-distributed queuing system.
- D. Amazon SQS is a distributed queuing system that is optimized for vertical scalability and for single-threaded sending or receiving speeds.

Answer: A

Explanation:

Amazon SQS is a distributed queuing system that is optimized for horizontal scalability, not for single-threaded sending or receiving speeds. A single client can send or receive Amazon SQS messages at a rate of about 5 to 50 messages per second. Higher receive performance can be achieved by requesting multiple messages (up to 10) in a single call. It may take several seconds before a message that has been to a queue is available to be received.

Reference: http://media.amazonwebservices.com/AWS_Storage_Options.pdf

NEW QUESTION 192

You need to set up security for your VPC and you know that Amazon VPC provides two features that you can use to increase security for your VPC: security groups and network access control lists (ACLs). You have already looked into security groups and you are now trying to understand ACLs. Which statement below is incorrect in relation to ACLs?

- A. Supports allow rules and deny rules.
- B. Is stateful: Return traffic is automatically allowed, regardless of any rules.
- C. Processes rules in number order when deciding whether to allow traffic.
- D. Operates at the subnet level (second layer of defense).

Answer: B

Explanation:

Amazon VPC provides two features that you can use to increase security for your VPC:

Security groups—Act as a firewall for associated Amazon EC2 instances, controlling both inbound and outbound traffic at the instance level

Network access control lists (ACLs)—Act as a firewall for associated subnets, controlling both inbound and outbound traffic at the subnet level

Security groups are stateful: (Return traffic is automatically allowed, regardless of any rules) Network ACLs are stateless: (Return traffic must be explicitly allowed by rules)

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Security.html

NEW QUESTION 195

A user comes to you and wants access to Amazon CloudWatch but only wants to monitor a specific LoadBalancer. Is it possible to give him access to a specific set of instances or a specific LoadBalancer?

- A. No because you can't use IAM to control access to CloudWatch data for specific resources.
- B. Yes
- C. You can use IAM to control access to CloudWatch data for specific resources.
- D. No because you need to be Sysadmin to access CloudWatch data.
- E. Yes
- F. Any user can see all CloudWatch data and needs no access right

Answer: A

Explanation:

Amazon CloudWatch integrates with AWS Identity and Access Management (IAM) so that you can

specify which CloudWatch actions a user in your AWS Account can perform. For example, you could create an IAM policy that gives only certain users in your organization permission to use GetMetricStatistics. They could then use the action to retrieve data about your cloud resources.

You can't use IAM to control access to CloudWatch data for specific resources. For example, you can't give a user access to CloudWatch data for only a specific set of instances or a specific LoadBalancer. Permissions granted using IAM cover all the cloud resources you use with CloudWatch. In addition, you can't use IAM roles with the Amazon CloudWatch command line tools.

Using Amazon CloudWatch with IAM doesn't change how you use CloudWatch. There are no changes to CloudWatch actions, and no new CloudWatch actions related to users and access control.

Reference: <http://docs.aws.amazon.com/AmazonCloudWatch/latest/DeveloperGuide/UsingIAM.html>

NEW QUESTION 198

A user is planning to make a mobile game which can be played online or offline and will be hosted on EC2.

The user wants to ensure that if someone breaks the highest score or they achieve some milestone they can inform all their colleagues through email. Which of the below mentioned AWS services helps achieve this goal?

- A. AWS Simple Workflow Service.
- B. AWS Simple Email Service.
- C. Amazon Cognito
- D. AWS Simple Queue Service

Answer: B

Explanation:

Amazon Simple Email Service (Amazon SES) is a highly scalable and cost-effective email-sending service for businesses and developers. It integrates with other AWS services, making it easy to send emails from applications that are hosted on AWS.

Reference: <http://aws.amazon.com/ses/faqs/>

NEW QUESTION 199

You have multiple VPN connections and want to provide secure communication between sites using the AWS VPN CloudHub. Which statement is the most accurate in describing what you must do to set this up correctly?

- A. Create a virtual private gateway with multiple customer gateways, each with unique Border Gateway Protocol (BGP) Autonomous System Numbers (ASNs)
- B. Create a virtual private gateway with multiple customer gateways, each with a unique set of keys
- C. Create a virtual public gateway with multiple customer gateways, each with a unique Private subnet
- D. Create a virtual private gateway with multiple customer gateways, each with unique subnet id

Answer: A

Explanation:

If you have multiple VPN connections, you can provide secure communication between sites using the AWS VPN CloudHub. The VPN CloudHub operates on a simple hub-and-spoke model that you can use with or without a VPC. This design is suitable for customers with multiple branch offices and existing Internet connections who'd like to implement a convenient, potentially low-cost hub-and-spoke model for primary or backup connectivity between these remote offices. To use the AWS VPN CloudHub, you must create a virtual private gateway with multiple customer gateways, each with unique Border Gateway Protocol (BGP) Autonomous System Numbers (ASNs). Customer gateways advertise the appropriate routes (BGP prefixes) over their VPN connections. These routing advertisements are received and re-advertised to each BGP peer, enabling each site to send data to and receive data from the other sites. The routes for each spoke must have unique ASNs and the sites must not have overlapping IP ranges. Each site can also send and receive data from the VPC as if they were using a standard VPN connection.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPN_CloudHub.html

NEW QUESTION 203

You need to create an Amazon Machine Image (AMI) for a customer for an application which does not appear to be part of the standard AWS AMI template that you can see in the AWS console. What are the alternative possibilities for creating an AMI on AWS?

- A. You can purchase an AMIs from a third party but cannot create your own AMI.
- B. You can purchase an AMIs from a third party or can create your own AMI.
- C. Only AWS can create AMIs and you need to wait till it becomes available.
- D. Only AWS can create AMIs and you need to request them to create one for you

Answer: B

Explanation:

You can purchase an AMIs from a third party, including AMIs that come with service contracts from organizations such as Red Hat. You can also create an AMI and sell it to other Amazon EC2 users. After you create an AMI, you can keep it private so that only you can use it, or you can share it with a specified list of AWS accounts. You can also make your custom AMI public so that the community can use it. Building a safe, secure, usable AMI for public consumption is a fairly straightforward process, if you follow a few simple guidelines.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/AMIs.html>

NEW QUESTION 204

Which one of the below is not an AWS Storage Service?

- A. Amazon S3
- B. Amazon Glacier
- C. Amazon CloudFront
- D. Amazon EBS

Answer: C

Explanation:

AWS Storage Services are: Amazon S3

Amazon Glacier Amazon EBS

AWS Storage Gateway

Reference: <https://console.aws.amazon.com/console>

NEW QUESTION 206

You are very concerned about security on your network because you have multiple programmers testing APIs and SDKs and you have no idea what is happening. You think CloudTrail may help but are not sure what it does. Which of the following statements best describes the AWS service CloudTrail?

- A. With AWS CloudTrail you can get a history of AWS API calls and related events for your account.
- B. With AWS CloudTrail you can get a history of IAM users for your account.
- C. With AWS CloudTrail you can get a history of S3 logfiles for your account.
- D. With AWS CloudTrail you can get a history of CloudFormation JSON scripts used for your account

Answer: A

Explanation:

With AWS CloudTrail, you can get a history of AWS API calls for your account, including API calls made via the AWS Management Console, the AWS SDKs, the command line tools, and higher-level AWS services. You can also identify which users and accounts called AWS APIs for services that support CloudTrail, the source IP address the calls were made from, and when the calls occurred.

You can identify which users and accounts called AWS for services that support CloudTrail, the source IP address the calls were made from, and when the calls occurred. You can integrate CloudTrail into applications using the API, automate trail creation for your organization, check the status of your trails, and control how administrators turn CloudTrail logging on and off.

Reference: http://docs.aws.amazon.com/awscloudtrail/latest/userguide/what_is_cloud_trail_top_level.html

NEW QUESTION 209

You receive a bill from AWS but are confused because you see you are incurring different costs for the exact same storage size in different regions on Amazon S3. You ask AWS why this is so. What response would you expect to receive from AWS?

- A. We charge less in different time zones.
- B. We charge less where our costs are less.
- C. This will balance out next bill.
- D. It must be a mistake.

Answer: B

Explanation:

Amazon S3 is storage for the internet. It's a simple storage service that offers software developers a highly-scalable, reliable, and low-latency data storage infrastructure at very low costs.

AWS charges less where their costs are less.

For example, their costs are lower in the US Standard Region than in the US West (Northern California) Region.

Reference: <https://aws.amazon.com/s3/faqs/>

NEW QUESTION 210

You are planning and configuring some EBS volumes for an application. In order to get the most performance out of your EBS volumes, you should attach them to an instance with enough to support your volumes.

- A. Redundancy
- B. Storage
- C. Bandwidth
- D. Memory

Answer: C

Explanation:

When you plan and configure EBS volumes for your application, it is important to consider the configuration of the instances that you will attach the volumes to. In order to get the most performance out of your EBS volumes, you should attach them to an instance with enough bandwidth to support your volumes, such as an EBS-optimized instance or an instance with 10 Gigabit network connectivity. This is especially important when you use General Purpose (SSD) or Provisioned IOPS (SSD) volumes, or when you stripe multiple volumes together in a RAID configuration.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-ec2-config.html>

NEW QUESTION 215

Can a single EBS volume be attached to multiple EC2 instances at the same time?

- A. Yes
- B. No
- C. Only for high-performance EBS volumes.
- D. Only when the instances are located in the US region

Answer: B

Explanation:

You can't attach an EBS volume to multiple EC2 instances. This is because it is equivalent to using a single hard drive with many computers at the same time.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/AmazonEBS.html>

NEW QUESTION 219

You have been asked to tighten up the password policies in your organization after a serious security breach, so you need to consider every possible security measure. Which of the following is not an account password policy for IAM Users that can be set?

- A. Force IAM users to contact an account administrator when the user has allowed his or her password to expire.
- B. A minimum password length.
- C. Force IAM users to contact an account administrator when the user has entered his password incorrectly.
- D. Prevent IAM users from reusing previous password

Answer: C

Explanation:

IAM users need passwords in order to access the AWS Management Console. (They do not need passwords if they will access AWS resources programmatically by using the CLI, AWS SDKs, or the APIs.)

You can use a password policy to do these things: Set a minimum password length.

Require specific character types, including uppercase letters, lowercase letters, numbers, and non-alphanumeric characters. Be sure to remind your users that passwords are case sensitive. Allow all IAM users to change their own passwords.

Require IAM users to change their password after a specified period of time (enable password expiration). Prevent IAM users from reusing previous passwords.

Force IAM users to contact an account administrator when the user has allowed his or her password to expire.

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/Using_ManagingPasswordPolicies.html

NEW QUESTION 222

Your organization is in the business of architecting complex transactional databases. For a variety of reasons, this has been done on EBS. What is AWS's recommendation for customers who have architected databases using EBS for backups?

- A. Backups to Amazon S3 be performed through the database management system.

- B. Backups to AWS Storage Gateway be performed through the database management system.
- C. If you take regular snapshots no further backups are required.
- D. Backups to Amazon Glacier be performed through the database management system

Answer: A

Explanation:

Data stored in Amazon EBS volumes is redundantly stored in multiple physical locations as part of normal operation of those services and at no additional charge. However, Amazon EBS replication is stored within the same availability zone, not across multiple zones; therefore, it is highly recommended that you conduct regular snapshots to Amazon S3 for long-term data durability.

For customers who have architected complex transactional databases using EBS, it is recommended that backups to Amazon S3 be performed through the database management system so that distributed transactions and logs can be checkpointed.

AWS does not perform backups of data that are maintained on virtual disks attached to running instances on Amazon EC2.

Reference: <http://d0.awsstatic.com/whitepapers/Security/AWS%20Security%20Whitepaper.pdf>

NEW QUESTION 226

You have three Amazon EC2 instances with Elastic IP addresses in the US East (Virginia) region, and you want to distribute requests across all three IPs evenly for users for whom US East (Virginia) is the appropriate region.

How many EC2 instances would be sufficient to distribute requests in other regions?

- A. 3
- B. 9
- C. 2
- D. 1

Answer: D

Explanation:

If your application is running on Amazon EC2 instances in two or more Amazon EC2 regions, and if you have more than one Amazon EC2 instance in one or more regions, you can use latency-based routing to route traffic to the correct region and then use weighted resource record sets to route traffic to instances within the region based on weights that you specify.

For example, suppose you have three Amazon EC2 instances with Elastic IP addresses in the US East (Virginia) region and you want to distribute requests across all three IPs evenly for users for whom US East (Virginia) is the appropriate region. Just one Amazon EC2 instance is sufficient in the other regions, although you can apply the same technique to many regions at once.

Reference: <http://docs.aws.amazon.com/Route53/latest/DeveloperGuide/Tutorials.html>

NEW QUESTION 230

A user has created a CloudFormation stack. The stack creates AWS services, such as EC2 instances, ELB, AutoScaling, and RDS. While creating the stack it created EC2, ELB and AutoScaling but failed to create RDS. What will CloudFormation do in this scenario?

- A. Rollback all the changes and terminate all the created services
- B. It will wait for the user's input about the error and correct the mistake after the input
- C. CloudFormation can never throw an error after launching a few services since it verifies all the steps before launching
- D. It will warn the user about the error and ask the user to manually create RDS

Answer: A

Explanation:

AWS CloudFormation is an application management tool which provides application modeling, deployment, configuration, management and related activities. The AWS CloudFormation stack is a collection of AWS resources which are created and managed as a single unit when AWS CloudFormation instantiates a template. If any of the services fails to launch, CloudFormation will rollback all the changes and terminate or delete all the created services.

Reference: <http://aws.amazon.com/cloudformation/faqs/>

NEW QUESTION 234

A major client who has been spending a lot of money on his internet service provider asks you to set up an AWS Direct Connection to try and save him some money. You know he needs high-speed connectivity. Which connection port speeds are available on AWS Direct Connect?

- A. 500Mbps and 1Gbps
- B. 1Gbps and 10Gbps
- C. 100Mbps and 1Gbps
- D. 1Gbps

Answer: B

Explanation:

AWS Direct Connect is a network service that provides an alternative to using the internet to utilize AWS cloud services.

Using AWS Direct Connect, data that would have previously been transported over the Internet can now be delivered through a private network connection between AWS and your datacenter or corporate network.

1Gbps and 10Gbps ports are available. Speeds of 50Mbps, 100Mbps, 200Mbps, 300Mbps, 400Mbps, and 500Mbps can be ordered from any APN partners supporting AWS Direct Connect.

Reference: <https://aws.amazon.com/directconnect/faqs/>

NEW QUESTION 236

In Amazon EC2, what is the limit of Reserved Instances per Availability Zone each month?

- A. 5
- B. 20
- C. 50
- D. 10

Answer: B

Explanation:

There are 20 Reserved Instances per Availability Zone in each month.
Reference: http://docs.aws.amazon.com/general/latest/gr/aws_service_limits.html

NEW QUESTION 240

Is it possible to get a history of all EC2 API calls made on your account for security analysis and operational troubleshooting purposes?

- A. Yes, by default, the history of your API calls is logged.
- B. Yes, you should turn on the CloudTrail in the AWS console.
- C. No, you can only get a history of VPC API calls.
- D. No, you cannot store history of EC2 API calls on Amazon.

Answer: B

Explanation:

To get a history of all EC2 API calls (including VPC and EBS) made on your account, you simply turn on CloudTrail in the AWS Management Console.
Reference: <https://aws.amazon.com/ec2/faqs/>

NEW QUESTION 242

You have just set up your first Elastic Load Balancer (ELB) but it does not seem to be configured properly. You discover that before you start using ELB, you have to configure the listeners for your load balancer. Which protocols does ELB use to support the load balancing of applications?

- A. HTTP and HTTPS
- B. HTTP, HTTPS, TCP, SSL and SSH
- C. HTTP, HTTPS, TCP, and SSL
- D. HTTP, HTTPS, TCP, SSL and SFTP

Answer: C

Explanation:

Before you start using Elastic Load Balancing (ELB), you have to configure the listeners for your load balancer. A listener is a process that listens for connection requests. It is configured with a protocol and a port number for front-end (client to load balancer) and back-end (load balancer to back-end instance) connections. Elastic Load Balancing supports the load balancing of applications using HTTP, HTTPS (secure HTTP), TCP, and SSL (secure TCP) protocols. The HTTPS uses the SSL protocol to establish secure connections over the HTTP layer. You can also use SSL protocol to establish secure connections over the TCP layer. The acceptable ports for both HTTPS/SSL and HTTP/TCP connections are 25, 80, 443, 465, 587, and 1024-65535.
Reference: <http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/elb-listener-config.html>

NEW QUESTION 245

After setting up some EC2 instances you now need to set up a monitoring solution to keep track of these instances and to send you an email when the CPU hits a certain threshold. Which statement below best describes what thresholds you can set to trigger a CloudWatch Alarm?

- A. Set a target value and choose whether the alarm will trigger when the value is greater than (>), greater than or equal to (>=), less than (<), or less than or equal to (<=) that value.
- B. Thresholds need to be set in IAM not CloudWatch
- C. Only default thresholds can be set you can't choose your own thresholds.
- D. Set a target value and choose whether the alarm will trigger when the value hits this threshold

Answer: A

Explanation:

Amazon CloudWatch is a monitoring service for AWS cloud resources and the applications you run on AWS. You can use Amazon CloudWatch to collect and track metrics, collect and monitor log files, and set alarms.
When you create an alarm, you first choose the Amazon CloudWatch metric you want it to monitor. Next, you choose the evaluation period (e.g., five minutes or one hour) and a statistical value to measure (e.g., Average or Maximum).
To set a threshold, set a target value and choose whether the alarm will trigger when the value is greater than (>), greater than or equal to (>=), less than (<), or less than or equal to (<=) that value.
Reference: <http://aws.amazon.com/cloudwatch/faqs/>

NEW QUESTION 247

After moving an E-Commerce website for a client from a dedicated server to AWS you have also set up auto scaling to perform health checks on the instances in your group and replace instances that fail these checks. Your client has come to you with his own health check system that he wants you to use as it has proved to be very useful prior to his site running on AWS. What do you think would be an appropriate response to this given all that you know about auto scaling?

- A. It is not possible to implement your own health check system
- B. You need to use AWS's health check system.
- C. It is not possible to implement your own health check system due to compatibility issues.
- D. It is possible to implement your own health check system and then send the instance's health information directly from your system to Cloud Watch.
- E. It is possible to implement your own health check system and then send the instance's health information directly from your system to Cloud Watch but only in the US East (Virginia) region.

Answer: C

Explanation:

Auto Scaling periodically performs health checks on the instances in your group and replaces instances that fail these checks. By default, these health checks use the results of EC2 instance status checks to determine the health of an instance. If you use a load balancer with your Auto Scaling group, you can optionally choose to include the results of Elastic Load Balancing health checks.

Auto Scaling marks an instance unhealthy if the calls to the Amazon EC2 action DescribeInstanceStatus returns any other state other than running, the system status shows impaired, or the calls to Elastic Load Balancing action DescribeInstanceHealth returns OutOfService in the instance state field.

After an instance is marked unhealthy because of an Amazon EC2 or Elastic Load Balancing health check, it is scheduled for replacement.

You can customize the health check conducted by your Auto Scaling group by specifying additional checks or by having your own health check system and then sending the instance's health information directly from your system to Auto Scaling.

Reference: <http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/healthcheck.html>

NEW QUESTION 249

When does the billing of an Amazon EC2 system begin?

- A. It starts when the Status column for your distribution changes from Creating to Deployed.
- B. It starts as soon as you click the create instance option on the main EC2 console.
- C. It starts when your instance reaches 720 instance hours.
- D. It starts when Amazon EC2 initiates the boot sequence of an AM instance.

Answer: D

Explanation:

Billing commences when Amazon EC2 initiates the boot sequence of an AM instance. Billing ends when the instance terminates, which could occur through a web services command, by running "shutdown -h", or through instance failure. When you stop an instance, Amazon shuts it down but doesn't charge hourly usage for a stopped instance, or data transfer fees, but charges for the storage for any Amazon EBS volumes.

Reference: <http://aws.amazon.com/ec2/faqs/>

NEW QUESTION 251

You have just discovered that you can upload your objects to Amazon S3 using Multipart Upload API. You start to test it out but are unsure of the benefits that it would provide. Which of the following is not a benefit of using multipart uploads?

- A. You can begin an upload before you know the final object size.
- B. Quick recovery from any network issues.
- C. Pause and resume object uploads.
- D. It's more secure than normal uploads.

Answer: D

Explanation:

Multipart upload in Amazon S3 allows you to upload a single object as a set of parts. Each part is a contiguous portion of the object's data. You can upload these object parts independently and in any order.

If transmission of any part fails, you can re-transmit that part without affecting other parts. After all parts of your object are uploaded, Amazon S3 assembles these parts and creates the object. In general, when

your object size reaches 100 MB, you should consider using multipart uploads instead of uploading the object in a single operation.

Using multipart upload provides the following advantages:

Improved throughput—You can upload parts in parallel to improve throughput.

Quick recovery from any network issues—Smaller part size minimizes the impact of restarting a failed upload due to a network error.

Pause and resume object uploads—You can upload object parts over time. Once you initiate a multipart upload there is no expiry; you must explicitly complete or abort the multipart upload.

Begin an upload before you know the final object size—You can upload an object as you are creating it. Reference:

<http://docs.aws.amazon.com/AmazonS3/latest/dev/uploadobjusingmpu.html>

NEW QUESTION 256

What is the data model of DynamoDB?

- A. Since DynamoDB is schema-less, there is no data model.
- B. "Items", with Keys and one or more Attribute; and "Attribute", with Name and Value.
- C. "Table", a collection of Items; "Items", with Keys and one or more Attribute; and "Attribute", with Name and Value.
- D. "Database", which is a set of "Tables", which is a set of "Items", which is a set of "Attributes".

Answer: C

Explanation:

The data model of DynamoDB is: "Table", a collection of Items;

"Items", with Keys and one or more Attribute; "Attribute", with Name and Value.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/DataModel.html>

NEW QUESTION 257

What happens to Amazon EBS root device volumes, by default, when an instance terminates?

- A. Amazon EBS root device volumes are moved to IAM.
- B. Amazon EBS root device volumes are copied into Amazon RDS.
- C. Amazon EBS root device volumes are automatically deleted.
- D. Amazon EBS root device volumes remain in the database until you delete the

Answer: C

Explanation:

By default, Amazon EBS root device volumes are automatically deleted when the instance terminates. Reference:

<http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/terminating-instances.html>

NEW QUESTION 259

Mike is appointed as Cloud Consultant in Netcrak Inc. Netcrak has the following VPCs set-up in the US East Region:

A VPC with CIDR block 10.10.0.0/16, a subnet in that VPC with CIDR block 10.10.1.0/24 A VPC with CIDR block 10.40.0.0/16, a subnet in that VPC with CIDR block 10.40.1.0/24

Netcrak Inc is trying to establish network connection between two subnets, a subnet with CIDR block 10.10.1.0/24 and another subnet with CIDR block 10.40.1.0/24. Which one of the following solutions should Mke recommend to Netcrak Inc?

- A. Create 2 Virtual Private Gateways and configure one with each VPC.
- B. Create one EC2 instance in each subnet, assign Elastic IPs to both instances, and configure a set up Site-to-Site VPN connection between both EC2 instances.
- C. Create a VPC Peering connection between both VPCs.
- D. Create 2 Internet Gateways, and attach one to each VP

Answer: C

Explanation:

A VPC peering connection is a networking connection between two VPCs that enables you to route traffic between them using private IP addresses. EC2 instances in either VPC can communicate with each other as if they are within the same network. You can create a VPC peering connection between your own VPCs, or with a VPC in another AWS account within a single region.

AWS uses the existing infrastructure of a VPC to create a VPC peering connection; it is neither a gateway nor a VPN connection, and does not rely on a separate piece of physical hardware.

Reference: <http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/vpc-peering.htm>

NEW QUESTION 263

You need to set up security for your VPC and you know that Amazon VPC provides two features that you can use to increase security for your VPC: Security groups and network access control lists (ACLs). You start to look into security groups first. Which statement below is incorrect in relation to security groups?

- A. Are stateful: Return traffic is automatically allowed, regardless of any rules.
- B. Evaluate all rules before deciding whether to allow traffic.
- C. Support allow rules and deny rules.
- D. Operate at the instance level (first layer of defense).

Answer: C

Explanation:

Amazon VPC provides two features that you can use to increase security for your VPC:

Security groups—Act as a firewall for associated Amazon EC2 instances, controlling both inbound and outbound traffic at the instance level and supports allow rules only.

Network access control lists (ACLs)—Act as a firewall for associated subnets, controlling both inbound and outbound traffic at the subnet level and supports allow rules and deny rules.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Security.html

NEW QUESTION 266

In relation to AWS CloudHSM, High-availability (HA) recovery is hands-off resumption by failed HA group members.

Prior to the introduction of this function, the HA feature provided redundancy and performance, but required that a failed/lost group member be reinstated.

- A. automatically
- B. periodically
- C. manually
- D. continuously

Answer: C

Explanation:

In relation to AWS CloudHSM, High-availability (HA) recovery is hands-off resumption by failed HA group members.

Prior to the introduction of this function, the HA feature provided redundancy and performance, but required that a failed/lost group member be manually reinstated.

Reference: <http://docs.aws.amazon.com/cloudhsm/latest/userguide/ha-best-practices.html>

NEW QUESTION 271

You have created a Route 53 latency record set from your domain to a machine in Northern Virginia and a similar record to a machine in Sydney.

When a user located in U S visits your domain he will be routed to:

- A. Northern Virginia
- B. Sydney
- C. Both, Northern Virginia and Sydney
- D. Depends on the Weighted Resource Record Sets

Answer: A

Explanation:

If your application is running on Amazon EC2 instances in two or more Amazon EC2 regions, and if you have more than one Amazon EC2 instance in one or more regions, you can use latency-based routing to route traffic to the correct region and then use weighted resource record sets to route traffic to instances within the region based on weights that you specify.

For example, suppose you have three Amazon EC2 instances with Elastic IP addresses in the US East (Virginia) region and you want to distribute requests across all three IPs evenly for users for whom US East (Virginia) is the appropriate region. Just one Amazon EC2 instance is sufficient in the other regions, although you can apply the same technique to many regions at once.

Reference: <http://docs.aws.amazon.com/Route53/latest/DeveloperGuide/Tutorials.html>

NEW QUESTION 274

Any person or application that interacts with AWS requires security credentials. AWS uses these credentials to identify who is making the call and whether to allow the requested access. You have just set up a VPC network for a client and you are now thinking about the best way to secure this network. You set up a security group called vpcsecuritygroup. Which following statement is true in respect to the initial settings that will be applied to this security group if you choose to use the default settings for this group?

- A. Allow all inbound traffic and allow no outbound traffic.
- B. Allow no inbound traffic and allow all outbound traffic.
- C. Allow inbound traffic on port 80 only and allow all outbound traffic.
- D. Allow all inbound traffic and allow all outbound traffic.

Answer: B

Explanation:

Amazon VPC provides advanced security features such as security groups and network access control lists to enable inbound and outbound filtering at the instance level and subnet level.

AWS assigns each security group a unique ID in the form sg-xxxxxxx. The following are the initial settings for a security group that you create:

Allow no inbound traffic Allow all outbound traffic

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/using-network-security.html>

NEW QUESTION 278

You are using Amazon SES as an email solution but are unsure of what its limitations are. Which statement below is correct in regards to that?

- A. New Amazon SES users who have received production access can send up to 1,000 emails per 24-hour period, at a maximum rate of 10 emails per second.
- B. Every Amazon SES sender has the same set of sending limits.
- C. Sending limits are based on messages rather than on recipients.
- D. Every Amazon SES sender has a unique set of sending limits.

Answer: D

Explanation:

Amazon Simple Email Service (Amazon SES) is a highly scalable and cost-effective email-sending service for businesses and developers. Amazon SES eliminates the complexity and expense of building an in-house email solution or licensing, installing, and operating a third-party email service for this type of email communication.

Every Amazon SES sender has a unique set of sending limits, which are calculated by Amazon SES on an ongoing basis:

Sending quota — the maximum number of emails you can send in a 24-hour period. Maximum send rate — the maximum number of emails you can send per second.

New Amazon SES users who have received production access can send up to 10,000 emails per 24-hour period, at a maximum rate of 5 emails per second.

Amazon SES automatically adjusts these limits upward, as long as you send high-quality email. If your existing quota is not adequate for your needs and the system has not automatically increased your quota, you can submit an SES Sending Quota Increase case at any time.

Sending limits are based on recipients rather than on messages. You can check your sending limits at any time by using the Amazon SES console.

Note that if your email is detected to be of poor or QUESTION able quality (e.g., high complaint rates, high bounce rates, spam, or abusive content), Amazon SES might temporarily or permanently reduce your permitted send volume, or take other action as AWS deems appropriate.

Reference: <https://aws.amazon.com/ses/faqs/>

NEW QUESTION 280

Having just set up your first Amazon Virtual Private Cloud (Amazon VPC) network, which defined a default network interface, you decide that you need to create and attach an additional network interface, known as an elastic network interface (ENI) to one of your instances. Which of the following statements is true regarding attaching network interfaces to your instances in your VPC?

- A. You can attach 5 ENIs per instance type.
- B. You can attach as many ENIs as you want.
- C. The number of ENIs you can attach varies by instance type.
- D. You can attach 100 ENIs total regardless of instance type.

Answer: C

Explanation:

Each instance in your VPC has a default network interface that is assigned a private IP address from the IP address range of your VPC. You can create and attach an additional network interface, known as an elastic network interface (ENI), to any instance in your VPC. The number of ENIs you can attach varies by instance type.

NEW QUESTION 283

A for a VPC is a collection of subnets (typically private) that you may want to designate for your backend RDS DB Instances.

- A. DB Subnet Set
- B. RDS Subnet Group
- C. DB Subnet Group
- D. DB Subnet Collection

Answer: C

Explanation:

DB Subnet Groups are a set of subnets (one per Availability Zone of a particular region) designed for your DB instances that reside in a VPC. They make it easy to manage Multi-AZ deployments as well as the conversion from a Single-AZ to a Multi-AZ one.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Overview.RDSVPC.html>

NEW QUESTION 284

A friend tells you he is being charged \$100 a month to host his WordPress website, and you tell him you can move it to AWS for him and he will only pay a fraction

of that, which makes him very happy. He then tells you he is being charged \$50 a month for the domain, which is registered with the same people that set it up, and he asks if it's possible to move that to AWS as well. You tell him you aren't sure, but will look into it. Which of the following statements is true in regards to transferring domain names to AWS?

- A. You can't transfer existing domains to AWS.
- B. You can transfer existing domains into Amazon Route 53's management.
- C. You can transfer existing domains via AWS Direct Connect.
- D. You can transfer existing domains via AWS Import/Export

Answer: B

Explanation:

With Amazon Route 53, you can create and manage your public DNS records with the AWS Management Console or with an easy-to-use API. If you need a domain name, you can find an available name and register it using Amazon Route 53. You can also transfer existing domains into Amazon Route 53's management.

Reference: <http://aws.amazon.com/route53/>

NEW QUESTION 289

AWS Identity and Access Management is a web service that enables Amazon Web Services (AWS) customers to manage users and user permissions in AWS. In addition to supporting IAM user policies, some services support resource-based permissions. Which of the following services are supported by resource-based permissions?

- A. Amazon SNS, and Amazon SQS and AWS Direct Connect.
- B. Amazon S3 and Amazon SQS and Amazon ElastiCache.
- C. Amazon S3, Amazon SNS, Amazon SQS, Amazon Glacier and Amazon EBS.
- D. Amazon Glacier, Amazon SNS, and Amazon CloudWatch

Answer: C

Explanation:

In addition to supporting IAM user policies, some services support resource-based permissions, which let you attach policies to the service's resources instead of to IAM users or groups. Resource-based permissions are supported by Amazon S3, Amazon SNS, Amazon SQS, Amazon Glacier and Amazon EBS.

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/Using_SpecificProducts.htm

NEW QUESTION 292

You are setting up your first Amazon Virtual Private Cloud (Amazon VPC) network so you decide you should probably use the AWS Management Console and the VPC Wizard. Which of the following is not an option for network architectures after launching the "Start VPC Wizard" in Amazon VPC page on the AWS Management Console?

- A. VPC with a Single Public Subnet Only
- B. VPC with a Public Subnet Only and Hardware VPN Access
- C. VPC with Public and Private Subnets and Hardware VPN Access
- D. VPC with a Private Subnet Only and Hardware VPN Access

Answer: B

Explanation:

Amazon VPC enables you to build a virtual network in the AWS cloud - no VPNs, hardware, or physical datacenters required.

Your AWS resources are automatically provisioned in a ready-to-use default VPC. You can choose to create additional VPCs by going to Amazon VPC page on the AWS Management Console and click on the "Start VPC Wizard" button.

You'll be presented with four basic options for network architectures. After selecting an option, you can modify the size and IP address range of the VPC and its subnets. If you select an option with Hardware VPN Access, you will need to specify the IP address of the VPN hardware on your network. You can modify the VPC to add more subnets or add or remove gateways at any time after the VPC has been created.

The four options are:

VPC with a Single Public Subnet Only VPC with Public and Private Subnets

VPC with Public and Private Subnets and Hardware VPN Access VPC with a Private Subnet Only and Hardware VPN Access Reference:

<https://aws.amazon.com/vpc/faqs/>

NEW QUESTION 297

A user is trying to launch a similar EC2 instance from an existing instance with the option "Launch More like this". The AMI of the selected instance is deleted. What will happen in this case?

- A. AWS does not need an AMI for the "Launch more like this" option
- B. AWS will launch the instance but will not create a new AMI
- C. AWS will create a new AMI and launch the instance
- D. AWS will throw an error saying that the AMI is deregistered

Answer: D

Explanation:

If the user has deregistered the AMI of an EC2 instance and is trying to launch a similar instance with the option "Launch more like this", AWS will throw an error saying that the AMI is deregistered or not available.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/launching-instance.html>

NEW QUESTION 301

A company wants to review the security requirements of Glacier. Which of the below mentioned statements is true with respect to the AWS Glacier data security?

- A. All data stored on Glacier is protected with AES-256 serverside encryption.
- B. All data stored on Glacier is protected with AES-128 serverside encryption.

- C. The user can set the serverside encryption flag to encrypt the data stored on Glacier.
- D. The data stored on Glacier is not encrypted by default

Answer: A

Explanation:

For Amazon Web Services, all the data stored on Amazon Glacier is protected using serverside encryption. AWS generates separate unique encryption keys for each Amazon Glacier archive, and encrypts it using AES-256. The encryption key then encrypts itself using AES-256 with a master key that is stored in a secure location.

Reference: http://media.amazonwebservices.com/AWS_Security_Best_Practices.pdf

NEW QUESTION 306

A friend wants you to set up a small BitTorrent storage area for him on Amazon S3. You tell him it is highly unlikely that AWS would allow such a thing in their infrastructure. However you decide to investigate. Which of the following statements best describes using BitTorrent with Amazon S3?

- A. Amazon S3 does not support the BitTorrent protocol because it is used for pirated software.
- B. You can use the BitTorrent protocol but only for objects that are less than 100 GB in size.
- C. You can use the BitTorrent protocol but you need to ask AWS for specific permissions first.
- D. You can use the BitTorrent protocol but only for objects that are less than 5 GB in size

Answer: D

Explanation:

BitTorrent is an open, peer-to-peer protocol for distributing files. You can use the BitTorrent protocol to retrieve any publicly-accessible object in Amazon S3. Amazon S3 supports the BitTorrent protocol so that developers can save costs when distributing content at high scale. Amazon S3 is useful for simple, reliable storage of any data. The default distribution mechanism for Amazon S3 data is via client/server download. In client/server distribution, the entire object is transferred point-to-point from Amazon S3 to every authorized user who requests that object. While client/server delivery is appropriate for a wide variety of use cases, it is not optimal for everybody. Specifically, the costs of client/server distribution increase linearly as the number of users downloading objects increases. This can make it expensive to distribute popular objects.

BitTorrent addresses this problem by recruiting the very clients that are downloading the object as distributors themselves: Each client downloads some pieces of the object from Amazon S3 and some from other clients, while simultaneously uploading pieces of the same object to other interested "peers." The benefit for publishers is that for large, popular files the amount of data actually supplied by Amazon S3 can be substantially lower than what it would have been serving the same clients via client/server download. Less data transferred means lower costs for the publisher of the object.

Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/S3Torrent.html>

NEW QUESTION 308

In the most recent company meeting, your CEO focused on the fact that everyone in the organization needs to make sure that all of the infrastructure that is built is truly scalable. Which of the following statements is incorrect in reference to scalable architecture?

- A. A scalable service is capable of handling heterogeneity.
- B. A scalable service is resilient.
- C. A scalable architecture won't be cost effective as it grows.
- D. Increasing resources results in a proportional increase in performance

Answer: C

Explanation:

In AWS it is critical to build a scalable architecture in order to take advantage of a scalable infrastructure. The cloud is designed to provide conceptually infinite scalability. However, you cannot leverage all that scalability in infrastructure if your architecture is not scalable. Both have to work together. You will have to identify the monolithic components and bottlenecks in your architecture, identify the areas where you cannot leverage the on-demand provisioning capabilities in your architecture, and work to refactor your application, in order to leverage the scalable infrastructure and take advantage of the cloud.

Characteristics of a truly scalable application:

Increasing resources results in a proportional increase in performance A scalable service is capable of handling heterogeneity

A scalable service is operationally efficient A scalable service is resilient

A scalable service should become more cost effective when it grows (Cost per unit reduces as the number of units increases)

Reference: http://media.amazonwebservices.com/AWS_Cloud_Best_Practices.pdf

NEW QUESTION 310

You are playing around with setting up stacks using JSON templates in CloudFormation to try and understand them a little better. You have set up about 5 or 6 but now start to wonder if you are being charged for these stacks. What is AWS's billing policy regarding stack resources?

- A. You are not charged for the stack resources if they are not taking any traffic.
- B. You are charged for the stack resources for the time they were operating (even if you deleted the stack right away)
- C. You are charged for the stack resources for the time they were operating (but not if you deleted the stack within 60 minutes)
- D. You are charged for the stack resources for the time they were operating (but not if you deleted the stack within 30 minutes)

Answer: B

Explanation:

A stack is a collection of AWS resources that you can manage as a single unit. In other words, you can create, update, or delete a collection of resources by creating, updating, or deleting stacks. All the resources in a stack are defined by the stack's AWS CloudFormation template. A stack, for instance, can include all the resources required to run a web application, such as a web server, a database, and networking rules. If you no longer require that web application, you can simply delete the stack, and all of its related resources are deleted.

You are charged for the stack resources for the time they were operating (even if you deleted the stack right away).

Reference: <http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/stacks.html>

NEW QUESTION 313

After deploying a new website for a client on AWS, he asks if you can set it up so that if it fails it can be automatically redirected to a backup website that he has stored on a dedicated server elsewhere. You are wondering whether Amazon Route 53 can do this. Which statement below is correct in regards to Amazon Route

53?

- A. Amazon Route 53 can't help detect an outage
- B. You need to use another service.
- C. Amazon Route 53 can help detect an outage of your website and redirect your end users to alternate locations.
- D. Amazon Route 53 can help detect an outage of your website but can't redirect your end users to alternate locations.
- E. Amazon Route 53 can't help detect an outage of your website, but can redirect your end users to alternate locations.

Answer: B

Explanation:

With DNS Failover, Amazon Route 53 can help detect an outage of your website and redirect your end users to alternate locations where your application is operating properly.

Reference:

<http://aws.amazon.com/about-aws/whats-new/2013/02/11/announcing-dns-failover-for-route-53/>

NEW QUESTION 318

In Route 53, what does a Hosted Zone refer to?

- A. A hosted zone is a collection of geographical load balancing rules for Route 53.
- B. A hosted zone is a collection of resource record sets hosted by Route 53.
- C. A hosted zone is a selection of specific resource record sets hosted by CloudFront for distribution to Route 53.
- D. A hosted zone is the Edge Location that hosts the Route 53 records for a use

Answer: B

Explanation:

A Hosted Zone refers to a selection of resource record sets hosted by Route 53.

Reference: <http://docs.aws.amazon.com/Route53/latest/DeveloperGuide/AboutHostedZones.html>

NEW QUESTION 320

All Amazon EC2 instances are assigned two IP addresses at launch. Which are those?

- A. 2 Elastic IP addresses
- B. A private IP address and an Elastic IP address
- C. A public IP address and an Elastic IP address
- D. A private IP address and a public IP address

Answer: D

Explanation:

In Amazon EC2-Classic every instance is given two IP Addresses: a private IP address and a public IP address

Reference:

<http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/using-instance-addressing.html#differences>

NEW QUESTION 322

You want to establish a dedicated network connection from your premises to AWS in order to save money by transferring data directly to AWS rather than through your internet service provider. You are sure there must be some other benefits beyond cost savings. Which of the following would not be considered a benefit if you were to establish such a connection?

- A. Elasticity
- B. Compatibility with all AWS services.
- C. Private connectMty to your Amazon VPC.
- D. Everything listed is a benefi

Answer: D

Explanation:

AWS Direct Connect makes it easy to establish a dedicated network connection from your premises to AWS.

Using AWS Direct Connect, you can establish private connectMty between AWS and your datacenter, office, or colocation environment, which in many cases can reduce your network costs, increase bandwidth throughput, and provide a more consistent network experience than internet-based connections.

You could expect the following benefits if you use AWS Direct Connect. Reduced bandwidth costs

Consistent network performance Compatibility with all AWS services Private connectMty to your Amazon VPC Elasticity

Simplicity

Reference: <http://aws.amazon.com/directconnect/>

NEW QUESTION 323

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual AWS-Solution-Architect-Associate Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the AWS-Solution-Architect-Associate Product From:

<https://www.2passeasy.com/dumps/AWS-Solution-Architect-Associate/>

Money Back Guarantee

AWS-Solution-Architect-Associate Practice Exam Features:

- * AWS-Solution-Architect-Associate Questions and Answers Updated Frequently
- * AWS-Solution-Architect-Associate Practice Questions Verified by Expert Senior Certified Staff
- * AWS-Solution-Architect-Associate Most Realistic Questions that Guarantee you a Pass on Your First Try
- * AWS-Solution-Architect-Associate Practice Test Questions in Multiple Choice Formats and Updates for 1 Year