



# **Amazon-Web-Services**

## **Exam Questions ANS-C01**

AWS Certified Advanced Networking Specialty Exam

## About ExamBible

*[Your Partner of IT Exam](#)*

## Found in 1998

ExamBible is a company specialized on providing high quality IT exam practice study materials, especially Cisco CCNA, CCDA, CCNP, CCIE, Checkpoint CCSE, CompTIA A+, Network+ certification practice exams and so on. We guarantee that the candidates will not only pass any IT exam at the first attempt but also get profound understanding about the certificates they have got. There are so many alike companies in this industry, however, ExamBible has its unique advantages that other companies could not achieve.

## Our Advances

### \* 99.9% Uptime

All examinations will be up to date.

### \* 24/7 Quality Support

We will provide service round the clock.

### \* 100% Pass Rate

Our guarantee that you will pass the exam.

### \* Unique Gurantee

If you do not pass the exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

#### NEW QUESTION 1

A company's network engineer needs to design a new solution to help troubleshoot and detect network anomalies. The network engineer has configured Traffic Mirroring. However, the mirrored traffic is overwhelming the Amazon EC2 instance that is the traffic mirror target. The EC2 instance hosts tools that the company's security team uses to analyze the traffic. The network engineer needs to design a highly available solution that can scale to meet the demand of the mirrored traffic.

Which solution will meet these requirements?

- A. Deploy a Network Load Balancer (NLB) as the traffic mirror target
- B. Behind the NL
- C. deploy a fleet of EC2 instances in an Auto Scaling group
- D. Use Traffic Mirroring as necessary.
- E. Deploy an Application Load Balancer (ALB) as the traffic mirror target
- F. Behind the ALB, deploy a fleet of EC2 instances in an Auto Scaling group
- G. Use Traffic Mirroring only during non-business hours.
- H. Deploy a Gateway Load Balancer (GLB) as the traffic mirror target
- I. Behind the GL
- J. deploy a fleet of EC2 instances in an Auto Scaling group
- K. Use Traffic Mirroring as necessary.
- L. Deploy an Application Load Balancer (ALB) with an HTTPS listener as the traffic mirror target
- M. Behind the AL
- N. deploy a fleet of EC2 instances in an Auto Scaling group
- O. Use Traffic Mirroring only during active events or business hours.

**Answer:** A

#### NEW QUESTION 2

A network engineer must develop an AWS CloudFormation template that can create a virtual private gateway, a customer gateway, a VPN connection, and static routes in a route table. During testing of the template, the network engineer notes that the CloudFormation template has encountered an error and is rolling back. What should the network engineer do to resolve the error?

- A. Change the order of resource creation in the CloudFormation template.
- B. Add the DependsOn attribute to the resource declaration for the virtual private gateway
- C. Specify the route table entry resource.
- D. Add a wait condition in the template to wait for the creation of the virtual private gateway.
- E. Add the DependsOn attribute to the resource declaration for the route table entry
- F. Specify the virtual private gateway resource.

**Answer:** D

#### NEW QUESTION 3

An IoT company sells hardware sensor modules that periodically send out temperature, humidity, pressure, and location data through the MQTT messaging protocol. The hardware sensor modules send this data to the company's on-premises MQTT brokers that run on Linux servers behind a load balancer. The hardware sensor modules have been hardcoded with public IP addresses to reach the brokers.

The company is growing and is acquiring customers across the world. The existing solution can no longer scale and is introducing additional latency because of the company's global presence. As a result, the company decides to migrate its entire infrastructure from on premises to the AWS Cloud. The company needs to migrate without reconfiguring the hardware sensor modules that are already deployed across the world. The solution also must minimize latency. The company migrates the MQTT brokers to run on Amazon EC2 instances. What should the company do next to meet these requirements?

- A. Place the EC2 instances behind a Network Load Balancer (NLB). Configure TCP listener
- B. Use Bring Your Own IP (BYOIP) from the on-premises network with the NLB.
- C. Place the EC2 instances behind a Network Load Balancer (NLB). Configure TCP listener
- D. Create an AWS Global Accelerator accelerator in front of the NLB. Use Bring Your Own IP (BYOIP) from the on-premises network with Global Accelerator.
- E. Place the EC2 instances behind an Application Load Balancer (ALB). Configure TCP listener
- F. Create an AWS Global Accelerator accelerator in front of the AL
- G. Use Bring Your Own IP (BYOIP) from the on-premises network with Global Accelerator
- H. Place the EC2 instances behind an Amazon CloudFront distribution
- I. Use Bring Your Own IP (BYOIP) from the on-premises network with CloudFront.

**Answer:** B

#### NEW QUESTION 4

A company deploys a new web application on Amazon EC2 instances. The application runs in private subnets in three Availability Zones behind an Application Load Balancer (ALB). Security auditors require encryption of all connections. The company uses Amazon Route 53 for DNS and uses AWS Certificate Manager (ACM) to automate SSL/TLS certificate provisioning. SSL/TLS connections are terminated on the ALB.

The company tests the application with a single EC2 instance and does not observe any problems. However, after production deployment, users report that they can log in but that they cannot use the application. Every new web request restarts the login process.

What should a network engineer do to resolve this issue?

- A. Modify the ALB listener configuration
- B. Edit the rule that forwards traffic to the target group
- C. Change the rule to enable group-level stickiness
- D. Set the duration to the maximum application session length.
- E. Replace the ALB with a Network Load Balance
- F. Create a TLS listener
- G. Create a new target group with the protocol type set to TLS. Register the EC2 instance
- H. Modify the target group configuration by enabling the stickiness attribute.
- I. Modify the ALB target group configuration by enabling the stickiness attribute
- J. Use an application-based cookie

- K. Set the duration to the maximum application session length.
- L. Remove the AL
- M. Create an Amazon Route 53 rule with a failover routing policy for the application nam
- N. Configure ACM to issue certificates for each EC2 instance.

**Answer: C**

#### NEW QUESTION 5

A company recently migrated its Amazon EC2 instances to VPC private subnets to satisfy a security compliance requirement. The EC2 instances now use a NAT gateway for internet access. After the migration, some long-running database queries from private EC2 instances to a publicly accessible third-party database no longer receive responses. The database query logs reveal that the queries successfully completed after 7 minutes but that the client EC2 instances never received the response.

Which configuration change should a network engineer implement to resolve this issue?

- A. Configure the NAT gateway timeout to allow connections for up to 600 seconds.
- B. Enable enhanced networking on the client EC2 instances.
- C. Enable TCP keepalive on the client EC2 instances with a value of less than 300 seconds.
- D. Close idle TCP connections through the NAT gateway.

**Answer: C**

#### Explanation:

When a TCP connection is idle for a long time, it may be terminated by network devices, including the NAT gateway. By enabling TCP keepalive, the client EC2 instances can periodically send packets to the third-party database to indicate that the connection is still active, preventing it from being terminated prematurely.

#### NEW QUESTION 6

A network engineer is designing the architecture for a healthcare company's workload that is moving to the AWS Cloud. All data to and from the on-premises environment must be encrypted in transit. All traffic also must be inspected in the cloud before the traffic is allowed to leave the cloud and travel to the on-premises environment or to the internet.

The company will expose components of the workload to the internet so that patients can reserve appointments. The architecture must secure these components and protect them against DDoS attacks. The architecture also must provide protection against financial liability for services that scale out during a DDoS event.

Which combination of steps should the network engineer take to meet all these requirements for the workload? (Choose three.)

- A. Use Traffic Mirroring to copy all traffic to a fleet of traffic capture appliances.
- B. Set up AWS WAF on all network components.
- C. Configure an AWS Lambda function to create Deny rules in security groups to block malicious IP addresses.
- D. Use AWS Direct Connect with MACsec support for connectivity to the cloud.
- E. Use Gateway Load Balancers to insert third-party firewalls for inline traffic inspection.
- F. Configure AWS Shield Advanced and ensure that it is configured on all public assets.

**Answer: DEF**

#### Explanation:

To meet the requirements for the healthcare company's workload that is moving to the AWS Cloud, the network engineer should take the following steps:

- Use AWS Direct Connect with MACsec support for connectivity to the cloud to ensure that all data to and from the on-premises environment is encrypted in transit (Option D).
- Use Gateway Load Balancers to insert third-party firewalls for inline traffic inspection to inspect all traffic in the cloud before it is allowed to leave (Option E).
- Configure AWS Shield Advanced and ensure that it is configured on all public assets to secure components exposed to the internet against DDoS attacks and provide protection against financial liability for services that scale out during a DDoS event (Option F).

These steps will help ensure that all data is encrypted in transit, all traffic is inspected before leaving the cloud, and components exposed to the internet are secured against DDoS attacks.

#### NEW QUESTION 7

A company is using custom DNS servers that run BIND for name resolution in its VPCs. The VPCs are deployed across multiple AWS accounts that are part of the same organization in AWS Organizations. All the VPCs are connected to a transit gateway. The BIND servers are running in a central VPC and are configured to forward all queries for an on-premises DNS domain to DNS servers that are hosted in an on-premises data center. To ensure that all the VPCs use the custom DNS servers, a network engineer has configured a VPC DHCP options set in all the VPCs that specifies the custom DNS servers to be used as domain name servers.

Multiple development teams in the company want to use Amazon Elastic File System (Amazon EFS). A development team has created a new EFS file system but cannot mount the file system to one of its Amazon EC2 instances. The network engineer discovers that the EC2 instance cannot resolve the IP address for the EFS mount point fs-33444567d.efs.us-east-1.amazonaws.com. The network engineer needs to implement a solution so that development teams throughout the organization can mount EFS file systems.

Which combination of steps will meet these requirements? (Choose two.)

- A. Configure the BIND DNS servers in the central VPC to forward queries for fs.efs.us-east-1.amazonaws.com to the Amazon provided DNS server (169.254.169.253).
- B. Create an Amazon Route 53 Resolver outbound endpoint in the central VP
- C. Update all the VPC DHCP options sets to use AmazonProvidedDNS for name resolution.
- D. Create an Amazon Route 53 Resolver inbound endpoint in the central VPCUpdate all the VPC DHCP options sets to use the Route 53 Resolver inbound endpoint in the central VPC for name resolution.
- E. Create an Amazon Route 53 Resolver rule to forward queries for the on-premises domain to the on-premises DNS server
- F. Share the rule with the organization by using AWS Resource Access Manager (AWS RAM). Associate the rule with all the VPCs.
- G. Create an Amazon Route 53 private hosted zone for the fs.efs.us-east-1.amazonaws.com domain. Associate the private hosted zone with the VPC where the EC2 instance is deploye
- H. Create an A record for fs-33444567d.efs.us-east-1.amazonaws.com in the private hosted zon
- I. Configure the A record to return the mount target of the EFS mount point.

**Answer: BD**

**Explanation:**

Option B suggests using Amazon Route 53 Resolver outbound endpoint, which would replace the existing BIND DNS servers with the AmazonProvidedDNS for name resolution. However, the scenario specifically mentions that the company is using custom DNS servers that run BIND for name resolution in its VPCs, so this solution would not work. Option D suggests creating a Route 53 Resolver rule to forward queries for the on-premises domain to the on-premises DNS servers, which would not address the issue of resolving the EFS mount point. The problem is not with resolving queries for the on-premises domain, but rather with resolving the IP address for the EFS mount point.

**NEW QUESTION 8**

An IoT company sells hardware sensor modules that periodically send out temperature, humidity, pressure, and location data through the MQTT messaging protocol. The hardware sensor modules send this data to the company's on-premises MQTT brokers that run on Linux servers behind a load balancer. The hardware sensor modules have been hardcoded with public IP addresses to reach the brokers.

The company is growing and is acquiring customers across the world. The existing solution can no longer scale and is introducing additional latency because of the company's global presence. As a result, the company decides to migrate its entire infrastructure from on premises to the AWS Cloud. The company needs to migrate without reconfiguring the hardware sensor modules that are already deployed across the world. The solution also must minimize latency.

The company migrates the MQTT brokers to run on Amazon EC2 instances. What should the company do next to meet these requirements?

- A. Place the EC2 instances behind a Network Load Balancer (NLB). Configure TCP listener
- B. Use Bring Your Own IP (BYOIP) from the on-premises network with the NLB.
- C. Place the EC2 instances behind a Network Load Balancer (NLB). Configure TCP listener
- D. Create an AWS Global Accelerator accelerator in front of the NLB. Use Bring Your Own IP (BYOIP) from the on-premises network with Global Accelerator.
- E. Place the EC2 instances behind an Application Load Balancer (ALB). Configure TCP listener
- F. Create an AWS Global Accelerator accelerator in front of the ALB
- G. Use Bring Your Own IP (BYOIP) from the on-premises network with Global Accelerator
- H. Place the EC2 instances behind an Amazon CloudFront distribution
- I. Use Bring Your Own IP (BYOIP) from the on-premises network with CloudFront.

**Answer: B**

**NEW QUESTION 9**

A company is planning to create a service that requires encryption in transit. The traffic must not be decrypted between the client and the backend of the service. The company will implement the service by using the gRPC protocol over TCP port 443. The service will scale up to thousands of simultaneous connections. The backend of the service will be hosted on an Amazon Elastic Kubernetes Service (Amazon EKS) cluster with the Kubernetes Cluster Autoscaler and the Horizontal Pod Autoscaler configured. The company needs to use mutual TLS for two-way authentication between the client and the backend.

Which solution will meet these requirements?

- A. Install the AWS Load Balancer Controller for Kubernetes
- B. Using that controller, configure a Network Load Balancer with a TCP listener on port 443 to forward traffic to the IP addresses of the backend service Pods.
- C. Install the AWS Load Balancer Controller for Kubernetes
- D. Using that controller, configure an Application Load Balancer with an HTTPS listener on port 443 to forward traffic to the IP addresses of the backend service Pods.
- E. Create a target group
- F. Add the EKS managed node group's Auto Scaling group as a target. Create an Application Load Balancer with an HTTPS listener on port 443 to forward traffic to the target group.
- G. Create a target group
- H. Add the EKS managed node group's Auto Scaling group as a target
- I. Create a Network Load Balancer with a TLS listener on port 443 to forward traffic to the target group.

**Answer: B**

**Explanation:**

<https://docs.aws.amazon.com/elasticloadbalancing/latest/application/load-balancer-target-groups.html#target-group>

**NEW QUESTION 10**

A company uses a hybrid architecture and has an AWS Direct Connect connection between its on-premises data center and AWS. The company has production applications that run in the on-premises data center. The company also has production applications that run in a VPC. The applications that run in the on-premises data center need to communicate with the applications that run in the VPC. The company is using corp.example.com as the domain name for the on-premises resources and is using an Amazon Route 53 private hosted zone for aws.example.com to host the VPC resources.

The company is using an open-source recursive DNS resolver in a VPC subnet and is using a DNS resolver in the on-premises data center. The company's on-premises DNS resolver has a forwarder that directs requests for the aws.example.com domain name to the DNS resolver in the VPC. The DNS resolver in the VPC has a forwarder that directs requests for the corp.example.com domain name to the DNS resolver in the on-premises data center. The company has decided to replace the open-source recursive DNS resolver with Amazon Route 53 Resolver endpoints.

Which combination of steps should a network engineer take to make this replacement? (Choose three.)

- A. Create a Route 53 Resolver rule to forward aws.example.com domain queries to the IP addresses of the outbound endpoint.
- B. Configure the on-premises DNS resolver to forward aws.example.com domain queries to the IP addresses of the inbound endpoint.
- C. Create a Route 53 Resolver inbound endpoint and a Route 53 Resolver outbound endpoint.
- D. Create a Route 53 Resolver rule to forward aws.example.com domain queries to the IP addresses of the inbound endpoint.
- E. Create a Route 53 Resolver rule to forward corp.example.com domain queries to the IP address of the on-premises DNS resolver.
- F. Configure the on-premises DNS resolver to forward aws.example.com queries to the IP addresses of the outbound endpoint.

**Answer: BCE**

**Explanation:**

To replace the open-source recursive DNS resolver with Amazon Route 53 Resolver endpoints in a hybrid architecture where on-premises applications need to communicate with applications running in a VPC, a network engineer should take the following steps:

- Create a Route 53 Resolver inbound endpoint and a Route 53 Resolver outbound endpoint. (Option C)
- Configure the on-premises DNS resolver to forward aws.example.com domain queries to the IP addresses of the inbound endpoint. (Option B)
- Create a Route 53 Resolver rule to forward corp.example.com domain queries to the IP address of the on-premises DNS resolver. (Option E)

These steps will allow for seamless replacement of the open-source recursive DNS resolver with Amazon Route 53 Resolver endpoints and enable communication.



between on-premises and VPC applications.

#### NEW QUESTION 10

A company's network engineer is designing an active-passive connection to AWS from two on-premises data centers. The company has set up AWS Direct Connect connections between the on-premises data centers and AWS. From each location, the company is using a transit VIF that connects to a Direct Connect gateway that is associated with a transit gateway.

The network engineer must ensure that traffic from AWS to the data centers is routed first to the primary data center. The traffic should be routed to the failover data center only in the case of an outage.

Which solution will meet these requirements?

- A. Set the BGP community tag for all prefixes from the primary data center to 7224:7100. Set the BGP community tag for all prefixes from the failover data center to 7224:7300
- B. Set the BGP community tag for all prefixes from the primary data center to 7224:7300. Set the BGP community tag for all prefixes from the failover data center to 7224:7100
- C. Set the BGP community tag for all prefixes from the primary data center to 7224:9300. Set the BGP community tag for all prefixes from the failover data center to 7224:9100
- D. Set the BGP community tag for all prefixes from the primary data center to 7224:9100. Set the BGP community tag for all prefixes from the failover data center to 7224:9300

**Answer:** B

#### NEW QUESTION 13

A company hosts an application on Amazon EC2 instances behind an Application Load Balancer (ALB). The company recently experienced a network security breach. A network engineer must collect and analyze logs that include the client IP address, target IP address, target port, and user agent of each user that accesses the application.

What is the MOST operationally efficient solution that meets these requirements?

- A. Configure the ALB to store logs in an Amazon S3 bucket
- B. Download the files from Amazon S3, and use a spreadsheet application to analyze the logs.
- C. Configure the ALB to push logs to Amazon Kinesis Data Stream
- D. Use Amazon Kinesis Data Analytics to analyze the logs.
- E. Configure Amazon Kinesis Data Streams to stream data from the ALB to Amazon OpenSearch Service (Amazon Elasticsearch Service). Use search operations in Amazon OpenSearch Service (Amazon Elasticsearch Service) to analyze the data.
- F. Configure the ALB to store logs in an Amazon S3 bucket
- G. Use Amazon Athena to analyze the logs in Amazon S3.

**Answer:** D

#### Explanation:

The most operationally efficient solution to collect and analyze logs that include the client IP address, target IP address, target port, and user agent of each user that accesses the application would be to configure the ALB to store logs in an Amazon S3 bucket and use Amazon Athena to analyze the logs in Amazon S3 (Option D). This solution allows for quick and easy analysis of log data without requiring manual download or manipulation of log files.

#### NEW QUESTION 16

A network engineer needs to set up an Amazon EC2 Auto Scaling group to run a Linux-based network appliance in a highly available architecture. The network engineer is configuring the new launch template for the Auto Scaling group.

In addition to the primary network interface the network appliance requires a second network interface that will be used exclusively by the application to exchange traffic with hosts over the internet. The company has set up a Bring Your Own IP (BYOIP) pool that includes an Elastic IP address that should be used as the public IP address for the second network interface.

How can the network engineer implement the required architecture?

- A. Configure the two network interfaces in the launch template
- B. Define the primary network interface to be created in one of the private subnets
- C. For the second network interface, select one of the public subnets
- D. Choose the BYOIP pool ID as the source of public IP addresses.
- E. Configure the primary network interface in a private subnet in the launch template
- F. Use the user data option to run a cloud-init script after boot to attach the second network interface from a subnet with auto-assign public IP addressing enabled.
- G. Create an AWS Lambda function to run as a lifecycle hook of the Auto Scaling group when an instance is launching
- H. In the Lambda function, assign a network interface to an AWS Global Accelerator endpoint.
- I. During creation of the Auto Scaling group, select subnets for the primary network interface
- J. Use the user data option to run a cloud-init script to allocate a second network interface and to associate an Elastic IP address from the BYOIP pool.

**Answer:** D

#### Explanation:

During creation of the Auto Scaling group, select subnets for the primary network interface. Use the user data option to run a cloud-init script to allocate a second network interface and to associate an Elastic IP address from the BYOIP pool.

This solution meets all of the requirements stated in the question. The primary network interface can be configured in a private subnet during creation of the Auto Scaling group. The user data option can be used to run a cloud-init script that will allocate a second network interface and associate an Elastic IP address from the BYOIP pool with it.

#### NEW QUESTION 17

A network engineer is designing a hybrid architecture that uses a 1 Gbps AWS Direct Connect connection between the company's data center and two AWS Regions: us-east-1 and eu-west-1. The VPCs in us-east-1 are connected by a transit gateway and need to access several on-premises databases. According to company policy, only one VPC in eu-west-1 can be connected to one on-premises server. The on-premises network segments the traffic between the databases and the server.

How should the network engineer set up the Direct Connect connection to meet these requirements?

- A. Create one hosted connection

- B. Use a transit VIF to connect to the transit gateway in us-east-1. Use a private VIF to connect to the VPC in eu-west-1. Use one Direct Connect gateway for both VIFs to route from the Direct Connect locations to the corresponding AWS Region along the path that has the lowest latency.
- C. Connect gateway for both VIFs to route from the Direct Connect locations to the corresponding AWS Region along the path that has the lowest latency.
- D. Create one hosted connection
- E. Use a transit VIF to connect to the transit gateway in us-east-1. Use a private VIF to connect to the VPC in eu-west-1. Use two Direct Connect gateways, one for each VIF, to route from the Direct Connect locations to the corresponding AWS Region along the path that has the lowest latency.
- F. Create one dedicated connection
- G. Use a transit VIF to connect to the transit gateway in us-east-1. Use a private VIF to connect to the VPC in eu-west-1. Use one Direct Connect gateway for both VIFs to route from the Direct Connect locations to the corresponding AWS Region along the path that has the lowest latency.
- H. Create one dedicated connection
- I. Use a transit VIF to connect to the transit gateway in us-east-1. Use a private VIF to connect to the VPC in eu-west-1. Use two Direct Connect gateways, one for each VIF, to route from the Direct Connect locations to the corresponding AWS Region along the path that has the lowest latency.

**Answer: B**

**Explanation:**

This solution meets the requirements of the company by using a single Direct Connect connection with two VIFs, one connected to the transit gateway in us-east-1 and the other connected to the VPC in eu-west-1. Two Direct Connect gateways are used, one for each VIF, to route traffic from the Direct Connect location to the corresponding AWS Region along the path that has the lowest latency. This setup ensures that traffic between the VPCs in us-east-1 and on-premises databases is routed through the transit gateway, while traffic between the VPC in eu-west-1 and the on-premises server is routed directly through the private VIF.

**NEW QUESTION 22**

A company is planning a migration of its critical workloads from an on-premises data center to Amazon EC2 instances. The plan includes a new 10 Gbps AWS Direct Connect dedicated connection from the on-premises data center to a VPC that is attached to a transit gateway. The migration must occur over encrypted paths between the on-premises data center and the AWS Cloud.

Which solution will meet these requirements while providing the HIGHEST throughput?

- A. Configure a public VIF on the Direct Connect connection
- B. Configure an AWS Site-to-Site VPN connection to the transit gateway as a VPN attachment.
- C. Configure a transit VIF on the Direct Connect connection
- D. Configure an IPsec VPN connection to an EC2 instance that is running third-party VPN software.
- E. Configure MACsec for the Direct Connect connection
- F. Configure a transit VIF to a Direct Connect gateway that is associated with the transit gateway.
- G. Configure a public VIF on the Direct Connect connection
- H. Configure two AWS Site-to-Site VPN connections to the transit gateway
- I. Enable equal-cost multi-path (ECMP) routing.

**Answer: C**

**Explanation:**

<https://aws.amazon.com/blogs/networking-and-content-delivery/adding-macsec-security-to-aws-direct-connect-c>

**NEW QUESTION 26**

A company is hosting an application on Amazon EC2 instances behind a Network Load Balancer (NLB). A solutions architect added EC2 instances in a second Availability Zone to improve the availability of the application. The solutions architect added the instances to the NLB target group.

The company's operations team notices that traffic is being routed only to the instances in the first Availability Zone.

What is the MOST operationally efficient solution to resolve this issue?

- A. Enable the new Availability Zone on the NLB
- B. Create a new NLB for the instances in the second Availability Zone
- C. Enable proxy protocol on the NLB
- D. Create a new target group with the instances in both Availability Zones

**Answer: A**

**Explanation:**

When adding instances in a new Availability Zone to an existing Network Load Balancer (NLB), it is important to ensure that the new Availability Zone is enabled on the NLB. This will allow traffic to be routed to instances in both Availability Zones. This can be done by editing the settings of the NLB and selecting the new Availability Zone from the list of available zones.

**NEW QUESTION 29**

A company is planning to deploy many software-defined WAN (SD-WAN) sites. The company is using AWS Transit Gateway and has deployed a transit gateway in the required AWS Region. A network engineer needs to deploy the SD-WAN hub virtual appliance into a VPC that is connected to the transit gateway. The solution must support at least 5 Gbps of throughput from the SD-WAN hub virtual appliance to other VPCs that are attached to the transit gateway.

Which solution will meet these requirements?

- A. Create a new VPC for the SD-WAN hub virtual appliance
- B. Create two IPsec VPN connections between the SD-WAN hub virtual appliance and the transit gateway
- C. Configure BGP over the IPsec VPN connections
- D. Assign a new CIDR block to the transit gateway
- E. Create a new VPC for the SD-WAN hub virtual appliance
- F. Attach the new VPC to the transit gateway with a VPC attachment
- G. Add a transit gateway Connect attachment
- H. Create a Connect peer and specify the GRE and BGP parameter
- I. Create a route in the appropriate VPC for the SD-WAN hub virtual appliance to route to the transit gateway.
- J. Create a new VPC for the SD-WAN hub virtual appliance
- K. Attach the new VPC to the transit gateway with a VPC attachment
- L. Create two IPsec VPN connections between the SD-WAN hub virtual appliance and the transit gateway
- M. Configure BGP over the IPsec VPN connections.
- N. Assign a new CIDR block to the transit gateway
- O. Create a new VPC for the SD-WAN hub virtual appliance

- P. Attach the new VPC to the transit gateway with a VPC attachmen
- Q. Add a transit gateway Connect attachmen
- R. Create a Connect peer and specify the VXLAN and BGP parameter
- S. Create a route in the appropriate VPC for the SD-WAN hub virtual appliance to route to the transit gateway.

**Answer:** D

### NEW QUESTION 33

A media company is implementing a news website for a global audience. The website uses Amazon CloudFront as its content delivery network. The backend runs on Amazon EC2 Windows instances behind an Application Load Balancer (ALB). The instances are part of an Auto Scaling group. The company's customers access the website by using service example com as the CloudFront custom domain name. The CloudFront origin points to an ALB that uses service-alb.example.com as the domain name.

The company's security policy requires the traffic to be encrypted in transit at all times between the users and the backend.

Which combination of changes must the company make to meet this security requirement? (Choose three.)

- A. Create a self-signed certificate for service.example.co
- B. Import the certificate into AWS Certificate Manager (ACM). Configure CloudFront to use this imported SSL/TLS certificat
- C. Change the default behavior to redirect HTTP to HTTPS.
- D. Create a certificate for service.example.com by using AWS Certificate Manager (ACM). Configure CloudFront to use this custom SSL/TLS certificat
- E. Change the default behavior to redirect HTTP to HTTPS.
- F. Create a certificate with any domain name by using AWS Certificate Manager (ACM) for the EC2 instance
- G. Configure the backend to use this certificate for its HTTPS listene
- H. Specify the instance target type during the creation of a new target group that uses the HTTPS protocol for its target
- I. Attach the existing Auto Scaling group to this new target group.
- J. Create a public certificate from a third-party certificate provider with any domain name for the EC2 instance
- K. Configure the backend to use this certificate for its HTTPS listene
- L. Specify the instance target type during the creation of a new target group that uses the HTTPS protocol for its target
- M. Attach the existing Auto Scaling group to this new target group.
- N. Create a certificate for service-alb.example.com by using AWS Certificate Manager (ACM). On the ALB add a new HTTPS listener that uses the new target group and the service-alb.example.com ACM certificat
- O. Modify the CloudFront origin to use the HTTPS protocol onl
- P. Delete the HTTP listener on the ALB.
- Q. Create a self-signed certificate for service-alb.example.co
- R. Import the certificate into AWS Certificate Manager (ACM). On the ALB add a new HTTPS listener that uses the new target group and the imported service-alb.example.com ACM certificat
- S. Modify the CloudFront origin to use the HTTPS protocol onl
- T. Delete the HTTP listener on the ALB.

**Answer:** BDE

### NEW QUESTION 34

A company operates its IT services through a multi-site hybrid infrastructure. The company deploys resources on AWS in the us-east-1 Region and in the eu-west-2 Region. The company also deploys resources in its own data centers that are located in the United States (US) and in the United Kingdom (UK). In both AWS Regions, the company uses a transit gateway to connect 15 VPCs to each other. The company has created a transit gateway peering connection between the two transit gateways. The VPC CIDR blocks do not overlap with each other or with IP addresses used within the data centers. The VPC CIDR prefixes can also be aggregated either on a Regional level or for the company's entire AWS environment.

The data centers are connected to each other by a private WAN connection. IP routing information is exchanged dynamically through Interior BGP (iBGP) sessions. The data centers maintain connectivity to AWS through one AWS Direct Connect connection in the US and one Direct Connect connection in the UK. Each Direct Connect connection is terminated on a Direct Connect gateway and is associated with a local transit gateway through a transit VIF.

Traffic follows the shortest geographical path from source to destination. For example, packets from the UK data center that are targeted to resources in eu-west-2 travel across the local Direct Connect connection. In cases of cross-Region data transfers, such as from the UK data center to VPCs in us-east-1, the private WAN connection must be used to minimize costs on AWS. A network engineer has configured each transit gateway association on the Direct Connect gateway to advertise VPC-specific CIDR IP prefixes only from the local Region. The routes toward the other Region must be learned through BGP from the routers in the other data center in the original, non-aggregated form.

The company recently experienced a problem with cross-Region data transfers because of issues with its private WAN connection. The network engineer needs to modify the routing setup to prevent similar interruptions in the future. The solution cannot modify the original traffic routing goal when the network is operating normally.

Which modifications will meet these requirements? (Choose two.)

- A. Remove all the VPC CIDR prefixes from the list of subnets advertised through the local Direct Connect connectio
- B. Add the company's entire AWS environment aggregate route to the list of subnets advertised through the local Direct Connect connection.
- C. Add the CIDR prefixes from the other Region VPCs and the local VPC CIDR blocks to the list of subnets advertised through the local Direct Connect connectio
- D. Configure data center routers to make routing decisions based on the BGP communities received.
- E. Add the aggregate IP prefix for the other Region and the local VPC CIDR blocks to the list of subnets advertised through the local Direct Connect connection.
- F. Add the aggregate IP prefix for the company's entire AWS environment and the local VPC CIDR blocks to the list of subnets advertised through the local Direct Connect connection.
- G. Remove all the VPC CIDR prefixes from the list of subnets advertised through the local Direct Connect connectio
- H. Add both Regional aggregate IP prefixes to the list of subnets advertised through the Direct Connect connection on both sides of the networ
- I. Configure data center routers to make routing decisions based on the BGP communities received.

**Answer:** AD

### NEW QUESTION 39

A company has created three VPCs: a production VPC, a nonproduction VPC, and a shared services VPC. The production VPC and the nonproduction VPC must each have communication with the shared services VPC. There must be no communication between the production VPC and the nonproduction VPC. A transit gateway is deployed to facilitate communication between VPCs.

Which route table configurations on the transit gateway will meet these requirements?

- A. Configure a route table with the production and nonproduction VPC attachments associated with propagated routes for only the shared services VP
- B. Create an additional route table with only the shared services VPC attachment associated with propagated routes from the production and nonproduction VPCs.



- C. Configure a route table with the production and nonproduction VPC attachments associated with propagated routes for each VP
- D. Create an additional route table with only the shared services VPC attachment associated with propagated routes from each VPC.
- E. Configure a route table with all the VPC attachments associated with propagated routes for only the shared services VPC
- Create an additional route table with only the shared services VPC attachment associated with propagated routes from the production and nonproduction VPCs.
- F. Configure a route table with the production and nonproduction VPC attachments associated with propagated routes disable
- G. Create an additional route table with only the shared services VPC attachment associated with propagated routes from the production and nonproduction VPCs.

**Answer:** A

#### NEW QUESTION 43

.....

## Relate Links

**100% Pass Your ANS-C01 Exam with ExamBible Prep Materials**

<https://www.exambible.com/ANS-C01-exam/>

## Contact us

We are proud of our high-quality customer service, which serves you around the clock 24/7.

Viste - <https://www.exambible.com/>