



Microsoft

Exam Questions DP-203

Data Engineering on Microsoft Azure

NEW QUESTION 1

- (Exam Topic 1)

You need to design the partitions for the product sales transactions. The solution must mee the sales transaction dataset requirements.

What should you include in the solution? To answer, select the appropriate options in the answer area. NOTE: Each correct selection is worth one point.

Answer Area

Partition product sales transactions data by:	<input type="checkbox"/> Sales date <input type="checkbox"/> Product ID <input type="checkbox"/> Promotion ID
Store product sales transactions data in:	<input type="checkbox"/> An Azure Synapse Analytics dedicated SQL pool <input type="checkbox"/> An Azure Synapse Analytics serverless SQL pool <input type="checkbox"/> An Azure Data Lake Storage Gen2 account linked to an Azure Synapse Analytics workspace

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Box 1: Sales date

Scenario: Contoso requirements for data integration include:

➤ Partition data that contains sales transaction records. Partitions must be designed to provide efficient loads by month. Boundary values must belong to the partition on the right.

Box 2: An Azure Synapse Analytics Dedicated SQL pool Scenario: Contoso requirements for data integration include:

➤ Ensure that data storage costs and performance are predictable.

The size of a dedicated SQL pool (formerly SQL DW) is determined by Data Warehousing Units (DWU). Dedicated SQL pool (formerly SQL DW) stores data in relational tables with columnar storage. This format significantly reduces the data storage costs, and improves query performance.

Synapse analytics dedicated sql pool Reference:

<https://docs.microsoft.com/en-us/azure/synapse-analytics/sql-data-warehouse/sql-data-warehouse-overview-wha>

NEW QUESTION 2

- (Exam Topic 1)

You need to integrate the on-premises data sources and Azure Synapse Analytics. The solution must meet the data integration requirements.

Which type of integration runtime should you use?

- A. Azure-SSIS integration runtime
- B. self-hosted integration runtime
- C. Azure integration runtime

Answer: C

NEW QUESTION 3

- (Exam Topic 3)

A company purchases IoT devices to monitor manufacturing machinery. The company uses an IoT appliance to communicate with the IoT devices.

The company must be able to monitor the devices in real-time. You need to design the solution.

What should you recommend?

- A. Azure Stream Analytics cloud job using Azure PowerShell
- B. Azure Analysis Services using Azure Portal
- C. Azure Data Factory instance using Azure Portal
- D. Azure Analysis Services using Azure PowerShell

Answer: A

Explanation:

Stream Analytics is a cost-effective event processing engine that helps uncover real-time insights from devices, sensors, infrastructure, applications and data quickly and easily.

Monitor and manage Stream Analytics resources with Azure PowerShell cmdlets and powershell scripting that execute basic Stream Analytics tasks.

Reference:

<https://cloudblogs.microsoft.com/sqlserver/2014/10/29/microsoft-adds-iot-streaming-analytics-data-production-a>

NEW QUESTION 4

- (Exam Topic 3)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this scenario, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an Azure Storage account that contains 100 GB of files. The files contain text and numerical values. 75% of the rows contain description data that has an average length of 1.1 MB.

You plan to copy the data from the storage account to an enterprise data warehouse in Azure Synapse Analytics.

You need to prepare the files to ensure that the data copies quickly. Solution: You convert the files to compressed delimited text files. Does this meet the goal?

- A. Yes
- B. No

Answer: A

Explanation:

All file formats have different performance characteristics. For the fastest load, use compressed delimited text files.

Reference:

<https://docs.microsoft.com/en-us/azure/sql-data-warehouse/guidance-for-loading-data>

NEW QUESTION 5

- (Exam Topic 3)

You need to create an Azure Data Factory pipeline to process data for the following three departments at your company: Ecommerce, retail, and wholesale. The solution must ensure that data can also be processed for the entire company.

How should you complete the Data Factory data flow script? To answer, drag the appropriate values to the correct targets. Each value may be used once, more than once, or not at all. You may need to drag the split bar between panes or scroll to view content.

NOTE: Each correct selection is worth one point.

Values	Answer Area
all, ecommerce, retail, wholesale	CleanData
dept=='ecommerce', dept=='retail', dept=='wholesale'	split(
dept=='ecommerce', dept=='wholesale', dept=='retail'	
disjoint: false	
disjoint: true) ~> SplitByDept@(
ecommerce, retail, wholesale, all)

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

The conditional split transformation routes data rows to different streams based on matching conditions. The conditional split transformation is similar to a CASE decision structure in a programming language. The transformation evaluates expressions, and based on the results, directs the data row to the specified stream.

Box 1: dept=='ecommerce', dept=='retail', dept=='wholesale'

First we put the condition. The order must match the stream labeling we define in Box 3. Syntax:

```
<incomingStream> split(
<conditionalExpression1>
<conditionalExpression2>
disjoint: {true | false}
) ~> <splitTx>@(stream1, stream2, ..., <defaultStream>)
```

Box 2: discount : false

disjoint is false because the data goes to the first matching condition. All remaining rows matching the third condition go to output stream all.

Box 3: ecommerce, retail, wholesale, all Label the streams

Reference:

<https://docs.microsoft.com/en-us/azure/data-factory/data-flow-conditional-split>

NEW QUESTION 6

- (Exam Topic 3)

You need to schedule an Azure Data Factory pipeline to execute when a new file arrives in an Azure Data Lake Storage Gen2 container.

Which type of trigger should you use?

- A. on-demand
- B. tumbling window
- C. schedule
- D. event

Answer: D

Explanation:

Event-driven architecture (EDA) is a common data integration pattern that involves production, detection, consumption, and reaction to events. Data integration scenarios often require Data Factory customers to trigger pipelines based on events happening in storage account, such as the arrival or deletion of a file in Azure Blob Storage account.

Reference:

<https://docs.microsoft.com/en-us/azure/data-factory/how-to-create-event-trigger>

NEW QUESTION 7

- (Exam Topic 3)

You are designing a statistical analysis solution that will use custom proprietary Python functions on near real-time data from Azure Event Hubs.

You need to recommend which Azure service to use to perform the statistical analysis. The solution must minimize latency.

What should you recommend?

- A. Azure Stream Analytics
- B. Azure SQL Database
- C. Azure Databricks
- D. Azure Synapse Analytics

Answer: A

NEW QUESTION 8

- (Exam Topic 3)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You are designing an Azure Stream Analytics solution that will analyze Twitter data.

You need to count the tweets in each 10-second window. The solution must ensure that each tweet is counted only once.

Does this meet the goal?


- A. Yes
- B. No

Answer: A

Explanation:

Tumbling windows are a series of fixed-sized, non-overlapping and contiguous time intervals. The following diagram illustrates a stream with a series of events and how they are mapped into 10-second tumbling windows.

Tell me the count of tweets per time zone every 10 seconds



```
SELECT TimeZone, COUNT(*) AS Count
FROM TwitterStream TIMESTAMP BY CreatedAt
GROUP BY TimeZone, TumblingWindow(second,10)
```

Reference:

<https://docs.microsoft.com/en-us/stream-analytics-query/tumbling-window-azure-stream-analytics>

NEW QUESTION 9

- (Exam Topic 3)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You plan to create an Azure Databricks workspace that has a tiered structure. The workspace will contain the following three workloads:

- > A workload for data engineers who will use Python and SQL.
- > A workload for jobs that will run notebooks that use Python, Scala, and SOL.
- > A workload that data scientists will use to perform ad hoc analysis in Scala and R.

The enterprise architecture team at your company identifies the following standards for Databricks environments:

- > The data engineers must share a cluster.
- > The job cluster will be managed by using a request process whereby data scientists and data engineers provide packaged notebooks for deployment to the cluster.
- > All the data scientists must be assigned their own cluster that terminates automatically after 120 minutes of inactivity. Currently, there are three data scientists.

You need to create the Databricks clusters for the workloads.

Solution: You create a Standard cluster for each data scientist, a High Concurrency cluster for the data engineers, and a Standard cluster for the jobs.

Does this meet the goal?

- A. Yes
- B. No

Answer: B

Explanation:

We would need a High Concurrency cluster for the jobs. Note:

Standard clusters are recommended for a single user. Standard can run workloads developed in any language: Python, R, Scala, and SQL.

A high concurrency cluster is a managed cloud resource. The key benefits of high concurrency clusters are that they provide Apache Spark-native fine-grained

sharing for maximum resource utilization and minimum query latencies.
Reference: <https://docs.azuredatabricks.net/clusters/configure.html>

NEW QUESTION 10

- (Exam Topic 3)

You have an Azure Data Lake Storage Gen2 account that contains a JSON file for customers. The file contains two attributes named FirstName and LastName. You need to copy the data from the JSON file to an Azure Synapse Analytics table by using Azure Databricks. A new column must be created that concatenates the FirstName and LastName values.

You create the following components:

- > A destination table in Azure Synapse
- > An Azure Blob storage container
- > A service principal

Which five actions should you perform in sequence next in is Databricks notebook? To answer, move the appropriate actions from the list of actions to the answer area and arrange them in the correct order.

Actions

Answer Area

Mount the Data Lake Storage onto DBFS.

Write the results to a table in Azure Synapse.

Perform transformations on the file.

Specify a temporary folder to stage the data.

Write the results to Data Lake Storage.

Read the file into a data frame.

Drop the data frame.

Perform transformations on the data frame.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Step 1: Read the file into a data frame.

You can load the json files as a data frame in Azure Databricks. Step 2: Perform transformations on the data frame.

Step 3: Specify a temporary folder to stage the data

Specify a temporary folder to use while moving data between Azure Databricks and Azure Synapse. Step 4: Write the results to a table in Azure Synapse.

You upload the transformed data frame into Azure Synapse. You use the Azure Synapse connector for Azure Databricks to directly upload a dataframe as a table in a Azure Synapse.

Step 5: Drop the data frame

Clean up resources. You can terminate the cluster. From the Azure Databricks workspace, select Clusters on the left. For the cluster to terminate, under Actions, point to the ellipsis (...) and select the Terminate icon.

Reference:

<https://docs.microsoft.com/en-us/azure/azure-databricks/databricks-extract-load-sql-data-warehouse>

NEW QUESTION 10

- (Exam Topic 3)

You plan to monitor an Azure data factory by using the Monitor & Manage app.

You need to identify the status and duration of activities that reference a table in a source database.

Which three actions should you perform in sequence? To answer, move the actions from the list of actions to the answer are and arrange them in the correct order.

Actions

Answer Area

From the Data Factory monitoring app, add the Source user property to the Activity Runs table.

From the Data Factory monitoring app, add the Source user property to the Pipeline Runs table.

From the Data Factory authoring UI, publish the pipelines.

From the Data Factory monitoring app, add a linked service to the Pipeline Runs table.

From the Data Factory authoring UI, generate a user property for Source on all activities.

From the Data Factory authoring UI, generate a user property for Source on all datasets.



- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Step 1: From the Data Factory authoring UI, generate a user property for Source on all activities. Step 2: From the Data Factory monitoring app, add the Source user property to Activity Runs table.

You can promote any pipeline activity property as a user property so that it becomes an entity that you can monitor. For example, you can promote the Source and Destination properties of the copy activity in your pipeline as user properties. You can also select Auto Generate to generate the Source and Destination user properties for a copy activity.

Step 3: From the Data Factory authoring UI, publish the pipelines

Publish output data to data stores such as Azure SQL Data Warehouse for business intelligence (BI) applications to consume.

References:

<https://docs.microsoft.com/en-us/azure/data-factory/monitor-visually>

NEW QUESTION 12

- (Exam Topic 3)

You plan to create an Azure Synapse Analytics dedicated SQL pool.

You need to minimize the time it takes to identify queries that return confidential information as defined by the company's data privacy regulations and the users who executed the queries.

Which two components should you include in the solution? Each correct answer presents part of the solution. NOTE: Each correct selection is worth one point.

- A. sensitivity-classification labels applied to columns that contain confidential information
- B. resource tags for databases that contain confidential information
- C. audit logs sent to a Log Analytics workspace
- D. dynamic data masking for columns that contain confidential information

Answer: AC

Explanation:

A: You can classify columns manually, as an alternative or in addition to the recommendation-based classification:

Home > MySampleDatabase2 (mydocsamplesqlserver/MySampleDatabase2)

MySampleDatabase2 (mydocsamplesqlserver/MySampleDatabase2) | Data Discovery & Classification

SQL database

Search (Ctrl+/) Save Discard + Add classification Feedback

Power Platform

- Power BI (preview)
- Power Apps (preview)
- Power Automate (preview)

Settings

- Configure
- Geo-Replication
- Connection strings
- Sync to other databases
- Add Azure Search
- Properties
- Locks

Integrations

- Stream analytics (preview)

Security

- Auditing
- Data Discovery & Classification
- Dynamic Data Masking
- Security Center
- Transparent data encryption

Intelligent Performance

- Performance overview

Overview Classification

15 columns with classification recommendations (Click to minimize)

Accept selected recommendations Dismiss selected recommendations Show dismissed recommendations

Select all Schema: 2 selected Table: 5 selected Filter by column

	Schema	Table	Column
<input type="checkbox"/>	SalesLT	Customer	FirstName
<input type="checkbox"/>	SalesLT	Customer	LastName
<input type="checkbox"/>	SalesLT	Customer	EmailAddress
<input type="checkbox"/>	SalesLT	Customer	Phone
<input type="checkbox"/>	SalesLT	Customer	PasswordHash
<input type="checkbox"/>	SalesLT	Customer	PasswordSalt
<input type="checkbox"/>	dbo	ErrorLog	Username
<input type="checkbox"/>	SalesLT	Address	AddressLine1
<input type="checkbox"/>	SalesLT	Address	AddressLine2
<input type="checkbox"/>	SalesLT	Address	City
<input type="checkbox"/>	SalesLT	Address	PostalCode
<input type="checkbox"/>	SalesLT	CustomerAddress	AddressType
<input type="checkbox"/>	SalesLT	SalesOrderHeader	AccountNumber
<input type="checkbox"/>	SalesLT	SalesOrderHeader	CreditCardApprovalCode
<input type="checkbox"/>	SalesLT	SalesOrderHeader	TaxAmt

- > Select Add classification in the top menu of the pane.
- > In the context window that opens, select the schema, table, and column that you want to classify, and the information type and sensitivity label.
- > Select Add classification at the bottom of the context window.

C: An important aspect of the information-protection paradigm is the ability to monitor access to sensitive data. Azure SQL Auditing has been enhanced to include a new field in the audit log called data_sensitivity_information. This field logs the sensitivity classifications (labels) of the data that was returned by a query. Here's an example:

d	client_ip	application_name	duration_milliseconds	response_rows	affected_rows	connection_id	data_sensitivity_information
	7.125	Microsoft SQL Server Management Studio - Query	1	847	847	C244A066-2271-...	Confidential - GDPR
	7.125	Microsoft SQL Server Management Studio - Query	2	32	32	C244A066-2271-...	Confidential
	7.125	Microsoft SQL Server Management Studio - Query	41	32	32	A7088FD4-759E-...	Confidential, Confidential - GDPR

Reference:

<https://docs.microsoft.com/en-us/azure/azure-sql/database/data-discovery-and-classification-overview>

NEW QUESTION 15

- (Exam Topic 3)

You are designing an Azure Databricks table. The table will ingest an average of 20 million streaming events per day.

You need to persist the events in the table for use in incremental load pipeline jobs in Azure Databricks. The solution must minimize storage costs and incremental load times.

What should you include in the solution?

- A. Partition by DateTime fields.
- B. Sink to Azure Queue storage.
- C. Include a watermark column.
- D. Use a JSON format for physical data storage.

Answer: B

Explanation:

The Databricks ABS-AQS connector uses Azure Queue Storage (AQS) to provide an optimized file source that lets you find new files written to an Azure Blob storage (ABS) container without repeatedly listing all of the files.

This provides two major advantages:

- > Lower costs: no more costly LIST API requests made to ABS.

Reference:

<https://docs.microsoft.com/en-us/azure/databricks/spark/latest/structured-streaming/aqs>

NEW QUESTION 18

- (Exam Topic 3)

You have an Azure Synapse Analytics dedicated SQL pool that contains a large fact table. The table contains 50 columns and 5 billion rows and is a heap.

Most queries against the table aggregate values from approximately 100 million rows and return only two columns.

You discover that the queries against the fact table are very slow. Which type of index should you add to provide the fastest query times?

- A. nonclustered columnstore
- B. clustered columnstore
- C. nonclustered
- D. clustered

Answer: B

Explanation:

Clustered columnstore indexes are one of the most efficient ways you can store your data in dedicated SQL pool. Columnstore tables won't benefit a query unless the table has more than 60 million rows. Reference: <https://docs.microsoft.com/en-us/azure/synapse-analytics/sql/best-practices-dedicated-sql-pool>

NEW QUESTION 20

- (Exam Topic 3)

You are planning the deployment of Azure Data Lake Storage Gen2. You have the following two reports that will access the data lake:

- > Report1: Reads three columns from a file that contains 50 columns.
- > Report2: Queries a single record based on a timestamp.

You need to recommend in which format to store the data in the data lake to support the reports. The solution must minimize read times. What should you recommend for each report? To answer, select the appropriate options in the answer area. NOTE: Each correct selection is worth one point.

Report1:

▼

Avro

CSV

Parquet

TSV

Report2:

▼

Avro

CSV

Parquet

TSV

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Report1: CSV
CSV: The destination writes records as delimited data. Report2: AVRO
AVRO supports timestamps.
Not Parquet, TSV: Not options for Azure Data Lake Storage Gen2. Reference: <https://streamsets.com/documentation/datacollector/latest/help/datacollector/UserGuide/Destinations/ADLS-G2>

NEW QUESTION 24

- (Exam Topic 3)

You have an Azure Stream Analytics job that is a Stream Analytics project solution in Microsoft Visual Studio. The job accepts data generated by IoT devices in the JSON format. You need to modify the job to accept data generated by the IoT devices in the Protobuf format. Which three actions should you perform from Visual Studio on sequence? To answer, move the appropriate actions from the list of actions to the answer area and arrange them in the correct order.

Actions

Answer Area

Change the Event Serialization Format to Protobuf in the input.json file of the job and reference the DLL.

Add an Azure Stream Analytics Custom Deserializer Project (.NET) project to the solution.

Add .NET deserializer code for Protobuf to the custom deserializer project.

Add .NET deserializer code for Protobuf to the Stream Analytics project.

Add an Azure Stream Analytics Application project to the solution.


- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Step 1: Add an Azure Stream Analytics Custom Deserializer Project (.NET) project to the solution. Create a custom deserializer

* 1. Open Visual Studio and select File > New > Project. Search for Stream Analytics and select Azure Stream Analytics Custom Deserializer Project (.NET). Give the project a name, like Protobuf Deserializer.



* 2. In Solution Explorer, right-click your Protobuf Deserializer project and select Manage NuGet Packages from the menu. Then install the Microsoft.Azure.StreamAnalytics and Google.Protobuf NuGet packages.

* 3. Add the MessageBodyProto class and the MessageBodyDeserializer class to your project.

* 4. Build the Protobuf Deserializer project.

Step 2: Add .NET deserializer code for Protobuf to the custom deserializer project

Azure Stream Analytics has built-in support for three data formats: JSON, CSV, and Avro. With custom .NET deserializers, you can read data from other formats such as Protocol Buffer, Bond and other user defined formats for both cloud and edge jobs.


Step 3: Add an Azure Stream Analytics Application project to the solution Add an Azure Stream Analytics project

> In Solution Explorer, right-click the Protobuf Deserializer solution and select Add > New Project. Under Azure Stream Analytics > Stream Analytics, choose Azure Stream Analytics Application. Name it ProtobufCloudDeserializer and select OK.

> Right-click References under the ProtobufCloudDeserializer Azure Stream Analytics project. Under Projects, add Protobuf Deserializer. It should be automatically populated for you.

Reference:

<https://docs.microsoft.com/en-us/azure/stream-analytics/custom-deserializer>



NEW QUESTION 27

- (Exam Topic 3)

You have an Azure Factory instance named DF1 that contains a pipeline named PL1. PL1 includes a tumbling window trigger.

You create five clones of PL1. You configure each clone pipeline to use a different data source.

You need to ensure that the execution schedules of the clone pipeline match the execution schedule of PL1. What should you do?

- A. Add a new trigger to each cloned pipeline
- B. Associate each cloned pipeline to an existing trigger.
- C. Create a tumbling window trigger dependency for the trigger of PL1.
- D. Modify the Concurrency setting of each pipeline.

Answer: B

NEW QUESTION 32

- (Exam Topic 3)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this scenario, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an Azure Storage account that contains 100 GB of files. The files contain text and numerical values. 75% of the rows contain description data that has an average length of 1.1 MB.

You plan to copy the data from the storage account to an Azure SQL data warehouse. You need to prepare the files to ensure that the data copies quickly.

Solution: You modify the files to ensure that each row is less than 1 MB. Does this meet the goal?

- A. Yes
- B. No

Answer: A

Explanation:

When exporting data into an ORC File Format, you might get Java out-of-memory errors when there are large text columns. To work around this limitation, export only a subset of the columns.

References:

<https://docs.microsoft.com/en-us/azure/sql-data-warehouse/guidance-for-loading-data>

NEW QUESTION 35

- (Exam Topic 3)

You need to output files from Azure Data Factory.

Which file format should you use for each type of output? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Columnar format:

▼

Avro
GZip
Parquet
TXT

JSON with a timestamp:

▼

Avro
GZip
Parquet
TXT

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Box 1: Parquet

Parquet stores data in columns, while Avro stores data in a row-based format. By their very nature, column-oriented data stores are optimized for read-heavy analytical workloads, while row-based databases are best for write-heavy transactional workloads.

Box 2: Avro

An Avro schema is created using JSON format.

AVRO supports timestamps.

Note: Azure Data Factory supports the following file formats (not GZip or TXT).

- Avro format
- Binary format
- Delimited text format
- Excel format
- JSON format
- ORC format
- Parquet format
- XML format

Reference:

<https://www.datanami.com/2018/05/16/big-data-file-formats-demystified>

NEW QUESTION 39

- (Exam Topic 3)

You have the following table named Employees.

first name	last name	hire date	employee type
Jane	Doe	2019-08-23	new
Ben	Smith	2017-12-15	Standard

You need to calculate the employee _type value based on the hire date value.

How should you complete the Transact-SQL statement? To answer, drag the appropriate values to the correct targets. Each value may be used once, more than once, or not at all. You may need to drag the split bar between panes or scroll to view content

NOTE: Each correct selection is worth one point.

Values

Answer Area

CASE
ELSE
OVER
PARTITION
ROW_NUMBER

```
SELECT
*,
Value
WHEN hire_date >= '2019-01-01' THEN
'New' Value 'Standard'
END AS employee_type
FROM
employees;
```

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Values

Answer Area

CASE
ELSE
OVER
PARTITION
ROW_NUMBER

```
SELECT
*,
CASE
WHEN hire_date >= '2019-01-01' THEN
'New' PARTITION 'Standard'
END AS employee_type
FROM
employees;
```

NEW QUESTION 40

- (Exam Topic 3)

You have two Azure Data Factory instances named ADFdev and ADFprod. ADFdev connects to an Azure DevOps Git repository. You publish changes from the main branch of the Git repository to ADFdev. You need to deploy the artifacts from ADFdev to ADFprod. What should you do first?

- A. From ADFdev, modify the Git configuration.
- B. From ADFdev, create a linked service.
- C. From Azure DevOps, create a release pipeline.
- D. From Azure DevOps, update the main branch.

Answer: C

Explanation:

In Azure Data Factory, continuous integration and delivery (CI/CD) means moving Data Factory pipelines from one environment (development, test, production) to another.

Note:

The following is a guide for setting up an Azure Pipelines release that automates the deployment of a data factory to multiple environments.

- > In Azure DevOps, open the project that's configured with your data factory.
 - > On the left side of the page, select Pipelines, and then select Releases.
 - > Select New pipeline, or, if you have existing pipelines, select New and then New release pipeline.
 - > In the Stage name box, enter the name of your environment.
 - > Select Add artifact, and then select the git repository configured with your development data factory.
- Select the publish branch of the repository for the Default branch. By default, this publish branch is adf_publish.

- > Select the Empty job template. Reference:

<https://docs.microsoft.com/en-us/azure/data-factory/continuous-integration-deployment>

NEW QUESTION 45

- (Exam Topic 3)

You have an Azure Stream Analytics job that receives clickstream data from an Azure event hub.

You need to define a query in the Stream Analytics job. The query must meet the following requirements: > Count the number of clicks within each 10-second window based on the country of a visitor.

- > Ensure that each click is NOT counted more than once. How should you define the Query?

- A. SELECT Country, Avg(*) AS AverageFROM ClickStream TIMESTAMP BY CreatedAt GROUP BY Country, SlidingWindow(second, 10)
- B. SELECT Country, Count(*) AS CountFROM ClickStream TIMESTAMP BY CreatedAt GROUP BY Country, TumblingWindow(second, 10)

C. SELECT Country, Avg(*) AS AverageFROM ClickStream TIMESTAMP BY CreatedAt GROUP BY Country, HoppingWindow(second, 10, 2)
D. SELECT Country, Count(*) AS CountFROM ClickStream TIMESTAMP BY CreatedAt GROUP BY Country, SessionWindow(second, 5, 10)

Answer: B

Explanation:

Tumbling window functions are used to segment a data stream into distinct time segments and perform a function against them, such as the example below. The key differentiators of a Tumbling window are that they repeat, do not overlap, and an event cannot belong to more than one tumbling window.

Example: Reference:

<https://docs.microsoft.com/en-us/azure/stream-analytics/stream-analytics-window-functions>

NEW QUESTION 47

- (Exam Topic 3)

You develop data engineering solutions for a company.

A project requires the deployment of data to Azure Data Lake Storage.

You need to implement role-based access control (RBAC) so that project members can manage the Azure Data Lake Storage resources.

Which three actions should you perform? Each correct answer presents part of the solution. NOTE: Each correct selection is worth one point.

- A. Assign Azure AD security groups to Azure Data Lake Storage.
- B. Configure end-user authentication for the Azure Data Lake Storage account.
- C. Configure service-to-service authentication for the Azure Data Lake Storage account.
- D. Create security groups in Azure Active Directory (Azure AD) and add project members.
- E. Configure access control lists (ACL) for the Azure Data Lake Storage account.

Answer: ADE

Explanation:

References:

<https://docs.microsoft.com/en-us/azure/data-lake-store/data-lake-store-secure-data>

NEW QUESTION 51

- (Exam Topic 3)

You have an enterprise data warehouse in Azure Synapse Analytics named DW1 on a server named Server1. You need to verify whether the size of the transaction log file for each distribution of DW1 is smaller than 160 GB.

What should you do?

- A. On the master database, execute a query against the sys.dm_pdw_nodes_os_performance_counters dynamic management view.
- B. From Azure Monitor in the Azure portal, execute a query against the logs of DW1.
- C. On DW1, execute a query against the sys.database_files dynamic management view.
- D. Execute a query against the logs of DW1 by using theGet-AzOperationalInsightSearchResult PowerShell cmdlet.

Answer: A

Explanation:

The following query returns the transaction log size on each distribution. If one of the log files is reaching 160 GB, you should consider scaling up your instance or limiting your transaction size.

-- Transaction log size SELECT

instance_name as distribution_db, cntr_value*1.0/1048576 as log_file_size_used_GB, pdw_node_id

FROM sys.dm_pdw_nodes_os_performance_counters WHERE

instance_name like 'Distribution_%'

AND counter_name = 'Log File(s) Used Size (KB)' References:

<https://docs.microsoft.com/en-us/azure/sql-data-warehouse/sql-data-warehouse-manage-monitor>

NEW QUESTION 55

- (Exam Topic 3)

You plan to implement an Azure Data Lake Storage Gen2 container that will contain CSV files. The size of the files will vary based on the number of events that occur per hour.

File sizes range from 4.KB to 5 GB.

You need to ensure that the files stored in the container are optimized for batch processing. What should you do?

- A. Compress the files.
- B. Merge the files.
- C. Convert the files to JSON
- D. Convert the files to Avro.

Answer: D

NEW QUESTION 60

- (Exam Topic 3)

You need to design an Azure Synapse Analytics dedicated SQL pool that meets the following requirements:

- Can return an employee record from a given point in time.
- Maintains the latest employee information.
- Minimizes query complexity.

How should you model the employee data?

- A. as a temporal table
- B. as a SQL graph table
- C. as a degenerate dimension table

D. as a Type 2 slowly changing dimension (SCD) table

Answer: D

Explanation:

A Type 2 SCD supports versioning of dimension members. Often the source system doesn't store versions, so the data warehouse load process detects and manages changes in a dimension table. In this case, the dimension table must use a surrogate key to provide a unique reference to a version of the dimension member. It also includes columns that define the date range validity of the version (for example, StartDate and EndDate) and possibly a flag column (for example, IsCurrent) to easily filter by current dimension members.

Reference:

<https://docs.microsoft.com/en-us/learn/modules/populate-slowly-changing-dimensions-azure-synapse-analytics>

NEW QUESTION 61

- (Exam Topic 3)

You configure monitoring for a Microsoft Azure SQL Data Warehouse implementation. The implementation uses PolyBase to load data from comma-separated value (CSV) files stored in Azure Data Lake Gen 2 using an external table.

Files with an invalid schema cause errors to occur. You need to monitor for an invalid schema error. For which error should you monitor?

A. EXTERNAL TABLE access failed due to internal error: 'Java exception raised on call to HdfsBridge_Connect:

Error[com.microsoft.polybase.client.KerberosSecureLogin] occurred while accessing external files.'

B. EXTERNAL TABLE access failed due to internal error: 'Java exception raised on call to HdfsBridge_Connect: Error [No FileSystem for scheme: wasbs] occurred while accessing external file.'

C. Cannot execute the query "Remote Query" against OLE DB provider "SQLNCLI11": for linked server "(null)", Query aborted- the maximum reject threshold (0 rows) was reached while regarding from an external source: 1 rows rejected out of total 1 rows processed.

D. EXTERNAL TABLE access failed due to internal error: 'Java exception raised on call to HdfsBridge_Connect: Error [Unable to instantiate LoginClass] occurredwhile accessing external files.'

Answer: C

Explanation:

Customer Scenario:

SQL Server 2016 or SQL DW connected to Azure blob storage. The CREATE EXTERNAL TABLE DDL points to a directory (and not a specific file) and the directory contains files with different schemas.

SSMS Error:

Select query on the external table gives the following error: Msg 7320, Level 16, State 110, Line 14

Cannot execute the query "Remote Query" against OLE DB provider "SQLNCLI11" for linked server "(null)". Query aborted-- the maximum reject threshold (0 rows) was reached while reading from an external source: 1 rows rejected out of total 1 rows processed.

Possible Reason:

The reason this error happens is because each file has different schema. The PolyBase external table DDL when pointed to a directory recursively reads all the files in that directory. When a column or data type mismatch happens, this error could be seen in SSMS.

Possible Solution:

If the data for each table consists of one file, then use the filename in the LOCATION section prepended by the directory of the external files. If there are multiple files per table, put each set of files into different directories in Azure Blob Storage and then you can point LOCATION to the directory instead of a particular file. The latter suggestion is the best practices recommended by SQLCAT even if you have one file per table.

NEW QUESTION 64

- (Exam Topic 3)

You have an Azure Synapse Analytics dedicated SQL pool that contains a table named Contacts. Contacts contains a column named Phone.

You need to ensure that users in a specific role only see the last four digits of a phone number when querying the Phone column.

What should you include in the solution?

A. a default value

B. dynamic data masking

C. row-level security (RLS)

D. column encryption

E. table partitions

Answer: C

NEW QUESTION 69

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

DP-203 Practice Exam Features:

- * DP-203 Questions and Answers Updated Frequently
- * DP-203 Practice Questions Verified by Expert Senior Certified Staff
- * DP-203 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * DP-203 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The DP-203 Practice Test Here](#)