

# Exam Questions DVA-C02

DVA-C02

<https://www.2passeasy.com/dumps/DVA-C02/>



### NEW QUESTION 1

A company is migrating legacy internal applications to AWS. Leadership wants to rewrite the internal employee directory to use native AWS services. A developer needs to create a solution for storing employee contact details and high-resolution photos for use with the new application.

Which solution will enable the search and retrieval of each employee's individual details and high-resolution photos using AWS APIs?

- A. Encode each employee's contact information and photos using Base64. Store the information in an Amazon DynamoDB table using a sort key.
- B. Store each employee's contact information in an Amazon DynamoDB table along with the object keys for the photos stored in Amazon S3.
- C. Use Amazon Cognito user pools to implement the employee directory in a fully managed software-as-a-service (SaaS) method.
- D. Store employee contact information in an Amazon RDS DB instance with the photos stored in Amazon Elastic File System (Amazon EFS).

**Answer: B**

### NEW QUESTION 2

A developer has written the following IAM policy to provide access to an Amazon S3 bucket:

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "s3:GetObject",
        "s3:PutObject"
      ],
      "Resource": "arn:aws:s3:::DOC-EXAMPLE-BUCKET/*"
    },
    {
      "Effect": "Deny",
      "Action": "s3:*",
      "Resource": "arn:aws:s3:::DOC-EXAMPLE-BUCKET/secrets*"
    }
  ]
}
```

Which access does the policy allow regarding the s3:GetObject and s3:PutObject actions?

- A. Access on all buckets except the "DOC-EXAMPLE-BUCKET" bucket
- B. Access on all buckets that start with "DOC-EXAMPLE-BUCKET" except the "DOC-EXAMPLE-BUCKET/secrets" bucket
- C. Access on all objects in the "DOC-EXAMPLE-BUCKET" bucket along with access to all S3 actions for objects in the "DOC-EXAMPLE-BUCKET" bucket that start with "secrets"
- D. Access on all objects in the "DOC-EXAMPLE-BUCKET" bucket except on objects that start with "secrets"

**Answer: D**

### NEW QUESTION 3

A company is running Amazon EC2 instances in multiple AWS accounts. A developer needs to implement an application that collects all the lifecycle events of the EC2 instances. The application needs to store the lifecycle events in a single Amazon Simple Queue Service (Amazon SQS) queue in the company's main AWS account for further processing.

Which solution will meet these requirements?

- A. Configure Amazon EC2 to deliver the EC2 instance lifecycle events from all accounts to the Amazon EventBridge event bus of the main account
- B. Add an EventBridge rule to the event bus of the main account that matches all EC2 instance lifecycle event
- C. Add the SQS queue as a target of the rule.
- D. Use the resource policies of the SQS queue in the main account to give each account permissions to write to that SQS queue
- E. Add to the Amazon EventBridge event bus of each account an EventBridge rule that matches all EC2 instance lifecycle event
- F. Add the SQS queue in the main account as a target of the rule.
- G. Write an AWS Lambda function that scans through all EC2 instances in the company accounts to detect EC2 instance lifecycle change
- H. Configure the Lambda function to write a notification message to the SQS queue in the main account if the function detects an EC2 instance lifecycle change
- I. Add an Amazon EventBridge scheduled rule that invokes the Lambda function every minute.
- J. Configure the permissions on the main account event bus to receive events from all account
- K. Create an Amazon EventBridge rule in each account to send all the EC2 instance lifecycle events to the main account event bus
- L. Add an EventBridge rule to the main account event bus that matches all EC2 instance lifecycle event
- M. Set the SQS queue as a target for the rule.

**Answer: D**

### NEW QUESTION 4

A developer is creating an application that will give users the ability to store photos from their cellphones in the cloud. The application needs to support tens of thousands of users. The application uses an Amazon API Gateway REST API that is integrated with AWS Lambda functions to process the photos. The application stores details about the photos in Amazon DynamoDB.

Users need to create an account to access the application. In the application, users must be able to upload photos and retrieve previously uploaded photos. The photos will range in size from 300 KB to 5 MB.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Use Amazon Cognito user pools to manage user account
- B. Create an Amazon Cognito user pool authorizer in API Gateway to control access to the AP

- C. Use the Lambda function to store the photos and details in the DynamoDB tabl
- D. Retrieve previously uploaded photos directly from the DynamoDB table.
- E. Use Amazon Cognito user pools to manage user account
- F. Create an Amazon Cognito user pool authorizer in API Gateway to control access to the AP
- G. Use the Lambda function to store the photos in Amazon S3. Store the object's S3 key as part of the photo details in the DynamoDB tabl
- H. Retrieve previously uploaded photos by querying DynamoDB for the S3 key.
- I. Create an IAM user for each user of the application during the sign-up proces
- J. Use IAM authentication to access the API Gateway AP
- K. Use the Lambda function to store the photos in Amazon S3. Store the object's S3 key as part of the photo details in the DynamoDB tabl
- L. Retrieve previously uploaded photos by querying DynamoDB for the S3 key.
- M. Create a users table in DynamoD
- N. Use the table to manage user account
- O. Create a Lambda authorizer that validates user credentials against the users tabl
- P. Integrate the Lambda authorizer with API Gateway to control access to the AP
- Q. Use the Lambda function to store the photos in Amazon S3. Store the object's S3 key as par of the photo details in the DynamoDB tabl
- R. Retrieve previously uploaded photos by querying DynamoDB for the S3 key.

**Answer: B**

#### NEW QUESTION 5

An ecommerce company is using an AWS Lambda function behind Amazon API Gateway as its application tier. To process orders during checkout, the application calls a POST API from the frontend. The POST API invokes the Lambda function asynchronously. In rare situations, the application has not processed orders. The Lambda application logs show no errors or failures. What should a developer do to solve this problem?

- A. Inspect the frontend logs for API failure
- B. Call the POST API manually by using the requests from the log file.
- C. Create and inspect the Lambda dead-letter queu
- D. Troubleshoot the failed function
- E. Reprocess the events.
- F. Inspect the Lambda logs in Amazon CloudWatch for possible error
- G. Fix the errors.
- H. Make sure that caching is disabled for the POST API in API Gateway.

**Answer: B**

#### NEW QUESTION 6

A developer is using an AWS Lambda function to generate avatars for profile pictures that are uploaded to an Amazon S3 bucket. The Lambda function is automatically invoked for profile pictures that are saved under the /original/ S3 prefix. The developer notices that some pictures cause the Lambda function to time out. The developer wants to implement a fallback mechanism by using another Lambda function that resizes the profile picture. Which solution will meet these requirements with the LEAST development effort?

- A. Set the image resize Lambda function as a destination of the avatar generator Lambda function for the events that fail processing.
- B. Create an Amazon Simple Queue Service (Amazon SQS) queu
- C. Set the SQS queue as a destination with an on failure condition for the avatar generator Lambda functio
- D. Configure the image resize Lambda function to poll from the SQS queue.
- E. Create an AWS Step Functions state machine that invokes the avatar generator Lambda function and uses the image resize Lambda function as a fallback
- F. Create an Amazon EventBridge rule that matches events from the S3 bucket to invoke the state machine.
- G. Create an Amazon Simple Notification Service (Amazon SNS) topi
- H. Set the SNS topic as a destination with an on failure condition for the avatar generator Lambda functio
- I. Subscribe the image resize Lambda function to the SNS topic.

**Answer: C**

#### NEW QUESTION 7

An application uses Lambda functions to extract metadata from files uploaded to an S3 bucket; the metadata is stored in Amazon DynamoDB. The application starts behaving unexpectedly, and the developer wants to examine the logs of the Lambda function code for errors. Based on this system configuration, where would the developer find the logs?

- A. Amazon S3
- B. AWS CloudTrail
- C. Amazon CloudWatch
- D. Amazon DynamoDB

**Answer: C**

#### NEW QUESTION 8

A company is using an AWS Lambda function to process records from an Amazon Kinesis data stream. The company recently observed slow processing of the records. A developer notices that the iterator age metric for the function is increasing and that the Lambda run duration is constantly above normal. Which actions should the developer take to increase the processing speed? (Choose two.)

- A. Increase the number of shards of the Kinesis data stream.
- B. Decrease the timeout of the Lambda function.
- C. Increase the memory that is allocated to the Lambda function.
- D. Decrease the number of shards of the Kinesis data stream.
- E. Increase the timeout of the Lambda function.

**Answer: AC**

**NEW QUESTION 9**

A developer has an application that makes batch requests directly to Amazon DynamoDB by using the BatchGetItem low-level API operation. The responses frequently return values in the UnprocessedKeys element. Which actions should the developer take to increase the resiliency of the application when the batch response includes values in UnprocessedKeys? (Choose two.)

- A. Retry the batch operation immediately.
- B. Retry the batch operation with exponential backoff and randomized delay.
- C. Update the application to use an AWS software development kit (AWS SDK) to make the requests.
- D. Increase the provisioned read capacity of the DynamoDB tables that the operation accesses.
- E. Increase the provisioned write capacity of the DynamoDB tables that the operation accesses.

**Answer:** BD

**NEW QUESTION 10**

A developer has an application that stores data in an Amazon S3 bucket. The application uses an HTTP API to store and retrieve objects. When the PutObject API operation adds objects to the S3 bucket the developer must encrypt these objects at rest by using server-side encryption with Amazon S3 managed keys (SSE-S3).

Which solution will meet this requirement?

- A. Create an AWS Key Management Service (AWS KMS) key.
- B. Assign the KMS key to the S3 bucket.
- C. Set the x-amz-server-side-encryption header when invoking the PutObject API operation.
- D. Provide the encryption key in the HTTP header of every request.
- E. Apply TLS to encrypt the traffic to the S3 bucket.

**Answer:** B

**NEW QUESTION 10**

A company is offering APIs as a service over the internet to provide unauthenticated read access to statistical information that is updated daily. The company uses Amazon API Gateway and AWS Lambda to develop the APIs. The service has become popular, and the company wants to enhance the responsiveness of the APIs.

Which action can help the company achieve this goal?

- A. Enable API caching in API Gateway.
- B. Configure API Gateway to use an interface VPC endpoint.
- C. Enable cross-origin resource sharing (CORS) for the APIs.
- D. Configure usage plans and API keys in API Gateway.

**Answer:** A

**NEW QUESTION 14**

A company has deployed an application on AWS Elastic Beanstalk. The company has configured the Auto Scaling group that is associated with the Elastic Beanstalk environment to have five Amazon EC2 instances. If the capacity is fewer than four EC2 instances during the deployment, application performance degrades. The company is using the all-at-once deployment policy.

What is the MOST cost-effective way to solve the deployment issue?

- A. Change the Auto Scaling group to six desired instances.
- B. Change the deployment policy to traffic splittin
- C. Specify an evaluation time of 1 hour.
- D. Change the deployment policy to rolling with additional batc
- E. Specify a batch size of 1.
- F. Change the deployment policy to rollin
- G. Specify a batch size of 2.

**Answer:** C

**NEW QUESTION 16**

A developer is building a web application that uses Amazon API Gateway to expose an AWS Lambda function to process requests from clients. During testing, the developer notices that the API Gateway times out even though the Lambda function finishes under the set time limit.

Which of the following API Gateway metrics in Amazon CloudWatch can help the developer troubleshoot the issue? (Choose two.)

- A. CacheHitCount
- B. IntegrationLatency
- C. CacheMissCount
- D. Latency
- E. Count

**Answer:** BD

**NEW QUESTION 20**

A developer is designing an AWS Lambda function that creates temporary files that are less than 10 MB during invocation. The temporary files will be accessed and modified multiple times during invocation. The developer has no need to save or retrieve these files in the future.

Where should the temporary files be stored?

- A. the /tmp directory
- B. Amazon Elastic File System (Amazon EFS)
- C. Amazon Elastic Block Store (Amazon EBS)

D. Amazon S3

**Answer:** A

**NEW QUESTION 25**

An application is processing clickstream data using Amazon Kinesis. The clickstream data feed into Kinesis experiences periodic spikes. The PutRecords API call occasionally fails and the logs show that the failed call returns the response shown below:

```
{
  "FailedRecordCount": 1,
  "Records": [
    {
      "SequenceNumber": "21269319989900637946712965403778482371",
      "ShardId": "shardId-000000000001"
    },
    {
      "ErrorCode": "ProvisionedThroughputExceededException",
      "ErrorMessage": "Rate exceeded for shard shardId-000000000001 in
        stream exampleStreamName under account 123456789."
    },
    {
      "SequenceNumber": "21269319989999637946712965403778482985",
      "ShardId": "shardId-000000000002"
    }
  ]
}
```

Which techniques will help mitigate this exception? (Choose two.)

- A. Which techniques will help mitigate this exception? (Choose two.)
- B. Use a PutRecord API instead of PutRecords.
- C. Reduce the frequency and/or size of the requests.
- D. Use Amazon SNS instead of Kinesis.
- E. Reduce the number of KCL consumers.

**Answer:** AC

**NEW QUESTION 26**

A developer is writing an AWS Lambda function. The developer wants to log key events that occur while the Lambda function runs. The developer wants to include a unique identifier to associate the events with a specific function invocation. The developer adds the following code to the Lambda function:

```
function handler(event, context) {
}
}
```

Which solution will meet this requirement?

- A. Obtain the request identifier from the AWS request ID field in the context object
- B. Configure the application to write logs to standard output.
- C. Obtain the request identifier from the AWS request ID field in the event object
- D. Configure the application to write logs to a file.
- E. Obtain the request identifier from the AWS request ID field in the event object
- F. Configure the application to write logs to standard output.
- G. Obtain the request identifier from the AWS request ID field in the context object
- H. Configure the application to write logs to a file.

**Answer:** D

**NEW QUESTION 28**

A developer is testing a new file storage application that uses an Amazon CloudFront distribution to serve content from an Amazon S3 bucket. The distribution accesses the S3 bucket by using an origin access identity (OAI). The S3 bucket's permissions explicitly deny access to all other users. The application prompts users to authenticate on a login page and then uses signed cookies to allow users to access their personal storage directories. The developer has configured the distribution to use its default cache behavior with restricted viewer access and has set the origin to point to the S3 bucket. However, when the developer tries to navigate to the login page, the developer receives a 403 Forbidden error. The developer needs to implement a solution to allow unauthenticated access to the login page. The solution also must keep all private content secure. Which solution will meet these requirements?

- A. Add a second cache behavior to the distribution with the same origin as the default cache behavior
- B. Set the path pattern for the second cache behavior to the path of the login page, and make viewer access unrestricted
- C. Keep the default cache behavior's settings unchanged.
- D. Add a second cache behavior to the distribution with the same origin as the default cache behavior
- E. Set the path pattern for the second cache behavior to \*, and make viewer access restricted
- F. Change the default cache behavior's path pattern to the path of the login page, and make viewer access unrestricted.
- G. Add a second origin as a failover origin to the default cache behavior
- H. Point the failover origin to the S3 bucket
- I. Set the path pattern for the primary origin to \*, and make viewer access restricted
- J. Set the path pattern for the failover origin to the path of the login page, and make viewer access unrestricted.

- K. Add a bucket policy to the S3 bucket to allow read access
- L. Set the resource on the policy to the Amazon Resource Name (ARN) of the login page object in the S3 bucket
- M. Add a CloudFront function to the default cache behavior to redirect unauthorized requests to the login page's S3 URL.

**Answer:** A

#### NEW QUESTION 32

An Amazon Kinesis Data Firehose delivery stream is receiving customer data that contains personally identifiable information. A developer needs to remove pattern-based customer identifiers from the data and store the modified data in an Amazon S3 bucket. What should the developer do to meet these requirements?

- A. Implement Kinesis Data Firehose data transformation as an AWS Lambda function
- B. Configure the function to remove the customer identifier
- C. Set an Amazon S3 bucket as the destination of the delivery stream.
- D. Launch an Amazon EC2 instance
- E. Set the EC2 instance as the destination of the delivery stream
- F. Run an application on the EC2 instance to remove the customer identifier
- G. Store the transformed data in an Amazon S3 bucket.
- H. Create an Amazon OpenSearch Service instance
- I. Set the OpenSearch Service instance as the destination of the delivery stream
- J. Use search and replace to remove the customer identifier
- K. Export the data to an Amazon S3 bucket.
- L. Create an AWS Step Functions workflow to remove the customer identifier
- M. As the last step in the workflow, store the transformed data in an Amazon S3 bucket
- N. Set the workflow as the destination of the delivery stream.

**Answer:** A

#### NEW QUESTION 36

A company receives food orders from multiple partners. The company has a microservices application that uses Amazon API Gateway APIs with AWS Lambda integration. Each partner sends orders by calling a customized API that is exposed through API Gateway. The API call invokes a shared Lambda function to process the orders.

Partners need to be notified after the Lambda function processes the orders. Each partner must receive updates for only the partner's own orders. The company wants to add new partners in the future with the fewest code changes possible.

Which solution will meet these requirements in the MOST scalable way?

- A. Create a different Amazon Simple Notification Service (Amazon SNS) topic for each partner
- B. Configure the Lambda function to publish messages for each partner to the partner's SNS topic.
- C. Create a different Lambda function for each partner
- D. Configure the Lambda function to notify each partner's service endpoint directly.
- E. Create an Amazon Simple Notification Service (Amazon SNS) topic
- F. Configure the Lambda function to publish messages with specific attributes to the SNS topic
- G. Subscribe each partner to the SNS topic
- H. Apply the appropriate filter policy to the topic subscriptions.
- I. Create one Amazon Simple Notification Service (Amazon SNS) topic
- J. Subscribe all partners to the SNS topic.

**Answer:** C

#### NEW QUESTION 41

A company wants to deploy and maintain static websites on AWS. Each website's source code is hosted in one of several version control systems, including AWS CodeCommit, Bitbucket, and GitHub.

The company wants to implement phased releases by using development, staging, user acceptance testing, and production environments in the AWS Cloud. Deployments to each environment must be started by code merges on the relevant Git branch. The company wants to use HTTPS for all data exchange. The company needs a solution that does not require servers to run continuously.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Host each website by using AWS Amplify with a serverless backend
- B. Connect the repository branches that correspond to each of the desired environments
- C. Start deployments by merging code changes to a desired branch.
- D. Host each website in AWS Elastic Beanstalk with multiple environments
- E. Use the EB CLI to link each repository branch
- F. Integrate AWS CodePipeline to automate deployments from version control code merges.
- G. Host each website in different Amazon S3 buckets for each environment
- H. Configure AWS CodePipeline to pull source code from version control
- I. Add an AWS CodeBuild stage to copy source code to Amazon S3.
- J. Host each website on its own Amazon EC2 instance
- K. Write a custom deployment script to bundle each website's static assets
- L. Copy the assets to Amazon EC2. Set up a workflow to run the script when code is merged.

**Answer:** A

#### NEW QUESTION 45

A company is migrating an on-premises database to Amazon RDS for MySQL. The company has read-heavy workloads. The company wants to refactor the code to achieve optimum read performance for queries.

Which solution will meet this requirement with LEAST current and future effort?

- A. Use a multi-AZ Amazon RDS deployment
- B. Increase the number of connections that the code makes to the database or increase the connection pool size if a connection pool is in use.

- C. Use a multi-AZ Amazon RDS deployment
- D. Modify the code so that queries access the secondary RDS instance.
- E. Deploy Amazon RDS with one or more read replicas
- F. Modify the application code so that queries use the URL for the read replicas.
- G. Use open source replication software to create a copy of the MySQL database on an Amazon EC2 instance
- H. Modify the application code so that queries use the IP address of the EC2 instance.

**Answer: B**

#### NEW QUESTION 46

A developer is designing a serverless application with two AWS Lambda functions to process photos. One Lambda function stores objects in an Amazon S3 bucket and stores the associated metadata in an Amazon DynamoDB table. The other Lambda function fetches the objects from the S3 bucket by using the metadata from the DynamoDB table. Both Lambda functions use the same Python library to perform complex computations and are approaching the quota for the maximum size of zipped deployment packages.

What should the developer do to reduce the size of the Lambda deployment packages with the LEAST operational overhead?

- A. Package each Python library in its own .zip file archive
- B. Deploy each Lambda function with its own copy of the library.
- C. Create a Lambda layer with the required Python libraries
- D. Use the Lambda layer in both Lambda functions.
- E. Combine the two Lambda functions into one Lambda function
- F. Deploy the Lambda function as a single.zip file archive.
- G. Download the Python library to an S3 bucket
- H. Program the Lambda functions to reference the object URLs.

**Answer: B**

#### NEW QUESTION 51

A company is implementing an application on Amazon EC2 instances. The application needs to process incoming transactions. When the application detects a transaction that is not valid, the application must send a chat message to the company's support team. To send the message, the application needs to retrieve the access token to authenticate by using the chat API.

A developer needs to implement a solution to store the access token. The access token must be encrypted at rest and in transit. The access token must also be accessible from other AWS accounts.

Which solution will meet these requirements with the LEAST management overhead?

- A. Use an AWS Systems Manager Parameter Store SecureString parameter that uses an AWS Key Management Service (AWS KMS) AWS managed key to store the access token
- B. Add a resource-based policy to the parameter to allow access from other accounts
- C. Update the IAM role of the EC2 instances with permissions to access Parameter Store
- D. Retrieve the token from Parameter Store with the decrypt flag enabled
- E. Use the decrypted access token to send the message to the chat.
- F. Encrypt the access token by using an AWS Key Management Service (AWS KMS) customer managed key
- G. Store the access token in an Amazon DynamoDB table
- H. Update the IAM role of the EC2 instances with permissions to access DynamoDB and AWS KMS
- I. Retrieve the token from DynamoDB
- J. Decrypt the token by using AWS KMS on the EC2 instance
- K. Use the decrypted access token to send the message to the chat.
- L. Use AWS Secrets Manager with an AWS Key Management Service (AWS KMS) customer managed key to store the access token
- M. Add a resource-based policy to the secret to allow access from other accounts
- N. Update the IAM role of the EC2 instances with permissions to access Secrets Manager
- O. Retrieve the token from Secrets Manager
- P. Use the decrypted access token to send the message to the chat.
- Q. Encrypt the access token by using an AWS Key Management Service (AWS KMS) AWS managed key. Store the access token in an Amazon S3 bucket
- R. Add a bucket policy to the S3 bucket to allow access from other accounts
- S. Update the IAM role of the EC2 instances with permissions to access Amazon S3 and AWS KMS
- T. Retrieve the token from the S3 bucket
- U. Decrypt the token by using AWS KMS on the EC2 instance
- V. Use the decrypted access token to send the message to the chat.

**Answer: B**

#### NEW QUESTION 55

A company has an Amazon S3 bucket that contains sensitive data. The data must be encrypted in transit and at rest. The company encrypts the data in the S3 bucket by using an AWS Key Management Service (AWS KMS) key. A developer needs to grant several other AWS accounts the permission to use the S3 GetObject operation to retrieve the data from the S3 bucket.

How can the developer enforce that all requests to retrieve the data provide encryption in transit?

- A. Define a resource-based policy on the S3 bucket to deny access when a request meets the condition "aws:SecureTransport": "false".
- B. Define a resource-based policy on the S3 bucket to allow access when a request meets the condition "aws:SecureTransport": "false".
- C. Define a role-based policy on the other accounts' roles to deny access when a request meets the condition of "aws:SecureTransport": "false".
- D. Define a resource-based policy on the KMS key to deny access when a request meets the condition of "aws:SecureTransport": "false".

**Answer: A**

#### NEW QUESTION 60

A financial company must store original customer records for 10 years for legal reasons. A complete record contains personally identifiable information (PII). According to local regulations, PII is available to only certain people in the company and must not be shared with third parties. The company needs to make the records available to third-party organizations for statistical analysis without sharing the PII.

A developer wants to store the original immutable record in Amazon S3. Depending on who accesses the S3 document, the document should be returned as is or

with all the PII removed. The developer has written an AWS Lambda function to remove the PII from the document. The function is named removePii. What should the developer do so that the company can meet the PII requirements while maintaining only one copy of the document?

- A. Set up an S3 event notification that invokes the removePii function when an S3 GET request is made. Call Amazon S3 by using a GET request to access the object without PII.
- B. Set up an S3 event notification that invokes the removePii function when an S3 PUT request is made. Call Amazon S3 by using a PUT request to access the object without PII.
- C. Create an S3 Object Lambda access point from the S3 console.
- D. Select the removePii function.
- E. Use S3 Access Points to access the object without PII.
- F. Create an S3 access point from the S3 console.
- G. Use the access point name to call the GetObjectLegalHold S3 API function.
- H. Pass in the removePii function name to access the object without PII.

**Answer: C**

#### NEW QUESTION 63

A development team wants to build a continuous integration/continuous delivery (CI/CD) pipeline. The team is using AWS CodePipeline to automate the code build and deployment. The team wants to store the program code to prepare for the CI/CD pipeline. Which AWS service should the team use to store the program code?

- A. AWS CodeDeploy
- B. AWS CodeArtifact
- C. AWS CodeCommit
- D. Amazon CodeGuru

**Answer: C**

#### NEW QUESTION 67

A company is building a serverless application on AWS. The application uses an AWS Lambda function to process customer orders 24 hours a day, 7 days a week. The Lambda function calls an external vendor's HTTP API to process payments. During load tests, a developer discovers that the external vendor payment processing API occasionally times out and returns errors. The company expects that some payment processing API calls will return errors. The company wants the support team to receive notifications in near real time only when the payment processing external API error rate exceeds 5% of the total number of transactions in an hour. Developers need to use an existing Amazon Simple Notification Service (Amazon SNS) topic that is configured to notify the support team. Which solution will meet these requirements?

- A. Write the results of payment processing API calls to Amazon CloudWatch.
- B. Use Amazon CloudWatch Logs Insights to query the CloudWatch log.
- C. Schedule the Lambda function to check the CloudWatch logs and notify the existing SNS topic.
- D. Publish custom metrics to CloudWatch that record the failures of the external payment processing API call.
- E. Configure a CloudWatch alarm to notify the existing SNS topic when error rate exceeds the specified rate.
- F. Publish the results of the external payment processing API calls to a new Amazon SNS topic.
- G. Subscribe the support team members to the new SNS topic.
- H. Write the results of the external payment processing API calls to Amazon S3. Schedule an Amazon Athena query to run at regular intervals.
- I. Configure Athena to send notifications to the existing SNS topic when the error rate exceeds the specified rate.

**Answer: B**

#### NEW QUESTION 72

A company is building a web application on AWS. When a customer sends a request, the application will generate reports and then make the reports available to the customer within one hour. Reports should be accessible to the customer for 8 hours. Some reports are larger than 1 MB. Each report is unique to the customer. The application should delete all reports that are older than 2 days. Which solution will meet these requirements with the LEAST operational overhead?

- A. Generate the reports and then store the reports as Amazon DynamoDB items that have a specified TTL.
- B. Generate a URL that retrieves the reports from DynamoDB.
- C. Provide the URL to customers through the web application.
- D. Generate the reports and then store the reports in an Amazon S3 bucket that uses server-side encryption. Attach the reports to an Amazon Simple Notification Service (Amazon SNS) message.
- E. Subscribe the customer to email notifications from Amazon SNS.
- F. Generate the reports and then store the reports in an Amazon S3 bucket that uses server-side encryption. Generate a presigned URL that contains an expiration date. Provide the URL to customers through the web application.
- G. Add S3 Lifecycle configuration rules to the S3 bucket to delete old reports.
- H. Generate the reports and then store the reports in an Amazon RDS database with a date stamp.
- I. Generate a URL that retrieves the reports from the RDS database.
- J. Provide the URL to customers through the web application.
- K. Schedule an hourly AWS Lambda function to delete database records that have expired date stamps.

**Answer: B**

#### NEW QUESTION 74

A developer is creating a template that uses AWS CloudFormation to deploy an application. The application is serverless and uses Amazon API Gateway, Amazon DynamoDB, and AWS Lambda. Which AWS service or tool should the developer use to define serverless resources in YAML?

- A. CloudFormation serverless intrinsic functions
- B. AWS Elastic Beanstalk

- C. AWS Serverless Application Model (AWS SAM)
- D. AWS Cloud Development Kit (AWS CDK)

**Answer:** C

**NEW QUESTION 76**

.....

## THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual DVA-C02 Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the DVA-C02 Product From:

<https://www.2passeasy.com/dumps/DVA-C02/>

## Money Back Guarantee

### **DVA-C02 Practice Exam Features:**

- \* DVA-C02 Questions and Answers Updated Frequently
- \* DVA-C02 Practice Questions Verified by Expert Senior Certified Staff
- \* DVA-C02 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- \* DVA-C02 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year