



Amazon

Exam Questions AWS-Certified-Solutions-Architect-Professional

Amazon AWS Certified Solutions Architect Professional

NEW QUESTION 1

By default, Amazon Cognito maintains the last-written version of the data. You can override this behavior and resolve data conflicts programmatically. In addition, push synchronization allows you to use Amazon Cognito to send a silent notification to all devices associated with an identity to notify them that new data is available.

- A. get
- B. post
- C. pull
- D. push

Answer: D

Explanation:

By default, Amazon Cognito maintains the last-written version of the data. You can override this behavior and resolve data conflicts programmatically. In addition, push synchronization allows you to use Amazon Cognito to send a silent push notification to all devices associated with an identity to notify them that new data is available.

Reference: <http://aws.amazon.com/cognito/faqs/>

NEW QUESTION 2

You want to use AWS CodeDeploy to deploy an application to Amazon EC2 instances running within an Amazon Virtual Private Cloud (VPC). What criterion must be met for this to be possible?

- A. The AWS CodeDeploy agent installed on the Amazon EC2 instances must be able to access only the public AWS CodeDeploy endpoint.
- B. The AWS CodeDeploy agent installed on the Amazon EC2 instances must be able to access only the public Amazon S3 service endpoint.
- C. The AWS CodeDeploy agent installed on the Amazon EC2 instances must be able to access the public AWS CodeDeploy and Amazon S3 service endpoints.
- D. It is not currently possible to use AWS CodeDeploy to deploy an application to Amazon EC2 instances running within an Amazon Virtual Private Cloud (VPC.)

Answer: C

Explanation:

You can use AWS CodeDeploy to deploy an application to Amazon EC2 instances running within an Amazon Virtual Private Cloud (VPC). However, the AWS CodeDeploy agent installed on the Amazon EC2 instances must be able to access the public AWS CodeDeploy and Amazon S3 service endpoints. Reference: <http://aws.amazon.com/codedeploy/faqs/>

NEW QUESTION 3

An IAM user is trying to perform an action on an object belonging to some other root account's bucket. Which of the below mentioned options will AWS S3 not verify?

- A. The object owner has provided access to the IAM user
- B. Permission provided by the parent of the IAM user on the bucket
- C. Permission provided by the bucket owner to the IAM user
- D. Permission provided by the parent of the IAM user

Answer: B

Explanation:

If the IAM user is trying to perform some action on the object belonging to another AWS user's bucket, S3 will verify whether the owner of the IAM user has given sufficient permission to him. It also verifies the policy for the bucket as well as the policy defined by the object owner.

Reference:

<http://docs.aws.amazon.com/AmazonS3/latest/dev/access-control-auth-workflow-object-operation.html>

NEW QUESTION 4

In the context of AWS IAM, identify a true statement about user passwords (login profiles).

- A. They must contain Unicode characters.
- B. They can contain any Basic Latin (ASCII) characters.
- C. They must begin and end with a forward slash (/).
- D. They cannot contain Basic Latin (ASCII) characters.

Answer: B

Explanation:

The user passwords (login profiles) of IAM users can contain any Basic Latin (ASCII) characters. Reference:

<http://docs.aws.amazon.com/IAM/latest/UserGuide/LimitationsOnEntities.html>

NEW QUESTION 5

An organization is planning to host a Wordpress blog as well a Joomla CMS on a single instance launched with VPC. The organization wants to have separate domains for each application and assign them using Route 53. The organization may have about ten instances each with two applications as mentioned above. While launching the instance, the organization configured two separate network interfaces (primary + ENI) and wanted to have two elastic IPs for that instance. It was suggested to use a public IP from AWS instead of an elastic IP as the number of elastic IPs is restricted. What action will you recommend to the organization?

- A. I agree with the suggestion but will prefer that the organization should use separate subnets with each ENI for different public IPs.
- B. I do not agree as it is required to have only an elastic IP since an instance has more than one ENI and AWS does not assign a public IP to an instance with multiple ENIs.
- C. I do not agree as AWS VPC does not attach a public IP to an ENI; so the user has to use only an elastic IP only.
- D. I agree with the suggestion and it is recommended to use a public IP from AWS since the organization is going to use DNS with Route 53.

Answer: B

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. An Elastic Network Interface (ENI) is a virtual network interface that the user can attach to an instance in a VPC.

The user can attach up to two ENIs with a single instance. However, AWS cannot assign a public IP when there are two ENIs attached to a single instance. It is recommended to assign an elastic IP in this scenario. If the organization wants more than 5 EIPs they can request AWS to increase the number.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/using-eni.html>

NEW QUESTION 6

A customer has a website which shows all the deals available across the market. The site experiences a load of 5 large EC2 instances generally. However, a week before Thanksgiving vacation they encounter a load of almost 20 large instances. The load during that period varies over the day based on the office timings.

Which of the below mentioned solutions is cost effective as well as help the website achieve better performance?

- A. Setup to run 10 instances during the pre-vacation period and only scale up during the office time by launching 10 more instances using the AutoScaling schedule.
- B. Keep only 10 instances running and manually launch 10 instances every day during office hours.
- C. During the pre-vacation period setup 20 instances to run continuously.
- D. During the pre-vacation period setup a scenario where the organization has 15 instances running and 5 instances to scale up and down using Auto Scaling based on the network I/O policy.

Answer: D

Explanation:

AWS provides an on demand, scalable infrastructure. AWS EC2 allows the user to launch On-Demand instances and the organization should create an AMI of the running instance. When the organization is experiencing varying loads and the time of the load is not known but it is higher than the routine traffic it is recommended that the organization launches a few instances before hand and then setups AutoScaling with policies which scale up and down as per the EC2 metrics, such as Network I/O or CPU utilization.

If the organization keeps all 10 additional instances as a part of the AutoScaling policy sometimes during a sudden higher load it may take time to launch instances and may not give an optimal performance. This is the reason it is recommended that the organization keeps an additional 5 instances running and the next 5 instances scheduled as per the AutoScaling policy for cost effectiveness.

Reference: http://media.amazonwebservices.com/AWS_Web_Hosting_Best_Practices.pdf

NEW QUESTION 7

In which step of using AWS Direct Connect should the user determine the required port speed?

- A. Complete the Cross Connect
- B. Verify Your Virtual Interface
- C. Download Router Configuration
- D. Submit AWS Direct Connect Connection Request

Answer: D

Explanation:

To submit an AWS Direct Connect connection request, you need to provide the following information: Your contact information.

The AWS Direct Connect Location to connect to.

Details of AWS Direct Connect partner if you use the AWS Partner Network (APN) service. The port speed you require, either 1 Gbps or 10 Gbps.

Reference: <http://docs.aws.amazon.com/directconnect/latest/UserGuide/getstarted.html#ConnectionRequest>

NEW QUESTION 8

In Amazon IAM, what is the maximum length for a role name?

- A. 128 characters
- B. 512 characters
- C. 64 characters
- D. 256 characters

Answer: C

Explanation:

In Amazon IAM, the maximum length for a role name is 64 characters.

Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/LimitationsOnEntities.html>

NEW QUESTION 9

How many g2.2xlarge on-demand instances can a user run in one region without taking any limit increase approval from AWS?

- A. 20
- B. 2
- C. 5
- D. 10

Answer: C

Explanation:

Generally AWS EC2 allows running 20 on-demand instances and 100 spot instances at a time. This limit can be increased by requesting at

<https://aws.amazon.com/contact-us/ec2-request>. Excluding certain types of instances, the limit is lower than mentioned above. For g2.2xlarge, the user can run only 5

on-demand instance at a time.

Reference: http://docs.aws.amazon.com/general/latest/gr/aws_service_limits.html#limits_ec2

NEW QUESTION 10

A user has created a MySQL RDS instance with PIOPS. Which of the below mentioned statements will help user understand the advantage of PIOPS?

- A. The user can achieve additional dedicated capacity for the EBS I/O with an enhanced RDS option
- B. It uses a standard EBS volume with optimized configuration the stacks
- C. It uses optimized EBS volumes and optimized configuration stacks
- D. It provides a dedicated network bandwidth between EBS and RDS

Answer: C

Explanation:

RDS DB instance storage comes in two types: standard and provisioned IOPS. Standard storage is allocated on the Amazon EBS volumes and connected to the user's DB instance. Provisioned IOPS uses

optimized EBS volumes and an optimized configuration stack. It provides additional, dedicated capacity for the EBS I/O.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Welcome.html>

NEW QUESTION 10

When does an AWS Data Pipeline terminate the AWS Data Pipeline-managed compute resources?

- A. AWS Data Pipeline terminates AWS Data Pipeline-managed compute resources every 2 hours.
- B. When the final actMty that uses the resources is running
- C. AWS Data Pipeline terminates AWS Data Pipeline-managed compute resources every 12 hours.
- D. When the final actMty that uses the resources has completed successfully or failed

Answer: D

Explanation:

Compute resources will be provisioned by AWS Data Pipeline when the first actMty for a scheduled time that uses those resources is ready to run, and those instances will be terminated when the final actMty that uses the resources has completed successfully or failed.

Reference: <https://aws.amazon.com/datapipeline/faqs/>

NEW QUESTION 15

If no explicit deny is found while applying IAM's Policy Evaluation Logic, the enforcement code looks for any instructions that would apply to the request.

- A. "cancel"
- B. "suspend"
- C. "allow"
- D. "valid"

Answer: C

Explanation:

If an explicit deny is not found among the applicable policies for a specific request, IAM's Policy Evaluation Logic checks for any "allow" instructions to check if the request can be successfully completed.

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage_EvaluationLogic.html

NEW QUESTION 17

The MySecureData company has five branches across the globe. They want to expand their data centers such that their web server will be in the AWS and each branch would have their own database in the local data center. Based on the user login, the company wants to connect to the data center. How can MySecureData company implement this scenario with the AWS VPC?

- A. Create five VPCs with the public subnet for the app server and setup the VPN gateway for each VPN to connect them indMdually.
- B. Use the AWS VPN CloudHub to communicate with multiple VPN connections.
- C. Use the AWS CloudGateway to communicate with multiple VPN connections.
- D. It is not possible to connect different data centers from a single VPC.

Answer: B

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. The user can create subnets as per the requirement within a VPC. If the user wants to connect VPC from his own data centre, he can setup a public and VPN only subnet which uses hardware VPN access to connect with his data centre. If the organization has multiple VPN connections, he can provide secure communication between sites using the AWS VPN CloudHub.

The VPN CloudHub operates on a simple hub-and-spoke model that the user can use with or without a VPC. This design is suitable for customers with multiple branch offices and existing internet connections who would like to implement a convenient, potentially low-cost hub-and-spoke model for primary or backup connectMty between remote offices.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPN_CloudHub.html

NEW QUESTION 21

One of your AWS Data Pipeline actMties has failed consequently and has entered a hard failure state after retrying thrice. You want to try it again. Is it possible to increase the number of automatic retries to more than thrice?

- A. Yes, you can increase the number of automatic retries to 6.
- B. Yes, you can increase the number of automatic retries to indefinite number.
- C. No, you cannot increase the number of automatic retries.
- D. Yes, you can increase the number of automatic retries to 10.

Answer: D

Explanation:

In AWS Data Pipeline, an actMty fails if all of its actMty attempts return with a failed state. By default, an actMty retries three times before entering a hard failure state. You can increase the number of automatic retries to 10. However, the system does not allow indefinite retries.

Reference: <https://aws.amazon.com/datapipeline/faqs/>

NEW QUESTION 22

True or False: In Amazon ElastiCache replication groups of Redis, for performance tuning reasons, you can change the roles of the cache nodes within the replication group, with the primary and one of the replicas exchanging roles.

- A. True, however, you get lower performance.
- B. FALSE
- C. TRUE
- D. False, you must recreate the replication group to improve performance tunin

Answer: C

Explanation:

In Amazon ElastiCache, a replication group is a collection of Redis Cache Clusters, with one primary read-write cluster and up to five secondary, read-only clusters, which are called read replicas. You can change the roles of the cache clusters within the replication group, with the primary cluster and one of the replicas exchanging roles. You might decide to do this for performance tuning reasons.

Reference: <http://docs.aws.amazon.com/AmazonElastiCache/latest/UserGuide/Replication.Redis.Groups.html>

NEW QUESTION 26

How much memory does the cr1.8xlarge instance type provide?

- A. 224 GB
- B. 124 GB
- C. 184 GB
- D. 244 GB

Answer: D

Explanation:

The CR1 instances are part of the memory optimized instances. They offer lowest cost per GB RAM among all the AWS instance families. CR1 instances are part of the new generation of memory optimized instances, which can offer up to 244 GB RAM and run on faster CPUs (Intel Xeon E5-2670 with NUMA support) in comparison to the NI2 instances of the same family. They support cluster networking for bandwidth intensive applications. cr1.8xlarge is one of the largest instance types of the CR1 family, which can offer 244 GB RAM.

Reference: <http://aws.amazon.com/ec2/instance-types/>

NEW QUESTION 30

How many cg1.4xlarge on-demand instances can a user run in one region without taking any limit increase approval from AWS?

- A. 20
- B. 2
- C. 5
- D. 10

Answer: B

Explanation:

Generally AWS EC2 allows running 20 on-demand instances and 100 spot instances at a time. This limit can be increased by requesting at <https://aws.amazon.com/contact-us/ec2-request>. Excluding certain types of instances, the limit is lower than mentioned above. For cg1.4xlarge, the user can run only 2

on-demand instances at a time.

Reference: http://docs.aws.amazon.com/general/latest/gr/aws_service_limits.html#limits_ec2

NEW QUESTION 35

You want to define permissions for a role in an IAM policy. Which of the following configuration formats should you use?

- A. An XML document written in the IAM Policy Language
- B. An XML document written in a language of your choice
- C. A JSON document written in the IAM Policy Language
- D. A JSON document written in a language of your choice

Answer: C

Explanation:

You define the permissions for a role in an IAM policy. An IAM policy is a JSON document written in the IAM Policy Language.

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/id_roles_terms-and-concepts.html

NEW QUESTION 37

An organization is setting up a backup and restore system in AWS of their in premise system. The organization needs High Availability(HA) and Disaster Recovery(DR) but is okay to have a longer recovery time to save costs. Which of the below mentioned setup options helps achieve the objective of cost saving as well as DR in the most effective way?

- A. Setup pre- configured sewers and create AMLs.. Use EIP and Route 53 to quickly switch over to AWS from in premise.
- B. Setup the backup data on S3 and transfer data to S3 regularly using the storage gateway.
- C. Setup a small instance with AutoScaling; in case of DR start diverting all the load to AWS from on premise.
- D. Replicate on premise DB to EC2 at regular intervals and setup a scenario similar to the pilot ligh

Answer: B

Explanation:

AWS has many solutions for Disaster Recovery(DR) and High Availability(HA). When the organization wants to have HA and DR but are okay to have a longer recovery time they should select the option backup and restore with S3. The data can be sent to S3 using either Direct Connect, Storage Gateway or over the internet.

The EC2 instance will pick the data from the S3 bucket when started and setup the environment. This process takes longer but is very cost effective due to the low pricing of S3. In all the other options, the EC2 instance might be running or there will be AMI storage costs.

Thus, it will be a costlier option. In this scenario the organization should plan appropriate tools to take a backup, plan the retention policy for data and setup security of the data.

Reference: http://d36cz9buwru1tt.cloudfront.net/AWS_Disaster_Recovery.pdf

NEW QUESTION 39

What feature of the load balancing service attempts to force subsequent connections to a service to be redirected to the same node as long as it is online?

- A. Node balance
- B. Session retention
- C. Session multiplexing
- D. Session persistence

Answer: D

Explanation:

Session persistence is a feature of the load balancing service. It attempts to force subsequent connections to a service to be redirected to the same node as long as it is online.

Reference:

<http://docs.rackspace.com/loadbalancers/api/v1.0/clb-devguide/content/Concepts-d1e233.html>

NEW QUESTION 41

What types of identities do Amazon Cognito identity pools support?

- A. They support both authenticated and unauthenticated identities.
- B. They support only unauthenticated identities.
- C. They support neither authenticated nor unauthenticated identities.
- D. They support only authenticated identitie

Answer: A

Explanation:

Amazon Cognito identity pools support both authenticated and unauthenticated identities. Authenticated identities belong to users who are authenticated by a public login provider or your own backend authentication process. Unauthenticated identities typically belong to guest users. Reference:

[http://docs.aws.amazon.com/cognito/devguide/identity/identity-pool\[s/](http://docs.aws.amazon.com/cognito/devguide/identity/identity-pool[s/)

NEW QUESTION 46

In IAM, which of the following is true of temporary security credentials?

- A. Once you issue temporary security credentials, they cannot be revoked.
- B. None of these are correct.
- C. Once you issue temporary security credentials, they can be revoked only when the virtual MFA device is used.
- D. Once you issue temporary security credentials, they can be revoke

Answer: A

Explanation:

Temporary credentials in IAM are valid throughout their defined duration of time and hence can't be revoked. However, because permissions are evaluated each time an AWS request is made using the credentials, you can achieve the effect of revoking the credentials by changing the permissions for the credentials even after they have been issued. Reference:

[http://docs.aws.amazon.com/IAM/latest/UserGuide/id_credentials_temp_control-access_disable-perms.h tml](http://docs.aws.amazon.com/IAM/latest/UserGuide/id_credentials_temp_control-access_disable-perms.html)

NEW QUESTION 48

The CFO of a company wants to allow one of his employees to view only the AWS usage report page. Which of the below mentioned IAM policy statements allows the user to have access to the AWS usage report page?

- A. "Effect": "Allow", "Action": ["Describe"], "Resource": "Billing"
- B. "Effect": "Allow", "Action": ["aws-portal: ViewBi||ing"], "Resource": ""
- C. "Effect": "Allow", "Action": ["aws-portal:ViewUsage"], "Resource": ""
- D. "Effect": "Allow", "Action": ["AccountUsage], "Resource": ""

Answer: C

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. If the CFO wants to allow only AWS usage report page access, the policy for that IAM user will be as given below:

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow", "Action": [
        "aws-portal:ViewUsage"
      ]
    }
  ]
}
```

Reference: <http://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/billing-permissions-ref.html>

NEW QUESTION 51

The user has provisioned the PIOPS volume with an EBS optimized instance. Generally speaking, in which I/O chunk should the bandwidth experienced by the user be measured by AWS?

- A. 128 KB
- B. 256 KB
- C. 64 KB
- D. 32 KB

Answer: B

Explanation:

IOPS are input/output operations per second. Amazon EBS measures each I/O operation per second (that is 256 KB or smaller) as one IOPS.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-io-characteristics.html>

NEW QUESTION 54

A user is planning to use EBS for his DB requirement. The user already has an EC2 instance running in the VPC private subnet. How can the user attach the EBS volume to a running instance?

- A. The user can create EBS in the same zone as the subnet of instance and attach that EBS to instance.
- B. It is not possible to attach an EBS to an instance running in VPC until the instance is stopped.
- C. The user can specify the same subnet while creating EBS and then attach it to a running instance.
- D. The user must create EBS within the same VPC and then attach it to a running instance.

Answer: A

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. The user can create subnets as per the requirement within a VPC. The VPC is always specific to a region. The user can create a VPC which can span multiple Availability Zones by adding one or more subnets in each Availability Zone. The instance launched will always be in the same availability zone of the respective subnet. When creating an EBS the user cannot specify the subnet or VPC. However, the user must create the EBS in the same zone as the instance so that it can attach the EBS volume to the running instance.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Subnets.html#VPCSubnet

NEW QUESTION 59

Cognito Sync is an AWS service that you can use to synchronize user profile data across mobile devices without requiring your own backend. When the device is online, you can synchronize data. If you also set up push sync, what does it allow you to do?

- A. Notify other devices that a user profile is available across multiple devices
- B. Synchronize user profile data with less latency
- C. Notify other devices immediately that an update is available
- D. Synchronize online data faster

Answer: C

Explanation:

Cognito Sync is an AWS service that you can use to synchronize user profile data across mobile devices without requiring your own backend. When the device is online, you can synchronize data, and if you have

also set up push sync, notify other devices immediately that an update is available. Reference: <http://docs.aws.amazon.com/cognito/devguide/sync/>

NEW QUESTION 64

An organization has hosted an application on the EC2 instances. There will be multiple users connecting to the instance for setup and configuration of application. The organization is planning to implement certain security best practices. Which of the below mentioned pointers will not help the organization achieve better security arrangement?

- A. Allow only IAM users to connect with the EC2 instances with their own secret access key.
- B. Create a procedure to revoke the access rights of the indM dual user when they are not required to connect to EC2 instance anymore for the purpose of application configuration.
- C. Apply the latest patch of OS and always keep it updated.
- D. Disable the password based login for all the user
- E. All the users should use their own keys to connect with the instance securely.

Answer: A

Explanation:

Since AWS is a public cloud any application hosted on EC2 is prone to hacker attacks. It becomes extremely important for a user to setup a proper security mechanism on the EC2 instances. A few of the security measures are listed below:

Always keep the OS updated with the latest patch

Always create separate users with in OS if they need to connect with the EC2 instances, create their keys and disable their password
Create a procedure using which the admin can revoke the access of the user when the business work on the EC2 instance is completed
Lock down unnecessary ports
Audit any proprietary applications that the user may be running on the EC2 instance
Provide temporary escalated privileges, such as sudo for users who need to perform occasional privileged tasks
The IAM is useful when users are required to work with AWS resources and actions, such as launching an instance. It is not useful to connect (RDP / SSH) with an instance.
Reference: <http://aws.amazon.com/articles/1233/>

NEW QUESTION 66

What RAID method is used on the Cloud Block Storage back-end to implement a very high level of reliability and performance?

- A. RAID 1 (Mirror)
- B. RAID 5 (Blocks striped, distributed parity)
- C. RAID 10 (Blocks mirrored and striped)
- D. RAID 2 (Bit level striping)

Answer: C

Explanation:

Cloud Block Storage back-end storage volumes employs the RAID 10 method to provide a very high level of reliability and performance.
Reference: http://www.rackspace.com/knowledge_center/product-faq/cloud-block-storage

NEW QUESTION 70

One of the AWS account owners faced a major challenge in June as his account was hacked and the hacker deleted all the data from his AWS account. This resulted in a major blow to the business.
Which of the below mentioned steps would not have helped in preventing this action?

- A. Setup an MFA for each user as well as for the root account user.
- B. Take a backup of the critical data to offsite / on premise.
- C. Create an AMI and a snapshot of the data at regular intervals as well as keep a copy to separate regions.
- D. Do not share the AWS access and secret access keys with others as well do not store it inside programs, instead use IAM roles.

Answer: C

Explanation:

AWS security follows the shared security model where the user is as much responsible as Amazon. If the user wants to have secure access to AWS while hosting applications on EC2, the first security rule to follow is to enable MFA for all users. This will add an added security layer. In the second step, the user should never give his access or secret access keys to anyone as well as store inside programs. The better solution is to use IAM roles. For critical data of the organization, the user should keep an offsite/ in premise backup which will help to recover critical data in case of security breach.
It is recommended to have AWS AMIs and snapshots as well as keep them at other regions so that they will help in the DR scenario. However, in case of a data security breach of the account they may not be very helpful as hacker can delete that.
Therefore ,creating an AMI and a snapshot of the data at regular intervals as well as keep a copy to separate regions, would not have helped in preventing this action.
Reference: http://media.amazonwebservices.com/pdf/AWS_Security_Whitepaper.pdf

NEW QUESTION 74

In Amazon SNS, to send push notifications to mobile devices using Amazon SNS and ADM, you need to obtain the following, except:

- A. Device token
- B. Client ID
- C. Registration ID
- D. Client secret

Answer: A

Explanation:

To send push notifications to mobile devices using Amazon SNS and ADM, you need to obtain the following: Registration ID and Client secret.
Reference: <http://docs.aws.amazon.com/sns/latest/dg/SNSMobilePushPrereq.html>

NEW QUESTION 79

How does in-memory caching improve the performance of applications in ElastiCache?

- A. It improves application performance by deleting the requests that do not contain frequently accessed data.
- B. It improves application performance by implementing good database indexing strategies.
- C. It improves application performance by using a part of instance RAM for caching important data.
- D. It improves application performance by storing critical pieces of data in memory for low-latency access

Answer: D

Explanation:

In Amazon ElastiCache, in-memory caching improves application performance by storing critical pieces of data in memory for low-latency access. Cached information may include the results of I/O-intensive database queries or the results of computationally intensive calculations.
Reference: <http://aws.amazon.com/elasticache/faqs/#g4>

NEW QUESTION 81

A user is thinking to use EBS PIOPS volume. Which of the below mentioned options is a right use case for the PIOPS EBS volume?

- A. Analytics
- B. System boot volume
- C. Nlongo DB
- D. Log processing

Answer: C

Explanation:

Provisioned IOPS volumes are designed to meet the needs of I/O-intensive workloads, particularly database workloads that are sensitive to storage performance and consistency in random access I/O throughput. Provisioned IOPS volumes are designed to meet the needs of I/O-intensive workloads, particularly database workloads, that are sensitive to storage performance and consistency in random access I/O throughput business applications, database workloads, such as NoSQL DB, RDBMS, etc. Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSVolumeTypes.html>

NEW QUESTION 83

In the context of policies and permissions in AWS IAM, the Condition element is .

- A. crucial while writing the IAM policies
- B. an optional element
- C. always set to null
- D. a mandatory element

Answer: B

Explanation:

The Condition element (or Condition block) lets you specify conditions for when a policy is in effect. The Condition element is optional. Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage_ElementDescriptions.html

NEW QUESTION 88

When using string conditions within IAM, short versions of the available comparators can be used instead of the more verbose ones. streqi is the short version of the string condition.

- A. StringEqualsIgnoreCase
- B. StringNotEqualsIgnoreCase
- C. StringLikeStringEquals
- D. StringNotEquals

Answer: A

Explanation:

When using string conditions within IAM, short versions of the available comparators can be used instead of the more verbose versions. For instance, streqi is the short version of StringEqualsIgnoreCase that checks for the exact match between two strings ignoring their case. Reference: <http://awsdocs.s3.amazonaws.com/SNS/20100331/sns-gsg-2010-03-31.pdf>

NEW QUESTION 90

Attempts, one of the three types of items associated with the schedule pipeline in the AWS Data Pipeline, provides robust data management. Which of the following statements is NOT true about Attempts?

- A. Attempts provide robust data management.
- B. AWS Data Pipeline retries a failed operation until the count of retries reaches the maximum number of allowed retry attempts.
- C. An AWS Data Pipeline Attempt object compiles the pipeline components to create a set of actionable instances.
- D. AWS Data Pipeline Attempt objects track the various attempts, results, and failure reasons if applicable.

Answer: C

Explanation:

Attempts, one of the three types of items associated with a schedule pipeline in AWS Data Pipeline, provides robust data management. AWS Data Pipeline retries a failed operation. It continues to do so until the task reaches the maximum number of allowed retry attempts. Attempt objects track the various attempts, results, and failure reasons if applicable. Essentially, it is the instance with a counter. AWS Data Pipeline performs retries using the same resources from the previous attempts, such as Amazon EMR clusters and EC2 instances.

Reference:

<http://docs.aws.amazon.com/datapipeline/latest/DeveloperGuide/dp-how-tasks-scheduled.html>

NEW QUESTION 91

Which of the following cannot be done using AWS Data Pipeline?

- A. Create complex data processing workloads that are fault tolerant, repeatable, and highly available.
- B. Regularly access your data where it's stored, transform and process it at scale, and efficiently transfer the results to another AWS service.
- C. Generate reports over data that has been stored.
- D. Move data between different AWS compute and storage services as well as on-premise data sources at specified intervals.

Answer: C

Explanation:

AWS Data Pipeline is a web service that helps you reliably process and move data between different AWS compute and storage services as well as on-premise data sources at specified intervals. With AWS Data Pipeline, you can regularly access your data where it's stored, transform and process it at scale, and efficiently transfer the results to another AWS.

AWS Data Pipeline helps you easily create complex data processing workloads that are fault tolerant, repeatable, and highly available. AWS Data Pipeline also allows you to move and process data that was

previously locked up in on-premise data silos. Reference: <http://aws.amazon.com/datapipeline/>

NEW QUESTION 92

Identify an application that polls AWS Data Pipeline for tasks and then performs those tasks.

- A. A task executor
- B. A task deployer
- C. A task runner
- D. A task optimizer

Answer: C

Explanation:

A task runner is an application that polls AWS Data Pipeline for tasks and then performs those tasks. You can either use Task Runner as provided by AWS Data Pipeline, or create a custom Task Runner application.

Task Runner is a default implementation of a task runner that is provided by AWS Data Pipeline. When Task Runner is installed and configured, it polls AWS Data Pipeline for tasks associated with pipelines that you have activated. When a task is assigned to Task Runner, it performs that task and reports its status back to AWS Data Pipeline. If your workflow requires non-default behavior, you'll need to implement that functionality in a custom task runner.

Reference:

<http://docs.aws.amazon.com/datapipeline/latest/DeveloperGuide/dp-how-remote-taskrunner-client.html>

NEW QUESTION 93

An organization is planning to use NoSQL DB for its scalable data needs. The organization wants to host an application securely in AWS VPC. What action can be recommended to the organization?

- A. The organization should setup their own NoSQL cluster on the AWS instance and configure route tables and subnets.
- B. The organization should only use a DynamoDB because by default it is always a part of the default subnet provided by AWS.
- C. The organization should use a DynamoDB while creating a table within the public subnet.
- D. The organization should use a DynamoDB while creating a table within a private subnet

Answer: A

Explanation:

The Amazon Virtual Private Cloud (Amazon VPC) allows the user to define a virtual networking environment in a private, isolated section of the Amazon Web Services (AWS) cloud. The user has complete control over the virtual networking environment. Currently VPC does not support DynamoDB. Thus, if the user wants to implement VPC, he has to setup his own NoSQL DB within the VPC. Reference:

http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Introduction.html

NEW QUESTION 98

What happens when Dedicated instances are launched into a VPC?

- A. If you launch an instance into a VPC that has an instance tenancy of dedicated, you must manually create a Dedicated instance.
- B. If you launch an instance into a VPC that has an instance tenancy of dedicated, your instance is created as a Dedicated instance, only based on the tenancy of the instance.
- C. If you launch an instance into a VPC that has an instance tenancy of dedicated, your instance is automatically a Dedicated instance, regardless of the tenancy of the instance.
- D. None of these are true

Answer: C

Explanation:

If you launch an instance into a VPC that has an instance tenancy of dedicated, your instance is automatically a Dedicated instance, regardless of the tenancy of the instance.

Reference: <http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/dedicated-instance.html>

NEW QUESTION 99

An organization is setting up RDS for their applications. The organization wants to secure RDS access with VPC. Which of the following options is not required while designing the RDS with VPC?

- A. The organization must create a subnet group with public and private subnet
- B. Both the subnets can be in the same or separate AZ.
- C. The organization should keep minimum of one IP address in each subnet reserved for RDS failover.
- D. If the organization is connecting RDS from the internet it must enable the VPC attributes DNS hostnames and DNS resolution.
- E. The organization must create a subnet group with VPC using more than one subnet which are a part of separate AZs.

Answer: A

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources, such as RDS into a virtual network that the user has defined. Subnets are segments of a VPC's IP address range that the user can designate to a group of VPC resources based on security and operational needs. A DB subnet group is a collection of subnets (generally private) that the user can create in a VPC and assign to the RDS DB instances. A DB subnet group allows the user to specify a particular VPC when creating the DB instances.

Each DB subnet group should have subnets in at least two Availability Zones in a given region. If the RDS instance is required to be accessible from the internet the organization must enable the VPC attributes, DNS hostnames and DNS resolution. For each RDS DB instance that the user runs in a VPC, he should reserve at least one address in each subnet in the DB subnet group for use by Amazon RDS for recovery actions.

Reference: http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER_VPC.html

NEW QUESTION 102

You create a VPN connection, and your VPN device supports Border Gateway Protocol (BGP). Which of the following should be specified to configure the VPN connection?

- A. Classless routing
- B. Classfull routing
- C. Dynamic routing
- D. Static routing

Answer: C

Explanation:

If you create a VPN connection, you must specify the type of routing that you plan to use, which will depend upon on the make and model of your VPN devices. If your VPN device supports Border Gateway Protocol (BGP), you need to specify dynamic routing when you configure your VPN connection. If your device does not support BGP, you should specify static routing.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_VPN.html

NEW QUESTION 107

An organization has developed an application which provides a smarter shopping experience. They need to show a demonstration to various stakeholders who may not be able to access the in premise application so they decide to host a demo version of the application on AWS. Consequently they will need a fixed elastic IP attached automatically to the instance when it is launched.

In this scenario which of the below mentioned options will not help assign the elastic IP automatically?

- A. Write a script which will fetch the instance metadata on system boot and assign the public IP using that metadata.
- B. Provide an elastic IP in the user data and setup a bootstrapping script which will fetch that elastic IP and assign it to the instance.
- C. Create a controlling application which launches the instance and assigns the elastic IP based on the parameter provided when that instance is booted.
- D. Launch instance with VPC and assign an elastic IP to the primary network interface

Answer: A

Explanation:

EC2 allows the user to launch On-Demand instances. If the organization is using an application temporarily only for demo purposes the best way to assign an elastic IP would be:

Launch an instance with a VPC and assign an EIP to the primary network interface. This way on every instance start it will have the same IP Create a bootstrapping script and provide it some metadata, such as user data which can be used to assign an EIP Create a controller instance which can schedule the start and stop of the instance and provide an EIP as a parameter so that the controller instance can check the instance boot and assign an EIP

The instance metadata gives the current instance data, such as the public/private IP. It can be of no use for assigning an EIP.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/AESDG-chapter-instancedata.html>

NEW QUESTION 109

In the context of IAM roles for Amazon EC2, which of the following NOT true about delegating permission to make API requests?

- A. You cannot create an IAM role.
- B. You can have the application retrieve a set of temporary credentials and use them.
- C. You can specify the role when you launch your instances.
- D. You can define which accounts or AWS services can assume the role

Answer: A

Explanation:

Amazon designed IAM roles so that your applications can securely make API requests from your instances, without requiring you to manage the security credentials that the applications use. Instead of creating and distributing your AWS credentials, you can delegate permission to make API requests using IAM roles as follows: Create an IAM role. Define which accounts or AWS services can assume the role. Define which API actions and resources the application can use after assuming the role. Specify the role when you launch your instances. Have the application retrieve a set of temporary credentials and use them.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/iam-roles-for-amazon-ec2.html>

NEW QUESTION 114

In Amazon Cognito what is a silent push notification?

- A. It is a push message that is received by your application on a user's device that will not be seen by the user
- B. It is a push message that is received by your application on a user's device that will return the user's geolocation.
- C. It is a push message that is received by your application on a user's device that will not be heard by the user
- D. It is a push message that is received by your application on a user's device that will return the user's authentication credentials.

Answer: A

Explanation:

Amazon Cognito uses the Amazon Simple Notification Service (SNS) to send silent push notifications to devices. A silent push notification is a push message that is received by your application on a user's device that will not be seen by the user.

Reference: <http://aws.amazon.com/cognito/faqs/>

NEW QUESTION 118

Which of following IAM policy elements lets you specify an exception to a list of actions?

- A. NotException
- B. ExceptionAction
- C. Exception
- D. NotAction

Answer: D

Explanation:

The NotAction element lets you specify an exception to a list of actions. Reference:

http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage_ElementDescriptions.html

NEW QUESTION 122

You are setting up some EBS volumes for a customer who has requested a setup which includes a RAID (redundant array of inexpensive disks). AWS has some recommendations for RAID setups. Which RAID setup is not recommended for Amazon EBS?

- A. RAID 1 only
- B. RAID 5 only
- C. RAID 5 and RAID 6
- D. RAID 0 only

Answer: C

Explanation:

With Amazon EBS, you can use any of the standard RAID configurations that you can use with a traditional bare metal server, as long as that particular RAID configuration is supported by the operating

system for your instance. This is because all RAID is accomplished at the software level. For greater I/O performance than you can achieve with a single volume, RAID 0 can stripe multiple volumes together; for on-instance redundancy, RAID 1 can mirror two volumes together.

RAID 5 and RAID 6 are not recommended for Amazon EBS because the parity write operations of these RAID modes consume some of the IOPS available to your volumes.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/raid-config.html>

NEW QUESTION 126

In the context of AWS Cloud Hardware Security Module(HSM), does your application need to reside in the same VPC as the CloudHSM instance?

- A. No, but the server or instance on which your application and the HSM client is running must have network (IP) reachability to the HSM.
- B. Yes, always
- C. No, but they must reside in the same Availability Zone.
- D. No, but it should reside in same Availability Zone as the DB instance

Answer: A

Explanation:

Your application does not need to reside in the same VPC as the CloudHSM instance.

However, the server or instance on which your application and the HSM client is running must have network (IP) reachability to the HSM. You can establish network connectivity in a variety of ways, including operating your application in the same VPC, with VPC peering, with a VPN connection, or with Direct Connect.

Reference: <https://aws.amazon.com/cloudhsm/faqs/>

NEW QUESTION 127

What is the role of the PollForTask action when it is called by a task runner in AWS Data Pipeline?

- A. It is used to retrieve the pipeline definition.
- B. It is used to report the progress of the task runner to AWS Data Pipeline.
- C. It is used to receive a task to perform from AWS Data Pipeline.
- D. It is used to inform AWS Data Pipeline of the outcome when the task runner completes a task

Answer: C

Explanation:

Task runners call PollForTask to receive a task to perform from AWS Data Pipeline. If tasks are ready in the work queue, PollForTask returns a response immediately. If no tasks are available in the queue, PollForTask uses long-polling and holds on to a poll connection for up to 90 seconds, during which time any newly scheduled tasks are handed to the task agent. Your remote worker should not call PollForTask again on the same worker group until it receives a response, and this may take up to 90 seconds. Reference: http://docs.aws.amazon.com/datapipeline/latest/APIReference/AP_PollForTask.html

NEW QUESTION 132

What is the average queue length recommended by AWS to achieve a lower latency for the 200 PIOPS EBS volume?

- A. 5
- B. 1
- C. 2
- D. 4

Answer: B

Explanation:

The queue length is the number of pending I/O requests for a device. The optimal average queue length will vary for every customer workload, and this value depends on a particular application's sensitivity to IOPS and latency. If the workload is not delivering enough I/O requests to maintain the optimal average queue

length, then the EBS volume might not consistently deliver the IOPS that have been provisioned. However, if the workload maintains an average queue length that is higher than the optimal value, then the per-request I/O latency will increase; in this case, the user should provision more IOPS for his volume. AWS recommends that the user should target an optimal average queue length of 1 for every 200 provisioned IOPS and tune that value based on his application requirements.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-workload-demand.html>

NEW QUESTION 133

A user is planning to host a Highly Available system on the AWS VPC. Which of the below mentioned statements is helpful in this scenario?

- A. Create VPC subnets in two separate availability zones and launch instances in different subnets.
- B. Create VPC with only one public subnet and launch instances in different AZs using that subnet.
- C. Create two VPCs in two separate zones and setup failover with ELB such that if one VPC fails it will divert traffic to another VPC.
- D. Create VPC with only one private subnet and launch instances in different AZs using that subnet

Answer: A

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. The VPC is always specific to a region. The user can create a VPC which can span multiple Availability Zones by adding one or more subnets in each Availability Zone. Each subnet must reside entirely within one Availability Zone and cannot span across zones.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Subnets.html#VPCSubnet

NEW QUESTION 137

A user is creating a PIOPS volume. What is the maximum ratio the user should configure between PIOPS and the volume size?

- A. 5
- B. 10
- C. 20
- D. 30

Answer: D

Explanation:

Provisioned IOPS volumes are designed to meet the needs of I/O-intensive workloads, particularly database workloads that are sensitive to storage performance and consistency in random access I/O throughput. A provisioned IOPS volume can range in size from 10 GB to 1 TB and the user can provision up to 4000 IOPS per volume.

The ratio of IOPS provisioned to the volume size requested can be a maximum of 30; for example, a volume with 3000 IOPS must be at least 100 GB.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSVolumeTypes.html>

NEW QUESTION 138

A government client needs you to set up secure cryptographic key storage for some of their extremely confidential data. You decide that the AWS CloudHSM is the best service for this. However, there seem to be a few pre-requisites before this can happen, one of those being a security group that has certain ports open. Which of the following is correct in regards to those security groups?

- A. A security group that has no ports open to your network.
- B. A security group that has only port 3389 (for RDP) open to your network.
- C. A security group that has only port 22 (for SSH) open to your network.
- D. A security group that has port 22 (for SSH) or port 3389 (for RDP) open to your network

Answer: D

Explanation:

AWS CloudHSM provides secure cryptographic key storage to customers by making hardware security modules (HSMs) available in the AWS cloud.

AWS CloudHSM requires the following environment before an HSM appliance can be provisioned. A virtual private cloud (VPC) in the region where you want the AWS CloudHSM service.

One private subnet (a subnet with no Internet gateway) in the VPC. The HSM appliance is provisioned into this subnet.

One public subnet (a subnet with an Internet gateway attached). The control instances are attached to this subnet.

An AWS Identity and Access Management (IAM) role that delegates access to your AWS resources to AWS CloudHSM.

An EC2 instance, in the same VPC as the HSM appliance, that has the SafeNet client software installed. This instance is referred to as the control instance and is used to connect to and manage the HSM appliance.

A security group that has port 22 (for SSH) or port 3389 (for RDP) open to your network. This security group is attached to your control instances so you can access them remotely.

NEW QUESTION 139

An organization is setting up a web application with the JEE stack. The application uses the JBoss app server and MySQL DB. The application has a logging module which logs all the activities whenever a business function of the JEE application is called. The logging activity takes some time due to the large size of the log file. If the application wants to setup a scalable infrastructure which of the below mentioned options will help achieve this setup?

- A. Host the log files on EBS with PIOPS which will have higher I/O.
- B. Host logging and the app server on separate servers such that they are both in the same zone.
- C. Host logging and the app server on the same instance so that the network latency will be shorter.
- D. Create a separate module for logging and using SQS compartmentalize the module such that all calls to logging are asynchronous.

Answer: D

Explanation:

The organization can always launch multiple EC2 instances in the same region across multiple AZs for HA and DR. The AWS architecture practice recommends compartmentalizing the functionality such that

they can both run in parallel without affecting the performance of the main application. In this scenario logging takes a longer time due to the large size of the log file. Thus, it is recommended that the organization should separate them out and make separate modules and make asynchronous calls among them. This way the application can scale as per the requirement and the performance will not bear the impact of logging.

Reference: <http://www.awsarchitectureblog.com/2014/03/aws-and-compartmentalization.html>

NEW QUESTION 144

A user has set the IAM policy where it denies all requests if a request is not from IP 10.10.10.1/32. The other policy says allow all requests between 5 PM to 7 PM. What will happen when a user is requesting access from IP 55.109.10.12/32 at 6 PM?

- A. It will deny access
- B. It is not possible to set a policy based on the time or IP
- C. IAM will throw an error for policy conflict
- D. It will allow access

Answer: A

Explanation:

When a request is made, the AWS IAM policy decides whether a given request should be allowed or denied. The evaluation logic follows these rules:

By default, all requests are denied. (In general, requests made using the account credentials for resources in the account are always allowed.)

An explicit allow policy overrides this default.

An explicit deny policy overrides any allows.

In this case since there are explicit deny and explicit allow statements. Thus, the request will be denied since deny overrides allow.

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage_EvaluationLogic.html

NEW QUESTION 148

Which of the following AWS services can be used to define alarms to trigger on a certain actMty, such as actMty success, failure, or delay in AWS Data Pipeline?

- A. Amazon SES
- B. Amazon CodeDeploy
- C. Amazon SNS
- D. Amazon SQS

Answer: C

Explanation:

In AWS Data Pipeline, you can define Amazon SNS alarms to trigger on actMties such as success, failure, or delay by creating an alarm object and referencing it in the onFail, onSuccess, or onLate slots of the actMty object.

Reference: <https://aws.amazon.com/datapipeline/faqs/>

NEW QUESTION 151

Which of the following components of AWS Data Pipeline polls for tasks and then performs those tasks?

- A. Pipeline Definition
- B. Task Runner
- C. Amazon Elastic MapReduce (EMR)
- D. AWS Direct Connect

Answer: B

Explanation:

Task Runner polls for tasks and then performs those tasks.

Reference: <http://docs.aws.amazon.com/datapipeline/latest/DeveloperGuide/what-is-datapipeline.html>

NEW QUESTION 156

A user is hosting a public website on AWS. The user wants to have the database and the app server on the AWS VPC. The user wants to setup a database that can connect to the Internet for any patch upgrade but cannot receive any request from the internet. How can the user set this up?

- A. Setup DB in a private subnet with the security group allowing only outbound traffic.
- B. Setup DB in a public subnet with the security group allowing only inbound data.
- C. Setup DB in a local data center and use a private gateway to connect the application with DB.
- D. Setup DB in a private subnet which is connected to the internet via NAT for outbound.

Answer: D

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. AWS provides two features that the user can use to increase security in VPC: security groups and network ACLs. When the user wants to setup both the DB and App on VPC, the user should make one public and one private subnet. The DB should be hosted in a private subnet and instances in that subnet cannot reach the internet. The user can allow an instance in his VPC to initiate outbound connections to the internet but prevent unsolicited inbound connections from the internet by using a Network Address Translation (NAT) instance.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Subnets.html

NEW QUESTION 160

In Amazon ElastiCache, the default cache port is:

- A. for Memcached 11210 and for Redis 6380.
- B. for Memcached 11211 and for Redis 6380.
- C. for Memcached 11210 and for Redis 6379.
- D. for Memcached 11211 and for Redis 6379.

Answer: D

Explanation:

In Amazon ElastiCache, you can specify a new port number for your cache cluster, which by default is 11211 for Memcached and 6379 for Redis.

Reference: <http://docs.aws.amazon.com/AmazonElastiCache/latest/UserGuide/GettingStarted.AuthorizeAccess.htm>

NEW QUESTION 161

Which of the following statements is correct about AWS Direct Connect?

- A. Connections to AWS Direct Connect require double clad fiber for 1 gigabit Ethernet with Auto Negotiation enabled for the port.
- B. An AWS Direct Connect location provides access to Amazon Web Services in the region it is associated with.
- C. AWS Direct Connect links your internal network to an AWS Direct Connect location over a standard 50 gigabit Ethernet cable.
- D. To use AWS Direct Connect, your network must be colocated with a new AWS Direct Connect location.

Answer: B

Explanation:

AWS Direct Connect links your internal network to an AWS Direct Connect location over a standard 1 gigabit or 10 gigabit Ethernet fiber-optic cable. An AWS Direct Connect location provides access to Amazon Web Services in the region it is associated with, as well as access to other US regions. To use AWS Direct Connect, your network is colocated with an existing AWS Direct Connect location. Connections to AWS Direct Connect require single mode fiber, 1000BASE-LX (1310nm) for 1 gigabit Ethernet, or 10GBASE-LR (1310nm) for 10 gigabit Ethernet. Auto Negotiation for the port must be disabled.

Reference: <http://docs.aws.amazon.com/directconnect/latest/UserGuide/Welcome.html>

NEW QUESTION 165

Is there any way to own a direct connection to Amazon Web Services?

- A. No, AWS only allows access from the public Internet.
- B. No, you can create an encrypted tunnel to VPC, but you cannot own the connection.
- C. Yes, you can via Amazon Dedicated Connection.
- D. Yes, you can via AWS Direct Connect.

Answer: D

Explanation:

AWS Direct Connect links your internal network to an AWS Direct Connect location over a standard 1 gigabit or 10 gigabit Ethernet fiber-optic cable. One end of the cable is connected to your router, the other to an AWS Direct Connect router. With this connection in place, you can create virtual interfaces directly to the AWS cloud (for example, to Amazon Elastic Compute Cloud (Amazon EC2) and Amazon Simple Storage Service (Amazon S3)) and to Amazon Virtual Private Cloud (Amazon VPC), bypassing Internet service providers in your network path.

Reference: <http://docs.aws.amazon.com/directconnect/latest/UserGuide/Welcome.html>

NEW QUESTION 170

In Amazon ElastiCache, which of the following statements is correct?

- A. When you launch an ElastiCache cluster into an Amazon VPC private subnet, every cache node is assigned a public IP address within that subnet.
- B. You cannot use ElastiCache in a VPC that is configured for dedicated instance tenancy.
- C. If your AWS account supports only the EC2-VPC platform, ElastiCache will never launch your cluster in a VPC.
- D. ElastiCache is not fully integrated with Amazon Virtual Private Cloud (VPC).

Answer: B

Explanation:

The VPC must allow non-dedicated EC2 instances. You cannot use ElastiCache in a VPC that is configured for dedicated instance tenancy.

Reference: <http://docs.aws.amazon.com/AmazonElastiCache/latest/UserGuide/AmazonVPC.EC.html>

NEW QUESTION 173

An organization has setup RDS with VPC. The organization wants RDS to be accessible from the internet. Which of the below mentioned configurations is not required in this scenario?

- A. The organization must enable the parameter in the console which makes the RDS instance publicly accessible.
- B. The organization must allow access from the internet in the RDS VPC security group.
- C. The organization must setup RDS with the subnet group which has an external IP.
- D. The organization must enable the VPC attributes DNS hostnames and DNS resolution.

Answer: C

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources, such as RDS into a virtual network that the user has defined. Subnets are segments of a VPC's IP address range that the user can designate to a group of VPC resources based on security and operational needs. A DB subnet group is a collection of subnets (generally private) that the user can create in a VPC and which the user assigns to the RDS DB instances. A DB subnet group allows the user to specify a particular VPC when creating DB instances. If the RDS instance is required to be accessible from the internet:

The organization must setup that the RDS instance is enabled with the VPC attributes, DNS hostnames and DNS resolution.

The organization must enable the parameter in the console which makes the RDS instance publicly accessible.

The organization must allow access from the internet in the RDS VPC security group. Reference:

http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER_VPC.html

NEW QUESTION 177

An organization, which has the AWS account ID as Q99988887777, has created 50 IAM users. All the users are added to the same group examkiller. If the organization has enabled that each IAM user can login with the AWS console, which AWS login URL will the IAM users use??

- A. <https://Q99988887777.aws.amazon.com/examkiller/>
- B. <https://signin.aws.amazon.com/examkiller/>
- C. <https://examkiller.signin.aws.amazon.com/999988887777/console/>
- D. <https://999988887777.signin.aws.amazon.com/console/>

Answer: D

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. Once the organization has created the IAM users, they will have a separate AWS console URL to login to the AWS console. The console login URL for the IAM user will be [https:// AWS_Account_ID.signin.aws.amazon.com/console/](https://AWS_Account_ID.signin.aws.amazon.com/console/). It uses only the AWS account ID and does not depend on the group or user ID.

Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/AccountAlias.html>

NEW QUESTION 180

You have deployed a web application targeting a global audience across multiple AWS Regions under the domain name.example.com. You decide to use Route53 Latency-Based Routing to serve web requests to users from the region closest to the user. To provide business continuity in the event of server downtime you configure weighted record sets associated with two web servers in separate Availability Zones per region. During a DR test you notice that when you disable all web servers in one of the regions Route53 does not automatically direct all users to the other region. What could be happening? (Choose 2 answers)

- A. Latency resource record sets cannot be used in combination with weighted resource record sets.
- B. You did not setup an HTTP health check to one or more of the weighted resource record sets associated with the disabled web servers.
- C. The value of the weight associated with the latency alias resource record set in the region with the disabled servers is higher than the weight for the other region.
- D. One of the two working web servers in the other region did not pass its HTTP health check.
- E. You did not set "Evaluate Target Health" to "Yes" on the latency alias resource record set associated with example.com in the region where you disabled the servers.

Answer: BE

NEW QUESTION 185

A read only news reporting site with a combined web and application tier and a database tier that receives large and unpredictable traffic demands must be able to respond to these traffic fluctuations automatically. What AWS services should be used to meet these requirements?

- A. Stateless instances for the web and application tier synchronized using ElastiCache Memcached in an autoscaling group monitored with CloudWatch and RDS with read replicas.
- B. Stateful instances for the web and application tier in an autoscaling group monitored with CloudWatch and RDS with read replicas.
- C. Stateful instances for the web and application tier in an autoscaling group monitored with CloudWatch.
- D. And multi-AZ RDS.
- E. Stateless instances for the web and application tier synchronized using ElastiCache Memcached in an autoscaling group monitored with CloudWatch and multi-AZ RDS.

Answer: A

NEW QUESTION 189

You are tasked with moving a legacy application from a virtual machine running inside your datacenter to an Amazon VPC. Unfortunately, this app requires access to a number of on-premises services and no one who configured the app still works for your company. Even worse, there's no documentation for it.

What will allow the application running inside the VPC to reach back and access its internal dependencies without being reconfigured? (Choose 3 answers)

- A. An AWS Direct Connect link between the VPC and the network housing the internal services.
- B. An Internet Gateway to allow a VPN connection.
- C. An Elastic IP address on the VPC instance.
- D. An IP address space that does not conflict with the one on-premises.
- E. Entries in Amazon Route 53 that allow the instance to resolve its dependencies' IP addresses.
- F. A VM Import of the current virtual machine.

Answer: ADF

NEW QUESTION 192

You have a periodic image analysis application that gets some files. It input analyzes them and for each file writes some data in output to a text file. The number of files in input per day is high and concentrated in a few hours of the day.

Currently, you have a server on EC2 with a large EBS volume that hosts the input data and the results. It takes almost 20 hours per day to complete the process. What services could be used to reduce the elaboration time and improve the availability of the solution?

- A. S3 to store I/O files.
- B. SQS to distribute elaboration commands to a group of hosts working in parallel.
- C. Auto scaling to dynamically size the group of hosts depending on the length of the SQS queue.
- D. EBS with Provisioned IOPS (PIOPS) to store I/O files.
- E. SNS to distribute elaboration commands to a group of hosts working in parallel. Auto Scaling to dynamically size the group of hosts depending on the number of SNS notifications.
- F. S3 to store I/O files, SNS to distribute elaboration commands to a group of hosts working in parallel.
- G. Auto scaling to dynamically size the group of hosts depending on the number of SNS notifications.
- H. EBS with Provisioned IOPS (PIOPS) to store I/O files. SQS to distribute elaboration commands to a group of hosts working in parallel. Auto Scaling to dynamically size the group of hosts depending on the length of the SQS queue.

Answer: D

NEW QUESTION 196

A large real-estate brokerage is exploring the option of adding a cost-effective location-based alert to their existing mobile application. The application backend infrastructure currently runs on AWS. Users who opt in to this service will receive alerts on their mobile device regarding real-estate offers in proximity to their location. For the alerts to be relevant, delivery time needs to be in the low minute count. The existing mobile app has 5 million users across the US. Which one of the following architectural suggestions would you make to the customer?

- A. The mobile application will submit its location to a web service endpoint utilizing Elastic Load Balancing and EC2 instances: DynamoDB will be used to store and retrieve relevant offers EC2 instances will communicate with mobile earners/device providers to push alerts back to mobile application.
- B. Use AWS DirectConnect or VPN to establish connectMty with mobile carriers EC2 instances will receive the mobile applications ' location through carrier connection: RDS will be used to store and relevant offers EC2 instances will communicate with mobile carriers to push alerts back to the mobile application
- C. The mobile application will send device location using SQ
- D. EC2 instances will retrieve the relevant others from DynamoDB AWS Mobile Push will be used to send offers to the mobile application
- E. The mobile application will send device location using AWS Nmobile Push EC2 instances will retrieve the relevant offers from DynamoDB EC2 instances will communicate with mobile carriers/device providers to push alerts back to the mobile application.

Answer: A

NEW QUESTION 199

Your company has HQ in Tokyo and branch offices all over the world and is using a logistics software with a multi-regional deployment on AWS in Japan, Europe and US

- A. The logistic software has a 3-tierarchitecture and currently uses MySQL 5.6 for data persistenc
- B. Each region has deployed its own database In the HQ region you run an hourly batch process reading data from every region to compute cross-regional reports that are sent by email to all offices this batch process must be completed as fast as possible to quickly optimize logistics how do you build the database architecture in order to meet the requirements'?
- C. For each regional deployment, use RDS MySQL with a master in the region and a read replica in theHQ region
- D. For each regional deployment, use NlySQL on EC2 with a master in the region and send hourly EBS snapshots to the HQ region
- E. For each regional deployment, use RDS MySQL with a master in the region and send hourly RDS snapshots to the HQ region
- F. For each regional deployment, use MySQL on EC2 with a master in the region and use S3 to copy data files hourly to the HQ region
- G. Use Direct Connect to connect all regional MySQL deployments to the HQ region and reduce network latency for the batch process

Answer: A

NEW QUESTION 204

A web design company currently runs several FTP servers that their 250 customers use to upload and download large graphic files They wish to move this system to AWS to make it more scalable, but they wish to maintain customer privacy and Keep costs to a minimum.
What AWS architecture would you recommend?

- A. ASK their customers to use an S3 client instead of an FTP clien
- B. Create a single S3 bucket Create an IAM user for each customer Put the IAM Users in a Group that has an IAM policy that permits access to sub-directories within the bucket via use of the 'username' Policy variable.
- C. Create a single S3 bucket with Reduced Redundancy Storage turned on and ask their customers to use an S3 client instead of an FTP client Create a bucket for each customer with a Bucket Policy that permits access only to that one customer.
- D. Create an auto-scaling group of FTP servers with a scaling policy to automatically scale-in when minimum network traffic on the auto-scaling group is below a given threshol
- E. Load a central list of ftp users from S3 as part of the user Data startup script on each Instance.
- F. Create a single S3 bucket with Requester Pays turned on and ask their customers to use an S3 client instead of an FTP client Create a bucket tor each customer with a Bucket Policy that permits access only to that one customer.

Answer: A

NEW QUESTION 205

You would like to create a mirror image of your production environment in another region for disaster recovery purposes. Which of the following AWS resources do not need to be recreated in the second region? (Choose 2 answers)

- A. Route 53 Record Sets
- B. IAM Roles
- C. Elastic IP Addresses (EIP)
- D. EC2 Key Pairs
- E. Launch configurations
- F. Security Groups

Answer: AC

NEW QUESTION 207

An enterprise wants to use a third-party SaaS application. The SaaS application needs to have access to issue several API commands to discover Amazon EC2 resources running within the enterprise's account The enterprise has internal security policies that require any outside access to their environment must conform to the principles of least prMlege and there must be controls in place to ensure that the credentials used by the SaaS vendor cannot be used by any other third party. Which of the following would meet all of these conditions?

- A. From the AWS Management Console, navigate to the Security Credentials page and retrieve the access and secret key for your account.
- B. Create an IAM user within the enterprise account assign a user policy to the IAM user that allows only the actions required by the SaaS application create a new access and secret key for the user and provide these credentials to the SaaS provider.
- C. Create an IAM role for cross-account access allows the SaaS provider's account to assume the role and assign it a policy that allows only the actions required by the SaaS application.
- D. Create an IAM role for EC2 instances, assign it a policy that allows only the actions required tor the Saas application to work, provide the role ARN to the SaaS provider to use when launching their application instances.

Answer: C

NEW QUESTION 208

Your company is getting ready to do a major public announcement of a social media site on AWS. The website is running on EC2 instances deployed across multiple Availability Zones with a Multi-AZ RDS MySQL Extra Large DB Instance. The site performs a high number of small reads and writes per second and relies on an eventual consistency model. After comprehensive tests you discover that there is read contention on RDS MySQL. Which are the best approaches to meet

these requirements? (Choose 2 answers)

- A. Deploy ElastiCache in-memory cache running in each availability zone
- B. Implement sharding to distribute load to multiple RDS MySQL instances
- C. Increase the RDS MySQL Instance size and Implement provisioned IOPS
- D. Add an RDS MySQL read replica in each availability zone

Answer: AC

NEW QUESTION 211

You are designing an intrusion detection prevention (IDS/IPS) solution for a customer web application in a single VPC. You are considering the options for implementing IOS IPS protection for traffic coming from the Internet.

Which of the following options would you consider? (Choose 2 answers)

- A. Implement IDS/IPS agents on each Instance running In VPC
- B. Configure an instance in each subnet to switch its network interface card to promiscuous mode and analyze network traffic.
- C. Implement Elastic Load Balancing with SSL listeners In front of the web applications
- D. Implement a reverse proxy layer in front of web servers and configure IDS/IPS agents on each reverse proxy server.

Answer: BD

NEW QUESTION 215

An International company has deployed a multi-tier web application that relies on DynamoDB in a single region For regulatory reasons they need disaster recovery capability In a separate region with a Recovery Time Objective of 2 hours and a Recovery Point Objective of 24 hours. They should synchronize their data on a regular basis and be able to provision me web application rapidly using CloudFormation.

The objective is to minimize changes to the existing web application, control the throughput of DynamoDB used for the synchronization of data and synchronize only the modified elements.

Which design would you choose to meet these requirements?

- A. Use AWS data Pipeline to schedule a DynamoDB cross region copy once a day, create a "Lastupdated" attribute in your DynamoDB table that would represent the timestamp of the last update and use it as a filter.
- B. Use EMR and write a custom script to retrieve data from DynamoDB in the current region using a SCAN operation and push it to DynamoDB in the second region.
- C. Use AWS data Pipeline to schedule an export of the DynamoDB table to S3 in the current region once a day then schedule another task immediately after it that will import data from S3 to DynamoDB in the other region.
- D. Send also each Ante into an SQS queue in me second region; use an auto-scaling group behind the SQS queue to replay the write in the second region.

Answer: A

NEW QUESTION 220

You are designing a social media site and are considering how to mitigate distributed denial-of-service (DDoS) attacks. Which of the below are viable mitigation techniques? (Choose 3 answers)

- A. Add multiple elastic network interfaces (ENIs) to each EC2 instance to increase the network bandwidth.
- B. Use dedicated instances to ensure that each instance has the maximum performance possible.
- C. Use an Amazon CloudFront distribution for both static and dynamic content.
- D. Use an Elastic Load Balancer with auto scaling groups at the we
- E. App and Amazon Relational Database Service (RDS) tiers
- F. Add alert Amazon CloudWatch to look for high Network in and CPU utilization.
- G. Create processes and capabilities to quickly add and remove rules to the instance OS firewall

Answer: CEF

NEW QUESTION 223

A customer has established an AWS Direct Connect connection to AWS. The link is up and routes are being advertised from the customer's end, however the customer is unable to connect from EC2 instances inside its VPC to servers residing in its datacenter.

Which of the following options provide a viable solution to remedy this situation? (Choose 2 answers)

- A. Add a route to the route table with an IPsec VPN connection as the target.
- B. Enable route propagation to the virtual pinnate gateway (VGW).
- C. Enable route propagation to the customer gateway (CGW).
- D. Modify the route table of all Instances using the 'route' command.
- E. Modify the Instances VPC subnet route table by adding a route back to the customer's on-premises environment.

Answer: AC

NEW QUESTION 226

A corporate web application is deployed within an Amazon Virtual Private Cloud (VPC) and is connected to the corporate data center via an IPsec VPN. The application must authenticate against the

on-premises LDAP server. After authentication, each logged-in user can only access an Amazon Simple Storage Space (S3) keyspace specific to that user.

Which two approaches can satisfy these objectives? (Choose 2 answers)

- A. Develop an identity broker that authenticates against IAM security Token service to assume a IAM role in order to get temporary AWS security credentials The application calls the identity broker to get AWS temporary security credentials with access to the appropriate S3 bucket.
- B. The application authenticates against LDAP and retrieves the name of an IAM role associated with the use
- C. The application then calls the IAM Security Token Service to assume that IAM rol
- D. The application can use the temporary credentials to access the appropriate S3 bucket.
- E. Develop an identity broker that authenticates against LDAP and then calls IAM Security Token Service to get IAM federated user credential

- F. The application calls the identity broker to get IAM federated user credentials with access to the appropriate S3 bucket.
- G. The application authenticates against LDAP the application then calls the AWS identity and AccessManagement (IAM) Security service to log in to IAM using the LDAP credentials the application can use the IAM temporary credentials to access the appropriate S3 bucket.
- H. The application authenticates against IAM Security Token Service using the LDAP credentials the application uses those temporary AWS security credentials to access the appropriate S3 bucket.

Answer: BC

NEW QUESTION 229

You are designing a personal document-archMng solution for your global enterprise with thousands of employee. Each employee has potentially gigabytes of data to be backed up in this archMng solution. The solution will be exposed to the employees as an application, where they can just drag and drop their files to the archMng system. Employees can retrieve their archives through a web interface. The corporate network has high bandwidth AWS Direct Connect connectMty to AWS.

You have a regulatory requirement that all data needs to be encrypted before being uploaded to the cloud.

How do you implement this in a highly available and cost-efficient way?

- A. Manage encryption keys on-premises in an encrypted relational databas
- B. Set up an on-premises server with sufficient storage to temporarily store files, and then upload them to Amazon S3, providing a client-side master key.
- C. Mange encryption keys in a Hardware Security Module (HSM) appliance on-premises serve r with sufficient storage to temporarily store, encrypt, and upload files directly into Amazon Glacier.
- D. Nlamage encryption keys in Amazon Key Management Service (KMS), upload to Amazon Simple Storage Service (S3) with client-side encryption using a KMS customer master key ID, and configure Amazon S3 lifecycle policies to store each object using the Amazon Glacier storage tier.
- E. Manage encryption keys in an AWS CloudHSMI applan
- F. Encrypt files prior to uploading on the employee desktop, and then upload directly into Amazon Glacier.

Answer: C

NEW QUESTION 230

A company is building a voting system for a popular TV show, viewers win watch the performances then visit the show's website to vote for their favorite performer. It is expected that in a short period of time after the show has finished the site will receive millions of visitors. The visitors will first login to the site using their Amazon.com credentials and then submit their vote. After the voting is completed the page will display the vote totals. The company needs to build the site such that can handle the rapid influx of traffic while maintaining good performance but also wants to keep costs to a minimum. Which of the design patterns below should they use?

- A. Use CloudFront and an Elastic Load balancer in front of an auto-scaled set of web servers, the web servers will first call the Login With Amazon service to authenticate the user then process the users vote and store the result into a multi-AZ Relational Database Service instance.
- B. Use CloudFront and the static website hosting feature of S3 with the Javascript SDK to call the Login With Amazon service to authenticate the user, use IAM Roles to gain permissions to a DynamoDB tableto store the users vote.
- C. Use CloudFront and an Elastic Load Balancer in front of an auto-scaled set of web servers, the web servers will first call the Login with Amazon service to authenticate the user, the web servers will process the users vote and store the result into a DynamoDB table using IAM Roles for EC2 instances to gain permissions to the DynamoDB table.
- D. Use CloudFront and an Elastic Load Balancer in front of an auto-scaled set of web servers, the web servers will first call the Login With Amazon service to authenticate the user, the web sewers win process the users vote and store the result into an SQS queue using IAM Roles for EC2 Instances to gain permissions to the SQS queu
- E. A set of application sewers will then retrieve the items from the queue and store the result into a DynamoDB table.

Answer: D

NEW QUESTION 233

You are designing a connectMty solution between on-premises infrastructure and Amazon VPC. Your servers on-premises will be communicating with your VPC instances. You will be establishing IPSec tunnels over the Internet You will be using VPN gateways, and terminating the IPSec tunnels on AWS supported customer gateways.

Which of the following objectives would you achieve by implementing an IPSec tunnel as outlined above? Choose 4 answers

- A. End-to-end protection of data in transit
- B. End-to-end Identity authentication
- C. Data encwption across the Internet
- D. Protection of data in transit over the Internet
- E. Peer identity authentication between VPN gateway and customer gateway
- F. Data integrity protection across the Internet

Answer: CDEF

NEW QUESTION 237

You are responsible for a web application that consists of an Elastic Load Balancing (ELB) load balancer in front of an Auto Scaling group of Amazon Elastic Compute Cloud (EC2) instances. For a recent deployment of a new version of the application, a new Amazon Machine Image (AMI) was created, and the Auto Scaling group was updated with a new launch configuration that refers to this new AMI. During the deployment, you received complaints from users that the website was responding with errors. All instances passed the ELB health checks.

What should you do in order to avoid errors for future deployments? (Choose 2 answer)

- A. Add an Elastic Load Balancing health check to the Auto Scaling grou
- B. Set a short period for the health checks to operate as soon as possible in order to prevent premature registration of the instance to theload balancer.
- C. Enable EC2 instance CloudWatch alerts to change the launch configuration's AMI to the previous on
- D. Gradually terminate instances that are using the new AMI.
- E. Set the Elastic Load Balancing health check configuration to target a part of the application that fully tests application health and returns an error if the tests fail.
- F. Create a new launch configuration that refers to the new AMI, and associate it with the grou
- G. Double the size of the group, wait for the new instances to become healthy, and reduce back to the original size.If new instances do not become healthy, associate the previous launch configuration.
- H. Increase the Elastic Load Balancing Unhealthy Threshold to a higher value to prevent an unhealthy instance from going into service behind the load balancer.

Answer: CD

NEW QUESTION 240

Which is a valid Amazon Resource name (ARN) for IAM?

- A. aws:iam::123456789012:instance-profile\Nebserver
- B. arn:aws:iam::123456789012:instance-profile/Webserver
- C. 123456789012:aws:iam::instance-profile\Nebserver
- D. arn:aws:iam::123456789012::instance-profile\Nebserver

Answer: B

NEW QUESTION 243

You are running a successful multitier web application on AWS and your marketing department has asked you to add a reporting tier to the application. The reporting tier will aggregate and publish status reports every 30 minutes from user-generated information that is being stored in your web application's database. You are currently running a Multi-AZ RDS MySQL instance for the database tier. You also have implemented ElastiCache as a database caching layer between the application tier and database tier. Please select the answer that will allow you to successfully implement the reporting tier with as little impact as possible to your database.

- A. Continually send transaction logs from your master database to an S3 bucket and generate the reports off the S3 bucket using S3 byte range requests.
- B. Generate the reports by querying the synchronously replicated standby RDS MySQL instance maintained through Multi-AZ.
- C. Launch a RDS Read Replica connected to your Multi AZ master database and generate reports by querying the Read Replica.
- D. Generate the reports by querying the ElastiCache database caching tier

Answer: C

NEW QUESTION 244

Your company plans to host a large donation website on Amazon Web Services (AWS). You anticipate a large and undetermined amount of traffic that will create many database writes. To be certain that you do not drop any writes to a database hosted on AWS. Which service should you use?

- A. Amazon RDS with provisioned IOPS up to the anticipated peak write throughput.
- B. Amazon Simple Queue Service (SQS) for capturing the writes and draining the queue to write to the database.
- C. Amazon ElastiCache to store the writes until the writes are committed to the database.
- D. Amazon DynamoDB with provisioned write throughput up to the anticipated peak write throughput

Answer: B

NEW QUESTION 247

You have an application running on an EC2 Instance which will allow users to download files from a private S3 bucket using a pre-signed URL. Before generating the URL the application should verify the existence of the file in S3.

How should the application use AWS credentials to access the S3 bucket securely?

- A. Use the AWS account access keys the application retrieves the credentials from the source code of the application.
- B. Create an IAM user for the application with permissions that allow list access to the S3 bucket launch the instance as the IAM user and retrieve the IAM user's credentials from the EC2 instance user data.
- C. Create an IAM role for EC2 that allows list access to objects in the S3 bucket
- D. Launch the instance with the role, and retrieve the role's credentials from the EC2 Instance metadata
- E. Create an IAM user for the application with permissions that allow list access to the S3 bucket
- F. The application retrieves the IAM user credentials from a temporary directory with permissions that allow read access only to the application user.

Answer: C

NEW QUESTION 249

You deployed your company website using Elastic Beanstalk and you enabled log file rotation to S3. An Elastic Map Reduce job is periodically analyzing the logs on S3 to build a usage dashboard that you share with your CIO.

You recently improved overall performance of the website using Cloud Front for dynamic content delivery and your website as the origin.

After this architectural change, the usage dashboard shows that the traffic on your website dropped by an order of magnitude. How do you fix your usage dashboard?

- A. Enable Cloud Front to deliver access logs to S3 and use them as input of the Elastic Map Reduce job.
- B. Turn on Cloud Trail and use trail log files on S3 as input of the Elastic Map Reduce job
- C. Change your log collection process to use Cloud Watch ELB metrics as input of the Elastic MapReduce job
- D. Use Elastic Beanstalk "Rebuild Environment" option to update log delivery to the Elastic Map Reduce job.
- E. Use Elastic Beanstalk "Restart App server(s)" option to update log delivery to the Elastic Map Reduce job.

Answer: D

NEW QUESTION 251

A web-startup runs its very successful social news application on Amazon EC2 with an Elastic Load Balancer, an Auto-Scaling group of Java/Tomcat application servers, and DynamoDB as data store. The main web-application best runs on m2 x large instances since it is highly memory-bound. Each new deployment requires semi-automated creation and testing of a new AMI for the application servers which takes quite a while and is therefore only done once per week. Recently, a new chat feature has been implemented in Node.js and waits to be integrated in the architecture. First tests show that the new component is CPU bound. Because the company has some experience with using Chef, they decided to streamline the deployment process and use AWS Ops Works as an application life cycle tool to simplify management of the application and reduce the deployment cycles.

What configuration in AWS Ops Works is necessary to integrate the new chat module in the most cost-efficient and flexible way?

- A. Create one AWS OpsWorks stack, create one AWS Ops Works layer, create one custom recipe

- B. Create one AWS OpsWorks stack create two AWS Ops Works layers, create one custom recipe
- C. Create two AWS OpsWorks stacks create two AWS Ops Works layers, create one custom recipe
- D. Create two AWS OpsWorks stacks create two AWS Ops Works layers, create two custom recipe

Answer: C

NEW QUESTION 252

Select the correct set of options. These are the initial settings for the default security group:

- A. Allow no inbound traffic, Allow all outbound traffic and Allow instances associated with this security group to talk to each other
- B. Allow all inbound traffic, Allow no outbound traffic and Allow instances associated with this security group to talk to each other
- C. Allow no inbound traffic, Allow all outbound traffic and Does NOT allow instances associated with this security group to talk to each other
- D. Allow all inbound traffic, Allow all outbound traffic and Does NOT allow instances associated with this security group to talk to each other

Answer: A

NEW QUESTION 257

A customer is deploying an SSL enabled web application to AWS and would like to implement a separation of roles between the EC2 service administrators that are entitled to login to instances as well as making API calls and the security officers who will maintain and have exclusive access to the application's X.509 certificate that contains the private key.

- A. Upload the certificate on an S3 bucket owned by the security officers and accessible only by EC2 Role of the web servers.
- B. Configure the web servers to retrieve the certificate upon boot from an CloudHSM is managed by the security officers.
- C. Configure system permissions on the web servers to restrict access to the certificate only to the authority security officers
- D. Configure IAM policies authorizing access to the certificate store only to the security officers and terminate SSL on an ELB.

Answer: D

NEW QUESTION 262

A web company is looking to implement an intrusion detection and prevention system into their deployed VPC. This platform should have the ability to scale to thousands of instances running inside of the VPC. How should they architect their solution to achieve these goals?

- A. Configure an instance with monitoring software and the elastic network interface (ENI) set to promiscuous mode packet sniffing to see an traffic across the VPC.
- B. Create a second VPC and route all traffic from the primary application VPC through the second VPC where the scalable virtualized IDS/IPS platform resides.
- C. Configure sewers running in the VPC using the host-based 'route' commands to send all traffic through the platform to a scalable virtualized IDS/IPS.
- D. Configure each host with an agent that collects all network traffic and sends that traffic to the IDS/IPS platform for inspection.

Answer: C

NEW QUESTION 263

You've been hired to enhance the overall security posture for a very large e-commerce site They have a well architected multi-tier application running in a VPC that uses ELBs in front of both the web and the app tier with static assets served directly from S3 They are using a combination of RDS and DynamoDB for their dynamic data and then archMng nightly into S3 for further processing with EMR They are concerned because they found questionable log entries and suspect someone is attempting to gain unauthorized access.

Which approach provides a cost effective scalable mitigation to this kind of attack?

- A. Recommend that they lease space at a DirectConnect partner location and establish a 1G DirectConnect connection to their VPC they would then establish Internet connectMty into their space, filter the traffic in hardware Web Application Firewall (WAF). And then pass the traffic through the DirectConnect connection into their application running in their VPC.
- B. Add previously identified hostile source IPs as an explicit INBOUND DENY NACL to the web tier subnet
- C. Add a WAF tier by creating a new ELB and an AutoScaling group of EC2 Instances running ahost-based WAF They would redirect Route 53 to resolve to the new WAF tier ELB The WAF tier would their pass the traffic to the current web tier The web tier Security Groups would be updated to only allow traffic from the WAF tier Security Group
- D. Remove all but TLS 1.2 from the web tier ELB and enable Advanced Protocol Filtering This will enable the ELB itself to perform WAF functionality.

Answer: C

NEW QUESTION 266

Your company is in the process of developing a next generation pet collar that collects biometric information to assist families with promoting healthy lifestyles for their pets Each collar will push 30kb of biometric data In JSON format every 2 seconds to a collection platform that will process and analyze the data providing health trending information back to the pet owners and veterinarians via a web portal Nmanagement has tasked you to architect the collection platform ensuring the following requirements are met.

Provide the ability for real-time analytics of the inbound biometric data Ensure processing of the biometric data is highly durable. Elastic and parallel The results of the analytic processing should be persisted for data mining

Which architecture outlined below win meet the initial requirements for the collection platform?

- A. Utilize S3 to collect the inbound sensor data analyze the data from S3 with a daily scheduled Data Pipeline and save the results to a Redshift Cluster.
- B. Utilize Amazon Kinesis to collect the inbound sensor data, analyze the data with Kinesis clients and save the results to a Redshift cluster using EMR.
- C. Utilize SQS to collect the inbound sensor data analyze the data from SQS with Amazon Kinesis and save the results to a Microsoft SQL Server RDS instance.
- D. Utilize EMR to collect the inbound sensor data, analyze the data from EUR with Amazon Kinesis and save me results to DynamoDB.

Answer: B

NEW QUESTION 268

Your team has a tomcat-based Java application you need to deploy into development, test and production environments. After some research, you opt to use Elastic Beanstalk due to its tight integration with your developer tools and RDS due to its ease of management. Your QA team lead points out that you need to roll a sanitized set of production data into your environment on a nightly basis.

Similarly, other software teams in your org want access to that same restored data via their EC2 instances in your VPC. The optimal setup for persistence and security that meets the above requirements would be the following.

- A. Create your RDS instance as part of your Elastic Beanstalk definition and alter its security group to allow access to it from hosts in your application subnets.
- B. Create your RDS instance separately and add its IP address to your application's DB connection strings in your code. Alter its security group to allow access to it from hosts within your VPC's IP address block.
- C. Create your RDS instance separately and pass its DNS name to your app's DB connection string as an environment variable.
- D. Create a security group for client machines and add it as a valid source for DB traffic to the security group of the RDS instance itself.
- E. Create your RDS instance separately and pass its DNS name to your app's DB connection string as an environment variable. Alter its security group to allow access to it from hosts in your application subnets.

Answer: A

NEW QUESTION 273

Your company has an on-premises multi-tier PHP web application, which recently experienced downtime due to a large burst in web traffic due to a company announcement. Over the coming days, you are expecting similar announcements to drive similar unpredictable bursts, and are looking to find ways to quickly improve your infrastructure's ability to handle unexpected increases in traffic.

The application currently consists of 2 tiers: a web tier which consists of a load balancer and several Linux Apache web servers as well as a database tier which hosts a Linux server hosting a MySQL database. Which scenario below will provide full site functionality, while helping to improve the ability of your application in the short timeframe required?

- A. Failover environment: Create an S3 bucket and configure it for website hosting.
- B. Migrate your DNS to Route53 using zone file import, and leverage Route53 DNS failover to failover to the S3 hosted website.
- C. Hybrid environment: Create an AMI, which can be used to launch web servers in EC2. Create an Auto Scaling group, which uses the AMI to scale the web tier based on incoming traffic.
- D. Leverage Elastic Load Balancing to balance traffic between on-premises web servers and those hosted in AWS.
- E. Offload traffic from on-premises environment: Setup a CloudFront distribution, and configure CloudFront to cache objects from a custom origin.
- F. Choose to customize your object cache behavior, and select a TTL that objects should exist in cache.
- G. Migrate to AWS: Use VM Import/Export to quickly convert an on-premises web server to an AMI.
- H. Create an Auto Scaling group, which uses the imported AMI to scale the web tier based on incoming traffic.
- I. Create an RDS read replica and setup replication between the RDS instance and on-premises MySQL server to migrate the database.

Answer: C

NEW QUESTION 275

An ERP application is deployed across multiple AZs in a single region. In the event of failure, the Recovery Time Objective (RTO) must be less than 3 hours, and the Recovery Point Objective (RPO) must be 15 minutes. The customer realizes that data corruption occurred roughly 1.5 hours ago.

What DR strategy could be used to achieve this RTO and RPO in the event of this kind of failure?

- A. Take hourly DB backups to S3, with transaction logs stored in S3 every 5 minutes.
- B. Use synchronous database master-slave replication between two availability zones.
- C. Take hourly DB backups to EC2 Instance Store volumes with transaction logs stored in S3 every 5 minutes.
- D. Take 15 minute DB backups stored in Glacier with transaction logs stored in S3 every 5 minutes.

Answer: A

NEW QUESTION 280

You are designing the network infrastructure for an application server in Amazon VPC. Users will access all application instances from the Internet, as well as from an on-premises network. The on-premises network is connected to your VPC over an AWS Direct Connect link. How would you design routing to meet the above requirements?

- A. Configure a single routing table with a default route via the Internet gateway.
- B. Propagate a default route via BGP on the AWS Direct Connect customer route.
- C. Associate the routing table with all VPC subnets.
- D. Configure a single routing table with a default route via the Internet gateway.
- E. Propagate specific routes for the on-premises networks via BGP on the AWS Direct Connect customer route.
- F. Associate the routing table with all VPC subnets.
- G. Configure a single routing table with two default routes: one to the Internet via an Internet gateway, the other to the on-premises network via the VPN gateway.
- H. Use this routing table across all subnets in the VPC.
- I. Configure two routing tables: one that has a default route via the Internet gateway, and other that has a default route via the VPN gateway.
- J. Associate both routing tables with each VPC subnet.

Answer: A

NEW QUESTION 284

What does elasticity mean to AWS?

- A. The ability to scale computing resources up easily, with minimal friction and down with latency.
- B. The ability to scale computing resources up and down easily, with minimal friction.
- C. The ability to provision cloud computing resources in expectation of future demand.
- D. The ability to recover from business continuity events with minimal friction.

Answer: B

NEW QUESTION 286

You have launched an EC2 instance with four (4) 500 GB EBS Provisioned IOPS volumes attached. The EC2 instance is EBS-Optimized and supports 500 Mbps throughput between EC2 and EBS. The four EBS volumes are configured as a single RAID 0 device, and each Provisioned IOPS volume is provisioned with 4,000 IOPS (4,000 16KB reads or writes), for a total of 16,000 random IOPS on the instance. The EC2 instance initially delivers the expected 16,000 IOPS random read

and write performance. Sometime later, in order to increase the total random I/O performance of the instance, you add an additional two 500 GB EBS Provisioned IOPS volumes to the RAID. Each volume is provisioned to 4,000 IOPS like the original four, for a total of 24,000 IOPS on the EC2 instance. Monitoring shows that the EC2 instance CPU utilization increased from 50% to 70%, but the total random IOPS measured at the instance level does not increase at all. What is the problem and a valid solution?

- A. The EBS-Optimized throughput limits the total IOPS that can be utilized; use an EBSOptimized instance that provides larger throughput.
- B. Small block sizes cause performance degradation, limiting the I/O throughput; configure the instance device driver and filesystem to use 64KB blocks to increase throughput.
- C. The standard EBS Instance root volume limits the total IOPS rate; change the instance root volume to also be a 500GB 4,000 Provisioned IOPS volume.
- D. Larger storage volumes support higher Provisioned IOPS rates; increase the provisioned volume storage of each of the 6 EBS volumes to 1TB.
- E. RAID 0 only scales linearly to about 4 devices; use RAID 0 with 4 EBS Provisioned IOPS volumes, but increase each Provisioned IOPS EBS volume to 6,000 IOPS.

Answer: C

NEW QUESTION 291

A newspaper organization has a on-premises application which allows the public to search its back catalogue and retrieve individual newspaper pages via a website written in Java. They have scanned the old newspapers into JPEGs (approx 17TB) and used Optical Character Recognition (OCR) to populate a commercial search product. The hosting platform and software are now end of life and the organization wants to migrate its archive to AWS and produce a cost efficient architecture and still be designed for availability and durability. Which is the most appropriate?

- A. Use S3 with reduced redundancy to store and serve the scanned files, install the commercial search application on EC2 Instances and configure with auto-scaling and an Elastic Load Balancer.
- B. Model the environment using CloudFormation use an EC2 instance running Apache webserver and an open source search application, stripe multiple standard EBS volumes together to store the JPEGs and search index.
- C. Use S3 with standard redundancy to store and serve the scanned files, use CloudSearch for query processing, and use Elastic Beanstalk to host the website across multiple availability zones.
- D. Use a single-AZ RDS MySQL instance to store the search index and the JPEG images use an EC2 instance to serve the website and translate user queries into SQL.
- E. Use a CloudFront download distribution to serve the JPEGs to the end users and install the current commercial search product, along with a Java Container on the website on EC2 instances and use Route53 with DNS round-robin.

Answer: C

NEW QUESTION 292

.....

About ExamBible

Your Partner of IT Exam

Found in 1998

ExamBible is a company specialized on providing high quality IT exam practice study materials, especially Cisco CCNA, CCDA, CCNP, CCIE, Checkpoint CCSE, CompTIA A+, Network+ certification practice exams and so on. We guarantee that the candidates will not only pass any IT exam at the first attempt but also get profound understanding about the certificates they have got. There are so many alike companies in this industry, however, ExamBible has its unique advantages that other companies could not achieve.

Our Advances

* 99.9% Uptime

All examinations will be up to date.

* 24/7 Quality Support

We will provide service round the clock.

* 100% Pass Rate

Our guarantee that you will pass the exam.

* Unique Gurantee

If you do not pass the exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

NEW QUESTION 1

By default, Amazon Cognito maintains the last-written version of the data. You can override this behavior and resolve data conflicts programmatically. In addition, push synchronization allows you to use Amazon Cognito to send a silent notification to all devices associated with an identity to notify them that new data is available.

- A. get
- B. post
- C. pull
- D. push

Answer: D

Explanation:

By default, Amazon Cognito maintains the last-written version of the data. You can override this behavior and resolve data conflicts programmatically. In addition, push synchronization allows you to use Amazon Cognito to send a silent push notification to all devices associated with an identity to notify them that new data is available.

Reference: <http://aws.amazon.com/cognito/faqs/>

NEW QUESTION 2

You want to use AWS CodeDeploy to deploy an application to Amazon EC2 instances running within an Amazon Virtual Private Cloud (VPC). What criterion must be met for this to be possible?

- A. The AWS CodeDeploy agent installed on the Amazon EC2 instances must be able to access only the public AWS CodeDeploy endpoint.
- B. The AWS CodeDeploy agent installed on the Amazon EC2 instances must be able to access only the public Amazon S3 service endpoint.
- C. The AWS CodeDeploy agent installed on the Amazon EC2 instances must be able to access the public AWS CodeDeploy and Amazon S3 service endpoints.
- D. It is not currently possible to use AWS CodeDeploy to deploy an application to Amazon EC2 instances running within an Amazon Virtual Private Cloud (VPC.)

Answer: C

Explanation:

You can use AWS CodeDeploy to deploy an application to Amazon EC2 instances running within an Amazon Virtual Private Cloud (VPC). However, the AWS CodeDeploy agent installed on the Amazon EC2 instances must be able to access the public AWS CodeDeploy and Amazon S3 service endpoints. Reference: <http://aws.amazon.com/codedeploy/faqs/>

NEW QUESTION 3

An IAM user is trying to perform an action on an object belonging to some other root account's bucket. Which of the below mentioned options will AWS S3 not verify?

- A. The object owner has provided access to the IAM user
- B. Permission provided by the parent of the IAM user on the bucket
- C. Permission provided by the bucket owner to the IAM user
- D. Permission provided by the parent of the IAM user

Answer: B

Explanation:

If the IAM user is trying to perform some action on the object belonging to another AWS user's bucket, S3 will verify whether the owner of the IAM user has given sufficient permission to him. It also verifies the policy for the bucket as well as the policy defined by the object owner.

Reference:

<http://docs.aws.amazon.com/AmazonS3/latest/dev/access-control-auth-workflow-object-operation.html>

NEW QUESTION 4

In the context of AWS IAM, identify a true statement about user passwords (login profiles).

- A. They must contain Unicode characters.
- B. They can contain any Basic Latin (ASCII) characters.
- C. They must begin and end with a forward slash (/).
- D. They cannot contain Basic Latin (ASCII) characters.

Answer: B

Explanation:

The user passwords (login profiles) of IAM users can contain any Basic Latin (ASCII) characters. Reference:

<http://docs.aws.amazon.com/IAM/latest/UserGuide/LimitationsOnEntities.html>

NEW QUESTION 5

An organization is planning to host a Wordpress blog as well a Joomla CMS on a single instance launched with VPC. The organization wants to have separate domains for each application and assign them using Route 53. The organization may have about ten instances each with two applications as mentioned above. While launching the instance, the organization configured two separate network interfaces (primary + ENI) and wanted to have two elastic IPs for that instance. It was suggested to use a public IP from AWS instead of an elastic IP as the number of elastic IPs is restricted. What action will you recommend to the organization?

- A. I agree with the suggestion but will prefer that the organization should use separate subnets with each ENI for different public IPs.
- B. I do not agree as it is required to have only an elastic IP since an instance has more than one ENI and AWS does not assign a public IP to an instance with multiple ENIs.
- C. I do not agree as AWS VPC does not attach a public IP to an ENI; so the user has to use only an elastic IP only.
- D. I agree with the suggestion and it is recommended to use a public IP from AWS since the organization is going to use DNS with Route 53.

Answer: B

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. An Elastic Network Interface (ENI) is a virtual network interface that the user can attach to an instance in a VPC.

The user can attach up to two ENIs with a single instance. However, AWS cannot assign a public IP when there are two ENIs attached to a single instance. It is recommended to assign an elastic IP in this scenario. If the organization wants more than 5 EIPs they can request AWS to increase the number.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/using-eni.html>

NEW QUESTION 6

A customer has a website which shows all the deals available across the market. The site experiences a load of 5 large EC2 instances generally. However, a week before Thanksgiving vacation they encounter a load of almost 20 large instances. The load during that period varies over the day based on the office timings.

Which of the below mentioned solutions is cost effective as well as help the website achieve better performance?

A. Setup to run 10 instances during the pre-vacation period and only scale up during the office time by launching 10 more instances using the AutoScaling schedule.

B. Keep only 10 instances running and manually launch 10 instances every day during office hours.

C. During the pre-vacation period setup 20 instances to run continuously.

D. During the pre-vacation period setup a scenario where the organization has 15 instances running and 5 instances to scale up and down using Auto Scaling based on the network I/O policy.

Answer: D

Explanation:

AWS provides an on demand, scalable infrastructure. AWS EC2 allows the user to launch On-Demand instances and the organization should create an AMI of the running instance. When the organization is experiencing varying loads and the time of the load is not known but it is higher than the routine traffic it is recommended that the organization launches a few instances before hand and then setups AutoScaling with policies which scale up and down as per the EC2 metrics, such as Network I/O or CPU utilization.

If the organization keeps all 10 additional instances as a part of the AutoScaling policy sometimes during a sudden higher load it may take time to launch instances and may not give an optimal performance. This is the reason it is recommended that the organization keeps an additional 5 instances running and the next 5 instances scheduled as per the AutoScaling policy for cost effectiveness.

Reference: http://media.amazonwebservices.com/AWS_Web_Hosting_Best_Practices.pdf

NEW QUESTION 7

In which step of using AWS Direct Connect should the user determine the required port speed?

A. Complete the Cross Connect

B. Verify Your Virtual Interface

C. Download Router Configuration

D. Submit AWS Direct Connect Connection Request

Answer: D

Explanation:

To submit an AWS Direct Connect connection request, you need to provide the following information: Your contact information.

The AWS Direct Connect Location to connect to.

Details of AWS Direct Connect partner if you use the AWS Partner Network (APN) service. The port speed you require, either 1 Gbps or 10 Gbps.

Reference: <http://docs.aws.amazon.com/directconnect/latest/UserGuide/getstarted.html#ConnectionRequest>

NEW QUESTION 8

In Amazon IAM, what is the maximum length for a role name?

A. 128 characters

B. 512 characters

C. 64 characters

D. 256 characters

Answer: C

Explanation:

In Amazon IAM, the maximum length for a role name is 64 characters.

Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/LimitationsOnEntities.html>

NEW QUESTION 9

How many g2.2xlarge on-demand instances can a user run in one region without taking any limit increase approval from AWS?

A. 20

B. 2

C. 5

D. 10

Answer: C

Explanation:

Generally AWS EC2 allows running 20 on-demand instances and 100 spot instances at a time. This limit can be increased by requesting at

<https://aws.amazon.com/contact-us/ec2-request>. Excluding certain types of instances, the limit is lower than mentioned above. For g2.2xlarge, the user can run only 5

on-demand instance at a time.

Reference: http://docs.aws.amazon.com/general/latest/gr/aws_service_limits.html#limits_ec2

NEW QUESTION 10

A user has created a MySQL RDS instance with PIOPS. Which of the below mentioned statements will help user understand the advantage of PIOPS?

- A. The user can achieve additional dedicated capacity for the EBS I/O with an enhanced RDS option
- B. It uses a standard EBS volume with optimized configuration the stacks
- C. It uses optimized EBS volumes and optimized configuration stacks
- D. It provides a dedicated network bandwidth between EBS and RDS

Answer: C

Explanation:

RDS DB instance storage comes in two types: standard and provisioned IOPS. Standard storage is allocated on the Amazon EBS volumes and connected to the user's DB instance. Provisioned IOPS uses

optimized EBS volumes and an optimized configuration stack. It provides additional, dedicated capacity for the EBS I/O.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Welcome.html>

NEW QUESTION 10

When does an AWS Data Pipeline terminate the AWS Data Pipeline-managed compute resources?

- A. AWS Data Pipeline terminates AWS Data Pipeline-managed compute resources every 2 hours.
- B. When the final actMty that uses the resources is running
- C. AWS Data Pipeline terminates AWS Data Pipeline-managed compute resources every 12 hours.
- D. When the final actMty that uses the resources has completed successfully or failed

Answer: D

Explanation:

Compute resources will be provisioned by AWS Data Pipeline when the first actMty for a scheduled time that uses those resources is ready to run, and those instances will be terminated when the final actMty that uses the resources has completed successfully or failed.

Reference: <https://aws.amazon.com/datapipeline/faqs/>

NEW QUESTION 15

If no explicit deny is found while applying IAM's Policy Evaluation Logic, the enforcement code looks for any instructions that would apply to the request.

- A. "cancel"
- B. "suspend"
- C. "a|low"
- D. "valid"

Answer: C

Explanation:

If an explicit deny is not found among the applicable policies for a specific request, IAM's Policy Evaluation Logic checks for any "allow" instructions to check if the request can be successfully completed.

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage_EvaluationLogic.html

NEW QUESTION 17

The MySecureData company has five branches across the globe. They want to expand their data centers such that their web server will be in the AWS and each branch would have their own database in the local data center. Based on the user login, the company wants to connect to the data center. How can MySecureData company implement this scenario with the AWS VPC?

- A. Create five VPCs with the public subnet for the app server and setup the VPN gateway for each VPN to connect them indMdually.
- B. Use the AWS VPN CloudHub to communicate with multiple VPN connections.
- C. Use the AWS CloudGateway to communicate with multiple VPN connections.
- D. It is not possible to connect different data centers from a single VPC.

Answer: B

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. The user can create subnets as per the requirement within a VPC. If the user wants to connect VPC from his own data centre, he can setup a public and VPN only subnet which uses hardware VPN access to connect with his data centre. If the organization has multiple VPN connections, he can provide secure communication between sites using the AWS VPN CloudHub.

The VPN CloudHub operates on a simple hub-and-spoke model that the user can use with or without a VPC. This design is suitable for customers with multiple branch offices and existing internet connections who would like to implement a convenient, potentially low-cost hub-and-spoke model for primary or backup connectMty between remote offices.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPN_CloudHub.html

NEW QUESTION 21

One of your AWS Data Pipeline actMties has failed consequently and has entered a hard failure state after retrying thrice. You want to try it again. Is it possible to increase the number of automatic retries to more than thrice?

- A. Yes, you can increase the number of automatic retries to 6.
- B. Yes, you can increase the number of automatic retries to indefinite number.
- C. No, you cannot increase the number of automatic retries.
- D. Yes, you can increase the number of automatic retries to 10.

Answer: D

Explanation:

In AWS Data Pipeline, an actMty fails if all of its actMty attempts return with a failed state. By default, an actMty retries three times before entering a hard failure state. You can increase the number of automatic retries to 10. However, the system does not allow indefinite retries.

Reference: <https://aws.amazon.com/datapipeline/faqs/>

NEW QUESTION 22

True or False: In Amazon ElastiCache replication groups of Redis, for performance tuning reasons, you can change the roles of the cache nodes within the replication group, with the primary and one of the replicas exchanging roles.

- A. True, however, you get lower performance.
- B. FALSE
- C. TRUE
- D. False, you must recreate the replication group to improve performance tunin

Answer: C

Explanation:

In Amazon ElastiCache, a replication group is a collection of Redis Cache Clusters, with one primary read-write cluster and up to five secondary, read-only clusters, which are called read replicas. You can change the roles of the cache clusters within the replication group, with the primary cluster and one of the replicas exchanging roles. You might decide to do this for performance tuning reasons.

Reference: <http://docs.aws.amazon.com/AmazonElastiCache/latest/UserGuide/Replication.Redis.Groups.html>

NEW QUESTION 26

How much memory does the cr1.8xlarge instance type provide?

- A. 224 GB
- B. 124 GB
- C. 184 GB
- D. 244 GB

Answer: D

Explanation:

The CR1 instances are part of the memory optimized instances. They offer lowest cost per GB RAM among all the AWS instance families. CR1 instances are part of the new generation of memory optimized instances, which can offer up to 244 GB RAM and run on faster CPUs (Intel Xeon E5-2670 with NUMA support) in comparison to the NI2 instances of the same family. They support cluster networking for bandwidth intensive applications. cr1.8xlarge is one of the largest instance types of the CR1 family, which can offer 244 GB RAM.

Reference: <http://aws.amazon.com/ec2/instance-types/>

NEW QUESTION 30

How many cg1.4xlarge on-demand instances can a user run in one region without taking any limit increase approval from AWS?

- A. 20
- B. 2
- C. 5
- D. 10

Answer: B

Explanation:

Generally AWS EC2 allows running 20 on-demand instances and 100 spot instances at a time. This limit can be increased by requesting at <https://aws.amazon.com/contact-us/ec2-request>. Excluding certain types of instances, the limit is lower than mentioned above. For cg1.4xlarge, the user can run only 2

on-demand instances at a time.

Reference: http://docs.aws.amazon.com/general/latest/gr/aws_service_limits.html#limits_ec2

NEW QUESTION 35

You want to define permissions for a role in an IAM policy. Which of the following configuration formats should you use?

- A. An XML document written in the IAM Policy Language
- B. An XML document written in a language of your choice
- C. A JSON document written in the IAM Policy Language
- D. A JSON document written in a language of your choice

Answer: C

Explanation:

You define the permissions for a role in an IAM policy. An IAM policy is a JSON document written in the IAM Policy Language.

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/id_roles_terms-and-concepts.html

NEW QUESTION 37

An organization is setting up a backup and restore system in AWS of their in premise system. The organization needs High Availability(HA) and Disaster Recovery(DR) but is okay to have a longer recovery time to save costs. Which of the below mentioned setup options helps achieve the objective of cost saving as well as DR in the most effective way?

- A. Setup pre- configured sewers and create AMLs.. Use EIP and Route 53 to quickly switch over to AWS from in premise.
- B. Setup the backup data on S3 and transfer data to S3 regularly using the storage gateway.
- C. Setup a small instance with AutoScaling; in case of DR start diverting all the load to AWS from on premise.
- D. Replicate on premise DB to EC2 at regular intervals and setup a scenario similar to the pilot ligh

Answer: B

Explanation:

AWS has many solutions for Disaster Recovery(DR) and High Availability(HA). When the organization wants to have HA and DR but are okay to have a longer recovery time they should select the option backup and restore with S3. The data can be sent to S3 using either Direct Connect, Storage Gateway or over the internet.

The EC2 instance will pick the data from the S3 bucket when started and setup the environment. This process takes longer but is very cost effective due to the low pricing of S3. In all the other options, the EC2 instance might be running or there will be AMI storage costs.

Thus, it will be a costlier option. In this scenario the organization should plan appropriate tools to take a backup, plan the retention policy for data and setup security of the data.

Reference: http://d36cz9buwru1tt.cloudfront.net/AWS_Disaster_Recovery.pdf

NEW QUESTION 39

What feature of the load balancing service attempts to force subsequent connections to a service to be redirected to the same node as long as it is online?

- A. Node balance
- B. Session retention
- C. Session multiplexing
- D. Session persistence

Answer: D

Explanation:

Session persistence is a feature of the load balancing service. It attempts to force subsequent connections to a service to be redirected to the same node as long as it is online.

Reference:

<http://docs.rackspace.com/loadbalancers/api/v1.0/clb-devguide/content/Concepts-d1e233.html>

NEW QUESTION 41

What types of identities do Amazon Cognito identity pools support?

- A. They support both authenticated and unauthenticated identities.
- B. They support only unauthenticated identities.
- C. They support neither authenticated nor unauthenticated identities.
- D. They support only authenticated identitie

Answer: A

Explanation:

Amazon Cognito identity pools support both authenticated and unauthenticated identities. Authenticated identities belong to users who are authenticated by a public login provider or your own backend authentication process. Unauthenticated identities typically belong to guest users. Reference:

[http://docs.aws.amazon.com/cognito/devguide/identity/identity-pool\[s/](http://docs.aws.amazon.com/cognito/devguide/identity/identity-pool[s/)

NEW QUESTION 46

In IAM, which of the following is true of temporary security credentials?

- A. Once you issue temporary security credentials, they cannot be revoked.
- B. None of these are correct.
- C. Once you issue temporary security credentials, they can be revoked only when the virtual MFA device is used.
- D. Once you issue temporary security credentials, they can be revoke

Answer: A

Explanation:

Temporary credentials in IAM are valid throughout their defined duration of time and hence can't be revoked. However, because permissions are evaluated each time an AWS request is made using the credentials, you can achieve the effect of revoking the credentials by changing the permissions for the credentials even after they have been issued. Reference:

[http://docs.aws.amazon.com/IAM/latest/UserGuide/id_credentials_temp_control-access_disable-perms.h tml](http://docs.aws.amazon.com/IAM/latest/UserGuide/id_credentials_temp_control-access_disable-perms.html)

NEW QUESTION 48

The CFO of a company wants to allow one of his employees to view only the AWS usage report page. Which of the below mentioned IAM policy statements allows the user to have access to the AWS usage report page?

- A. "Effect": "Allow", "Action": ["Describe"], "Resource": "Billing"
- B. "Effect": "Allow", "Action": ["aws-portal: ViewBi||ing"], "Resource": ""
- C. "Effect": "Allow", "Action": ["aws-portal:ViewUsage"], "Resource": ""
- D. "Effect": "Allow", "Action": ["AccountUsage], "Resource": ""

Answer: C

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. If the CFO wants to allow only AWS usage report page access, the policy for that IAM user will be as given below:

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow", "Action": [
        "aws-portal:ViewUsage"
      ]
    }
  ]
}
```

Reference: <http://docs.aws.amazon.com/awsaccountbilling/latest/aboutv2/billing-permissions-ref.html>

NEW QUESTION 51

The user has provisioned the PIOPS volume with an EBS optimized instance. Generally speaking, in which I/O chunk should the bandwidth experienced by the user be measured by AWS?

- A. 128 KB
- B. 256 KB
- C. 64 KB
- D. 32 KB

Answer: B

Explanation:

IOPS are input/output operations per second. Amazon EBS measures each I/O operation per second (that is 256 KB or smaller) as one IOPS.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-io-characteristics.html>

NEW QUESTION 54

A user is planning to use EBS for his DB requirement. The user already has an EC2 instance running in the VPC private subnet. How can the user attach the EBS volume to a running instance?

- A. The user can create EBS in the same zone as the subnet of instance and attach that EBS to instance.
- B. It is not possible to attach an EBS to an instance running in VPC until the instance is stopped.
- C. The user can specify the same subnet while creating EBS and then attach it to a running instance.
- D. The user must create EBS within the same VPC and then attach it to a running instance.

Answer: A

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. The user can create subnets as per the requirement within a VPC. The VPC is always specific to a region. The user can create a VPC which can span multiple Availability Zones by adding one or more subnets in each Availability Zone. The instance launched will always be in the same availability zone of the respective subnet. When creating an EBS the user cannot specify the subnet or VPC. However, the user must create the EBS in the same zone as the instance so that it can attach the EBS volume to the running instance.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Subnets.html#VPCSubnet

NEW QUESTION 59

Cognito Sync is an AWS service that you can use to synchronize user profile data across mobile devices without requiring your own backend. When the device is online, you can synchronize data. If you also set up push sync, what does it allow you to do?

- A. Notify other devices that a user profile is available across multiple devices
- B. Synchronize user profile data with less latency
- C. Notify other devices immediately that an update is available
- D. Synchronize online data faster

Answer: C

Explanation:

Cognito Sync is an AWS service that you can use to synchronize user profile data across mobile devices without requiring your own backend. When the device is online, you can synchronize data, and if you have

also set up push sync, notify other devices immediately that an update is available. Reference: <http://docs.aws.amazon.com/cognito/devguide/sync/>

NEW QUESTION 64

An organization has hosted an application on the EC2 instances. There will be multiple users connecting to the instance for setup and configuration of application. The organization is planning to implement certain security best practices. Which of the below mentioned pointers will not help the organization achieve better security arrangement?

- A. Allow only IAM users to connect with the EC2 instances with their own secret access key.
- B. Create a procedure to revoke the access rights of the indMdual user when they are not required to connect to EC2 instance anymore for the purpose of application configuration.
- C. Apply the latest patch of OS and always keep it updated.
- D. Disable the password based login for all the user
- E. All the users should use their own keys to connect with the instance securely.

Answer: A

Explanation:

Since AWS is a public cloud any application hosted on EC2 is prone to hacker attacks. It becomes extremely important for a user to setup a proper security mechanism on the EC2 instances. A few of the security measures are listed below:

Always keep the OS updated with the latest patch

Always create separate users with in OS if they need to connect with the EC2 instances, create their keys and disable their password
Create a procedure using which the admin can revoke the access of the user when the business work on the EC2 instance is completed
Lock down unnecessary ports
Audit any proprietary applications that the user may be running on the EC2 instance
Provide temporary escalated privileges, such as sudo for users who need to perform occasional privileged tasks
The IAM is useful when users are required to work with AWS resources and actions, such as launching an instance. It is not useful to connect (RDP / SSH) with an instance.
Reference: <http://aws.amazon.com/articles/1233/>

NEW QUESTION 66

What RAID method is used on the Cloud Block Storage back-end to implement a very high level of reliability and performance?

- A. RAID 1 (Mirror)
- B. RAID 5 (Blocks striped, distributed parity)
- C. RAID 10 (Blocks mirrored and striped)
- D. RAID 2 (Bit level striping)

Answer: C

Explanation:

Cloud Block Storage back-end storage volumes employs the RAID 10 method to provide a very high level of reliability and performance.
Reference: http://www.rackspace.com/knowledge_center/product-faq/cloud-block-storage

NEW QUESTION 70

One of the AWS account owners faced a major challenge in June as his account was hacked and the hacker deleted all the data from his AWS account. This resulted in a major blow to the business.
Which of the below mentioned steps would not have helped in preventing this action?

- A. Setup an MFA for each user as well as for the root account user.
- B. Take a backup of the critical data to offsite / on premise.
- C. Create an AMI and a snapshot of the data at regular intervals as well as keep a copy to separate regions.
- D. Do not share the AWS access and secret access keys with others as well do not store it inside programs, instead use IAM roles.

Answer: C

Explanation:

AWS security follows the shared security model where the user is as much responsible as Amazon. If the user wants to have secure access to AWS while hosting applications on EC2, the first security rule to follow is to enable MFA for all users. This will add an added security layer. In the second step, the user should never give his access or secret access keys to anyone as well as store inside programs. The better solution is to use IAM roles. For critical data of the organization, the user should keep an offsite/ in premise backup which will help to recover critical data in case of security breach.
It is recommended to have AWS AMIs and snapshots as well as keep them at other regions so that they will help in the DR scenario. However, in case of a data security breach of the account they may not be very helpful as hacker can delete that.
Therefore ,creating an AMI and a snapshot of the data at regular intervals as well as keep a copy to separate regions, would not have helped in preventing this action.
Reference: http://media.amazonwebservices.com/pdf/AWS_Security_Whitepaper.pdf

NEW QUESTION 74

In Amazon SNS, to send push notifications to mobile devices using Amazon SNS and ADM, you need to obtain the following, except:

- A. Device token
- B. Client ID
- C. Registration ID
- D. Client secret

Answer: A

Explanation:

To send push notifications to mobile devices using Amazon SNS and ADM, you need to obtain the following: Registration ID and Client secret.
Reference: <http://docs.aws.amazon.com/sns/latest/dg/SNSMobilePushPrereq.html>

NEW QUESTION 79

How does in-memory caching improve the performance of applications in ElastiCache?

- A. It improves application performance by deleting the requests that do not contain frequently accessed data.
- B. It improves application performance by implementing good database indexing strategies.
- C. It improves application performance by using a part of instance RAM for caching important data.
- D. It improves application performance by storing critical pieces of data in memory for low-latency access

Answer: D

Explanation:

In Amazon ElastiCache, in-memory caching improves application performance by storing critical pieces of data in memory for low-latency access. Cached information may include the results of I/O-intensive database queries or the results of computationally intensive calculations.
Reference: <http://aws.amazon.com/elasticache/faqs/#g4>

NEW QUESTION 81

A user is thinking to use EBS PIOPS volume. Which of the below mentioned options is a right use case for the PIOPS EBS volume?

- A. Analytics
- B. System boot volume
- C. Nlongo DB
- D. Log processing

Answer: C

Explanation:

Provisioned IOPS volumes are designed to meet the needs of I/O-intensive workloads, particularly database workloads that are sensitive to storage performance and consistency in random access I/O throughput. Provisioned IOPS volumes are designed to meet the needs of I/O-intensive workloads, particularly database workloads, that are sensitive to storage performance and consistency in random access I/O throughput business applications, database workloads, such as NoSQL DB, RDBMS, etc. Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSVolumeTypes.html>

NEW QUESTION 83

In the context of policies and permissions in AWS IAM, the Condition element is .

- A. crucial while writing the IAM policies
- B. an optional element
- C. always set to null
- D. a mandatory element

Answer: B

Explanation:

The Condition element (or Condition block) lets you specify conditions for when a policy is in effect. The Condition element is optional. Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage_ElementDescriptions.html

NEW QUESTION 88

When using string conditions within IAM, short versions of the available comparators can be used instead of the more verbose ones. streqi is the short version of the string condition.

- A. StringEqualsIgnoreCase
- B. StringNotEqualsIgnoreCase
- C. StringLikeStringEquals
- D. StringNotEquals

Answer: A

Explanation:

When using string conditions within IAM, short versions of the available comparators can be used instead of the more verbose versions. For instance, streqi is the short version of StringEqualsIgnoreCase that checks for the exact match between two strings ignoring their case. Reference: <http://awsdocs.s3.amazonaws.com/SNS/20100331/sns-gsg-2010-03-31.pdf>

NEW QUESTION 90

Attempts, one of the three types of items associated with the schedule pipeline in the AWS Data Pipeline, provides robust data management. Which of the following statements is NOT true about Attempts?

- A. Attempts provide robust data management.
- B. AWS Data Pipeline retries a failed operation until the count of retries reaches the maximum number of allowed retry attempts.
- C. An AWS Data Pipeline Attempt object compiles the pipeline components to create a set of actionable instances.
- D. AWS Data Pipeline Attempt objects track the various attempts, results, and failure reasons if applicable.

Answer: C

Explanation:

Attempts, one of the three types of items associated with a schedule pipeline in AWS Data Pipeline, provides robust data management. AWS Data Pipeline retries a failed operation. It continues to do so until the task reaches the maximum number of allowed retry attempts. Attempt objects track the various attempts, results, and failure reasons if applicable. Essentially, it is the instance with a counter. AWS Data Pipeline performs retries using the same resources from the previous attempts, such as Amazon EMR clusters and EC2 instances.

Reference:

<http://docs.aws.amazon.com/datapipeline/latest/DeveloperGuide/dp-how-tasks-scheduled.html>

NEW QUESTION 91

Which of the following cannot be done using AWS Data Pipeline?

- A. Create complex data processing workloads that are fault tolerant, repeatable, and highly available.
- B. Regularly access your data where it's stored, transform and process it at scale, and efficiently transfer the results to another AWS service.
- C. Generate reports over data that has been stored.
- D. Move data between different AWS compute and storage services as well as on-premise data sources at specified intervals.

Answer: C

Explanation:

AWS Data Pipeline is a web service that helps you reliably process and move data between different AWS compute and storage services as well as on-premise data sources at specified intervals. With AWS Data Pipeline, you can regularly access your data where it's stored, transform and process it at scale, and efficiently transfer the results to another AWS.

AWS Data Pipeline helps you easily create complex data processing workloads that are fault tolerant, repeatable, and highly available. AWS Data Pipeline also allows you to move and process data that was

previously locked up in on-premise data silos. Reference: <http://aws.amazon.com/datapipeline/>

NEW QUESTION 92

Identify an application that polls AWS Data Pipeline for tasks and then performs those tasks.

- A. A task executor
- B. A task deployer
- C. A task runner
- D. A task optimizer

Answer: C

Explanation:

A task runner is an application that polls AWS Data Pipeline for tasks and then performs those tasks. You can either use Task Runner as provided by AWS Data Pipeline, or create a custom Task Runner application.

Task Runner is a default implementation of a task runner that is provided by AWS Data Pipeline. When Task Runner is installed and configured, it polls AWS Data Pipeline for tasks associated with pipelines that you have activated. When a task is assigned to Task Runner, it performs that task and reports its status back to AWS Data Pipeline. If your workflow requires non-default behavior, you'll need to implement that functionality in a custom task runner.

Reference:

<http://docs.aws.amazon.com/datapipeline/latest/DeveloperGuide/dp-how-remote-taskrunner-client.html>

NEW QUESTION 93

An organization is planning to use NoSQL DB for its scalable data needs. The organization wants to host an application securely in AWS VPC. What action can be recommended to the organization?

- A. The organization should setup their own NoSQL cluster on the AWS instance and configure route tables and subnets.
- B. The organization should only use a DynamoDB because by default it is always a part of the default subnet provided by AWS.
- C. The organization should use a DynamoDB while creating a table within the public subnet.
- D. The organization should use a DynamoDB while creating a table within a private subnet

Answer: A

Explanation:

The Amazon Virtual Private Cloud (Amazon VPC) allows the user to define a virtual networking environment in a private, isolated section of the Amazon Web Services (AWS) cloud. The user has complete control over the virtual networking environment. Currently VPC does not support DynamoDB. Thus, if the user wants to implement VPC, he has to setup his own NoSQL DB within the VPC. Reference:

http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Introduction.html

NEW QUESTION 98

What happens when Dedicated instances are launched into a VPC?

- A. If you launch an instance into a VPC that has an instance tenancy of dedicated, you must manually create a Dedicated instance.
- B. If you launch an instance into a VPC that has an instance tenancy of dedicated, your instance is created as a Dedicated instance, only based on the tenancy of the instance.
- C. If you launch an instance into a VPC that has an instance tenancy of dedicated, your instance is automatically a Dedicated instance, regardless of the tenancy of the instance.
- D. None of these are true

Answer: C

Explanation:

If you launch an instance into a VPC that has an instance tenancy of dedicated, your instance is automatically a Dedicated instance, regardless of the tenancy of the instance.

Reference: <http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/dedicated-instance.html>

NEW QUESTION 99

An organization is setting up RDS for their applications. The organization wants to secure RDS access with VPC. Which of the following options is not required while designing the RDS with VPC?

- A. The organization must create a subnet group with public and private subnet
- B. Both the subnets can be in the same or separate AZ.
- C. The organization should keep minimum of one IP address in each subnet reserved for RDS failover.
- D. If the organization is connecting RDS from the internet it must enable the VPC attributes DNS hostnames and DNS resolution.
- E. The organization must create a subnet group with VPC using more than one subnet which are a part of separate AZs.

Answer: A

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources, such as RDS into a virtual network that the user has defined. Subnets are segments of a VPC's IP address range that the user can designate to a group of VPC resources based on security and operational needs. A DB subnet group is a collection of subnets (generally private) that the user can create in a VPC and assign to the RDS DB instances. A DB subnet group allows the user to specify a particular VPC when creating the DB instances.

Each DB subnet group should have subnets in at least two Availability Zones in a given region. If the RDS instance is required to be accessible from the internet the organization must enable the VPC attributes, DNS hostnames and DNS resolution. For each RDS DB instance that the user runs in a VPC, he should reserve at least one address in each subnet in the DB subnet group for use by Amazon RDS for recovery actions.

Reference: http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER_VPC.html

NEW QUESTION 102

You create a VPN connection, and your VPN device supports Border Gateway Protocol (BGP). Which of the following should be specified to configure the VPN connection?

- A. Classless routing
- B. Classfull routing
- C. Dynamic routing
- D. Static routing

Answer: C

Explanation:

If you create a VPN connection, you must specify the type of routing that you plan to use, which will depend upon on the make and model of your VPN devices. If your VPN device supports Border Gateway Protocol (BGP), you need to specify dynamic routing when you configure your VPN connection. If your device does not support BGP, you should specify static routing.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_VPN.html

NEW QUESTION 107

An organization has developed an application which provides a smarter shopping experience. They need to show a demonstration to various stakeholders who may not be able to access the in premise application so they decide to host a demo version of the application on AWS. Consequently they will need a fixed elastic IP attached automatically to the instance when it is launched.

In this scenario which of the below mentioned options will not help assign the elastic IP automatically?

- A. Write a script which will fetch the instance metadata on system boot and assign the public IP using that metadata.
- B. Provide an elastic IP in the user data and setup a bootstrapping script which will fetch that elastic IP and assign it to the instance.
- C. Create a controlling application which launches the instance and assigns the elastic IP based on the parameter provided when that instance is booted.
- D. Launch instance with VPC and assign an elastic IP to the primary network interface

Answer: A

Explanation:

EC2 allows the user to launch On-Demand instances. If the organization is using an application temporarily only for demo purposes the best way to assign an elastic IP would be:

Launch an instance with a VPC and assign an EIP to the primary network interface. This way on every instance start it will have the same IP Create a bootstrapping script and provide it some metadata, such as user data which can be used to assign an EIP Create a controller instance which can schedule the start and stop of the instance and provide an EIP as a parameter so that the controller instance can check the instance boot and assign an EIP

The instance metadata gives the current instance data, such as the public/private IP. It can be of no use for assigning an EIP.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/AESDG-chapter-instancedata.html>

NEW QUESTION 109

In the context of IAM roles for Amazon EC2, which of the following NOT true about delegating permission to make API requests?

- A. You cannot create an IAM role.
- B. You can have the application retrieve a set of temporary credentials and use them.
- C. You can specify the role when you launch your instances.
- D. You can define which accounts or AWS services can assume the role

Answer: A

Explanation:

Amazon designed IAM roles so that your applications can securely make API requests from your instances, without requiring you to manage the security credentials that the applications use. Instead of creating and distributing your AWS credentials, you can delegate permission to make API requests using IAM roles as follows: Create an IAM role. Define which accounts or AWS services can assume the role. Define which API actions and resources the application can use after assuming the role. Specify the role when you launch your instances. Have the application retrieve a set of temporary credentials and use them.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/iam-roles-for-amazon-ec2.html>

NEW QUESTION 114

In Amazon Cognito what is a silent push notification?

- A. It is a push message that is received by your application on a user's device that will not be seen by the user
- B. It is a push message that is received by your application on a user's device that will return the user's geolocation.
- C. It is a push message that is received by your application on a user's device that will not be heard by the user
- D. It is a push message that is received by your application on a user's device that will return the user's authentication credentials.

Answer: A

Explanation:

Amazon Cognito uses the Amazon Simple Notification Service (SNS) to send silent push notifications to devices. A silent push notification is a push message that is received by your application on a user's device that will not be seen by the user.

Reference: <http://aws.amazon.com/cognito/faqs/>

NEW QUESTION 118

Which of following IAM policy elements lets you specify an exception to a list of actions?

- A. NotException
- B. ExceptionAction
- C. Exception
- D. NotAction

Answer: D

Explanation:

The NotAction element lets you specify an exception to a list of actions. Reference:

http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage_ElementDescriptions.html

NEW QUESTION 122

You are setting up some EBS volumes for a customer who has requested a setup which includes a RAID (redundant array of inexpensive disks). AWS has some recommendations for RAID setups. Which RAID setup is not recommended for Amazon EBS?

- A. RAID 1 only
- B. RAID 5 only
- C. RAID 5 and RAID 6
- D. RAID 0 only

Answer: C

Explanation:

With Amazon EBS, you can use any of the standard RAID configurations that you can use with a traditional bare metal server, as long as that particular RAID configuration is supported by the operating

system for your instance. This is because all RAID is accomplished at the software level. For greater I/O performance than you can achieve with a single volume, RAID 0 can stripe multiple volumes together; for on-instance redundancy, RAID 1 can mirror two volumes together.

RAID 5 and RAID 6 are not recommended for Amazon EBS because the parity write operations of these RAID modes consume some of the IOPS available to your volumes.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/raid-config.html>

NEW QUESTION 126

In the context of AWS Cloud Hardware Security Module(HSM), does your application need to reside in the same VPC as the CloudHSM instance?

- A. No, but the server or instance on which your application and the HSM client is running must have network (IP) reachability to the HSM.
- B. Yes, always
- C. No, but they must reside in the same Availability Zone.
- D. No, but it should reside in same Availability Zone as the DB instance

Answer: A

Explanation:

Your application does not need to reside in the same VPC as the CloudHSM instance.

However, the server or instance on which your application and the HSM client is running must have network (IP) reachability to the HSM. You can establish network connectivity in a variety of ways, including operating your application in the same VPC, with VPC peering, with a VPN connection, or with Direct Connect.

Reference: <https://aws.amazon.com/cloudhsm/faqs/>

NEW QUESTION 127

What is the role of the PollForTask action when it is called by a task runner in AWS Data Pipeline?

- A. It is used to retrieve the pipeline definition.
- B. It is used to report the progress of the task runner to AWS Data Pipeline.
- C. It is used to receive a task to perform from AWS Data Pipeline.
- D. It is used to inform AWS Data Pipeline of the outcome when the task runner completes a task

Answer: C

Explanation:

Task runners call PollForTask to receive a task to perform from AWS Data Pipeline. If tasks are ready in the work queue, PollForTask returns a response immediately. If no tasks are available in the queue, PollForTask uses long-polling and holds on to a poll connection for up to 90 seconds, during which time any newly scheduled tasks are handed to the task agent. Your remote worker should not call PollForTask again on the same worker group until it receives a response, and this may take up to 90 seconds. Reference: http://docs.aws.amazon.com/datapipeline/latest/APIReference/AP_PollForTask.html

NEW QUESTION 132

What is the average queue length recommended by AWS to achieve a lower latency for the 200 PIOPS EBS volume?

- A. 5
- B. 1
- C. 2
- D. 4

Answer: B

Explanation:

The queue length is the number of pending I/O requests for a device. The optimal average queue length will vary for every customer workload, and this value

depends on a particular application's sensitivity to IOPS and latency. If the workload is not delivering enough I/O requests to maintain the optimal average queue length, then the EBS volume might not consistently deliver the IOPS that have been provisioned. However, if the workload maintains an average queue length that is higher than the optimal value, then the per-request I/O latency will increase; in this case, the user should provision more IOPS for his volume. AWS recommends that the user should target an optimal average queue length of 1 for every 200 provisioned IOPS and tune that value based on his application requirements.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-workload-demand.html>

NEW QUESTION 133

A user is planning to host a Highly Available system on the AWS VPC. Which of the below mentioned statements is helpful in this scenario?

- A. Create VPC subnets in two separate availability zones and launch instances in different subnets.
- B. Create VPC with only one public subnet and launch instances in different AZs using that subnet.
- C. Create two VPCs in two separate zones and setup failover with ELB such that if one VPC fails it will divert traffic to another VPC.
- D. Create VPC with only one private subnet and launch instances in different AZs using that subnet

Answer: A

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. The VPC is always specific to a region. The user can create a VPC which can span multiple Availability Zones by adding one or more subnets in each Availability Zone. Each subnet must reside entirely within one Availability Zone and cannot span across zones.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Subnets.html#VPCSubnet

NEW QUESTION 137

A user is creating a PIOPS volume. What is the maximum ratio the user should configure between PIOPS and the volume size?

- A. 5
- B. 10
- C. 20
- D. 30

Answer: D

Explanation:

Provisioned IOPS volumes are designed to meet the needs of I/O-intensive workloads, particularly database workloads that are sensitive to storage performance and consistency in random access I/O throughput. A provisioned IOPS volume can range in size from 10 GB to 1 TB and the user can provision up to 4000 IOPS per volume.

The ratio of IOPS provisioned to the volume size requested can be a maximum of 30; for example, a volume with 3000 IOPS must be at least 100 GB.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSVolumeTypes.html>

NEW QUESTION 138

A government client needs you to set up secure cryptographic key storage for some of their extremely confidential data. You decide that the AWS CloudHSM is the best service for this. However, there seem to be a few pre-requisites before this can happen, one of those being a security group that has certain ports open. Which of the following is correct in regards to those security groups?

- A. A security group that has no ports open to your network.
- B. A security group that has only port 3389 (for RDP) open to your network.
- C. A security group that has only port 22 (for SSH) open to your network.
- D. A security group that has port 22 (for SSH) or port 3389 (for RDP) open to your network

Answer: D

Explanation:

AWS CloudHSM provides secure cryptographic key storage to customers by making hardware security modules (HSMs) available in the AWS cloud.

AWS CloudHSM requires the following environment before an HSM appliance can be provisioned. A virtual private cloud (VPC) in the region where you want the AWS CloudHSM service.

One private subnet (a subnet with no Internet gateway) in the VPC. The HSM appliance is provisioned into this subnet.

One public subnet (a subnet with an Internet gateway attached). The control instances are attached to this subnet.

An AWS Identity and Access Management (IAM) role that delegates access to your AWS resources to AWS CloudHSM.

An EC2 instance, in the same VPC as the HSM appliance, that has the SafeNet client software installed. This instance is referred to as the control instance and is used to connect to and manage the HSM appliance.

A security group that has port 22 (for SSH) or port 3389 (for RDP) open to your network. This security group is attached to your control instances so you can access them remotely.

NEW QUESTION 139

An organization is setting up a web application with the JEE stack. The application uses the JBoss app server and MySQL DB. The application has a logging module which logs all the activities whenever a business function of the JEE application is called. The logging activity takes some time due to the large size of the log file. If the application wants to setup a scalable infrastructure which of the below mentioned options will help achieve this setup?

- A. Host the log files on EBS with PIOPS which will have higher I/O.
- B. Host logging and the app server on separate servers such that they are both in the same zone.
- C. Host logging and the app server on the same instance so that the network latency will be shorter.
- D. Create a separate module for logging and using SQS compartmentalize the module such that all calls to logging are asynchronous.

Answer: D

Explanation:

The organization can always launch multiple EC2 instances in the same region across multiple AZs for HA and DR. The AWS architecture practice recommends compartmentalizing the functionality such that

they can both run in parallel without affecting the performance of the main application. In this scenario logging takes a longer time due to the large size of the log file. Thus, it is recommended that the organization should separate them out and make separate modules and make asynchronous calls among them. This way the application can scale as per the requirement and the performance will not bear the impact of logging.

Reference: <http://www.awsarchitectureblog.com/2014/03/aws-and-compartmentalization.html>

NEW QUESTION 144

A user has set the IAM policy where it denies all requests if a request is not from IP 10.10.10.1/32. The other policy says allow all requests between 5 PM to 7 PM. What will happen when a user is requesting access from IP 55.109.10.12/32 at 6 PM?

- A. It will deny access
- B. It is not possible to set a policy based on the time or IP
- C. IAM will throw an error for policy conflict
- D. It will allow access

Answer: A

Explanation:

When a request is made, the AWS IAM policy decides whether a given request should be allowed or denied. The evaluation logic follows these rules:

By default, all requests are denied. (In general, requests made using the account credentials for resources in the account are always allowed.)

An explicit allow policy overrides this default.

An explicit deny policy overrides any allows.

In this case since there are explicit deny and explicit allow statements. Thus, the request will be denied since deny overrides allow.

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage_EvaluationLogic.html

NEW QUESTION 148

Which of the following AWS services can be used to define alarms to trigger on a certain actMty, such as actMty success, failure, or delay in AWS Data Pipeline?

- A. Amazon SES
- B. Amazon CodeDeploy
- C. Amazon SNS
- D. Amazon SQS

Answer: C

Explanation:

In AWS Data Pipeline, you can define Amazon SNS alarms to trigger on actMties such as success, failure, or delay by creating an alarm object and referencing it in the onFail, onSuccess, or onLate slots of the actMty object.

Reference: <https://aws.amazon.com/datapipeline/faqs/>

NEW QUESTION 151

Which of the following components of AWS Data Pipeline polls for tasks and then performs those tasks?

- A. Pipeline Definition
- B. Task Runner
- C. Amazon Elastic MapReduce (EMR)
- D. AWS Direct Connect

Answer: B

Explanation:

Task Runner polls for tasks and then performs those tasks.

Reference: <http://docs.aws.amazon.com/datapipeline/latest/DeveloperGuide/what-is-datapipeline.html>

NEW QUESTION 156

A user is hosting a public website on AWS. The user wants to have the database and the app server on the AWS VPC. The user wants to setup a database that can connect to the Internet for any patch upgrade but cannot receive any request from the internet. How can the user set this up?

- A. Setup DB in a private subnet with the security group allowing only outbound traffic.
- B. Setup DB in a public subnet with the security group allowing only inbound data.
- C. Setup DB in a local data center and use a private gateway to connect the application with DB.
- D. Setup DB in a private subnet which is connected to the internet via NAT for outbound.

Answer: D

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. AWS provides two features that the user can use to increase security in VPC: security groups and network ACLs. When the user wants to setup both the DB and App on VPC, the user should make one public and one private subnet. The DB should be hosted in a private subnet and instances in that subnet cannot reach the internet. The user can allow an instance in his VPC to initiate outbound connections to the internet but prevent unsolicited inbound connections from the internet by using a Network Address Translation (NAT) instance.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Subnets.html

NEW QUESTION 160

In Amazon ElastiCache, the default cache port is:

- A. for Memcached 11210 and for Redis 6380.
- B. for Memcached 11211 and for Redis 6380.
- C. for Memcached 11210 and for Redis 6379.
- D. for Memcached 11211 and for Redis 6379.

Answer: D

Explanation:

In Amazon ElastiCache, you can specify a new port number for your cache cluster, which by default is 11211 for Memcached and 6379 for Redis.

Reference: <http://docs.aws.amazon.com/AmazonElastiCache/latest/UserGuide/GettingStarted.AuthorizeAccess.htm>

NEW QUESTION 161

Which of the following statements is correct about AWS Direct Connect?

- A. Connections to AWS Direct Connect require double clad fiber for 1 gigabit Ethernet with Auto Negotiation enabled for the port.
- B. An AWS Direct Connect location provides access to Amazon Web Services in the region it is associated with.
- C. AWS Direct Connect links your internal network to an AWS Direct Connect location over a standard 50 gigabit Ethernet cable.
- D. To use AWS Direct Connect, your network must be colocated with a new AWS Direct Connect location.

Answer: B

Explanation:

AWS Direct Connect links your internal network to an AWS Direct Connect location over a standard 1 gigabit or 10 gigabit Ethernet fiber-optic cable. An AWS Direct Connect location provides access to Amazon Web Services in the region it is associated with, as well as access to other US regions. To use AWS Direct Connect, your network is colocated with an existing AWS Direct Connect location. Connections to AWS Direct Connect require single mode fiber, 1000BASE-LX (1310nm) for 1 gigabit Ethernet, or 10GBASE-LR (1310nm) for 10 gigabit Ethernet. Auto Negotiation for the port must be disabled.

Reference: <http://docs.aws.amazon.com/directconnect/latest/UserGuide/Welcome.html>

NEW QUESTION 165

Is there any way to own a direct connection to Amazon Web Services?

- A. No, AWS only allows access from the public Internet.
- B. No, you can create an encrypted tunnel to VPC, but you cannot own the connection.
- C. Yes, you can via Amazon Dedicated Connection.
- D. Yes, you can via AWS Direct Connect.

Answer: D

Explanation:

AWS Direct Connect links your internal network to an AWS Direct Connect location over a standard 1 gigabit or 10 gigabit Ethernet fiber-optic cable. One end of the cable is connected to your router, the other to an AWS Direct Connect router. With this connection in place, you can create virtual interfaces directly to the AWS cloud (for example, to Amazon Elastic Compute Cloud (Amazon EC2) and Amazon Simple Storage Service (Amazon S3)) and to Amazon Virtual Private Cloud (Amazon VPC), bypassing Internet service providers in your network path.

Reference: <http://docs.aws.amazon.com/directconnect/latest/UserGuide/Welcome.html>

NEW QUESTION 170

In Amazon ElastiCache, which of the following statements is correct?

- A. When you launch an ElastiCache cluster into an Amazon VPC private subnet, every cache node is assigned a public IP address within that subnet.
- B. You cannot use ElastiCache in a VPC that is configured for dedicated instance tenancy.
- C. If your AWS account supports only the EC2-VPC platform, ElastiCache will never launch your cluster in a VPC.
- D. ElastiCache is not fully integrated with Amazon Virtual Private Cloud (VPC).

Answer: B

Explanation:

The VPC must allow non-dedicated EC2 instances. You cannot use ElastiCache in a VPC that is configured for dedicated instance tenancy.

Reference: <http://docs.aws.amazon.com/AmazonElastiCache/latest/UserGuide/AmazonVPC.EC.html>

NEW QUESTION 173

An organization has setup RDS with VPC. The organization wants RDS to be accessible from the internet. Which of the below mentioned configurations is not required in this scenario?

- A. The organization must enable the parameter in the console which makes the RDS instance publicly accessible.
- B. The organization must allow access from the internet in the RDS VPC security group.
- C. The organization must setup RDS with the subnet group which has an external IP.
- D. The organization must enable the VPC attributes DNS hostnames and DNS resolution.

Answer: C

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources, such as RDS into a virtual network that the user has defined. Subnets are segments of a VPC's IP address range that the user can designate to a group of VPC resources based on security and operational needs. A DB subnet group is a collection of subnets (generally private) that the user can create in a VPC and which the user assigns to the RDS DB instances. A DB subnet group allows the user to specify a particular VPC when creating DB instances. If the RDS instance is required to be accessible from the internet:

The organization must setup that the RDS instance is enabled with the VPC attributes, DNS hostnames and DNS resolution.

The organization must enable the parameter in the console which makes the RDS instance publicly accessible.

The organization must allow access from the internet in the RDS VPC security group. Reference:

http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER_VPC.html

NEW QUESTION 177

An organization, which has the AWS account ID as Q99988887777, has created 50 IAM users. All the users are added to the same group examkiller. If the organization has enabled that each IAM user can login with the AWS console, which AWS login URL will the IAM users use??

- A. <https://Q99988887777.aws.amazon.com/examkiller/>
- B. <https://signin.aws.amazon.com/examkiller/>
- C. <https://examkiller.signin.aws.amazon.com/999988887777/console/>
- D. <https://999988887777.signin.aws.amazon.com/console/>

Answer: D

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. Once the organization has created the IAM users, they will have a separate AWS console URL to login to the AWS console. The console login URL for the IAM user will be [https:// AWS_Account_ID.signin.aws.amazon.com/console/](https://AWS_Account_ID.signin.aws.amazon.com/console/). It uses only the AWS account ID and does not depend on the group or user ID.

Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/AccountAlias.html>

NEW QUESTION 180

You have deployed a web application targeting a global audience across multiple AWS Regions under the domain name.example.com. You decide to use Route53 Latency-Based Routing to serve web requests to users from the region closest to the user. To provide business continuity in the event of server downtime you configure weighted record sets associated with two web servers in separate Availability Zones per region. During a DR test you notice that when you disable all web servers in one of the regions Route53 does not automatically direct all users to the other region. What could be happening? (Choose 2 answers)

- A. Latency resource record sets cannot be used in combination with weighted resource record sets.
- B. You did not setup an HTTP health check to one or more of the weighted resource record sets associated with the disabled web servers.
- C. The value of the weight associated with the latency alias resource record set in the region with the disabled servers is higher than the weight for the other region.
- D. One of the two working web servers in the other region did not pass its HTTP health check.
- E. You did not set "Evaluate Target Health" to "Yes" on the latency alias resource record set associated with example.com in the region where you disabled the servers.

Answer: BE

NEW QUESTION 185

A read only news reporting site with a combined web and application tier and a database tier that receives large and unpredictable traffic demands must be able to respond to these traffic fluctuations automatically. What AWS services should be used to meet these requirements?

- A. Stateless instances for the web and application tier synchronized using ElastiCache Memcached in an autoscaling group monitored with CloudWatch and RDS with read replicas.
- B. Stateful instances for the web and application tier in an autoscaling group monitored with CloudWatch and RDS with read replicas.
- C. Stateful instances for the web and application tier in an autoscaling group monitored with CloudWatch.
- D. And multi-AZ RDS.
- E. Stateless instances for the web and application tier synchronized using ElastiCache Memcached in an autoscaling group monitored with CloudWatch and multi-AZ RDS.

Answer: A

NEW QUESTION 189

You are tasked with moving a legacy application from a virtual machine running inside your datacenter to an Amazon VPC. Unfortunately, this app requires access to a number of on-premises services and no one who configured the app still works for your company. Even worse, there's no documentation for it.

What will allow the application running inside the VPC to reach back and access its internal dependencies without being reconfigured? (Choose 3 answers)

- A. An AWS Direct Connect link between the VPC and the network housing the internal services.
- B. An Internet Gateway to allow a VPN connection.
- C. An Elastic IP address on the VPC instance.
- D. An IP address space that does not conflict with the one on-premises.
- E. Entries in Amazon Route 53 that allow the instance to resolve its dependencies' IP addresses.
- F. A VM Import of the current virtual machine.

Answer: ADF

NEW QUESTION 192

You have a periodic image analysis application that gets some files. It input analyzes them and for each file writes some data in output to a text file. The number of files in input per day is high and concentrated in a few hours of the day.

Currently, you have a server on EC2 with a large EBS volume that hosts the input data and the results. It takes almost 20 hours per day to complete the process. What services could be used to reduce the elaboration time and improve the availability of the solution?

- A. S3 to store I/O files.
- B. SQS to distribute elaboration commands to a group of hosts working in parallel.
- C. Auto scaling to dynamically size the group of hosts depending on the length of the SQS queue.
- D. EBS with Provisioned IOPS (PIOPS) to store I/O files.
- E. SNS to distribute elaboration commands to a group of hosts working in parallel. Auto Scaling to dynamically size the group of hosts depending on the number of SNS notifications.
- F. S3 to store I/O files, SNS to distribute elaboration commands to a group of hosts working in parallel.
- G. Auto scaling to dynamically size the group of hosts depending on the number of SNS notifications.
- H. EBS with Provisioned IOPS (PIOPS) to store I/O files. SQS to distribute elaboration commands to a group of hosts working in parallel. Auto Scaling to dynamically size the group of hosts depending on the length of the SQS queue.

Answer: D

NEW QUESTION 196

A large real-estate brokerage is exploring the option of adding a cost-effective location-based alert to their existing mobile application. The application backend infrastructure currently runs on AWS. Users who opt in to this service will receive alerts on their mobile device regarding real-estate offers in proximity to their location. For the alerts to be relevant, delivery time needs to be in the low minute count. The existing mobile app has 5 million users across the US. Which one of the following architectural suggestions would you make to the customer?

- A. The mobile application will submit its location to a web service endpoint utilizing Elastic Load Balancing and EC2 instances: DynamoDB will be used to store and retrieve relevant offers EC2 instances will communicate with mobile earners/device providers to push alerts back to mobile application.
- B. Use AWS DirectConnect or VPN to establish connectMty with mobile carriers EC2 instances will receive the mobile applications ' location through carrier connection: RDS will be used to store and relevant offers EC2 instances will communicate with mobile carriers to push alerts back to the mobile application
- C. The mobile application will send device location using SQ
- D. EC2 instances will retrieve the relevant others from DynamoDB AWS Mobile Push will be used to send offers to the mobile application
- E. The mobile application will send device location using AWS Nmobile Push EC2 instances will retrieve the relevant offers from DynamoDB EC2 instances will communicate with mobile carriers/device providers to push alerts back to the mobile application.

Answer: A

NEW QUESTION 199

Your company has HQ in Tokyo and branch offices all over the world and is using a logistics software with a multi-regional deployment on AWS in Japan, Europe and US

- A. The logistic software has a 3-tierarchitecture and currently uses MySQL 5.6 for data persistenc
- B. Each region has deployed its own database In the HQ region you run an hourly batch process reading data from every region to compute cross-regional reports that are sent by email to all offices this batch process must be completed as fast as possible to quickly optimize logistics how do you build the database architecture in order to meet the requirements'?
- C. For each regional deployment, use RDS MySQL with a master in the region and a read replica in theHQ region
- D. For each regional deployment, use NlySQL on EC2 with a master in the region and send hourly EBS snapshots to the HQ region
- E. For each regional deployment, use RDS MySQL with a master in the region and send hourly RDS snapshots to the HQ region
- F. For each regional deployment, use MySQL on EC2 with a master in the region and use S3 to copy data files hourly to the HQ region
- G. Use Direct Connect to connect all regional MySQL deployments to the HQ region and reduce network latency for the batch process

Answer: A

NEW QUESTION 204

A web design company currently runs several FTP servers that their 250 customers use to upload and download large graphic files They wish to move this system to AWS to make it more scalable, but they wish to maintain customer privacy and Keep costs to a minimum.
What AWS architecture would you recommend?

- A. ASK their customers to use an S3 client instead of an FTP clien
- B. Create a single S3 bucket Create an IAM user for each customer Put the IAM Users in a Group that has an IAM policy that permits access to sub-directories within the bucket via use of the 'username' Policy variable.
- C. Create a single S3 bucket with Reduced Redundancy Storage turned on and ask their customers to use an S3 client instead of an FTP client Create a bucket for each customer with a Bucket Policy that permits access only to that one customer.
- D. Create an auto-scaling group of FTP servers with a scaling policy to automatically scale-in when minimum network traffic on the auto-scaling group is below a given threshol
- E. Load a central list of ftp users from S3 as part of the user Data startup script on each Instance.
- F. Create a single S3 bucket with Requester Pays turned on and ask their customers to use an S3 client instead of an FTP client Create a bucket tor each customer with a Bucket Policy that permits access only to that one customer.

Answer: A

NEW QUESTION 205

You would like to create a mirror image of your production environment in another region for disaster recovery purposes. Which of the following AWS resources do not need to be recreated in the second region? (Choose 2 answers)

- A. Route 53 Record Sets
- B. IAM Roles
- C. Elastic IP Addresses (EIP)
- D. EC2 Key Pairs
- E. Launch configurations
- F. Security Groups

Answer: AC

NEW QUESTION 207

An enterprise wants to use a third-party SaaS application. The SaaS application needs to have access to issue several API commands to discover Amazon EC2 resources running within the enterprise's account The enterprise has internal security policies that require any outside access to their environment must conform to the principles of least prMlege and there must be controls in place to ensure that the credentials used by the SaaS vendor cannot be used by any other third party. Which of the following would meet all of these conditions?

- A. From the AWS Management Console, navigate to the Security Credentials page and retrieve the access and secret key for your account.
- B. Create an IAM user within the enterprise account assign a user policy to the IAM user that allows only the actions required by the SaaS application create a new access and secret key for the user and provide these credentials to the SaaS provider.
- C. Create an IAM role for cross-account access allows the SaaS provider's account to assume the role and assign it a policy that allows only the actions required by the SaaS application.
- D. Create an IAM role for EC2 instances, assign it a policy that allows only the actions required tor the Saas application to work, provide the role ARN to the SaaS provider to use when launching their application instances.

Answer: C

NEW QUESTION 208

Your company is getting ready to do a major public announcement of a social media site on AWS. The website is running on EC2 instances deployed across multiple Availability Zones with a Multi-AZ RDS MySQL Extra Large DB Instance. The site performs a high number of small reads and writes per second and relies on an eventual consistency model. After comprehensive tests you discover that there is read contention on RDS MySQL. Which are the best approaches to meet

these requirements? (Choose 2 answers)

- A. Deploy ElastiCache in-memory cache running in each availability zone
- B. Implement sharding to distribute load to multiple RDS MySQL instances
- C. Increase the RDS MySQL Instance size and Implement provisioned IOPS
- D. Add an RDS MySQL read replica in each availability zone

Answer: AC

NEW QUESTION 211

You are designing an intrusion detection prevention (IDS/IPS) solution for a customer web application in a single VPC. You are considering the options for implementing IOS IPS protection for traffic coming from the Internet.

Which of the following options would you consider? (Choose 2 answers)

- A. Implement IDS/IPS agents on each Instance running In VPC
- B. Configure an instance in each subnet to switch its network interface card to promiscuous mode and analyze network traffic.
- C. Implement Elastic Load Balancing with SSL listeners In front of the web applications
- D. Implement a reverse proxy layer in front of web servers and configure IDS/IPS agents on each reverse proxy server.

Answer: BD

NEW QUESTION 215

An International company has deployed a multi-tier web application that relies on DynamoDB in a single region For regulatory reasons they need disaster recovery capability In a separate region with a Recovery Time Objective of 2 hours and a Recovery Point Objective of 24 hours. They should synchronize their data on a regular basis and be able to provision me web application rapidly using CloudFormation.

The objective is to minimize changes to the existing web application, control the throughput of DynamoDB used for the synchronization of data and synchronize only the modified elements.

Which design would you choose to meet these requirements?

- A. Use AWS data Pipeline to schedule a DynamoDB cross region copy once a day, create a "Lastupdated" attribute in your DynamoDB table that would represent the timestamp of the last update and use it as a filter.
- B. Use EMR and write a custom script to retrieve data from DynamoDB in the current region using a SCAN operation and push it to DynamoDB in the second region.
- C. Use AWS data Pipeline to schedule an export of the DynamoDB table to S3 in the current region once a day then schedule another task immediately after it that will import data from S3 to DynamoDB in the other region.
- D. Send also each Ante into an SQS queue in me second region; use an auto-scaling group behind the SQS queue to replay the write in the second region.

Answer: A

NEW QUESTION 220

You are designing a social media site and are considering how to mitigate distributed denial-of-service (DDoS) attacks. Which of the below are viable mitigation techniques? (Choose 3 answers)

- A. Add multiple elastic network interfaces (ENIs) to each EC2 instance to increase the network bandwidth.
- B. Use dedicated instances to ensure that each instance has the maximum performance possible.
- C. Use an Amazon CloudFront distribution for both static and dynamic content.
- D. Use an Elastic Load Balancer with auto scaling groups at the we
- E. App and Amazon Relational Database Service (RDS) tiers
- F. Add alert Amazon CloudWatch to look for high Network in and CPU utilization.
- G. Create processes and capabilities to quickly add and remove rules to the instance OS firewall

Answer: CEF

NEW QUESTION 223

A customer has established an AWS Direct Connect connection to AWS. The link is up and routes are being advertised from the customer's end, however the customer is unable to connect from EC2 instances inside its VPC to servers residing in its datacenter.

Which of the following options provide a viable solution to remedy this situation? (Choose 2 answers)

- A. Add a route to the route table with an IPsec VPN connection as the target.
- B. Enable route propagation to the virtual pinnate gateway (VGW).
- C. Enable route propagation to the customer gateway (CGW).
- D. Modify the route table of all Instances using the 'route' command.
- E. Modify the Instances VPC subnet route table by adding a route back to the customer's on-premises environment.

Answer: AC

NEW QUESTION 226

A corporate web application is deployed within an Amazon Virtual Private Cloud (VPC) and is connected to the corporate data center via an IPsec VPN. The application must authenticate against the

on-premises LDAP server. After authentication, each logged-in user can only access an Amazon Simple Storage Space (S3) keyspace specific to that user.

Which two approaches can satisfy these objectives? (Choose 2 answers)

- A. Develop an identity broker that authenticates against IAM security Token service to assume a IAM role in order to get temporary AWS security credentials The application calls the identity broker to get AWS temporary security credentials with access to the appropriate S3 bucket.
- B. The application authenticates against LDAP and retrieves the name of an IAM role associated with the use
- C. The application then calls the IAM Security Token Service to assume that IAM rol
- D. The application can use the temporary credentials to access the appropriate S3 bucket.
- E. Develop an identity broker that authenticates against LDAP and then calls IAM Security Token Service to get IAM federated user credential

- F. The application calls the identity broker to get IAM federated user credentials with access to the appropriate S3 bucket.
- G. The application authenticates against LDAP the application then calls the AWS identity and AccessManagement (IAM) Security service to log in to IAM using the LDAP credentials the application can use the IAM temporary credentials to access the appropriate S3 bucket.
- H. The application authenticates against IAM Security Token Service using the LDAP credentials the application uses those temporary AWS security credentials to access the appropriate S3 bucket.

Answer: BC

NEW QUESTION 229

You are designing a personal document-archMng solution for your global enterprise with thousands of employee. Each employee has potentially gigabytes of data to be backed up in this archMng solution. The solution will be exposed to the employees as an application, where they can just drag and drop their files to the archMng system. Employees can retrieve their archives through a web interface. The corporate network has high bandwidth AWS Direct Connect connectMty to AWS.

You have a regulatory requirement that all data needs to be encrypted before being uploaded to the cloud.

How do you implement this in a highly available and cost-efficient way?

- A. Manage encryption keys on-premises in an encrypted relational databas
- B. Set up an on-premises server with sufficient storage to temporarily store files, and then upload them to Amazon S3, providing a client-side master key.
- C. Mange encryption keys in a Hardware Security Module (HSM) appliance on-premises serve r with sufficient storage to temporarily store, encrypt, and upload files directly into Amazon Glacier.
- D. Nlamage encryption keys in Amazon Key Management Service (KMS), upload to Amazon Simple Storage Service (S3) with client-side encryption using a KMS customer master key ID, and configure Amazon S3 lifecycle policies to store each object using the Amazon Glacier storage tier.
- E. Manage encryption keys in an AWS CloudHSMI applan
- F. Encrypt files prior to uploading on the employee desktop, and then upload directly into Amazon Glacier.

Answer: C

NEW QUESTION 230

A company is building a voting system for a popular TV show, viewers win watch the performances then visit the show's website to vote for their favorite performer. It is expected that in a short period of time after the show has finished the site will receive millions of visitors. The visitors will first login to the site using their Amazon.com credentials and then submit their vote. After the voting is completed the page will display the vote totals. The company needs to build the site such that can handle the rapid influx of traffic while maintaining good performance but also wants to keep costs to a minimum. Which of the design patterns below should they use?

- A. Use CloudFront and an Elastic Load balancer in front of an auto-scaled set of web servers, the web servers will first call the Login With Amazon service to authenticate the user then process the users vote and store the result into a multi-AZ Relational Database Service instance.
- B. Use CloudFront and the static website hosting feature of S3 with the Javascript SDK to call the Login With Amazon service to authenticate the user, use IAM Roles to gain permissions to a DynamoDB tableto store the users vote.
- C. Use CloudFront and an Elastic Load Balancer in front of an auto-scaled set of web servers, the web servers will first call the Login with Amazon service to authenticate the user, the web servers will process the users vote and store the result into a DynamoDB table using IAM Roles for EC2 instances to gain permissions to the DynamoDB table.
- D. Use CloudFront and an Elastic Load Balancer in front of an auto-scaled set of web servers, the web servers will first call the Login With Amazon service to authenticate the user, the web sewers win process the users vote and store the result into an SQS queue using IAM Roles for EC2 Instances to gain permissions to the SQS queu
- E. A set of application sewers will then retrieve the items from the queue and store the result into a DynamoDB table.

Answer: D

NEW QUESTION 233

You are designing a connectMty solution between on-premises infrastructure and Amazon VPC. Your servers on-premises will be communicating with your VPC instances. You will be establishing IPSec tunnels over the Internet You will be using VPN gateways, and terminating the IPSec tunnels on AWS supported customer gateways.

Which of the following objectives would you achieve by implementing an IPSec tunnel as outlined above? Choose 4 answers

- A. End-to-end protection of data in transit
- B. End-to-end Identity authentication
- C. Data encwption across the Internet
- D. Protection of data in transit over the Internet
- E. Peer identity authentication between VPN gateway and customer gateway
- F. Data integrity protection across the Internet

Answer: CDEF

NEW QUESTION 237

You are responsible for a web application that consists of an Elastic Load Balancing (ELB) load balancer in front of an Auto Scaling group of Amazon Elastic Compute Cloud (EC2) instances. For a recent deployment of a new version of the application, a new Amazon Machine Image (AMI) was created, and the Auto Scaling group was updated with a new launch configuration that refers to this new AMI. During the deployment, you received complaints from users that the website was responding with errors. All instances passed the ELB health checks.

What should you do in order to avoid errors for future deployments? (Choose 2 answer)

- A. Add an Elastic Load Balancing health check to the Auto Scaling grou
- B. Set a short period for the health checks to operate as soon as possible in order to prevent premature registration of the instance to theload balancer.
- C. Enable EC2 instance CloudWatch alerts to change the launch configuration's AMI to the previous on
- D. Gradually terminate instances that are using the new AMI.
- E. Set the Elastic Load Balancing health check configuration to target a part of the application that fully tests application health and returns an error if the tests fail.
- F. Create a new launch configuration that refers to the new AMI, and associate it with the grou
- G. Double the size of the group, wait for the new instances to become healthy, and reduce back to the original size.If new instances do not become healthy, associate the previous launch configuration.
- H. Increase the Elastic Load Balancing Unhealthy Threshold to a higher value to prevent an unhealthy instance from going into service behind the load balancer.

Answer: CD

NEW QUESTION 240

Which is a valid Amazon Resource name (ARN) for IAM?

- A. aws:iam::123456789012:instance-profile/Nebserver
- B. arn:aws:iam::123456789012:instance-profile/Webserver
- C. 123456789012:aws:iam::instance-profile/Nebserver
- D. arn:aws:iam::123456789012::instance-profile/Nebserver

Answer: B

NEW QUESTION 243

You are running a successful multitier web application on AWS and your marketing department has asked you to add a reporting tier to the application. The reporting tier will aggregate and publish status reports every 30 minutes from user-generated information that is being stored in your web application's database. You are currently running a Multi-AZ RDS MySQL instance for the database tier. You also have implemented ElastiCache as a database caching layer between the application tier and database tier. Please select the answer that will allow you to successfully implement the reporting tier with as little impact as possible to your database.

- A. Continually send transaction logs from your master database to an S3 bucket and generate the reports off the S3 bucket using S3 byte range requests.
- B. Generate the reports by querying the synchronously replicated standby RDS MySQL instance maintained through Multi-AZ.
- C. Launch a RDS Read Replica connected to your Multi AZ master database and generate reports by querying the Read Replica.
- D. Generate the reports by querying the ElastiCache database caching tier

Answer: C

NEW QUESTION 244

Your company plans to host a large donation website on Amazon Web Services (AWS). You anticipate a large and undetermined amount of traffic that will create many database writes. To be certain that you do not drop any writes to a database hosted on AWS. Which service should you use?

- A. Amazon RDS with provisioned IOPS up to the anticipated peak write throughput.
- B. Amazon Simple Queue Service (SQS) for capturing the writes and draining the queue to write to the database.
- C. Amazon ElastiCache to store the writes until the writes are committed to the database.
- D. Amazon DynamoDB with provisioned write throughput up to the anticipated peak write throughput

Answer: B

NEW QUESTION 247

You have an application running on an EC2 Instance which will allow users to download files from a private S3 bucket using a pre-signed URL. Before generating the URL the application should verify the existence of the file in S3.

How should the application use AWS credentials to access the S3 bucket securely?

- A. Use the AWS account access keys the application retrieves the credentials from the source code of the application.
- B. Create an IAM user for the application with permissions that allow list access to the S3 bucket launch the instance as the IAM user and retrieve the IAM user's credentials from the EC2 instance user data.
- C. Create an IAM role for EC2 that allows list access to objects in the S3 bucket
- D. Launch the instance with the role, and retrieve the role's credentials from the EC2 Instance metadata
- E. Create an IAM user for the application with permissions that allow list access to the S3 bucket
- F. The application retrieves the IAM user credentials from a temporary directory with permissions that allow read access only to the application user.

Answer: C

NEW QUESTION 249

You deployed your company website using Elastic Beanstalk and you enabled log file rotation to S3. An Elastic Map Reduce job is periodically analyzing the logs on S3 to build a usage dashboard that you share with your CIO.

You recently improved overall performance of the website using Cloud Front for dynamic content delivery and your website as the origin.

After this architectural change, the usage dashboard shows that the traffic on your website dropped by an order of magnitude. How do you fix your usage dashboard?

- A. Enable Cloud Front to deliver access logs to S3 and use them as input of the Elastic Map Reduce job.
- B. Turn on Cloud Trail and use trail log files on S3 as input of the Elastic Map Reduce job
- C. Change your log collection process to use Cloud Watch ELB metrics as input of the Elastic MapReduce job
- D. Use Elastic Beanstalk "Rebuild Environment" option to update log delivery to the Elastic Map Reduce job.
- E. Use Elastic Beanstalk "Restart App server(s)" option to update log delivery to the Elastic Map Reduce job.

Answer: D

NEW QUESTION 251

A web-startup runs its very successful social news application on Amazon EC2 with an Elastic Load Balancer, an Auto-Scaling group of Java/Tomcat application servers, and DynamoDB as data store. The main web-application best runs on m2 x large instances since it is highly memory-bound. Each new deployment requires semi-automated creation and testing of a new AMI for the application servers which takes quite a while and is therefore only done once per week. Recently, a new chat feature has been implemented in Node.js and waits to be integrated in the architecture. First tests show that the new component is CPU bound. Because the company has some experience with using Chef, they decided to streamline the deployment process and use AWS Ops Works as an application life cycle tool to simplify management of the application and reduce the deployment cycles.

What configuration in AWS Ops Works is necessary to integrate the new chat module in the most cost-efficient and flexible way?

- A. Create one AWS OpsWorks stack, create one AWS Ops Works layer, create one custom recipe

- B. Create one AWS OpsWorks stack create two AWS Ops Works layers, create one custom recipe
- C. Create two AWS OpsWorks stacks create two AWS Ops Works layers, create one custom recipe
- D. Create two AWS OpsWorks stacks create two AWS Ops Works layers, create two custom recipe

Answer: C

NEW QUESTION 252

Select the correct set of options. These are the initial settings for the default security group:

- A. Allow no inbound traffic, Allow all outbound traffic and Allow instances associated with this security group to talk to each other
- B. Allow all inbound traffic, Allow no outbound traffic and Allow instances associated with this security group to talk to each other
- C. Allow no inbound traffic, Allow all outbound traffic and Does NOT allow instances associated with this security group to talk to each other
- D. Allow all inbound traffic, Allow all outbound traffic and Does NOT allow instances associated with this security group to talk to each other

Answer: A

NEW QUESTION 257

A customer is deploying an SSL enabled web application to AWS and would like to implement a separation of roles between the EC2 service administrators that are entitled to login to instances as well as making API calls and the security officers who will maintain and have exclusive access to the application's X.509 certificate that contains the private key.

- A. Upload the certificate on an S3 bucket owned by the security officers and accessible only by EC2 Role of the web servers.
- B. Configure the web servers to retrieve the certificate upon boot from an CloudHSM is managed by the security officers.
- C. Configure system permissions on the web servers to restrict access to the certificate only to the authority security officers
- D. Configure IAM policies authorizing access to the certificate store only to the security officers and terminate SSL on an ELB.

Answer: D

NEW QUESTION 262

A web company is looking to implement an intrusion detection and prevention system into their deployed VPC. This platform should have the ability to scale to thousands of instances running inside of the VPC. How should they architect their solution to achieve these goals?

- A. Configure an instance with monitoring software and the elastic network interface (ENI) set to promiscuous mode packet sniffing to see an traffic across the VPC.
- B. Create a second VPC and route all traffic from the primary application VPC through the second VPC where the scalable virtualized IDS/IPS platform resides.
- C. Configure sewers running in the VPC using the host-based 'route' commands to send all traffic through the platform to a scalable virtualized IDS/IPS.
- D. Configure each host with an agent that collects all network traffic and sends that traffic to the IDS/IPS platform for inspection.

Answer: C

NEW QUESTION 263

You've been hired to enhance the overall security posture for a very large e-commerce site They have a well architected multi-tier application running in a VPC that uses ELBs in front of both the web and the app tier with static assets served directly from S3 They are using a combination of RDS and DynamoDB for their dynamic data and then archMng nightly into S3 for further processing with EMR They are concerned because they found questionable log entries and suspect someone is attempting to gain unauthorized access.

Which approach provides a cost effective scalable mitigation to this kind of attack?

- A. Recommend that they lease space at a DirectConnect partner location and establish a 1G DirectConnect connection to their VPC they would then establish Internet connectMty into their space, filter the traffic in hardware Web Application Firewall (WAF). And then pass the traffic through the DirectConnect connection into their application running in their VPC.
- B. Add previously identified hostile source IPs as an explicit INBOUND DENY NACL to the web tier subnet
- C. Add a WAF tier by creating a new ELB and an AutoScaling group of EC2 Instances running ahost-based WAF They would redirect Route 53 to resolve to the new WAF tier ELB The WAF tier would their pass the traffic to the current web tier The web tier Security Groups would be updated to only allow traffic from the WAF tier Security Group
- D. Remove all but TLS 1.2 from the web tier ELB and enable Advanced Protocol Filtering This will enable the ELB itself to perform WAF functionality.

Answer: C

NEW QUESTION 266

Your company is in the process of developing a next generation pet collar that collects biometric information to assist families with promoting healthy lifestyles for their pets Each collar will push 30kb of biometric data In JSON format every 2 seconds to a collection platform that will process and analyze the data providing health trending information back to the pet owners and veterinarians via a web portal Nmanagement has tasked you to architect the collection platform ensuring the following requirements are met.

Provide the ability for real-time analytics of the inbound biometric data Ensure processing of the biometric data is highly durable. Elastic and parallel The results of the analytic processing should be persisted for data mining

Which architecture outlined below win meet the initial requirements for the collection platform?

- A. Utilize S3 to collect the inbound sensor data analyze the data from S3 with a daily scheduled Data Pipeline and save the results to a Redshift Cluster.
- B. Utilize Amazon Kinesis to collect the inbound sensor data, analyze the data with Kinesis clients and save the results to a Redshift cluster using EMR.
- C. Utilize SQS to collect the inbound sensor data analyze the data from SQS with Amazon Kinesis and save the results to a Microsoft SQL Server RDS instance.
- D. Utilize EMR to collect the inbound sensor data, analyze the data from EUR with Amazon Kinesis and save me results to DynamoDB.

Answer: B

NEW QUESTION 268

Your team has a tomcat-based Java application you need to deploy into development, test and production environments. After some research, you opt to use Elastic Beanstalk due to its tight integration with your developer tools and RDS due to its ease of management. Your QA team lead points out that you need to roll a sanitized set of production data into your environment on a nightly basis.

Similarly, other software teams in your org want access to that same restored data via their EC2 instances in your VPC. The optimal setup for persistence and security that meets the above requirements would be the following.

- A. Create your RDS instance as part of your Elastic Beanstalk definition and alter its security group to allow access to it from hosts in your application subnets.
- B. Create your RDS instance separately and add its IP address to your application's DB connection strings in your code. Alter its security group to allow access to it from hosts within your VPC's IP address block.
- C. Create your RDS instance separately and pass its DNS name to your app's DB connection string as an environment variable.
- D. Create a security group for client machines and add it as a valid source for DB traffic to the security group of the RDS instance itself.
- E. Create your RDS instance separately and pass its DNS name to your app's DB connection string as an environment variable. Alter its security group to allow access to it from hosts in your application subnets.

Answer: A

NEW QUESTION 273

Your company has an on-premises multi-tier PHP web application, which recently experienced downtime due to a large burst in web traffic due to a company announcement. Over the coming days, you are expecting similar announcements to drive similar unpredictable bursts, and are looking to find ways to quickly improve your infrastructure's ability to handle unexpected increases in traffic.

The application currently consists of 2 tiers: a web tier which consists of a load balancer and several Linux Apache web servers, as well as a database tier which hosts a Linux server hosting a MySQL database. Which scenario below will provide full site functionality, while helping to improve the ability of your application in the short timeframe required?

- A. Failover environment: Create an S3 bucket and configure it for website hosting.
- B. Migrate your DNS to Route53 using zone file import, and leverage Route53 DNS failover to failover to the S3 hosted website.
- C. Hybrid environment: Create an AMI, which can be used to launch web servers in EC2. Create an Auto Scaling group, which uses the AMI to scale the web tier based on incoming traffic.
- D. Leverage Elastic Load Balancing to balance traffic between on-premises web servers and those hosted in AWS.
- E. Offload traffic from on-premises environment: Setup a CloudFront distribution, and configure CloudFront to cache objects from a custom origin.
- F. Choose to customize your object cache behavior, and select a TTL that objects should exist in cache.
- G. Migrate to AWS: Use VM Import/Export to quickly convert an on-premises web server to an AMI.
- H. Create an Auto Scaling group, which uses the imported AMI to scale the web tier based on incoming traffic.
- I. Create an RDS read replica and setup replication between the RDS instance and on-premises MySQL server to migrate the database.

Answer: C

NEW QUESTION 275

An ERP application is deployed across multiple AZs in a single region. In the event of failure, the Recovery Time Objective (RTO) must be less than 3 hours, and the Recovery Point Objective (RPO) must be 15 minutes. The customer realizes that data corruption occurred roughly 1.5 hours ago.

What DR strategy could be used to achieve this RTO and RPO in the event of this kind of failure?

- A. Take hourly DB backups to S3, with transaction logs stored in S3 every 5 minutes.
- B. Use synchronous database master-slave replication between two availability zones.
- C. Take hourly DB backups to EC2 Instance Store volumes with transaction logs stored in S3 every 5 minutes.
- D. Take 15 minute DB backups stored in Glacier with transaction logs stored in S3 every 5 minutes.

Answer: A

NEW QUESTION 280

You are designing the network infrastructure for an application server in Amazon VPC. Users will access all application instances from the Internet, as well as from an on-premises network. The on-premises network is connected to your VPC over an AWS Direct Connect link. How would you design routing to meet the above requirements?

- A. Configure a single routing table with a default route via the Internet gateway.
- B. Propagate a default route via BGP on the AWS Direct Connect customer route.
- C. Associate the routing table with all VPC subnets.
- D. Configure a single routing table with a default route via the Internet gateway.
- E. Propagate specific routes for the on-premises networks via BGP on the AWS Direct Connect customer route.
- F. Associate the routing table with all VPC subnets.
- G. Configure a single routing table with two default routes: one to the Internet via an Internet gateway, the other to the on-premises network via the VPN gateway.
- H. Use this routing table across all subnets in the VPC.
- I. Configure two routing tables: one that has a default route via the Internet gateway, and another that has a default route via the VPN gateway.
- J. Associate both routing tables with each VPC subnet.

Answer: A

NEW QUESTION 284

What does elasticity mean to AWS?

- A. The ability to scale computing resources up easily, with minimal friction and down with latency.
- B. The ability to scale computing resources up and down easily, with minimal friction.
- C. The ability to provision cloud computing resources in expectation of future demand.
- D. The ability to recover from business continuity events with minimal friction.

Answer: B

NEW QUESTION 286

You have launched an EC2 instance with four (4) 500 GB EBS Provisioned IOPS volumes attached. The EC2 instance is EBS-Optimized and supports 500 Mbps throughput between EC2 and EBS. The four EBS volumes are configured as a single RAID 0 device, and each Provisioned IOPS volume is provisioned with 4,000 IOPS (4,000 16KB reads or writes), for a total of 16,000 random IOPS on the instance. The EC2 instance initially delivers the expected 16,000 IOPS random read

and write performance. Sometime later, in order to increase the total random I/O performance of the instance, you add an additional two 500 GB EBS Provisioned IOPS volumes to the RAID. Each volume is provisioned to 4,000 IOPS like the original four, for a total of 24,000 IOPS on the EC2 instance. Monitoring shows that the EC2 instance CPU utilization increased from 50% to 70%, but the total random IOPS measured at the instance level does not increase at all. What is the problem and a valid solution?

- A. The EBS-Optimized throughput limits the total IOPS that can be utilized; use an EBSOptimized instance that provides larger throughput.
- B. Small block sizes cause performance degradation, limiting the I/O throughput; configure the instance device driver and filesystem to use 64KB blocks to increase throughput.
- C. The standard EBS Instance root volume limits the total IOPS rate; change the instance root volume to also be a 500GB 4,000 Provisioned IOPS volume.
- D. Larger storage volumes support higher Provisioned IOPS rates; increase the provisioned volume storage of each of the 6 EBS volumes to 1TB.
- E. RAID 0 only scales linearly to about 4 devices; use RAID 0 with 4 EBS Provisioned IOPS volumes, but increase each Provisioned IOPS EBS volume to 6,000 IOPS.

Answer: C

NEW QUESTION 291

A newspaper organization has a on-premises application which allows the public to search its back catalogue and retrieve individual newspaper pages via a website written in Java. They have scanned the old newspapers into JPEGs (approx 17TB) and used Optical Character Recognition (OCR) to populate a commercial search product. The hosting platform and software are now end of life and the organization wants to migrate its archive to AWS and produce a cost efficient architecture and still be designed for availability and durability. Which is the most appropriate?

- A. Use S3 with reduced redundancy to store and serve the scanned files, install the commercial search application on EC2 Instances and configure with auto-scaling and an Elastic Load Balancer.
- B. Model the environment using CloudFormation use an EC2 instance running Apache webserver and an open source search application, stripe multiple standard EBS volumes together to store the JPEGs and search index.
- C. Use S3 with standard redundancy to store and serve the scanned files, use CloudSearch for query processing, and use Elastic Beanstalk to host the website across multiple availability zones.
- D. Use a single-AZ RDS MySQL instance to store the search index and the JPEG images use an EC2 instance to serve the website and translate user queries into SQL.
- E. Use a CloudFront download distribution to serve the JPEGs to the end users and install the current commercial search product, along with a Java Container on the website on EC2 instances and use Route53 with DNS round-robin.

Answer: C

NEW QUESTION 292

.....

Relate Links

100% Pass Your AWS-Certified-Solutions-Architect-Professional Exam with Examible Prep Materials

<https://www.exambible.com/AWS-Certified-Solutions-Architect-Professional-exam/>

Contact us

We are proud of our high-quality customer service, which serves you around the clock 24/7.

Viste - <https://www.exambible.com/>