

Exam Questions AWS-SysOps

AWS Certified SysOps Administrator Associate

<https://www.2passeasy.com/dumps/AWS-SysOps/>



NEW QUESTION 1

Your team is excited about the use of AWS because now they have access to programmable Infrastructure. You have been asked to manage your AWS infrastructure in a manner similar to the way you might manage application code. You want to be able to deploy exact copies of different versions of your infrastructure, stage changes into different environments, revert back to previous versions, and identify what versions are running at any particular time (development, test, QA, production).

Which approach addresses this requirement?

- A. Use cost allocation reports and AWS Opsworks to deploy and manage your infrastructure
- B. Use AWS CloudWatch metrics and alerts along with resource tagging to deploy and manage your infrastructure
- C. Use AWS Beanstalk and a version control system like GIT to deploy and manage your infrastructure
- D. Use AWS CloudFormation and a version control system like GIT to deploy and manage your infrastructure

Answer: B

Explanation: Reference:

<http://aws.amazon.com/opsworks/faqs/>

NEW QUESTION 2

A media company produces new video files on-premises every day with a total size of around 100GBs after compression. All files have a size of 1-2 GB and need to be uploaded to Amazon S3 every night in a fixed time window between 3am and 5am. Current upload takes almost 3 hours, although less than half of the available bandwidth is used.

What step(s) would ensure that the file uploads are able to complete in the allotted time window?

- A. Increase your network bandwidth to provide faster throughput to S3
- B. Upload the files in parallel to S3
- C. Pack all files into a single archive, upload it to S3, then extract the files in AWS
- D. Use AWS Import/Export to transfer the video files

Answer: B

Explanation: Reference:

<http://aws.amazon.com/importexport/faqs/>

NEW QUESTION 3

What would happen to an RDS (Relational Database Service) multi-Availability Zone deployment of the primary DB instance if it fails?

- A. The IP of the primary DB instance is switched to the standby DB instance
- B. The RDS (Relational Database Service) DB instance reboots
- C. A new DB instance is created in the standby availability zone
- D. The canonical name record (CNAME) is changed from primary to standby

Answer: D

NEW QUESTION 4

Your EC2-Based Multi-tier application includes a monitoring instance that periodically makes application-level read-only requests of various application components and if any of those fail more than three times in 30 seconds calls CloudWatch to fire an alarm, and the alarm notifies your operations team by email and SMS of a possible application health problem. However, you also need to watch the watcher - the monitoring instance itself - and be notified if it becomes unhealthy.

Which of the following is a simple way to achieve that goal?

- A. Run another monitoring instance that pings the monitoring instance and fires a CloudWatch alarm that notifies your operations team should the primary monitoring instance become unhealthy
- B. Set a CloudWatch alarm based on EC2 system and instance status checks and have the alarm notify your operations team of any detected problem with the monitoring instance
- C. Set a CloudWatch alarm based on the CPU utilization of the monitoring instance and have the alarm notify your operations team if the CPU usage exceeds 50% for more than one minute; then have your monitoring application go into a CPU-bound loop should it detect any application problem
- D. Have the monitoring instances post messages to an SQS queue and then dequeue those messages on another instance. Should the queue cease to have new messages, the second instance should first terminate the original monitoring instance, start another backup monitoring instance, and assume the role of the previous monitoring instance, beginning adding messages to the SQS queue

Answer: D

NEW QUESTION 5

How can the domain's zone apex for example "myzoneapexdomain.com" be pointed towards an Elastic Load Balancer?

- A. By using an AAAA record
- B. By using an A record
- C. By using an Amazon Route 53 CNAME record
- D. By using an Amazon Route 53 Alias record

Answer: D

Explanation: Reference:

<http://docs.aws.amazon.com/Route53/latest/DeveloperGuide/resource-record-sets-choosing-alias-non-alias.html>

NEW QUESTION 6

You are tasked with setting up a cluster of EC2 Instances for a NoSQL database. The database requires random read IO disk performance up to a 100,000 IOPS at 4KB block size per node.

Which of the following EC2 instances will perform the best for this workload?

- A. A High-Memory Quadruple Extra Large (m2.4xlarge) with EBS-Optimized set to true and a Provisioned IOPS EBS volume
- B. A Cluster Compute Eight Extra Large (cc2.8xlarge) using instance storage
- C. High I/O Quadruple Extra Large (hi1.4xlarge) using instance storage
- D. A Cluster GPU Quadruple Extra Large (cg1.4xlarge) using four separate 4000 PIOPS EBS volumes in a RAID 0 configuration

Answer: C

Explanation: Explanation: Reference:

<http://aws.amazon.com/ec2/instance-types/>

NEW QUESTION 7

When preparing for a compliance assessment of your system built inside of AWS, what are three best-practices for you to prepare for an audit? Choose 3 answers

- A. Gather evidence of your IT operational controls
- B. Request and obtain applicable third-party audited AWS compliance reports and certifications
- C. Request and obtain a compliance and security tour of an AWS data center for a pre-assessment security review
- D. Request and obtain approval from AWS to perform relevant network scans and in-depth penetration tests of your system's Instances and endpoints
- E. Schedule meetings with AWS's third-party auditors to provide evidence of AWS compliance that maps to your control objectives

Answer: ABD

NEW QUESTION 8

You use S3 to store critical data for your company. Several users within your group currently have full permissions to your S3 buckets. You need to come up with a solution that does not impact your users and also protect against the accidental deletion of objects.

Which two options will address this issue? Choose 2 answers

- A. Enable versioning on your S3 Buckets
- B. Configure your S3 Buckets with MFA delete
- C. Create a Bucket policy and only allow read only permissions to all users at the bucket level
- D. Enable object lifecycle policies and configure the data older than 3 months to be archived in Glacier

Answer: AB

NEW QUESTION 9

You have been asked to leverage Amazon VPC, EC2 and SQS to implement an application that submits and receives millions of messages per second to a message queue. You want to ensure your application has sufficient bandwidth between your EC2 instances and SQS. Which option will provide the most scalable solution for communicating between the application and SQS?

- A. Ensure the application instances are properly configured with an Elastic Load Balancer
- B. Ensure the application instances are launched in private subnets with the EBS-optimized option enabled
- C. Ensure the application instances are launched in public subnets with the `associate-public-ip-address=true` option enabled
- D. Launch application instances in private subnets with an Auto Scaling group and Auto Scaling triggers configured to watch the SQS queue size

Answer: B

Explanation: Reference:

<http://www.cardinalpath.com/autoscaling-your-website-with-amazon-web-services-part-2/>

NEW QUESTION 10

You have a web-style application with a stateless but CPU and memory-intensive web tier running on a cc2 8xlarge EC2 instance inside of a VPC. The instance when under load is having problems returning requests within the SLA as defined by your business. The application maintains its state in a DynamoDB table, but the data tier is properly provisioned and responses are consistently fast.

How can you best resolve the issue of the application responses not meeting your SLA?

- A. Add another cc2 8xlarge application instance, and put both behind an Elastic Load Balancer
- B. Move the cc2 8xlarge to the same Availability Zone as the DynamoDB table
- C. Cache the database responses in ElastiCache for more rapid access
- D. Move the database from DynamoDB to RDS MySQL in scale-out read-replica configuration

Answer: B

Explanation: Reference:

<http://aws.amazon.com/elasticmapreduce/faqs/>

NEW QUESTION 10

You need to design a VPC for a web-application consisting of an Elastic Load Balancer (ELB), a fleet of web/application servers, and an RDS database. The entire Infrastructure must be distributed over 2 availability zones.

Which VPC configuration works while assuring the database is not available from the Internet?

- A. One public subnet for ELB one public subnet for the web-servers, and one private subnet for the database
- B. One public subnet for ELB two private subnets for the web-servers, two private subnets for RDS
- C. Two public subnets for ELB two private subnets for the web-servers and two private subnets for RDS
- D. Two public subnets for ELB two public subnets for the web-servers, and two public subnets for RDS

Answer: A

NEW QUESTION 11

You have a server with a 500GB Amazon EBS data volume. The volume is 80% full. You need to back up the volume at regular intervals and be able to re-create the volume in a new Availability Zone in the shortest time possible. All applications using the volume can be paused for a period of a few minutes with no discernible user impact.

Which of the following backup methods will best fulfill your requirements?

- A. Take periodic snapshots of the EBS volume
- B. Use a third party Incremental backup application to back up to Amazon Glacier
- C. Periodically back up all data to a single compressed archive and archive to Amazon S3 using a parallelized multi-part upload
- D. Create another EBS volume in the second Availability Zone attach it to the Amazon EC2 instance, and use a disk manager to mirror the two disks

Answer: D

Explanation: Reference:

<http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-creating-snapshot.html>

NEW QUESTION 13

You have decided to change the Instance type for instances running in your application tier that are using Auto Scaling. In which area below would you change the instance type definition?

- A. Auto Scaling launch configuration
- B. Auto Scaling group
- C. Auto Scaling policy
- D. Auto Scaling tags

Answer: A

Explanation: Reference:

<http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/WhatIsAutoScaling.html>

NEW QUESTION 17

You are designing a system that has a Bastion host. This component needs to be highly available without human intervention. Which of the following approaches would you select?

- A. Run the bastion on two instances one in each AZ
- B. Run the bastion on an active Instance in one AZ and have an AMI ready to boot up in the event of failure
- C. Configure the bastion instance in an Auto Scaling group Specify the Auto Scaling group to include multiple AZs but have a min-size of 1 and max-size of 1
- D. Configure an ELB in front of the bastion instance

Answer: C

NEW QUESTION 19

When assessing an organization's use of AWS API access credentials which of the following three credentials should be evaluated? Choose 3 answers

- A. Key pairs
- B. Console passwords
- C. Access keys
- D. Signing certificates
- E. Security Group memberships

Answer: ACD

Explanation: Reference:

http://media.amazonwebservices.com/AWS_Operational_Checklists.pdf

NEW QUESTION 22

You run a web application where web servers on EC2 Instances are in an Auto Scaling group. Monitoring over the last 6 months shows that 6 web servers are necessary to handle the minimum load. During the day up to 12 servers are needed. Five to six days per year, the number of web servers required might go up to 15.

What would you recommend to minimize costs while being able to provide high availability?

- A. 6 Reserved instances (heavy utilization). 6 Reserved instances (medium utilization), rest covered by On-Demand instances
- B. 6 Reserved instances (heavy utilization). 6 On-Demand instances, rest covered by Spot Instances
- C. 6 Reserved instances (heavy utilization). 6 Spot instances, rest covered by On-Demand instances
- D. 6 Reserved instances (heavy utilization). 6 Reserved instances (medium utilization) rest covered by Spot instances

Answer: B

NEW QUESTION 26

You have a web application leveraging an Elastic Load Balancer (ELB) in front of the web servers deployed using an Auto Scaling Group. Your database is running on Relational

Database Service (RDS). The application serves out technical articles and responses to them. In general, there are more views of an article than there are responses to the article. On occasion, an article on the site becomes extremely popular, resulting in significant traffic increases that cause the site to go down.

What could you do to help alleviate the pressure on the infrastructure while maintaining availability during these events?

Choose 3 answers

- A. Leverage CloudFront for the delivery of the article
- B. Add RDS read-replicas for the read traffic going to your relational database
- C. Leverage ElastiCache for caching the most frequently used data
- D. Use SQS to queue up the requests for the technical posts and deliver them out of the queue
- E. Use Route53 health checks to fail over to an S3 bucket for an error page

Answer: ACE

NEW QUESTION 31

You are tasked with the migration of a highly trafficked Node.js application to AWS. In order to comply with organizational standards, Chef recipes must be used to configure the application servers that host this application and to support application lifecycle events.

Which deployment option meets these requirements while minimizing administrative burden?

- A. Create a new stack within Opsworks, add the appropriate layers to the stack, and deploy the application
- B. Create a new application within Elastic Beanstalk and deploy this application to a new environment
- C. Launch a Node.js server from a community AMI and manually deploy the application to the launched EC2 instance
- D. Launch and configure Chef Server on an EC2 instance and leverage the AWS CLI to launch application servers and configure those instances using Chef

Answer: B

Explanation: Reference:

<http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/using-features.deployment.html>

NEW QUESTION 34

What is a placement group?

- A. A collection of Auto Scaling groups in the same Region
- B. Feature that enables EC2 instances to interact with each other via high bandwidth, low latency connections
- C. A collection of Elastic Load Balancers in the same Region or Availability Zone
- D. A collection of authorized CloudFront edge locations for a distribution

Answer: B

Explanation: Reference:

<http://aws.amazon.com/ec2/faqs/>

NEW QUESTION 35

An application that you are managing has EC2 instances & DynamoDB tables deployed to several AWS Regions. In order to monitor the performance of the application globally, you would like to see two graphs: 1) Avg CPU Utilization across all EC2 instances and 2) Number of Throttled Requests for all DynamoDB tables.

How can you accomplish this?

- A. Tag your resources with the application name, and select the tag name as the dimension in the CloudWatch Management console to view the respective graphs
- B. Use the CloudWatch CLI tools to pull the respective metrics from each regional endpoint. Aggregate the data offline & store it for graphing in CloudWatch
- C. Add SNMP traps to each instance and DynamoDB table. Leverage a central monitoring server to capture data from each instance and table. Put the aggregate data into CloudWatch for graphing
- D. Add a CloudWatch agent to each instance and attach one to each DynamoDB table
- E. When configuring the agent, set the appropriate application name & view the graphs in CloudWatch

Answer: C

NEW QUESTION 36

You are currently hosting multiple applications in a VPC and have logged numerous port scans coming in from a specific IP address block. Your security team has requested that all access from the offending IP address block be denied for the next 24 hours.

Which of the following is the best method to quickly and temporarily deny access from the specified IP address block?

- A. Create an IAM policy to modify Windows Firewall settings on all hosts in the VPC to deny access from the IP address block
- B. Modify the Network ACLs associated with all public subnets in the VPC to deny access from the IP address block
- C. Add a rule to all of the VPC's Security Groups to deny access from the IP address block
- D. Modify the Windows Firewall settings on all Amazon Machine Images (AMIs) that your organization uses in that VPC to deny access from the IP address block

Answer: B

Explanation: Reference:

http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_SecurityGroups.html

NEW QUESTION 38

Which of the following requires a custom CloudWatch metric to monitor?

- A. Data transfer of an EC2 instance
- B. Disk usage activity of an EC2 instance
- C. Memory Utilization of an EC2 instance
- D. CPU Utilization of an EC2 instance

Answer: C

Explanation: Reference:
<http://aws.amazon.com/cloudwatch/>

NEW QUESTION 39

When an EC2 EBS-backed (EBS root) instance is stopped, what happens to the data on any ephemeral store volumes?

- A. Data will be deleted and will no longer be accessible
- B. Data is automatically saved in an EBS volume
- C. Data is automatically saved as an EBS snapshot
- D. Data is unavailable until the instance is restarted

Answer: D

NEW QUESTION 42

The majority of your Infrastructure is on premises and you have a small footprint on AWS. Your company has decided to roll out a new application that is heavily dependent on low latency connectivity to LDAP for authentication. Your security policy requires minimal changes to the company's existing application user management processes.

What option would you implement to successfully launch this application?

- A. Create a second, independent LDAP server in AWS for your application to use for authentication
- B. Establish a VPN connection so your applications can authenticate against your existing on-premises LDAP servers
- C. Establish a VPN connection between your data center and AWS, create a LDAP replica on AWS and configure your application to use the LDAP replica for authentication
- D. Create a second LDAP domain on AWS, establish a VPN connection to establish a trust relationship between your new and existing domains and use the new domain for authentication

Answer: D

Explanation: Reference:
<http://msdn.microsoft.com/en-us/library/azure/jj156090.aspx>

NEW QUESTION 46

Your organization's security policy requires that all privileged users either use frequently rotated passwords or one-time access credentials in addition to username/password.

Which two of the following options would allow an organization to enforce this policy for AWS users?

Choose 2 answers

- A. Configure multi-factor authentication for privileged IAM users
- B. Create IAM users for privileged accounts
- C. Implement identity federation between your organization's Identity provider leveraging the IAM Security Token Service
- D. Enable the IAM single-use password policy option for privileged users

Answer: CD

NEW QUESTION 51

Your application currently leverages AWS Auto Scaling to grow and shrink as load increases/decreases and has been performing well. Your marketing team expects a steady ramp up in traffic to follow an upcoming campaign that will result in a 20x growth in traffic over 4 weeks. Your forecast for the approximate number of Amazon EC2 instances necessary to meet the peak demand is 175.

What should you do to avoid potential service disruptions during the ramp up in traffic?

- A. Ensure that you have pre-allocated 175 Elastic IP addresses so that each server will be able to obtain one as it launches
- B. Check the service limits in Trusted Advisor and adjust as necessary so the forecasted count remains within limit
- C. Change your Auto Scaling configuration to set a desired capacity of 175 prior to the launch of the marketing campaign
- D. Pre-warm your Elastic Load Balancer to match the requests per second anticipated during peak demand prior to the marketing campaign

Answer: D

NEW QUESTION 53

Which of the following are characteristics of Amazon VPC subnets?

Choose 2 answers

- A. Each subnet maps to a single Availability Zone
- B. A CIDR block mask of /25 is the smallest range supported

- C. Instances in a private subnet can communicate with the internet only if they have an Elastic IP
- D. By default, all subnets can route between each other, whether they are private or public
- E. V Each subnet spans at least 2 Availability zones to provide a high-availability environment

Answer: CE

NEW QUESTION 56

You are creating an Auto Scaling group whose Instances need to insert a custom metric into CloudWatch. Which method would be the best way to authenticate your CloudWatch PUT request?

- A. Create an IAM role with the Put MetricData permission and modify the Auto Scaling launch configuration to launch instances in that role
- B. Create an IAM user with the PutMetricData permission and modify the Auto Scaling launch configuration to inject the userscredentials into the instance User Data
- C. Modify the appropriate Cloud Watch metric policies to allow the Put MetricData permission to instances from the Auto Scaling group
- D. Create an IAM user with the PutMetricData permission and put the credentials in a private repository and have applications on the server pull the credentials as needed

Answer: A

NEW QUESTION 58

You have an Auto Scaling group associated with an Elastic Load Balancer (ELB). You have noticed that instances launched via the Auto Scaling group are being marked unhealthy due to an ELB health check, but these unhealthy instances are not being terminated. What do you need to do to ensure instances marked unhealthy by the ELB will be terminated and replaced?

- A. Change the thresholds set on the Auto Scaling group health check
- B. Add an Elastic Load Balancing health check to your Auto Scaling group
- C. Increase the value for the Health check interval set on the Elastic Load Balancer
- D. Change the health check set on the Elastic Load Balancer to use TCP rather than HTTP checks

Answer: B

Explanation: Reference:

<http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/as-add-elb-healthcheck.html>

Add an Elastic Load Balancing Health Check to your Auto Scaling Group

By default, an Auto Scaling group periodically reviews the results of EC2 instance status to determine the health state of each instance. However, if you have associated your Auto Scaling group with an Elastic Load Balancing load balancer, you can choose to use the Elastic Load Balancing health check. In this case, Auto Scaling determines the health status of your instances by checking the results of both the EC2 instance status check and the Elastic Load Balancing instance health check.

For information about EC2 instance status checks, see *Monitor Instances With Status Checks* in the *Amazon EC2 User Guide for Linux Instances*. For information about Elastic Load Balancing health checks, see *Health Check* in the *Elastic Load Balancing Developer Guide*.

This topic shows you how to add an Elastic Load Balancing health check to your Auto Scaling group, assuming that you have created a load balancer and have registered the load balancer with your Auto Scaling group. If you have not registered the load balancer with your Auto Scaling group, see *Set Up a Scaled and Load-Balanced Application*.

Auto Scaling marks an instance unhealthy if the calls to the Amazon EC2 action `DescribeInstanceStatus` return any state other than `running`, the system status shows `impaired`, or the calls to Elastic Load Balancing action `DescribeInstanceHealth` returns `OutOfService` in the instance state field.

If there are multiple load balancers associated with your Auto Scaling group, Auto Scaling checks the health state of your EC2 instances by making health check calls to each load balancer. For each call, if the Elastic Load Balancing action returns any state other than `InService`, the instance is marked as unhealthy. After Auto Scaling marks an instance as unhealthy, it remains in that state, even if subsequent calls from other load balancers return an `InService` state for the same instance.

NEW QUESTION 59

Your company is moving towards tracking web page users with a small tracking

image loaded on each page. Currently you are serving this image out of US-East, but are starting to get concerned about the time it takes to load the image for users on the west coast.

What are the two best ways to speed up serving this image?

Choose 2 answers

- A. Use Route 53's Latency Based Routing and serve the image out of US-West-2 as well as US-East-1
- B. Serve the image out through CloudFront
- C. Serve the image out of S3 so that it isn't being served out of your web application tier
- D. Use EBS PIOPs to serve the image faster out of your EC2 instances

Answer: AD

NEW QUESTION 63

You receive a frantic call from a new DBA who accidentally dropped a table containing all your customers.

Which Amazon RDS feature will allow you to reliably restore your database to within 5 minutes of when the mistake was made?

- A. Multi-AZ RDS
- B. RDS snapshots
- C. RDS read replicas
- D. RDS automated backup

Answer: D

Explanation: Reference:

<http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Overview.BackingUpAndRestoringAmazonRDSInstances.html>

NEW QUESTION 66

You have started a new job and are reviewing your company's infrastructure on AWS. You notice one web application where they have an Elastic Load Balancer (ELB) in front of web instances in an Auto Scaling Group. When you check the metrics for the ELB in CloudWatch, you see four healthy instances in Availability Zone (AZ) A and zero in AZ B. There are zero unhealthy instances. What do you need to fix to balance the instances across AZs?

- A. Set the ELB to only be attached to another AZ
- B. Make sure Auto Scaling is configured to launch in both AZs
- C. Make sure your AMI is available in both AZs
- D. Make sure the maximum size of the Auto Scaling Group is greater than 4

Answer: B

NEW QUESTION 70

You have identified network throughput as a bottleneck on your m1.small EC2 instance when uploading data into Amazon S3 in the same region. How do you remedy this situation?

- A. Add an additional ENI
- B. Change to a larger instance
- C. Use DirectConnect between EC2 and S3
- D. Use EBS PIOPS on the local volume

Answer: B

Explanation: Reference:

https://media.amazonwebservices.com/AWS_Amazon_EMR_Best_Practices.pdf

NEW QUESTION 74

You are using ElastiCache Memcached to store session state and cache database queries in your infrastructure. You notice in CloudWatch that Evictions and GetMisses are both very high.

What two actions could you take to rectify this?
Choose 2 answers

- A. Increase the number of nodes in your cluster
- B. Tweak the max_item_size parameter
- C. Shrink the number of nodes in your cluster
- D. Increase the size of the nodes in the cluster

Answer: BD

NEW QUESTION 78

An organization's security policy requires multiple copies of all critical data to be replicated across at least a primary and backup data center. The organization has decided to store some critical data on Amazon S3.

Which option should you implement to ensure this requirement is met?

- A. Use the S3 copy API to replicate data between two S3 buckets in different regions
- B. You do not need to implement anything since S3 data is automatically replicated between regions
- C. Use the S3 copy API to replicate data between two S3 buckets in different facilities within an AWS Region
- D. You do not need to implement anything since S3 data is automatically replicated between multiple facilities within an AWS Region

Answer: D

NEW QUESTION 80

Which services allow the customer to retain full administrative privileges of the underlying EC2 instances?

Choose 2 answers

- A. Amazon Elastic Map Reduce
- B. Elastic Load Balancing
- C. AWS Elastic Beanstalk
- D. Amazon ElastiCache
- E. Amazon Relational Database service

Answer: AC

NEW QUESTION 81

You have been asked to propose a multi-region deployment of a web-facing application where a controlled portion of your traffic is being processed by an alternate region.

Which configuration would achieve that goal?

- A. Route53 record sets with weighted routing policy
- B. Route53 record sets with latency based routing policy
- C. Auto Scaling with scheduled scaling actions set
- D. Elastic Load Balancing with health checks enabled

Answer: D

Explanation: Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/TerminologyandKeyConcepts.html>

NEW QUESTION 83

When attached to an Amazon VPC which two components provide connectivity with external networks? Choose 2 answers

- A. Elastic IPS (EIP)
- B. NAT Gateway (NAT)
- C. Internet Gateway (IGW)
- D. Virtual Private Gateway (VGW)

Answer: CD

NEW QUESTION 88

You are attempting to connect to an instance in Amazon VPC without success. You have already verified that the VPC has an Internet Gateway (IGW), the instance has an associated Elastic IP (EIP), and correct security group rules are in place.

Which VPC component should you evaluate next?

- A. The configuration of a NAT instance
- B. The configuration of the Routing Table
- C. The configuration of the Internet Gateway (IGW)
- D. The configuration of SRC/DST checking

Answer: B

Explanation: Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/UserScenariosForVPC.html>

NEW QUESTION 90

You have been asked to automate many routine systems administrator backup and recovery activities. Your current plan is to leverage AWS-managed solutions as much as possible and automate the rest with the AWS CLI and scripts.

Which task would be best accomplished with a script?

- A. Creating daily EBS snapshots with a monthly rotation of snapshots
- B. Creating daily RDS snapshots with a monthly rotation of snapshots
- C. Automatically detect and stop unused or underutilized EC2 instances
- D. Automatically add Auto Scaled EC2 instances to an Amazon Elastic Load Balancer

Answer: A

NEW QUESTION 94

What are characteristics of Amazon S3? Choose 2 answers

- A. Objects are directly accessible via a URL
- B. S3 should be used to host a relational database
- C. S3 allows you to store objects of virtually unlimited size
- D. S3 allows you to store virtually unlimited amounts of data
- E. S3 offers Provisioned IOPS

Answer: AD

NEW QUESTION 96

You have a Linux EC2 web server instance running inside a VPC. The instance is in a public subnet and has an EIP associated with it so you can connect to it over the Internet via HTTP or SSH. The instance was also fully accessible when you last logged in via SSH, and was also serving web requests on port 80.

Now you are not able to SSH into the host nor does it respond to web requests on port 80 that were working fine last time you checked. You have double-checked that all networking configuration parameters (security groups, route tables, IGW, EIP, NACLs, etc) are properly configured (and you haven't made any changes to those anyway since you were last able to reach the instance). You look at the EC2 console and notice that system status check shows "impaired."

Which should be your next step in troubleshooting and attempting to get the instance back to a healthy state so that you can log in again?

- A. Stop and start the instance so that it will be able to be redeployed on a healthy host system that most likely will fix the "impaired" system status
- B. Reboot your instance so that the operating system will have a chance to boot in a clean healthy state that most likely will fix the "impaired" system status
- C. Add another dynamic private IP address to the instance and try to connect via that new path, since the networking stack of the OS may be locked up causing the "impaired" system status
- D. Add another Elastic Network Interface to the instance and try to connect via that new path since the networking stack of the OS may be locked up causing the "impaired" system status
- E. un-map and then re-map the EIP to the instance, since the IGW/VNAT gateway may not be working properly, causing the "impaired" system status

Answer: A

Explanation: Topic 2, Volume B

NEW QUESTION 101

A user is accessing RDS from an application. The user has enabled the Multi-AZ feature with the MS SQL RDS DB. During a planned outage, how will AWS ensure that a switch from DB to a standby replica will not affect access to the application?

- A. RDS will have an internal IP which will redirect all requests to the new DB
- B. RDS uses DNS to switch over to stand by replica for seamless transition
- C. The switch over changes Hardware so RDS does not need to worry about access
- D. RDS will have both the DBs running independently and the user has to manually switch over

Answer: B

Explanation:

In the event of a planned or unplanned outage of a DB instance, Amazon RDS automatically switches to a standby replica in another Availability Zone if the user has enabled Multi AZ. The automatic failover mechanism simply changes the DNS record of the DB instance to point to the standby DB instance. As a result, the user will need to re-establish any existing connections to the DB instance. However, as the DNS is the same, the application can access DB seamlessly.

NEW QUESTION 104

A user is trying to understand the ACL and policy for an S3 bucket. Which of the below mentioned policy permissions is equivalent to the WRITE ACL on a bucket?

- A. s3:GetObjectAcl
- B. s3:GetObjectVersion
- C. s3:ListBucketVersions
- D. s3:DeleteObject

Answer: D

Explanation:

Amazon S3 provides a set of operations to work with the Amazon S3 resources. Each AWS S3 bucket can have an ACL (Access Control List. or bucket policy associated with it. The WRITE ACL list allows the other AWS accounts to write/modify to that bucket. The equivalent S3 bucket policy permission for it is s3:DeleteObject.

NEW QUESTION 109

A user is trying to connect to a running EC2 instance using SSH. However, the user gets a connection time out error. Which of the below mentioned options is not a possible reason for rejection?

- A. The access key to connect to the instance is wrong
- B. The security group is not configured properly
- C. The private key used to launch the instance is not correct
- D. The instance CPU is heavily loaded

Answer: A

Explanation:

If the user is trying to connect to a Linux EC2 instance and receives the connection time out error the probable reasons are: Security group is not configured with the SSH port The private key pair is not right The user name to login is wrong The instance CPU is heavily loaded, so it does not allow more connections

NEW QUESTION 110

A user is planning to use AWS Cloudformation. Which of the below mentioned functionalities does not help him to correctly understand Cloudformation?

- A. Cloudformation follows the DevOps model for the creation of Dev & Test
- B. AWS Cloudformation does not charge the user for its service but only charges for the AWS resources created with it
- C. Cloudformation works with a wide variety of AWS services, such as EC2, EBS, VPC, IAM, S3, RDS, ELB, etc
- D. CloudFormation provides a set of application bootstrapping scripts which enables the user to install Software

Answer: A

Explanation:

AWS Cloudformation is an application management tool which provides application modelling, deployment, configuration, management and related activities. It supports a wide variety of AWS services, such as EC2, EBS, AS, ELB, RDS, VPC, etc. It also provides application bootstrapping scripts which enable the user to install software packages or create folders. It is free of the cost and only charges the user for the services created with it. The only challenge is that it does not follow any model, such as DevOps; instead customers can define templates and use them to provision and manage the AWS resources in an orderly way.

NEW QUESTION 112

A user wants to disable connection draining on an existing ELB. Which of the below mentioned statements helps the user disable connection draining on the ELB?

- A. The user can only disable connection draining from CLI
- B. It is not possible to disable the connection draining feature once enabled
- C. The user can disable the connection draining feature from EC2 -> ELB console or from CLI
- D. The user needs to stop all instances before disabling connection draining

Answer: C

Explanation:

The Elastic Load Balancer connection draining feature causes the load balancer to stop sending new requests to the back-end instances when the instances are deregistering or become unhealthy, while ensuring that inflight requests continue to be served. The user can enable or disable connection draining from the AWS EC2 console -> ELB or using CLI.

NEW QUESTION 117

You are managing the AWS account of a big organization. The organization has more than 1000+ employees and they want to provide access to the various services to most of the employees. Which of the below mentioned options is the best possible solution in this case?

- A. The user should create a separate IAM user for each employee and provide access to them as per the policy
- B. The user should create an IAM role and attach STS with the rol
- C. The user should attach that role to the EC2 instance and setup AWS authentication on that server
- D. The user should create IAM groups as per the organization's departments and add each user to the group for better access control
- E. Attach an IAM role with the organization's authentication service to authorize each user for various AWS services

Answer: D

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. The user is managing an AWS account for an organization that already has an identity system, such as the login system for the corporate network (SSO.. In this case, instead of creating individual IAM users or groups for each user who need AWS access, it may be more practical to use a proxy server to translate the user identities from the organization network into the temporary AWS security credentials. This proxy server will attach an IAM role to the user after authentication.

NEW QUESTION 121

A user has created a VPC with CIDR 20.0.0.0/16 using the wizard. The user has created a public subnet CIDR (20.0.0.0/24. and VPN only subnets CIDR (20.0.1.0/24. along with the VPN gateway (vgw-12345. to connect to the user's data centre. Which of the below mentioned options is a valid entry for the main route table in this scenario?

- A. Destination: 20.0.0.0/24 and Target: vgw-12345
- B. Destination: 20.0.0.0/16 and Target: ALL
- C. Destination: 20.0.1.0/16 and Target: vgw-12345
- D. Destination: 0.0.0.0/0 and Target: vgw-12345

Answer: D

Explanation:

The user can create subnets as per the requirement within a VPC. If the user wants to connect VPC from his own data centre, he can setup a public and VPN only subnet which uses hardware VPN access to connect with his data centre. When the user has configured this setup with Wizard, it will create a virtual private gateway to route all traffic of the VPN subnet. Here are the valid entries for the main route table in this scenario: Destination: 0.0.0.0/0 & Target: vgw-12345 (To route all internet traffic to the VPN gateway. Destination: 20.0.0.0/16 & Target: local (To allow local routing in VPC.

NEW QUESTION 125

A user has configured an Auto Scaling group with ELB. The user has enabled detailed CloudWatch monitoring on Auto Scaling. Which of the below mentioned statements will help the user understand the functionality better?

- A. It is not possible to setup detailed monitoring for Auto Scaling
- B. In this case, Auto Scaling will send data every minute and will charge the user extra
- C. Detailed monitoring will send data every minute without additional charges
- D. Auto Scaling sends data every minute only and does not charge the user

Answer: B

Explanation:

CloudWatch is used to monitor AWS as well as the custom services. It provides either basic or detailed monitoring for the supported AWS products. In basic monitoring, a service sends data points to CloudWatch every five minutes, while in detailed monitoring a service sends data points to CloudWatch every minute. Auto Scaling includes 7 metrics and 1 dimension, and sends data to CloudWatch every 5 minutes by default. The user can enable detailed monitoring for Auto Scaling, which sends data to CloudWatch every minute. However, this will have some extra-costs.

NEW QUESTION 129

An organization is generating digital policy files which are required by the admins for verification. Once the files are verified they may not be required in the future unless there is some compliance issue. If the organization wants to save them in a cost effective way, which is the best possible solution?

- A. AWS RRS
- B. AWS S3
- C. AWS RDS
- D. AWS Glacier

Answer: D

Explanation:

Amazon S3 stores objects according to their storage class. There are three major storage classes: Standard, Reduced Redundancy and Glacier. Standard is for AWS S3 and provides very high durability. However, the costs are a little higher. Reduced redundancy is for less critical files. Glacier is for archival and the files which are accessed infrequently. It is an extremely low-cost storage service that provides secure and durable storage for data archiving and backup.

NEW QUESTION 133

A user has created a VPC with CIDR 20.0.0.0/16 with only a private subnet and VPN connection using the VPC wizard. The user wants to connect to the instance in a private subnet over SSH. How should the user define the security rule for SSH?

- A. Allow Inbound traffic on port 22 from the user's network

- B. The user has to create an instance in EC2 Classic with an elastic IP and configure the security group of a private subnet to allow SSH from that elastic IP
- C. The user can connect to a instance in a private subnet using the NAT instance
- D. Allow Inbound traffic on port 80 and 22 to allow the user to connect to a private subnet over the Internet

Answer: A

Explanation:

The user can create subnets as per the requirement within a VPC. If the user wants to connect VPC from his own data centre, the user can setup a case with a VPN only subnet (private. which uses VPN access to connect with his data centre. When the user has configured this setup with Wizard, all network connections to the instances in the subnet will come from his data centre. The user has to configure the security group of the private subnet which allows the inbound traffic on SSH (port 22. from the data centre's network range.

NEW QUESTION 136

A system admin is managing buckets, objects and folders with AWS S3. Which of the below mentioned statements is true and should be taken in consideration by the sysadmin?

- A. The folders support only ACL
- B. Both the object and bucket can have an Access Policy but folder cannot have policy
- C. Folders can have a policy
- D. Both the object and bucket can have ACL but folders cannot have ACL

Answer: A

Explanation:

A sysadmin can grant permission to the S3 objects or the buckets to any user or make objects public using the bucket policy and user policy. Both use the JSON-based access policy language. Generally if user is defining the ACL on the bucket, the objects in the bucket do not inherit it and vice a versa. The bucket policy can be defined at the bucket level which allows the objects as well as the bucket to be public with a single policy applied to that bucket. It cannot be applied at the object level. The folders are similar to objects with no content. Thus, folders can have only ACL and cannot have a policy.

NEW QUESTION 139

A user has developed an application which is required to send the data to a NoSQL database. The user wants to decouple the data sending such that the application keeps processing and sending data but does not wait for an acknowledgement of DB. Which of the below mentioned applications helps in this scenario?

- A. AWS Simple Notification Service
- B. AWS Simple Workflow
- C. AWS Simple Queue Service
- D. AWS Simple Query Service

Answer: C

Explanation:

Amazon Simple Queue Service (SQS. is a fast, reliable, scalable, and fully managed message queuing service. SQS provides a simple and cost-effective way to decouple the components of an application. In this case, the user can use AWS SQS to send messages which are received from an application and sent to DB. The application can continue processing data without waiting for any acknowledgement from DB. The user can use SQS to transmit any volume of data without losing messages or requiring other services to always be available.

NEW QUESTION 142

A sys admin is maintaining an application on AWS. The application is installed on EC2 and user has configured ELB and Auto Scaling. Considering future load increase, the user is planning to launch new servers proactively so that they get registered with ELB. How can the user add these instances with Auto Scaling?

- A. Increase the desired capacity of the Auto Scaling group
- B. Increase the maximum limit of the Auto Scaling group
- C. Launch an instance manually and register it with ELB on the fly
- D. Decrease the minimum limit of the Auto Scaling grou

Answer: A

Explanation:

A user can increase the desired capacity of the Auto Scaling group and Auto Scaling will launch a new instance as per the new capacity. The newly launched instances will be registered with ELB if Auto Scaling group is configured with ELB. If the user decreases the minimum size the instances will be removed from Auto Scaling. Increasing the maximum size will not add instances but only set the maximum instance cap.

NEW QUESTION 147

An admin is planning to monitor the ELB. Which of the below mentioned services does not help the admin capture the monitoring information about the ELB activity?

- A. ELB Access logs
- B. ELB health check
- C. CloudWatch metrics
- D. ELB API calls with CloudTrail

Answer: B

Explanation:

The admin can capture information about Elastic Load Balancer using either: CloudWatch Metrics ELB Logs files which are stored in the S3 bucket CloudTrail with API calls which can notify the user as well generate logs for each API calls The health check is internally performed by ELB and does not help the admin get the ELB activity.

NEW QUESTION 149

An organization has created 5 IAM users. The organization wants to give them the same login ID but different passwords. How can the organization achieve this?

- A. The organization should create a separate login ID but give the IAM users the same alias so that each one can login with their alias
- B. The organization should create each user in a separate region so that they have their own URL to login
- C. It is not possible to have the same login ID for multiple IAM users of the same account
- D. The organization should create various groups and add each user with the same login ID to different group
- E. The user can login with their own group ID

Answer: C

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. Whenever the organization is creating an IAM user, there should be a unique ID for each user. It is not possible to have the same login ID for multiple users. The names of users, groups, roles, instance profiles must be alphanumeric, including the following common characters: plus (+), equal (=), comma (,), period (.), at (@), and dash (-).

NEW QUESTION 152

A sys admin has created the below mentioned policy and applied to an S3 object named aws.jpg. The aws.jpg is inside a bucket named cloudacademy. What does this policy define?

```
"Statement": [{
  "Sid": "Stmnt1388811069831",
  "Effect": "Allow",
  "Principal": { "AWS": "*" },
  "Action": [ "s3:GetObjectAcl", "s3:ListBucket", "s3:GetObject" ],
  "Resource": [ "arn:aws:s3:::cloudacademy/* .jpg" ]
}]
```

- A. It is not possible to define a policy at the object level
- B. It will make all the objects of the bucket cloudacademy as public
- C. It will make the bucket cloudacademy as public
- D. the aws.jpg object as public

Answer: A

Explanation:

A system admin can grant permission to the S3 objects or buckets to any user or make objects public using the bucket policy and user policy. Both use the JSON-based access policy language. Generally if the user is defining the ACL on the bucket, the objects in the bucket do not inherit it and vice versa. The bucket policy can be defined at the bucket level which allows the objects as well as the bucket to be public with a single policy applied to that bucket. It cannot be applied at the object level.

NEW QUESTION 156

A user is planning to evaluate AWS for their internal use. The user does not want to incur any charge on his account during the evaluation. Which of the below mentioned AWS services would incur a charge if used?

- A. AWS S3 with 1 GB of storage
- B. AWS micro instance running 24 hours daily
- C. AWS ELB running 24 hours a day
- D. AWS PIOPS volume of 10 GB size

Answer: D

Explanation:

AWS is introducing a free usage tier for one year to help the new AWS customers get started in Cloud. The free tier can be used for anything that the user wants to run in the Cloud. AWS offers a handful of AWS services as a part of this which includes 750 hours of free micro instances and 750 hours of ELB. It includes the AWS S3 of 5 GB and AWS EBS general purpose volume upto 30 GB. PIOPS is not part of free usage tier.

NEW QUESTION 158

A user is planning to use AWS Cloud formation for his automatic deployment requirements. Which of the below mentioned components are required as a part of the template?

- A. Parameters
- B. Outputs
- C. Template version
- D. Resources

Answer: D

Explanation:

AWS Cloud formation is an application management tool which provides application modelling, deployment, configuration, management and related activities. The template is a JSON-format, text-based file that describes all the AWS resources required to deploy and run an application. It can have option fields, such as

Template Parameters, Output, Data tables, and Template file format version. The only mandatory value is Resource. The user can define the AWS services which will be used/ created by this template inside the Resource section

NEW QUESTION 160

A user has launched 10 instances from the same AMI ID using Auto Scaling. The user is trying to see the average CPU utilization across all instances of the last 2 weeks under the CloudWatch console. How can the user achieve this?

- A. View the Auto Scaling CPU metrics
- B. Aggregate the data over the instance AMI ID
- C. The user has to use the CloudWatch analyzer to find the average data across instances
- D. It is not possible to see the average CPU utilization of the same AMI ID since the instance ID is different

Answer: B

Explanation:

Amazon CloudWatch is basically a metrics repository. Either the user can send the custom data or an AWS product can put metrics into the repository, and the user can retrieve the statistics based on those metrics. The statistics are metric data aggregations over specified periods of time. Aggregations are made using the namespace, metric name, dimensions, and the data point unit of measure, within the time period that is specified by the user. To aggregate the data across instances launched with AMI, the user should select the AMI ID under EC2 metrics and select the aggregate average to view the data.

NEW QUESTION 163

An organization is planning to use AWS for 5 different departments. The finance department is responsible to pay for all the accounts. However, they want the cost separation for each account to map with the right cost centre. How can the finance department achieve this?

- A. Create 5 separate accounts and make them a part of one consolidate billing
- B. Create 5 separate accounts and use the IAM cross account access with the roles for better management
- C. Create 5 separate IAM users and set a different policy for their access
- D. Create 5 separate IAM groups and add users as per the department's employees

Answer: A

Explanation:

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS) accounts within a single organization by making a single paying account. Consolidated billing enables the organization to see a combined view of the AWS charges incurred by each account as well as obtain a detailed cost report for each of the individual AWS accounts associated with the paying account.

NEW QUESTION 164

A user has launched an ELB which has 5 instances registered with it. The user deletes the ELB by mistake. What will happen to the instances?

- A. ELB will ask the user whether to delete the instances or not
- B. Instances will be terminated
- C. ELB cannot be deleted if it has running instances registered with it
- D. Instances will keep running

Answer: D

Explanation:

When the user deletes the Elastic Load Balancer, all the registered instances will be deregistered. However, they will continue to run. The user will incur charges if he does not take any action on those instances.

NEW QUESTION 168

A user is running one instance for only 3 hours every day. The user wants to save some cost with the instance. Which of the below mentioned Reserved Instance categories is advised in this case?

- A. The user should not use RI; instead only go with the on-demand pricing
- B. The user should use the AWS high utilized RI
- C. The user should use the AWS medium utilized RI
- D. The user should use the AWS low utilized RI

Answer: A

Explanation:

The AWS Reserved Instance provides the user with an option to save some money by paying a one-time fixed amount and then save on the hourly rate. It is advisable that if the user is having 30% or more usage of an instance per day, he should go for a RI. If the user is going to use an EC2 instance for more than 2200-2500 hours per year, RI will help the user save some cost. Here, the instance is not going to run for less than 1500 hours. Thus, it is advisable that the user should use the on-demand pricing.

NEW QUESTION 172

A user has setup connection draining with ELB to allow in-flight requests to continue while the instance is being deregistered through Auto Scaling. If the user has not specified the draining time, how long will ELB allow inflight requests traffic to continue?

- A. 600 seconds

- B. 3600 seconds
- C. 300 seconds
- D. 0 seconds

Answer: C

Explanation:

The Elastic Load Balancer connection draining feature causes the load balancer to stop sending new requests to the back-end instances when the instances are deregistering or become unhealthy, while ensuring that inflight requests continue to be served. The user can specify a maximum time (3600 seconds) for the load balancer to keep the connections alive before reporting the instance as deregistered. If the user does not specify the maximum timeout period, by default, the load balancer will close the connections to the deregistering instance after 300 seconds.

NEW QUESTION 177

A user has created an S3 bucket which is not publicly accessible. The bucket is having thirty objects which are also private. If the user wants to make the objects public, how can he configure this with minimal efforts?

- A. The user should select all objects from the console and apply a single policy to mark them public
- B. The user can write a program which programmatically makes all objects public using S3 SDK
- C. Set the AWS bucket policy which marks all objects as public
- D. Make the bucket ACL as public so it will also mark all objects as public

Answer: C

Explanation:

A system admin can grant permission of the S3 objects or buckets to any user or make the objects public using the bucket policy and user policy. Both use the JSON-based access policy language. Generally if the user is defining the ACL on the bucket, the objects in the bucket do not inherit it and vice versa. The bucket policy can be defined at the bucket level which allows the objects as well as the bucket to be public with a single policy applied to that bucket.

NEW QUESTION 178

A user is checking the CloudWatch metrics from the AWS console. The user notices that the CloudWatch data is coming in UTC. The user wants to convert the data to a local time zone. How can the user perform this?

- A. In the CloudWatch dashboard the user should set the local timezone so that CloudWatch shows the data only in the local time zone
- B. In the CloudWatch console select the local timezone under the Time Range tab to view the data as per the local timezone
- C. The CloudWatch data is always in UTC; the user has to manually convert the data
- D. The user should have send the local timezone while uploading the data so that CloudWatch will show the data only in the local timezone

Answer: B

Explanation:

If the user is viewing the data inside the CloudWatch console, the console provides options to filter values either using the relative period, such as days/hours or using the Absolute tab where the user can provide data with a specific date and time. The console also provides the option to search using the local timezone under the time range caption in the console because the time range tab allows the user to change the time zone.

NEW QUESTION 183

A user has created a queue named "myqueue" with SQS. There are four messages published to queue which are not received by the consumer yet. If the user tries to delete the queue, what will happen?

- A. A user can never delete a queue manually
- B. AWS deletes it after 30 days of inactivity on queue
- C. It will delete the queue
- D. It will initiate the delete but wait for four days before deleting until all messages are deleted automatically
- E. It will ask user to delete the messages first

Answer: B

Explanation:

SQS allows the user to move data between distributed components of applications so they can perform different tasks without losing messages or requiring each component to be always available. The user can delete a queue at any time, whether it is empty or not. It is important to note that queues retain messages for a set period of time. By default, a queue retains messages for four days.

NEW QUESTION 184

A customer is using AWS for Dev and Test. The customer wants to setup the Dev environment with Cloudformation. Which of the below mentioned steps are not required while using Cloudformation?

- A. Create a stack
- B. Configure a service
- C. Create and upload the template
- D. Provide the parameters configured as part of the template

Answer: B

Explanation:

AWS Cloudformation is an application management tool which provides application modelling, deployment, configuration, management and related activities. AWS

CloudFormation introduces two concepts: the template and the stack. The template is a JSON-format, text-based file that describes all the AWS resources required to deploy and run an application. The stack is a collection of AWS resources which are created and managed as a single unit when AWS CloudFormation instantiates a template. While creating a stack, the user uploads the template and provides the data for the parameters if required.

NEW QUESTION 187

A user has configured ELB with three instances. The user wants to achieve High Availability as well as redundancy with ELB. Which of the below mentioned AWS services helps the user achieve this for ELB?

- A. Route 53
- B. AWS Mechanical Turk
- C. Auto Scaling
- D. AWS EMR

Answer: A

Explanation:

The user can provide high availability and redundancy for applications running behind Elastic Load Balancer by enabling the Amazon Route 53 Domain Name System (DNS) failover for the load balancers. Amazon Route 53 is a DNS service that provides reliable routing to the user's infrastructure.

NEW QUESTION 190

A user has enabled the Multi AZ feature with the MS SQL RDS database server. Which of the below mentioned statements will help the user understand the Multi AZ feature better?

- A. In a Multi AZ, AWS runs two DBs in parallel and copies the data asynchronously to the replica copy
- B. In a Multi AZ, AWS runs two DBs in parallel and copies the data synchronously to the replica copy
- C. In a Multi AZ, AWS runs just one DB but copies the data synchronously to the standby replica
- D. AWS MS SQL does not support the Multi AZ feature

Answer: C

Explanation:

Amazon RDS provides high availability and failover support for DB instances using Multi-AZ deployments. In a Multi-AZ deployment, Amazon RDS automatically provisions and maintains a synchronous standby replica in a different Availability Zone. The primary DB instance is synchronously replicated across Availability Zones to a standby replica to provide data redundancy, eliminate I/O freezes, and minimize latency spikes during system backups. Running a DB instance with high availability can enhance availability during planned system maintenance, and help protect your databases against DB instance failure and Availability Zone disruption. Note that the high-availability feature is not a scaling solution for read-only scenarios; you cannot use a standby replica to serve read traffic. To service read-only traffic, you should use a read replica.

NEW QUESTION 191

An organization is setting up programmatic billing access for their AWS account. Which of the below mentioned services is not required or enabled when the organization wants to use programmatic access?

- A. Programmatic access
- B. AWS bucket to hold the billing report
- C. AWS billing alerts
- D. Monthly Billing report

Answer: C

Explanation:

AWS provides an option to have programmatic access to billing. Programmatic Billing Access leverages the existing Amazon Simple Storage Service (Amazon S3) APIs. Thus, the user can build applications that reference his billing data from a CSV (comma-separated value) file stored in an Amazon S3 bucket. To enable programmatic access, the user has to first enable the monthly billing report. Then the user needs to provide an AWS bucket name where the billing CSV will be uploaded. The user should also enable the Programmatic access option.

NEW QUESTION 193

A user has stored data on an encrypted EBS volume. The user wants to share the data with his friend's AWS account. How can user achieve this?

- A. Create an AMI from the volume and share the AMI
- B. Copy the data to an unencrypted volume and then share
- C. Take a snapshot and share the snapshot with a friend
- D. If both the accounts are using the same encryption key then the user can share the volume directly

Answer: B

Explanation:

AWS EBS supports encryption of the volume. It also supports creating volumes from existing snapshots provided the snapshots are created from encrypted volumes. If the user is having data on an encrypted volume and is trying to share it with others, he has to copy the data from the encrypted volume to a new unencrypted volume. Only then can the user share it as an encrypted volume data. Otherwise the snapshot cannot be shared.

NEW QUESTION 194

A user has created a web application with Auto Scaling. The user is regularly monitoring the application and he observed that the traffic is highest on Thursday and

Friday between 8 AM to 6 PM. What is the best solution to handle scaling in this case?

- A. Add a new instance manually by 8 AM Thursday and terminate the same by 6 PM Friday
- B. Schedule Auto Scaling to scale up by 8 AM Thursday and scale down after 6 PM on Friday
- C. Schedule a policy which may scale up every day at 8 AM and scales down by 6 PM
- D. Configure a batch process to add a instance by 8 AM and remove it by Friday 6 PM

Answer: B

Explanation:

Auto Scaling based on a schedule allows the user to scale the application in response to predictable load changes. In this case the load increases by Thursday and decreases by Friday. Thus, the user can setup the scaling activity based on the predictable traffic patterns of the web application using Auto Scaling scale by Schedule.

NEW QUESTION 197

A user has launched an EC2 instance. The user is planning to setup the CloudWatch alarm. Which of the below mentioned actions is not supported by the CloudWatch alarm?

- A. Notify the Auto Scaling launch config to scale up
- B. Send an SMS using SNS
- C. Notify the Auto Scaling group to scale down
- D. Stop the EC2 instance

Answer: B

Explanation:

A user can create a CloudWatch alarm that takes various actions when the alarm changes state. An alarm watches a single metric over the time period that the user has specified, and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The actions could be sending a notification to an Amazon Simple Notification Service topic (SMS, Email, and HTTP end point.), notifying the Auto Scaling policy or changing the state of the instance to Stop/Terminate.

NEW QUESTION 200

A root account owner has created an S3 bucket testmycloud. The account owner wants to allow everyone to upload the objects as well as enforce that the person who uploaded the object should manage the permission of those objects. Which is the easiest way to achieve this?

- A. The root account owner should create a bucket policy which allows the IAM users to upload the object
- B. The root account owner should create the bucket policy which allows the other account owners to set the object policy of that bucket
- C. The root account should use ACL with the bucket to allow everyone to upload the object
- D. The root account should create the IAM users and provide them the permission to upload content to the bucket

Answer: C

Explanation:

Each AWS S3 bucket and object has an ACL (Access Control List. associated with it. An ACL is a list of grants identifying the grantee and the permission granted. The user can use ACLs to grant basic read/write permissions to other AWS accounts. ACLs use an Amazon S3-specific XML schema. The user cannot grant permissions to other users in his account. ACLs are suitable for specific scenarios. For example, if a bucket owner allows other AWS accounts to upload objects, permissions to these objects can only be managed using the object ACL by the AWS account that owns the object.

NEW QUESTION 203

An organization has added 3 of his AWS accounts to consolidated billing. One of the AWS accounts has purchased a Reserved Instance (RI. of a small instance size in the US-East-1a zone. All other AWS accounts are running instances of a small size in the same zone. What will happen in this case for the RI pricing?

- A. Only the account that has purchased the RI will get the advantage of RI pricing
- B. One instance of a small size and running in the US-East-1a zone of each AWS account will get the benefit of RI pricing
- C. Any single instance from all the three accounts can get the benefit of AWS RI pricing if they are running in the same zone and are of the same size
- D. If there are more than one instances of a small size running across multiple accounts in the same zone no one will get the benefit of RI

Answer: C

Explanation:

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS. accounts within a single organization by making a single paying account. For billing purposes, consolidated billing treats all the accounts on the consolidated bill as one account. This means that all accounts on a consolidated bill can receive the hourly cost benefit of the Amazon EC2 Reserved Instances purchased by any other account. In this case only one Reserved Instance has been purchased by one account. Thus, only a single instance from any of the accounts will get the advantage of RI. AWS will implement the blended rate for each instance if more than one instance is running concurrently.

NEW QUESTION 207

A user has enabled detailed CloudWatch metric monitoring on an Auto Scaling group. Which of the below mentioned metrics will help the user identify the total number of instances in an Auto Scaling group cluding pending, terminating and running instances?

- A. GroupTotalInstances
- B. GroupSumInstances
- C. It is not possible to get a count of all the three metrics together
- D. The user has to find the individual number of running, terminating and pending instances and sum it

E. GroupInstancesCount

Answer: A

Explanation:

CloudWatch is used to monitor AWS as well as the custom services. For Auto Scaling, CloudWatch provides various metrics to get the group information, such as the Number of Pending, Running or Terminating instances at any moment. If the user wants to get the total number of Running, Pending and Terminating instances at any moment, he can use the GroupTotalInstances metric.

NEW QUESTION 209

A user is trying to configure the CloudWatch billing alarm. Which of the below mentioned steps should be performed by the user for the first time alarm creation in the AWS Account Management section?

- A. Enable Receiving Billing Reports
- B. Enable Receiving Billing Alerts
- C. Enable AWS billing utility
- D. Enable CloudWatch Billing Threshold

Answer: B

Explanation:

AWS CloudWatch supports enabling the billing alarm on the total AWS charges. Before the user can create an alarm on the estimated charges, he must enable monitoring of the estimated AWS charges, by selecting the option “Enable receiving billing alerts”. It takes about 15 minutes before the user can view the billing data. The user can then create the alarms.

NEW QUESTION 214

A user wants to make so that whenever the CPU utilization of the AWS EC2 instance is above 90%, the redlight of his bedroom turns on. Which of the below mentioned AWS services is helpful for this purpose?

- A. AWS CloudWatch + AWS SES
- B. AWS CloudWatch + AWS SNS
- C. Non
- D. It is not possible to configure the light with the AWS infrastructure services
- E. AWS CloudWatch and a dedicated software turning on the light

Answer: B

Explanation:

Amazon Simple Notification Service (Amazon SNS) is a fast, flexible, and fully managed push messaging service. Amazon SNS can deliver notifications by SMS text message or email to the Amazon Simple Queue Service (SQS) queues or to any HTTP endpoint. The user can configure some sensor devices at his home which receives data on the HTTP end point (REST calls) and turn on the red light. The user can configure the CloudWatch alarm to send a notification to the AWS SNS HTTP end point (the sensor device) and it will turn the light red when there is an alarm condition.

NEW QUESTION 215

A user has created an ELB with Auto Scaling. Which of the below mentioned offerings from ELB helps the user to stop sending new requests traffic from the load balancer to the EC2 instance when the instance is being deregistered while continuing in-flight requests?

- A. ELB sticky session
- B. ELB deregistration check
- C. ELB connection draining
- D. ELB auto registration Off

Answer: C

Explanation:

The Elastic Load Balancer connection draining feature causes the load balancer to stop sending new requests to the back-end instances when the instances are deregistering or become unhealthy, while ensuring that in-flight requests continue to be served.

NEW QUESTION 216

A user has setup a web application on EC2. The user is generating a log of the application performance at every second. There are multiple entries for each second. If the user wants to send that data to CloudWatch every minute, what should he do?

- A. The user should send only the data of the 60th second as CloudWatch will map the receive data timezone with the sent data timezone
- B. It is not possible to send the custom metric to CloudWatch every minute
- C. Give CloudWatch the Min, Max, Sum, and SampleCount of a number of every minute
- D. Calculate the average of one minute and send the data to CloudWatch

Answer: C

Explanation:

Amazon CloudWatch aggregates statistics according to the period length that the user has specified while getting data from CloudWatch. The user can publish as many data points as he wants with the same or similar time stamps. CloudWatch aggregates them by the period length when the user calls get statistics about those data points. CloudWatch records the average (sum of all items divided by the number of items) of the values received for every 1-minute period, as well as the number of samples, maximum value, and minimum value for the same time period. CloudWatch will aggregate all the data which have time stamps within a

one-minute period.

NEW QUESTION 219

A user has configured CloudWatch monitoring on an EBS backed EC2 instance. If the user has not attached any additional device, which of the below mentioned metrics will always show a 0 value?

- A. DiskReadBytes
- B. NetworkIn
- C. NetworkOut
- D. CPUUtilization

Answer: A

Explanation:

CloudWatch is used to monitor AWS as the well custom services. For EC2 when the user is monitoring the EC2 instances, it will capture the 7 Instance level and 3 system check parameters for the EC2 instance. Since this is an EBS backed instance, it will not have ephemeral storage attached to it. Out of the 7 EC2 metrics, the 4 metrics DiskReadOps, DiskWriteOps, DiskReadBytes and DiskWriteBytes are disk related data and available only when there is ephemeral storage attached to an instance. For an EBS backed instance without any additional device, this data will be 0.

NEW QUESTION 224

A user is trying to aggregate all the CloudWatch metric data of the last 1 week. Which of the below mentioned statistics is not available for the user as a part of data aggregation?

- A. Aggregate
- B. Sum
- C. Sample data
- D. Average

Answer: A

Explanation:

Amazon CloudWatch is basically a metrics repository. Either the user can send the custom data or an AWS product can put metrics into the repository, and the user can retrieve the statistics based on those metrics. The statistics are metric data aggregations over specified periods of time. Aggregations are made using the namespace, metric name, dimensions, and the data point unit of measure, within the time period that is specified by the user. CloudWatch supports Sum, Min, Max, Sample Data and Average statistics aggregation.

NEW QUESTION 228

A user has created numerous EBS volumes. What is the general limit for each AWS account for the maximum number of EBS volumes that can be created?

- A. 10000
- B. 5000
- C. 100
- D. 1000

Answer: B

Explanation:

A user can attach multiple EBS volumes to the same instance within the limits specified by his AWS account. Each AWS account has a limit on the number of Amazon EBS volumes that the user can create, and the total storage available. The default limit for the maximum number of volumes that can be created is 5000.

NEW QUESTION 233

An organization has configured the custom metric upload with CloudWatch. The organization has given permission to its employees to upload data using CLI as well SDK. How can the user track the calls made to CloudWatch?

- A. The user can enable logging with CloudWatch which logs all the activities
- B. Use CloudTrail to monitor the API calls
- C. Create an IAM user and allow each user to log the data using the S3 bucket
- D. Enable detailed monitoring with CloudWatch

Answer: B

Explanation:

AWS CloudTrail is a web service which will allow the user to monitor the calls made to the Amazon CloudWatch API for the organization's account, including calls made by the AWS Management Console, Command Line Interface (CLI), and other services. When CloudTrail logging is turned on, CloudWatch will write log files into the Amazon S3 bucket, which is specified during the CloudTrail configuration.

NEW QUESTION 237

A user is launching an EC2 instance in the US East region. Which of the below mentioned options is recommended by AWS with respect to the selection of the availability zone?

- A. Always select the US-East-1-a zone for HA
- B. Do not select the AZ; instead let AWS select the AZ
- C. The user can never select the availability zone while launching an instance

D. Always select the AZ while launching an instance

Answer: B

Explanation:

When launching an instance with EC2, AWS recommends not to select the availability zone (AZ). AWS specifies that the default Availability Zone should be accepted. This is because it enables AWS to select the best Availability Zone based on the system health and available capacity. If the user launches additional instances, only then an Availability Zone should be specified. This is to specify the same or different AZ from the running instances.

NEW QUESTION 238

An organization has created 50 IAM users. The organization has introduced a new policy which will change the access of an IAM user. How can the organization implement this effectively so that there is no need to apply the policy at the individual user level?

- A. Use the IAM groups and add users as per their role to different groups and apply policy to group
- B. The user can create a policy and apply it to multiple users in a single go with the AWS CLI
- C. Add each user to the IAM role as per their organization role to achieve effective policy setup
- D. Use the IAM role and implement access at the role level

Answer: A

Explanation:

With AWS IAM, a group is a collection of IAM users. A group allows the user to specify permissions for a collection of users, which can make it easier to manage the permissions for those users. A group helps an organization manage access in a better way; instead of applying at the individual level, the organization can apply at the group level which is applicable to all the users who are a part of that group.

NEW QUESTION 239

An organization, which has the AWS account ID as 999988887777, has created 50 IAM users. All the users are added to the same group cloudacademy. If the organization has enabled that each IAM user can login with the AWS console, which AWS login URL will the IAM users use?

- A. [https:// 999988887777.signin.aws.amazon.com/console/](https://999988887777.signin.aws.amazon.com/console/)
- B. [https:// signin.aws.amazon.com/cloudacademy/](https://signin.aws.amazon.com/cloudacademy/)
- C. [https:// cloudacademy.signin.aws.amazon.com/999988887777/console/](https://cloudacademy.signin.aws.amazon.com/999988887777/console/)
- D. [https:// 999988887777.aws.amazon.com/ cloudacademy/](https://999988887777.aws.amazon.com/cloudacademy/)

Answer: A

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. Once the organization has created the IAM users, they will have a separate AWS console URL to login to the AWS console. The console login URL for the IAM user will be [https:// AWS_Account_ID.signin.aws.amazon.com/console/](https://AWS_Account_ID.signin.aws.amazon.com/console/). It uses only the AWS account ID and does not depend on the group or user ID.

NEW QUESTION 244

An organization is using AWS since a few months. The finance team wants to visualize the pattern of AWS spending. Which of the below AWS tool will help for this requirement?

- A. AWS Cost Manager
- B. AWS Cost Explorer
- C. AWS CloudWatch
- D. AWS Consolidated Billing

Answer: B

Explanation:

The AWS Billing and Cost Management console includes the Cost Explorer tool for viewing AWS cost data as a graph. It does not charge extra to user for this service. With Cost Explorer the user can filter graphs using resource tags or with services in AWS. If the organization is using Consolidated Billing it helps generate report based on linked accounts. This will help organization to identify areas that require further inquiry. The organization can view trends and use that to understand spend and to predict future costs.

NEW QUESTION 248

A user has configured an Auto Scaling group with ELB. The user has enabled detailed CloudWatch monitoring on Elastic Load balancing. Which of the below mentioned statements will help the user understand this functionality better?

- A. ELB sends data to CloudWatch every minute only and does not charge the user
- B. ELB will send data every minute and will charge the user extra
- C. ELB is not supported by CloudWatch
- D. It is not possible to setup detailed monitoring for ELB

Answer: A

Explanation:

CloudWatch is used to monitor AWS as well as the custom services. It provides either basic or detailed monitoring for the supported AWS products. In basic monitoring, a service sends data points to CloudWatch every five minutes, while in detailed monitoring a service sends data points to CloudWatch every minute. Elastic Load Balancing includes 10 metrics and 2 dimensions, and sends data to CloudWatch every minute. This does not cost extra.

NEW QUESTION 249

A sys admin has created a shopping cart application and hosted it on EC2. The EC2 instances are running behind ELB. The admin wants to ensure that the end user request will always go to the EC2 instance where the user session has been created. How can the admin configure this?

- A. Enable ELB cross zone load balancing
- B. Enable ELB cookie setup
- C. Enable ELB sticky session
- D. Enable ELB connection draining

Answer: C

Explanation:

Generally AWS ELB routes each request to a zone with the minimum load. The Elastic Load Balancer provides a feature called sticky session which binds the user's session with a specific EC2 instance. If the sticky session is enabled the first request from the user will be redirected to any of the EC2 instances. But, henceforth, all requests from the same user will be redirected to the same EC2 instance. This ensures that all requests coming from the user during the session will be sent to the same application instance.

NEW QUESTION 251

An organization has created 50 IAM users. The organization wants that each user can change their password but cannot change their access keys. How can the organization achieve this?

- A. The organization has to create a special password policy and attach it to each user
- B. The root account owner has to use CLI which forces each IAM user to change their password on first login
- C. By default each IAM user can modify their passwords
- D. The root account owner can set the policy from the IAM console under the password policy screen

Answer: D

Explanation:

With AWS IAM, organizations can use the AWS Management Console to display, create, change or delete a password policy. As a part of managing the password policy, the user can enable all users to manage their own passwords. If the user has selected the option which allows the IAM users to modify their password, he does not need to set a separate policy for the users. This option in the AWS console allows changing only the password.

NEW QUESTION 252

A user has created a subnet with VPC and launched an EC2 instance in that subnet with only default settings. Which of the below mentioned options is ready to use on the EC2 instance as soon as it is launched?

- A. Elastic IP
- B. Private IP
- C. Public IP
- D. Internet gateway

Answer: B

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to a user's AWS account. A subnet is a range of IP addresses in the VPC. The user can launch the AWS resources into a subnet. There are two supported platforms into which a user can launch instances: EC2-Classic and EC2-VPC. When the user launches an instance which is not a part of the non-default subnet, it will only have a private IP assigned to it. The instances part of a subnet can communicate with each other but cannot communicate over the internet or to the AWS services, such as RDS / S3.

NEW QUESTION 256

A user is trying to delete an Auto Scaling group from CLI. Which of the below mentioned steps are to be performed by the user?

- A. Terminate the instances with the `ec2-terminate-instance` command
- B. Terminate the Auto Scaling instances with the `as-terminate-instance` command
- C. Set the minimum size and desired capacity to 0
- D. There is no need to change the capacity
- E. Run the `as-delete-group` command and it will reset all values to 0

Answer: C

Explanation:

If the user wants to delete the Auto Scaling group, the user should manually set the values of the minimum and desired capacity to 0. Otherwise Auto Scaling will not allow for the deletion of the group from CLI. While trying from the AWS console, the user need not set the values to 0 as the Auto Scaling console will automatically do so.

NEW QUESTION 261

A user is launching an instance. He is on the "Tag the instance" screen. Which of the below mentioned information will not help the user understand the functionality of an AWS tag?

- A. Each tag will have a key and value

- B. The user can apply tags to the S3 bucket
- C. The maximum value of the tag key length is 64 unicode characters
- D. AWS tags are used to find the cost distribution of various resources

Answer: C

Explanation:

AWS provides cost allocation tags to categorize and track the AWS costs. When the user applies tags to his AWS resources, AWS generates a cost allocation report as a comma-separated value (CSV file. with the usage and costs aggregated by those tags. Each tag will have a key-value and can be applied to services, such as EC2, S3, RDS, EMR, etc. The maximum size of a tag key is 128 unicode characters.

NEW QUESTION 263

A user has a refrigerator plant. The user is measuring the temperature of the plant every 15 minutes. If the user wants to send the data to CloudWatch to view the data visually, which of the below mentioned statements is true with respect to the information given above?

- A. The user needs to use AWS CLI or API to upload the data
- B. The user can use the AWS Import Export facility to import data to CloudWatch
- C. The user will upload data from the AWS console
- D. The user cannot upload data to CloudWatch since it is not an AWS service metric

Answer: A

Explanation:

AWS CloudWatch supports the custom metrics. The user can always capture the custom data and upload the data to CloudWatch using CLI or APIs. While sending the data the user has to include the metric name, namespace and timezone as part of the request.

NEW QUESTION 264

A user has recently started using EC2. The user launched one EC2 instance in the default subnet in EC2-VPC Which of the below mentioned options is not attached or available with the EC2 instance when it is launched?

- A. Public IP address
- B. Internet gateway
- C. Elastic IP
- D. Private IP address

Answer: C

Explanation:

A Virtual Private Cloud (VPC. is a virtual network dedicated to a user's AWS account. A subnet is a range of IP addresses in the VPC. The user can launch the AWS resources into a subnet. There are two supported platforms into which a user can launch instances: EC2-Classic and EC2-VPC (default subnet.. A default VPC has all the benefits of EC2-VPC and the ease of use of EC2-Classic. Each instance that the user launches into a default subnet has a private IP address and a public IP address. These instances can communicate with the internet through an internet gateway. An internet gateway enables the EC2 instances to connect to the internet through the Amazon EC2 network edge.

NEW QUESTION 268

A user has setup an RDS DB with Oracle. The user wants to get notifications when someone modifies the security group of that DB. How can the user configure that?

- A. It is not possible to get the notifications on a change in the security group
- B. Configure SNS to monitor security group changes
- C. Configure event notification on the DB security group
- D. Configure the CloudWatch alarm on the DB for a change in the security group

Answer: C

Explanation:

Amazon RDS uses the Amazon Simple Notification Service to provide a notification when an Amazon RDS event occurs. These events can be configured for source categories, such as DB instance, DB security group, DB snapshot and DB parameter group. If the user is subscribed to a Configuration Change category for a DB security group, he will be notified when the DB security group is changed.

NEW QUESTION 272

An organization wants to move to Cloud. They are looking for a secure encrypted database storage option. Which of the below mentioned AWS functionalities helps them to achieve this?

- A. AWS MFA with EBS
- B. AWS EBS encryption
- C. Multi-tier encryption with Redshift
- D. AWS S3 server side storage

Answer: B

Explanation:

AWS EBS supports encryption of the volume while creating new volumes. It also supports creating volumes from existing snapshots provided the snapshots are created from encrypted volumes. The data at rest, the I/O as well as all the snapshots of EBS will be encrypted. The encryption occurs on the servers that host the

EC2 instances, providing encryption of data as it moves between the EC2 instances and EBS storage. EBS encryption is based on the AES-256 cryptographic algorithm, which is the industry standard

NEW QUESTION 274

A user has configured the AWS CloudWatch alarm for estimated usage charges in the US East region. Which of the below mentioned statements is not true with respect to the estimated charges?

Exhibit:



- A. It will store the estimated charges data of the last 14 days
- B. It will include the estimated charges of every AWS service
- C. The metric data will represent the data of all the regions
- D. The metric data will show data specific to that region

Answer: D

Explanation:

When the user has enabled the monitoring of estimated charges for the AWS account with AWS CloudWatch, the estimated charges are calculated and sent several times daily to CloudWatch in the form of metric data. This data will be stored for 14 days. The billing metric data is stored in the US East (Northern Virginia) Region and represents worldwide charges. This data also includes the estimated charges for every service in AWS used by the user, as well as the estimated overall AWS charges.

NEW QUESTION 275

A user is trying to understand AWS SNS. To which of the below mentioned end points is SNS unable to send a notification?

- A. Email JSON
- B. HTTP
- C. AWS SQS
- D. AWS SES

Answer: D

Explanation:

Amazon Simple Notification Service (Amazon SNS) is a fast, flexible, and fully managed push messaging service. Amazon SNS can deliver notifications by SMS text message or email to the Amazon Simple Queue Service (SQS) queues or to any HTTP endpoint. The user can select one of the following transports as part of the subscription requests: "HTTP", "HTTPS", "Email", "Email-JSON", "SQS", "and SMS".

NEW QUESTION 276

A sys admin is trying to understand EBS snapshots. Which of the below mentioned statements will not be useful to the admin to understand the concepts about a snapshot?

- A. The snapshot is synchronous
- B. It is recommended to stop the instance before taking a snapshot for consistent data
- C. The snapshot is incremental
- D. The snapshot captures the data that has been written to the hard disk when the snapshot command was executed

Answer: A

Explanation:

The AWS snapshot is a point in time backup of an EBS volume. When the snapshot command is executed it will capture the current state of the data that is written on the drive and take a backup. For a better and consistent snapshot of the root EBS volume, AWS recommends stopping the instance. For additional volumes it is recommended to unmount the device. The snapshots are asynchronous and incremental.

NEW QUESTION 277

A user has created a VPC with CIDR 20.0.0.0/24. The user has created a public subnet with CIDR 20.0.0.0/25 and a private subnet with CIDR 20.0.0.128/25. The user has launched one instance each in the private and public subnets. Which of the below mentioned options cannot be the correct IP address (private IP) assigned to an instance in the public or private subnet?

- A. 20.0.0.255
- B. 20.0.0.132
- C. 20.0.0.122
- D. 20.0.0.55

Answer: A

Explanation:

When the user creates a subnet in VPC, he specifies the CIDR block for the subnet. In this case the user has created a VPC with the CIDR block 20.0.0.0/24, which supports 256 IP addresses (20.0.0.0 to 20.0.0.255). The public subnet will have IP addresses between 20.0.0.0 - 20.0.0.127 and the private subnet will have IP addresses between 20.0.0.128 - 20.0.0.255. AWS reserves the first four IP addresses and the last IP address in each subnet's CIDR block. These are not available for the user to use. Thus, the instance cannot have an IP address of 20.0.0.255

NEW QUESTION 279

A user has launched an EBS backed EC2 instance. What will be the difference while performing the restart or stop/start options on that instance?

- A. For restart it does not charge for an extra hour, while every stop/start it will be charged as a separate hour
- B. Every restart is charged by AWS as a separate hour, while multiple start/stop actions during a single hour will be counted as a single hour
- C. For every restart or start/stop it will be charged as a separate hour
- D. For restart it charges extra only once, while for every stop/start it will be charged as a separate hour

Answer: A

Explanation:

For an EC2 instance launched with an EBS backed AMI, each time the instance state is changed from stop to start/ running, AWS charges a full instance hour, even if these transitions happen multiple times within a single hour. Anyway, rebooting an instance AWS does not charge a new instance billing hour.

Topic 3, Volume C

NEW QUESTION 281

A user has created a VPC with a public subnet. The user has terminated all the instances which are part of the subnet. Which of the below mentioned statements is true with respect to this scenario?

- A. The user cannot delete the VPC since the subnet is not deleted
- B. All network interface attached with the instances will be deleted
- C. When the user launches a new instance it cannot use the same subnet
- D. The subnet to which the instances were launched with will be deleted

Answer: B

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. When an instance is launched it will have a network interface attached with it. The user cannot delete the subnet until he terminates the instance and deletes the network interface. When the user terminates the instance all the network interfaces attached with it are also deleted.

NEW QUESTION 284

A user has deployed an application on an EBS backed EC2 instance. For a better performance of application, it requires dedicated EC2 to EBS traffic. How can the user achieve this?

- A. Launch the EC2 instance as EBS dedicated with PIOPS EBS
- B. Launch the EC2 instance as EBS enhanced with PIOPS EBS
- C. Launch the EC2 instance as EBS dedicated with PIOPS EBS
- D. Launch the EC2 instance as EBS optimized with PIOPS EBS

Answer: D

Explanation:

Any application which has performance sensitive workloads and requires minimal variability with dedicated EC2 to EBS traffic should use provisioned IOPS EBS volumes, which are attached to an EBS-optimized EC2 instance or it should use an instance with 10 Gigabit network connectivity. Launching an instance that is EBS optimized provides the user with a dedicated connection between the EC2 instance and the EBS volume.

NEW QUESTION 286

A user has launched an EC2 Windows instance from an instance store backed AMI. The user wants to convert the AMI to an EBS backed AMI. How can the user convert it?

- A. Attach an EBS volume to the instance and unbundle all the AMI bundled data inside the EBS
- B. A Windows based instance store backed AMI cannot be converted to an EBS backed AMI
- C. It is not possible to convert an instance store backed AMI to an EBS backed AMI
- D. Attach an EBS volume and use the copy command to copy all the ephemeral content to the EBS Volume

Answer: B

Explanation:

Generally when a user has launched an EC2 instance from an instance store backed AMI, it can be converted to an EBS backed AMI provided the user has attached the EBS volume to the instance and unbundles the AMI data to it. However, if the instance is a Windows instance, AWS does not allow this. In this case, since the instance is a Windows instance, the user cannot convert it to an EBS backed AMI.

NEW QUESTION 288

A user has configured ELB with Auto Scaling. The user suspended the Auto Scaling terminate process only for a while. What will happen to the availability zone rebalancing process (AZRebalance. during this period?

- A. Auto Scaling will not launch or terminate any instances
- B. Auto Scaling will allow the instances to grow more than the maximum size
- C. Auto Scaling will keep launching instances till the maximum instance size
- D. It is not possible to suspend the terminate process while keeping the launch active

Answer: B

Explanation:

Auto Scaling performs various processes, such as Launch, Terminate, Availability Zone Rebalance (AZRebalance. etc. The AZRebalance process type seeks to maintain a balanced number of instances across Availability Zones within a region. If the user suspends the Terminate process, the AZRebalance process can cause the Auto Scaling group to grow up to ten percent larger than the maximum size. This is because Auto Scaling allows groups to temporarily grow larger than the maximum size during rebalancing activities. If Auto Scaling cannot terminate instances, the Auto Scaling group could remain up to ten percent larger than the maximum size until the user resumes the Terminate process type.

NEW QUESTION 291

A sys admin has enabled logging on ELB. Which of the below mentioned fields will not be a part of the log file name?

- A. Load Balancer IP
- B. EC2 instance IP
- C. S3 bucket name
- D. Random string

Answer: B

Explanation:

Elastic Load Balancing access logs capture detailed information for all the requests made to the load balancer. Elastic Load Balancing publishes a log file from each load balancer node at the interval that the user has specified. The load balancer can deliver multiple logs for the same period. Elastic Load Balancing creates log file names in the following format: "{Bucket}/{Prefix}/AWSLogs/{AWS AccountID}/elasticloadbalancing/{Region}/{Year}/{Month}/{Day}/{AWS Account ID}_elasticloadbalancing_{Region}_{Load Balancer Name}_{End Time}_{Load Balancer IP}_{Random String}.log"

NEW QUESTION 295

A user has configured ELB with SSL using a security policy for secure negotiation between the client and load balancer. Which of the below mentioned security policies is supported by ELB?

- A. Dynamic Security Policy
- B. All the other options
- C. Predefined Security Policy
- D. Default Security Policy

Answer: C

Explanation:

Elastic Load Balancing uses a Secure Socket Layer (SSL) negotiation configuration which is known as a Security Policy. It is used to negotiate the SSL connections between a client and the load balancer. ELB supports two policies: Predefined Security Policy, which comes with predefined cipher and SSL protocols; Custom Security Policy, which allows the user to configure a policy.

NEW QUESTION 298

A user has created a VPC with CIDR 20.0.0.0/24. The user has used all the IPs of CIDR and wants to increase the size of the VPC. The user has two subnets: public (20.0.0.0/28) and private (20.0.1.0/28). How can the user change the size of the VPC?

- A. The user can delete all the instances of the subne
- B. Change the size of the subnets to 20.0.0.0/32 and 20.0.1.0/32, respectively
- C. Then the user can increase the size of the VPC using CLI
- D. It is not possible to change the size of the VPC once it has been created
- E. The user can add a subnet with a higher range so that it will automatically increase the size of the VPC
- F. The user can delete the subnets first and then modify the size of the VPC

Answer: B

Explanation:

Once the user has created a VPC, he cannot change the CIDR of that VPC. The user has to terminate all the instances, delete the subnets and then delete the VPC. Create a new VPC with a higher size and launch instances with the newly created VPC and subnets.

NEW QUESTION 301

A user has launched 5 instances in EC2-CLASSIC and attached 5 elastic IPs to the five different instances in the US East region. The user is creating a VPC in the same region. The user wants to assign an elastic IP to the VPC instance. How can the user achieve this?

- A. The user has to request AWS to increase the number of elastic IPs associated with the account
- B. AWS allows 10 EC2 Classic IPs per region; so it will allow to allocate new Elastic IPs to the same region
- C. The AWS will not allow to create a new elastic IP in VPC; it will throw an error
- D. The user can allocate a new IP address in VPC as it has a different limit than EC2

Answer: D

Explanation: Section: (none)

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. A user can have 5 IP addresses per region with EC2 Classic. The user can have 5 separate IPs with VPC in the same region as it has a separate limit than EC2 Classic.

NEW QUESTION 306

A user has launched an EC2 instance store backed instance in the US-East-1a zone. The user created AMI #1 and copied it to the Europe region. After that, the user made a few updates to the application running in the US-East-1a zone. The user makes an AMI#2 after the changes. If the user launches a new instance in Europe from the AMI #1 copy, which of the below mentioned statements is true?

- A. The new instance will have the changes made after the AMI copy as AWS just copies the reference of the original AMI during the copyin
- B. Thus, the copied AMI will have all the updated data
- C. The new instance will have the changes made after the AMI copy since AWS keeps updating the AMI
- D. It is not possible to copy the instance store backed AMI from one region to another
- E. The new instance in the EU region will not have the changes made after the AMI copy

Answer: D

Explanation:

Within EC2, when the user copies an AMI, the new AMI is fully independent of the source AMI; there is no link to the original (source) AMI. The user can modify the source AMI without affecting the new AMI and vice versa. Therefore, in this case even if the source AMI is modified, the copied AMI of the EU region will not have the changes. Thus, after copy the user needs to copy the new source AMI to the destination region to get those changes.

NEW QUESTION 309

An AWS account owner has setup multiple IAM users. One IAM user only has CloudWatch access. He has setup the alarm action which stops the EC2 instances when the CPU utilization is below the threshold limit. What will happen in this case?

- A. It is not possible to stop the instance using the CloudWatch alarm
- B. CloudWatch will stop the instance when the action is executed
- C. The user cannot set an alarm on EC2 since he does not have the permission
- D. The user can setup the action but it will not be executed if the user does not have EC2 rights

Answer: D

Explanation:

Amazon CloudWatch alarms watch a single metric over a time period that the user specifies and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The user can setup an action which stops the instances when their CPU utilization is below a certain threshold for a certain period of time. The EC2 action can either terminate or stop the instance as part of the EC2 action. If the IAM user has read/write permissions for Amazon CloudWatch but not for Amazon EC2, he can still create an alarm. However, the stop or terminate actions will not be performed on the

Amazon EC2 instance.

NEW QUESTION 311

When an EC2 instance is backed by an S3-Dased AML is terminated, what happens to the data on the root volume?

- A. Data is automatically deleted
- B. Data is automatically saved as an EBS snapsho
- C. Data is unavailable until the instance is restarted
- D. Data is automatically saved as an EBS volum

Answer: A

NEW QUESTION 312

A user has launched two EBS backed EC2 instances in the US-East-1a region. The user wants to change the zone of one of the instances. How can the user change it?

- A. The zone can only be modified using the AWS CLI
- B. It is not possible to change the zone of an instance after it is launched
- C. Stop one of the instances and change the availability zone
- D. From the AWS EC2 console, select the Actions - > Change zones and specify the new zone

Answer: B

Explanation:

With AWS EC2, when a user is launching an instance he can select the availability zone (AZ. at the time of launch. If the zone is not selected, AWS selects it on behalf of the user. Once the instance is launched, the user cannot change the zone of that instance unless he creates an AML of that instance and launches a new instance from it.

NEW QUESTION 313

A user is sending the data to CloudWatch using the CloudWatch API. The user is sending data 90 minutes in the future. What will CloudWatch do in this case?

- A. CloudWatch will accept the data
- B. It is not possible to send data of the future
- C. It is not possible to send the data manually to CloudWatch
- D. The user cannot send data for more than 60 minutes in the future

Answer: A

Explanation:

With Amazon CloudWatch, each metric data point must be marked with a time stamp. The user can send the data using CLI but the time has to be in the UTC format. If the user does not provide the time, CloudWatch will take the data received time in the UTC timezone. The time stamp sent by the user can be up to two weeks in the past and up to two hours into the future.

NEW QUESTION 314

A system admin is planning to encrypt all objects being uploaded to S3 from an application. The system admin does not want to implement his own encryption algorithm; instead he is planning to use server side encryption by supplying his own key (SSE-C.. Which parameter is not required while making a call for SSE-C?

- A. x-amz-server-side-encryption-customer-key-AES-256
- B. x-amz-server-side-encryption-customer-key
- C. x-amz-server-side-encryption-customer-algorithm
- D. x-amz-server-side-encryption-customer-key-MD5

Answer: A

Explanation:

AWS S3 supports client side or server side encryption to encrypt all data at rest. The server side encryption can either have the S3 supplied AES-256 encryption key or the user can send the key along with each API call to supply his own encryption key (SSE-C.. When the user is supplying his own encryption key, the user has to send the below mentioned parameters as a part of the API calls: x-amz-server-side-encryption-customer-algorithm: Specifies the encryption algorithm x-amz-server-side-encryption-customer-key: To provide the base64-encoded encryption key x-amz-server-side-encryption-customer-key-MD5: To provide the base64-encoded 128-bit MD5 digest of the encryption key

NEW QUESTION 319

Which of the following statements about this S3 bucket policy is true?

```
{
  "Id": "IPAllowPolicy",
  "Statement": [
    {
      "Sid": "IPAllow",
      "Action": "s3:*",
      "Effect": "Allow",
      "Resource": "arn:aws:s3::mybucket/*",
      "Condition": {
        "IpAddress": {
          "aws:SourceIp": "192.168.100.0/24"
        },
        "NotIpAddress": {
          "aws:SourceIp": "192.168.100.188/32"
        }
      }
    },
    {
      "Principal": {
        "AWS": [
          "*"
        ]
      }
    }
  ]
}
```

- A. Denies the server with the IP address 192.166 100.0 full access to the "mybucket" bucket
- B. Denies the server with the IP address 192.166 100.188 full access to the "mybucket bucket
- C. Grants all the servers within the 192 168 100 0/24 subnet full access to the "mybucket" bucket
- D. Grants all the servers within the 192 168 100 188/32 subnet full access to the "mybucket" bucket

Answer: C

NEW QUESTION 320

A user has created an Auto Scaling group with default configurations from CLI. The user wants to setup the CloudWatch alarm on the EC2 instances, which are launched by the Auto Scaling group. The user has setup an alarm to monitor the CPU utilization every minute. Which of the below mentioned statements is true?

- A. It will fetch the data at every minute but the four data points [corresponding to 4 minutes] will not have value since the EC2 basic monitoring metrics are collected every five minutes
- B. It will fetch the data at every minute as detailed monitoring on EC2 will be enabled by the default launch configuration of Auto Scaling
- C. The alarm creation will fail since the user has not enabled detailed monitoring on the EC2 instances
- D. The user has to first enable detailed monitoring on the EC2 instances to support alarm monitoring at every minute

Answer: B

Explanation:

CloudWatch is used to monitor AWS as well as the custom services. To enable detailed instance monitoring for a new Auto Scaling group, the user does not need to take any extra steps. When the user creates an Auto Scaling launch config using CLI, each launch configuration contains a flag named InstanceMonitoring.Enabled. The default value of this flag is true. Thus, by default detailed monitoring will be enabled for Auto Scaling as well as for all the instances launched by that Auto Scaling group.

NEW QUESTION 321

An organization has created one IAM user and applied the below mentioned policy to the user. What entitlements do the IAM users avail with this policy?

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "ec2:Describe*",
      "Resource": "*"
    },
    {
      "Effect": "Allow"
      "Action": [
        "cloudwatch:ListMetrics",
        "cloudwatch:GetMetricStatistics",
        "cloudwatch:Describe*"
      ],
      "Resource": "*"
    },
    {
      "Effect": "Allow",
      "Action": "autoscaling:Describe*",
      "Resource": "*"
    }
  ]
}
```


- A. The policy will allow the user to perform all read only activities on the EC2 services
- B. The policy will allow the user to list all the EC2 resources except EBS
- C. The policy will allow the user to perform all read and write activities on the EC2 services
- D. The policy will allow the user to perform all read only activities on the EC2 services except load Balancing

Answer: D

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. If an organization wants to setup read only access to EC2 for a particular user, they should mention the action in the IAM policy which entitles the user for Describe rights for EC2, CloudWatch, Auto Scaling and ELB. In the policy shown below, the user will have read only access for EC2 and EBS, CloudWatch and Auto Scaling. Since ELB is not mentioned as a part of the list, the user will not have access to ELB.

```
{
"Version": "2012-10-17",
"Statement": [
{
"Effect": "Allow",
"Action": "ec2:Describe*",
"Resource": "*"
},
{
"Effect": "Allow",
"Action": [
"cloudwatch:ListMetrics",
"cloudwatch:GetMetricStatistics",
"cloudwatch:Describe*"
],
"Resource": "*"
},
{
"Effect": "Allow",
"Action": "autoscaling:Describe*",
"Resource": "*"
}
]
}
```

NEW QUESTION 322

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual AWS-SysOps Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the AWS-SysOps Product From:

<https://www.2passeasy.com/dumps/AWS-SysOps/>

Money Back Guarantee

AWS-SysOps Practice Exam Features:

- * AWS-SysOps Questions and Answers Updated Frequently
- * AWS-SysOps Practice Questions Verified by Expert Senior Certified Staff
- * AWS-SysOps Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * AWS-SysOps Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year