

## 1z0-808 Dumps

### Java SE 8 Programmer I

<https://www.certleader.com/1z0-808-dumps.html>



**NEW QUESTION 1**

Given the code fragment:

```
public static void main(String[] args) {  
    int ans;  
    try {  
        int num = 10;  
        int div = 0;  
        ans = num / div;  
    } catch (ArithmeticException ae) {  
        ans = 0; // line n1  
    } catch (Exception e) {  
        System.out.println("Invalid calculation");  
    }  
    System.out.println("Answer = " + ans); // line n2  
}
```

What is the result?

- A. Answer = 0
- B. Invalid calculation
- C. Compilation fails only at line n1.
- D. Compilation fails only at line n2.
- E. Compilation fails at line n1 and line2.

**Answer: C****Explanation:**

```
1  
2 public class Test {  
3     public static void main(String[] args) {  
4         int ans;  
5         try {  
6             int num = 10;  
7             int div = 0;  
8             ans = num / div;  
9         } catch (ArithmeticException ae) {  
10            ans = 0;  
11        } catch (Exception e) {  
12            System.out.println("Invalid calculation");  
13        }  
14        System.out.println("Answer = " + ans); //line n2  
15    }  
16 }  
17
```

✖ variable ans might not have been initialized

✖

**NEW QUESTION 2**

Given the content of three files:

A.java:

```
public class A {  
    public void a() {}  
    int a;  
}
```

B.java:

```
public class B {  
    private int doStuff() {  
        private int x = 100;  
        return x++;  
    }  
}
```

C.java:

```
import java.io.*;  
package p1;  
class A {  
    public void main(String fileName) throws IOException { }  
}
```

Which statement is true?

- A. Only the A.Java file compiles successfully.

- B. Only the B.java file compiles successfully.
- C. Only the C.java file compiles successfully.
- D. The A.java and B.java files compile successfully.
- E. The B.java and C.java files compile successfully.
- F. The A.java and C.java files compile successfully.

**Answer:** A

### NEW QUESTION 3

Given the following classes:

```
public class Employee {  
    public int salary;  
}  
  
public class Manager extends Employee {  
    public int budget;  
}  
  
public class Director extends Manager {  
    public int stockOptions;  
}
```

And given the following main method:

```
public static void main(String[] args) {  
    Employee employee = new Employee();  
    Manager manager = new Manager();  
    Director director = new Director();  
    //line n1  
}
```

Which two options fail to compile when placed at line n1 of the main method? (Choose two.)

- A. employee.salary = 50\_000;
- B. director.salary = 80\_000;
- C. employee.budget = 200\_000;
- D. manager.budget = 1\_000\_000;
- E. manager.stockOption = 500;
- F. director.stockOptions = 1\_000;

**Answer:** CE

### NEW QUESTION 4

Given the code fragment:

```
int x = 100;  
int a = x++;  
int b = ++x;  
int c = x++;  
int d = (a < b) ? (a < c) ? a : (b < c) ? b : c : x;  
System.out.println(d);
```

What is the result?

- A. 100
- B. 101
- C. 102
- D. 103
- E. Compilation fails

**Answer:** E

### NEW QUESTION 5

Given this code for a Planet object:

```
public class Planet {  
    public String name;  
    public int moons;  
  
    public Planet(String name, int moons) {  
        this.name = name;  
        this.moons = moons;  
    }  
}
```

And this method:

```
public static void main(String[] args){  
    Planet[] planets = {  
        new Planet("Mercury", 0),  
        new Planet("Venus", 0),  
        new Planet("Earth", 1),  
        new Planet("Mars", 2)  
    };  
  
    System.out.println(planets);  
    System.out.println(planets[2].name);  
    System.out.println(planets[2].moons);  
}
```

What is the output?

- A  
planets  
Earth  
1
- B  
[LPlanets.Planet;@15db9742  
Earth  
1
- C  
[LPlanets.Planet;@15db9742  
Planets.Planet@6d06d69c  
1
- D  
[LPlanets.Planet;@15db9742  
Planets.Planet@6d06d69c  
[LPlanets.Moon;@7852e922
- E  
[LPlanets.Planet;@15db9742  
Venus  
0

- A. Option A  
B. Option B  
C. Option C  
D. Option D  
E. Option E

**Answer:** C

#### NEW QUESTION 6

Given the code fragment:

```
public static void main(String[] args) {  
    short s1 = 200;  
    Integer s2 = 400;  
    Long s3 = (long) s1 + s2;           //line n1  
    String s4 = (String) (s3 * s2);     //line n2  
    System.out.println("Sum is " + s4);  
}
```

What is the result?

- A. Sum is 600
- B. Compilation fails at line n1.
- C. Compilation fails at line n2.
- D. A ClassCastException is thrown at line n1.
- E. A ClassCastException is thrown at line n2.

**Answer: C**

#### NEW QUESTION 7

Given the code from the Greeting.Java file:

```
public class Greeting {  
    public static void main(String[] args) {  
        System.out.println("Hello " + args[0]);  
    }  
}
```

Which set of commands prints Hello Duke in the console?

- ☐ A) javac Greeting  
java Greeting Duke
- ☐ B) javac Greeting.java Duke  
java Greeting
- ☐ C) javac Greeting.java  
java Greeting Duke
- ☐ D) javac Greeting.java  
java Greeting.class Duke

- A. Option A
- B. Option B
- C. Option C
- D. Option D

**Answer: C**

#### NEW QUESTION 8

Given the code fragment:

```
public static void main(String[] args) {  
    LocalDate date = LocalDate.of(2012, 1, 30);  
    date.plusDays(10);  
    System.out.println(date);  
}
```

What is the result?

- A. 2012-02-10 00:00
- B. 2012-01-30
- C. 2012-02-10
- D. A DateTimeException is thrown at runtime.

**Answer: B**

**Explanation:**





#### NEW QUESTION 9

Given:

```
public class Fieldinit {
    char c;
    boolean b;
    float f;
    void printAll() {
        System.out.println ("c = " + c);
        System.out.println ("b = " + b);
        System.out.println ("f = " + f);
    }
    public static void main (String [] args) {
        FieldInit f = new FieldInit ();
        f.printAll ();
    }
}
```

What is the result?

A

```
c=
b = false
f = 0.0
```

B

```
c= null
b = true
f = 0.0
```

C

```
c=0
b = false
f = 0.0f
```

D

```
c= null
b = false
f = 0.0F
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

**Answer: A**

**NEW QUESTION 10**

Given:

```
public class MyClass {  
    public static void main(String[] args) {  
        String s = "Java SE 8 1";  
        int len = s.trim().length();  
        System.out.print(len);  
    }  
}
```

What is the result?

- A. Compilation fails.
- B. 11
- C. 8
- D. 9
- E. 10

**Answer: B****NEW QUESTION 10**

Given:

```
interface Readable {  
    public void readBook();  
    public void setBookMark();  
}  
  
abstract class Book implements Readable {    // line n1  
    public void readBook() { }  
    // line n2  
}  
  
class EBook extends Book {                    // line n3  
    public void readBook() { }  
    // line n4  
}
```

And given the code fragment: `Book book1 = new EBook(); book1.readBook();`

Which option enables the code to compile?

- ☐ A) Replace the code fragment at line n1 with:  
`class Book implements Readable {`
- ☐ B) At line n2 insert:  
`public abstract void setBookMark();`
- ☐ C) Replace the code fragment at line n3 with:  
`abstract class EBook extends Book {`
- ☐ D) At line n4 insert:  
`public void setBookMark() { }`

- A. Option A
- B. Option B
- C. Option C
- D. Option D

**Answer: D****NEW QUESTION 14**

Given the code fragment:

```
abstract class Toy {  
    int price;  
    // line n1  
}
```

Which three code fragments are valid at line n1?

A

```
public static void insertToy() {  
    /* code goes here */  
}
```

B

```
final Toy getToy() {  
    return new Toy();  
}
```

C

```
public void printToy();
```

D

```
public int calculatePrice() {  
    return price;  
}
```

E

```
public abstract int computeDiscount();
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D
- E. Option E

**Answer:** CDE**NEW QUESTION 19**

Which is true about the switch statement?

- A. Its expression can evaluate to a collection of values.
- B. The break statement, at the end of each case block, is optional.
- C. Its case label literals can be changed at runtime.
- D. It must contain the default section.

**Answer:** B**NEW QUESTION 23**

Given:

```
class X {  
    int i;  
    static int j;  
    public static void main(String[] args) {  
        X x1 = new X();  
        X x2 = new X();  
        x1.i = 3;  
        x1.j = 4;  
        x2.i = 5;  
        x2.j = 6;  
        System.out.println(  
            x1.i + " " +  
            x1.j + " " +  
            x2.i + " " +  
            x2.j);  
    }  
}
```

What is the result?

- A. 3 4 5 6
- B. 3 4 3 6
- C. 5 4 5 6
- D. 3 6 5 6



Answer: D

Explanation:

```
3 6 5 6
Completed with exit code: 0
```

#### NEW QUESTION 27

Given this class:

```
public class CheckingAccount {
    public int amount;
    //line n1
}
```

And given this main method, located in another class:

```
public static void main(String[] args) {
    CheckingAccount acct = new CheckingAccount();
    //line n2
}
```

Which three pieces of code, when inserted independently, set the value of amount to 100?

A

At line n1 insert:

```
public CheckingAccount() {
    amount = 100;
}
```

B

At line n2 insert:

```
this.amount = 100;
```

C

At line n2 insert:

```
amount = 100;
```

D

At line n1 insert:

```
public CheckingAccount() {
    this.amount = 100;
}
```

E

At line n2 insert:

```
acct.amount = 100;
```

F

At line n1 insert:

```
public CheckingAccount() {
    acct.amount = 100;
}
```

A. Option A

B. Option B

C. Option C

D. Option D

E. Option E

F. Option F

Answer: DE

#### NEW QUESTION 32

Given the code fragment:

```
7.  StringBuilder sb1 = new StringBuilder("Duke");
8.  String str1 = sb1.toString();
9.  // insert code here
10. System.out.print(str1 == str2);
```

Which code fragment, when inserted at line 9, enables the code to print true?

- A. String str2 = str1;
- B. String str2 = new String(str1);
- C. String str2 = sb1. toString();
- D. String str2 = "Duke";

**Answer:** A

#### NEW QUESTION 37

Given:

```
class Test {
    int a1;

    public static void doProduct(int a) {
        a = a * a;
    }

    public static void doString(String s) {
        s.concat(" " + s);
    }

    public static void main(String[] args) {
        Test item = new Test();
        item.a1 = 11;
        String sb = "Hello";
        Integer i = 10;
        doProduct(i);
        doString(sb);
        doProduct(item.a1);
        System.out.println(i + " " + sb + " " + item.a1);
    }
}
```

What is the result?

- A. 10 Hello Hello 11
- B. 10 Hello Hello 121
- C. 100 Hello 121
- D. 100 Hello Hello 121
- E. 10 Hello 11

**Answer:** E

#### NEW QUESTION 41

Given:

```
public class Triangle {
    static double area;
    int b = 2, h = 3;
    public static void main(String[] args) {
        double p, b, h;          //line n1
        if (area == 0) {
            b = 3;
            h = 4;
            p = 0.5;
            area = p * b * h;      //line n2
        }
        System.out.println("Area is " + area);
    }
}
```

What is the result?

- A. Area is 6.0
- B. Area is 3.0
- C. Compilation fails at line n1
- D. Compilation fails at line n2.

**Answer:** D

**NEW QUESTION 46**

Which two code fragments cause a compilation error? (Choose two.)

- A. float flt = 100.00F;
- B. float flt = (float) 1\_11.00;
- C. Float flt = 100.00;
- D. double y1 = 203.22;float flt = y1;
- E. int y2 = 100;float flt = (float) y2 ;

**Answer:** AD

**NEW QUESTION 51**

Given the code fragment:

```
int wd = 0;
String days[] = {"sun", "mon", "wed", "sat"};
for (String s:days) {
    switch (s) {
        case "sat":
        case "sun":
            wd -= 1;
            break;
        case "mon":
            wd++;
        case "wed":
            wd += 2;
    }
}
System.out.println(wd);
```

What is the result?

- A. 3
- B. 4
- C. -1
- D. Compilation fails.

**Answer:** A

**NEW QUESTION 54**

Given:

```
public class Test {
    int x, y;

    public Test(int x, int y) {
        initialize(x, y);
    }

    public void initialize(int x, int y) {
        this.x = x * x;
        this.y = y * y;
    }

    public static void main(String[] args) {
        int x = 3, y = 5;
        Test obj = new Test(x, y);
        System.out.println(x + " " + y);
    }
}
```

What is the result?

- A. Compilation fails.
- B. 3 5
- C. 0 0
- D. 9 25

**Answer:** B

**NEW QUESTION 59**

Given the code fragment:

```
public static void main(String[] args) {
    StringBuilder sb = new StringBuilder("Java");
    String s = "Java";

    if (sb.toString().equals(s.toString())) {
        System.out.println("Match 1");
    } else if (sb.equals(s)) {
        System.out.println("Match 2");
    } else {
        System.out.println("No Match");
    }
}
```

What is the result?

- A. Match 1
- B. Match 2
- C. No Match
- D. A NullPointerException is thrown at runtime.

**Answer:** A

#### NEW QUESTION 63

Given:

```
class Caller {
    private void init () {
        System.out.println("Initialized");
    }

    private void start () {
        init();
        System.out.println("Started");
    }
}

public class TestCall {
    public static void main(String[] args) {
        Caller c = new Caller();
        c.start();
        c.init();
    }
}
```

What is the result?

- A. An exception is thrown at runtime.
- B. InitializedStartedInitialized
- C. InitializedStarted
- D. Compilation fails.

**Answer:** D

#### NEW QUESTION 65

Which two statements are true? (Choose two.)

- A. Error class is unextendable.
- B. Error class is extendable.
- C. Error is a RuntimeException.
- D. Error is an Exception.
- E. Error is a Throwable.

**Answer:** BC

#### NEW QUESTION 69

Given the code fragment:

```
int nums1[] = {1, 2, 3};
int nums2[] = {1, 2, 3, 4, 5};
nums 2 = nums 1;
for (int x : nums2){
    System.out.print(x + ":");
}
```

What is the result?

- A. 1:2:3:4:5:
- B. 1:2:3:
- C. Compilation fails.
- D. An ArrayOutOfBoundsException is thrown at runtime.

**Answer:** A

#### NEW QUESTION 70

Given the code fragment:

```
public static void main(String[] args) {  
    int[][] arr = new int [2] [4];  
    arr[0] = new int []{1, 3, 5, 7};  
    arr[1] = new int []{1, 3};  
    for (int[] a : arr) {  
        for (int i : a) {  
            System.out.print(i+ " ");  
        }  
        System.out.println();  
    }  
}
```

What is the result?

- A. Compilation fails.
- B.  
1 3  
1 3
- C.  
1 3  
followed by an ArrayIndexOutOfBoundsException
- D.  
1 3  
1 3 0 0
- E.  
1 3 5 7  
1 3

- A. Option A
- B. Option B
- C. Option C
- D. Option D
- E. Option E

**Answer:** E

**Explanation:**



1234567891011121314

Your Code ...

```
1- public class MyClass {
2-     public static void main (String [] args) {
3-         int [][] arr =new int [2] [4];
4-         arr[0] = new int [] {1, 3, 5, 7};
5-         arr[1] = new int [] {1, 3};
6-         for (int [] a : arr) {
7-             for (int i : a) {
8-                 System.out.print(i+ " ");
9-             }
10-            System.out.println ();
11-        }
12-    }
13- }
14- }
```

External Libraries ...

Add External Library (from Maven Repo)

CommandLine Arguments ...

Interactive mode :

☐ OFF

Version:

JDK 9.0.1

Stdin Inputs...

Execute

Save

My Projects

Recent

Collaborate

More Options -

Result...

CPU Time: 0.13 sec(s), Memory: 30680 kilobyte(s) compiled and executed in 0.705 sec(s)

1 3 5 7  
1 3

## NEW QUESTION 75

.....

## Thank You for Trying Our Product

\* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

\* One year free update

You can enjoy free update one year. 24x7 online support.

\* Trusted by Millions

We currently serve more than 30,000,000 customers.

\* Shop Securely

All transactions are protected by VeriSign!

**100% Pass Your 1z0-808 Exam with Our Prep Materials Via below:**

<https://www.certleader.com/1z0-808-dumps.html>