

Exam Questions 76940X

Avaya Converged Platform Support Exam

<https://www.2passeasy.com/dumps/76940X/>



NEW QUESTION 1

A support engineer has completed the upgrade of a PodFX 3.1 system to ACP 4200 4.0. What should the engineer do with Virtual Machine snapshots that were created during the upgrade process?

- A. The VM snapshots should be backed up to external storage and deleted immediately.
- B. The VM snapshots should be deleted immediately.
- C. The VM snapshots should be deleted within 72 hours of the verified, successful completion of the upgrade process.
- D. The VM snapshots should be left as they are as a backup of the upgrade process.

Answer: C

NEW QUESTION 2

A support engineer is upgrading a PodFX 3.1 system to ACP 4200 4.0. The engineer is upgrading the VMware vCenter Server from Release 6.0 to Release 6.5. Which two statements about the vSphere Update Manager (VUM) data migration are true? (Choose two.)

- A. The VMware-Migration-Assistant executable file is run on the Management Server Console where the current version of VUM is currently running.
- B. The VMware-Migration-Assistant executable file is run on the ESXi host where the current version of VUM is currently running.
- C. VUM data migration is optional.
- D. VUM data migration is mandatory.

Answer: AD

NEW QUESTION 3

A support engineer is upgrading a PodFX 3.1 system to ACP 4200 4.0. In preparation for upgrading the HPE server firmware, the engineer notices that another colleague has already downloaded files. Which two files should the engineer use? (Choose two.)

- A. hp-firmware-ilo4-2.60-1.1.i386.rpm
- B. bp-avaya-dl360g9-g10-ACP-4_0-New-only.iso
- C. SP99382.exe
- D. ACP_40_ilo4_261.bin

Answer: BD

NEW QUESTION 4

A support engineer is planning to migrate to Avaya Orchestrator from POS Applications. What are three tasks required as part of setting up Orchestrator? (Choose three.)

- A. Add to Storage Array.
- B. Add to System Manager.
- C. Change the Web interface's orchestratoradmin password.
- D. Change the CLI's root and aoadmin password.
- E. Activate the License.

Answer: BCE

NEW QUESTION 5

Which feature in Avaya Orchestrator allows a support engineer to select the management protocols and credentials of the equipment that is to be monitored within the ACP 4200?

- A. Monitoring Setup
- B. Orchestrator Security Center
- C. Device and Credentials Editor
- D. ACP Configuration Wizard

Answer: D

NEW QUESTION 6

A support engineer is tasked to power down a VSP switch using the management tools available for the ACP 4200. Which statement is true about how the engineer would accomplish this task?

- A. Login to Enterprise Device Manager and use the chassis power down option.
- B. Login to Servertech PDU Web Interface and use the outlet control option.
- C. This can only be done if the engineer is on-site to switch off the VSP's power switch.
- D. This can only be done if the engineer is on-site to remove the VSP's power cable.

Answer: A

NEW QUESTION 7

Which key consideration is critical when upgrading an application in your ACP 4200 system?

- A. Ensuring that the application server is able to contact <http://support.avaya.com>
- B. Validating the customer lifecycle workbook information and updating any undocumented changes that were made
- C. Ensuring that you have the latest VSP software installed
- D. Checking the IP Template for the application information and updating it with any changes made to the application

Answer: C

NEW QUESTION 8

Which statement about the LifeCycle Manage Workbook (LCM) and any time there is a change made to the ACP 4200 implementation is true?

- A. The LCM only needs to be updated when hardware devices are changed.
- B. Retrieve the LCM from ACP 4200 support prior to making any changes.
- C. The LCM is only needed when receiving the ACP 4200.
- D. Update the LCM with all changes and submit it via email to podfxsupport@avaya.com.

Answer: D

NEW QUESTION 9

A support engineer is upgrading a PodFX 3.1 system to ACP 4200 4.0. The system has two pairs of ServerTech PDUs. Which statement about the PDU firmware file describes the upgrade process that the engineer needs to follow?

- A. It will need to be uploaded to all 4 PDUs.
- B. It will need to be uploaded to each PDU Management Web Interface.
- C. It will need to be uploaded to one PD
- D. This PDU will then distribute the file to the remaining 3 PDUs.
- E. It will need to be uploaded to Orchestrato
- F. Orchestrator will then distribute the file to the 4 PDUs.

Answer: C

NEW QUESTION 10

What would a support engineer expect to find when using MSC to support, troubleshoot and maintain the ACP 4200 4.0?

- A. All current and previous license files
- B. Software library store
- C. Pod Upgrade Manager (PUM)
- D. VMware vSphere client application for VMware 6.5

Answer: D

NEW QUESTION 10

A support engineer is upgrading a PodFX 3.1 system to ACP 4200 4.0. The engineer is upgrading the ESXi hosts to VMware ESXi 6.5. Which two statements about this upgrade process are true? (Choose two.)

- A. ESXi hosts are upgraded all at the same time.
- B. ESXi hosts are upgraded one after another.
- C. One baseline group must be created using vSphere Update Manager to be used for all ESXi hosts.
- D. Separate baseline groups must be created using vSphere Update Manager for each individual ESXi host.

Answer: AC

NEW QUESTION 11

To get a visualization of the hardware components, and their positions in the ACP 4200 rack, which management application can an engineer use?

- A. MSC
- B. Orchestrator
- C. vCenter Client in Flash mode
- D. vCenter Client in HTML5 mode:

Answer: B

NEW QUESTION 15

A support engineer is tasked with working on an ACP 4200 4.0 system.

Which three pieces of equipment would the engineer expect to find in the rack that will differentiate the system from an earlier release of PodFx 3.X or CPOD 2.X? (Choose three.)

- A. Dell R601 Servers
- B. VSP 4824
- C. HP Nimble Storage CS1000
- D. HP Proliant DL360 G10 Servers
- E. VSP 7254

Answer: BCD

NEW QUESTION 18

A maintenance window had been scheduled to allow for the upgrade of the firmware of one of the VSP switches in the ACP. However, steps were not taken to avoid receiving unnecessary notifications during this period. As a result, when the upgrade process started the VSP switch shows multiple critical alerts. At this point, what would a support engineer do to reduce the amount of these unwanted alerts?

- A. Use the Post-Event Downtime feature in Orchestrator.

- B. Use the Mass Acknowledgments feature in Orchestrator.
- C. Use the Recurring Downtime feature in Orchestrator.
- D. The engineer will have to wait for the upgrade process to complete.

Answer: B

NEW QUESTION 20

Before a switch that has failed can be replaced with a new switch, what needs to be done?

- A. The replacement switch needs to have its configs defaulted.
- B. The remaining switch that is not being replaced needs to have its configs reset to defaults.
- C. The switch can be replaced without any preparation.
- D. The switch needs to have the appropriate backup restored on it.

Answer: A

NEW QUESTION 23

When performing a BIOS or firmware upgrade on physical host servers, why is it important to have vSphere access?

- A. The VMs must be restarted before the upgrade process.
- B. vSphere is needed to shut down the physical server.
- C. VMs must be shut down before the process.
- D. The server must be placed in maintenance mode before the upgrade.

Answer: C

NEW QUESTION 27

For the HP Server iLO interface, where is the default password located?

- A. Default Password is MAC Address
- B. LifeCycle Management Workbook
- C. HP Server Admin Guide
- D. Tag on server

Answer: D

NEW QUESTION 30

What is the primary purpose or function of Enterprise Device Manager (EDM)?

- A. EDM provides an interface for administrator to monitor the health of the Nimble Storage array in a single pane and allows them to make changes to storage, protection, access, and performance configuration.
- B. EDM provides access to HP Proliant Servers' out-of-band management facilities
- C. It allows for control and monitoring of HP servers.
- D. EDM is the device management software application for Extreme Network's VSP platforms.
- E. EDM provides a robust web interface which allows for monitoring of the ServerTech PDU and control of its individual power outlet.

Answer: C

NEW QUESTION 33

To use the Management Server Console (MSC) as their time source, how would the engineer configure the ESXi hosts?

- A. Login to the MSC, run the time_configuration.bat script.
- B. Login to the MSC, set Services > Time configuration > NTP Clients = IP addresses of the ESXi hosts.
- C. Login to the ESXi Hosts using the CLI, run the time_configuration.sh script.
- D. Login to vCenter server using the Web UI, set host > manage > Time configuration = IP address of the MSC.

Answer: B

NEW QUESTION 35

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual 76940X Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the 76940X Product From:

<https://www.2passeasy.com/dumps/76940X/>

Money Back Guarantee

76940X Practice Exam Features:

- * 76940X Questions and Answers Updated Frequently
- * 76940X Practice Questions Verified by Expert Senior Certified Staff
- * 76940X Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * 76940X Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year